

TBS




**Transient and lightning
protection systems**

South Africa

2020/2021

OBO
BETTERMANN

O-line



**Contact
Customer Service**
Tel: +27 11 378 3700
Fax: +27 11 493 0334
email: o-line@o-line.com

www.o-line.com

O-line

Planning and mounting aids

	Planning aids	4
	Surge protection device, type 1+2, for industry	99
	Surge protection energy technology, arrestor, type 1	137
	Surge protection device, type 2	143
	Surge protection energy technology, arrestor, type 2+3	183
	Surge protection energy technology, arrestor, type 3	205
	Surge protection device for photovoltaics	213
	Surge protection, data and information technology	237
	Surge protection, Ex protection	341
	Protection and spark gaps	351
	Measuring and test systems	357
	Equipotential bonding systems	361
	Earthing systems	379
	Air-termination and down-conductor systems	407
	OBO isCon® system and insulated lightning protection	475
	Directories	495

OBO Construct planning aids

Digital selection aids for earthing systems and surge protection

The OBO Construct electronic planning aids are programs developed to support electrical installation engineers and planners in the design of electrical installation systems. In particular, in complex areas such as surge protection and earthing, there are countless technical and standard general conditions to be observed. The two OBO Construct programs for earthing and surge protection systems should provide active help here. Systematic questions simplify the search for suitable products and guaranteed surge protection systems and earthing systems which fulfil the standards.

OBO Construct for earthing systems


The digital selection aid can be used for the easy planning and configuration of earthing systems. The simple and intuitive user guidance leads you through the individual components of the earthing system step by step. The software then automatically calculates the amounts required and the matching accessories. The application can be opened on any end device irrespective of its operating system – be it smartphone, tablet or desktop PC.

OBO Construct for surge protection

This online tool aids you in the project-orientated selection and connection of suitable surge protection systems and provides you with information on the OBO surge protection systems. You can create your personal materials list, connection diagram and invitation to tender texts quickly, efficiently and in a targeted manner for complete surge protection in the fields of energy technology, photovoltaics, telecommunication, MSR, TV, HF and data technology. The result can be exported easily into Excel format for further processing.

Benefits

- Time and place-independent work assistance
- Transmit planning requirements to complete product systems
- Find suitable products quickly and simply
- Calculate material and parts lists automatically
- Download configuration results as Excel or Word files





Lightning protection guide. Safely routed.

Reference work and planning aid for electrical installation engineers and technical planners

At OBO Bettermann, we can look back on more than 90 years of experience in the field of lightning and surge protection. This experience and, of course, the latest standards and technical innovations have flowed into the company's new lightning protection guide. The brochure allows you to plan installations in the field of lightning and surge protection faster and more easily.

It contains a balanced mixture of both basic and expert knowledge, as well as planning and selection aids for the protection of buildings and systems.

The new lightning protection guide can be requested by calling +49 2373 89 - 1700 and is also available for download on the OBO website.



Topics

- Basic principles
- The external lightning protection system
- Air-termination and down-conductor systems
- Examples and selection aids for wind load calculation conform with Eurocode 1+3
- Earthing systems with foundation earther to current DIN 18014
- The internal lightning protection system
- Equipotential bonding systems
- Overvoltage protection systems
- Current standards
- New selection and planning aids
- Examples



Contents of planning and mounting aids

	Basic principles of surge voltage protection	13
	Surge protection energy technology	23
	Surge protection arrestor, type 1+2, type 1	
	Surge protection arrestor, type 2, type 2+3	
	Surge protection arrestor, type 3	
	Surge protection device for photovoltaics	27
	Surge protection device for data and information technology	33
	Protection and spark gaps	51
	Measuring and test systems	55
	Equipotential bonding systems	59
	Earthing systems	63
	Air-termination and down-conductor systems	71
	OBO isCon® system and insulated lightning protection	83
	Additional information	92



OBO TBS seminars: First-hand knowledge

With a comprehensive programme of training courses and seminars on the subject of surge voltage and lightning protection systems, OBO is able to support its customers with specialist knowledge from a single source. Alongside the basic theoretical principles, the programme also deals with practical implementation in everyday applications. Special calculation and application examples round off the comprehensive programme of knowledge transfer.

Invitations to tender on the Internet at www.ausschreiben.de

More than 10,000 entries from the cable support systems, fire protection systems, connection and fastening systems, transient and lightning protection systems, cable routing systems, device systems and underfloor systems can be recalled for free. Regular updates and extensions mean that you always have a comprehensive overview of the OBO products. All the current file formats (PDF, DOC, GAEB, HTML, TEXT, XML, ÖNORM) are available.
www.ausschreiben.de



Invitations to tender, product information and data sheets

We can make life easier for you, with our comprehensive selection of materials designed for practical applications, which provide you with effective support with the planning and calculation of a project. These include:

- Invitations to tender
- Product information
- Data sheets
- Data sheets

Invitations to tender for lightning protection/earthing at the highest level:

OBO manufacturers products to RAL GZ642-5 and is dedicated to compliance with the RAL directives. Lightning protection and earthing products can be used for invitations to tender according to RAL.

These documents are continually updated and can be downloaded for free at any time from the Internet download area at www.obo-bettermann.com.



Customer service and credibility

Friendliness, reliability and competence create acceptance, credibility and lasting working relationships. These shared values arise from OBO's consistent orientation around the wishes and needs of its customers. Close partnerships with customers is OBO's foremost priority.

Help and advice

Answers to questions about products and installation, planning advice for complex projects – OBO's staff will help you through every phase of your project, no matter what field it is in. We are constantly improving the support we provide in every phase of collaboration, laying the foundations for genuine partnerships.

Speed and reliability

Optimised procedures and highly developed logistics ensure that OBO products are in the right place at the right time, anywhere in the world. OBO offers comprehensive support for large-scale projects, from planning all the way to installation.



Lightning protection guide

Free order
and download from
www.obo.de

- Production location
- Subsidiary
- Representative






OBO Engineering Services

OBO engineering situated in Selby Johannesburg is a newly established division designed to provide technical assistance to the African Market within the field of lightning and surge protection. The Division which has an experienced design and solutions team will now complement its already world renown products through providing the following services:

- Earth resistivity testing with detailed report on findings
- Risk assessments with detailed report and mitigation measures
- Site assessments
- Detailed engineering designs with Bill of materials
- 2D & 3D drawings of lightning protection systems in (CAD) format
- Detailed installation instructions
- Calculation of separation distances according to IEC/SANS 62305
- Selection of Surge Protection devices
- Detailed Tender Specifications in accordance with IEC/SANS codes





BET Test Centre generator for lightning current tests


OBO's advanced Technical Facilities consisting of its in house BET Test Centre make provision for tests to be carried out up to 200 kA. The generator was planned and constructed in cooperation with Soest Technical College. Due to the intensive planning and scientific support in the construction of the test system, it has worked for 20 years without errors and meets current standardised test requirements.

The centre allows for a magnitude of test to be carried out including that of new developments, modifications to existing OBO products and also comparison tests with competitive products. These include lightning protection components, surge protection devices and lightning arrestors.



Tests for lightning protection components are carried out according to IEC 62561, for spark gaps according to IEC 62561 and for lightning and surge protection devices according to IEC 61643-11. This is only a small amount of the testing standards used for tests in the BET Test Centre.





This makes OBO Engineering Services your partner in the planning of complex systems and projects. The visualisation of the lightning protection measures indicates clearly each stage of the planning process, how the lightning protection solutions can be integrated into the project.

OBO Engineering Services include the construct and design of detailed Lightning Protection systems for various industries including but not limited to:

- Renewable energy- Rooftop PV, CSP plants, Biogas, PV plants etc.
- Commercial
- Industrial
- Domestic
- Security
- Food & Process Industry
- Oil and Gas Industry
- Telecommunication
- Transportation
- HV, MV & LV networks



Minor cause, major effect: Damage caused by surge voltages



Our dependency on electrical and electronic equipment continues to increase, in both our professional and private lives. Data networks in companies or emergency facilities such as hospitals and fire stations are lifelines for an essential real time information exchange. Sensitive databases, e.g. in banks or media publishers, need reliable transmission paths.

It is not only lightning strikes that pose a latent threat to these systems. More and more frequently, today's electronic aids are damaged by surge voltages caused by remote lightning discharges or switching operations in large electrical systems. During thunderstorms too, high volumes of energy are instantaneously released. These voltage peaks can penetrate a building through all manner of conductive connections and cause enormous damage.



Financial implications of lightning and surge voltage damage

1



Financial losses can only be considered in isolation in cases where no legal or insurance requirements relating to personal safety apply.

Substantial losses result from the destruction of electrical devices, notably:

- Computers and servers
- Telephone systems
- Fire alarm systems
- Monitoring systems
- Lift, garage door and roller shutter drives
- Consumer electronics
- Kitchen appliances

Further costs can also be incurred due to outages and consequential damage in relation to:

- Loss of data
- Production outage
- Loss of contactability (Internet, telephone, fax)
- Defective heating systems
- Costs due to faults and false alarms in fire and burglar alarm systems



Financial losses are on the rise

Current statistics and estimates of insurance companies show: Damage levels caused by surges – excluding consequential or outage costs – long since reached drastic levels due to the growing dependency on electronic "aids". It's no surprise then that property insurers are checking more and more claims and stipulating the use of devices to protect against surges. Information on protection measures can be found in, for example, the German Directive VdS 2010.

Year	Number of lightning and surge voltage damage cases	Paid damages for lightning and surge voltage damage
1999	490,000	€310 million
2006	550,000	€340 million
2007	520,000	€330 million
2008	480,000	€350 million
2009	490,000	€340 million
2010	330,000	€220 million
2011	440,000	€330 million
2012	410,000	€330 million
2013	340,000	€240 million
2014	410,000	€340 million
2015	350,000	€240 million
2016	300,000	€250 million

Number of instances of damage from lightning and surge voltages and amounts paid out by home and contents insurance companies (the example is of Germany); source: GDV extrapolation based on industry and risk statistics; numbers rounded to the nearest €10,000 or €10 million.



Lightning and surge protection standards

When planning and executing a lightning protection system, it is necessary to observe all relevant national annexes and take account of any special circumstances or applications and the safety stipulations in the relevant country-specific supplements.

A lightning and surge protection system consists of several systems, each tailored to each of the others. At its most basic, a lightning and surge protection system consists of one internal and one external lightning protection system.

These, in turn, can be categorised as follows:

- Air-termination devices
- Down-conductors
- Earthing systems
- Area shielding
- Separation distance
- Lightning protection equipotential bonding system

These systems must be carefully selected for the application at hand, and used in a coordinated way. Installation of the systems takes place according to various application and product standards. The supplements to the international IEC guidelines and harmonised European versions of the various country-specific translations often contain additional informative information specific to the country in question.

Product standards

To ensure that the components can withstand the loads to which they are likely to be exposed in application, they must be checked against the respective product standard for external and internal lightning protection.



External and internal lightning protection systems

Standard	German supplement	Contents
VDE 0185-305-1 (IEC 62305-1)		Protection against lightning – Part 1: General principles
VDE 0185-305-2 (IEC 62305-2)		Protection against lightning – Part 2: Risk management
	1	Lightning risk in Germany
	2	Calculation aids for estimating the risk of damage for buildings
	3	Additional information on use of EN 62305-2
VDE 0185-305-3 (IEC 62305-3)		Protection against lightning – Part 3: Physical damage to structures and life hazard
	1	Additional information on use of EN 62305-3
	2	Additional information for building structures
	3	Additional information for the testing and servicing of lightning protection systems
	4	Use of metal roofs in lightning protection systems
	5	Lightning and surge protection in PV power supply systems
VDE 0185-305-4 (IEC 62305-4)		Protection against lightning – Part 4: Electrical and electronic systems within structures
	1	Distribution of the lightning current
VDE 0675-6-11 (IEC 0675-6-11)		Low-voltage surge protective devices – Part 11: Surge protective devices connected to low-voltage power systems
VDE 0100-534 (IEC 60364-5-53)		Low-voltage electrical installations – Part 5-53: Selection and erection of electrical equipment – Isolation, switching and control – Clause 534: Devices for protection against surge voltages
VDE 0100-443 (IEC 60364-4-44)		Low-voltage electrical installations – Part 4-44: Protection for safety – Protection against voltage disturbances and electromagnetic disturbances – Clause 443: Protection against surge voltages of atmospheric origin or due to switching
VDE 0100-712 (IEC 60364-7-712)		Requirements for operational premises, special rooms and systems – photovoltaic (PV) power supply systems


Key lightning protection standards and specifications

Product standards	Contents
VDE 0185-561-1 (IEC 62561-1)	Lightning protection system components – Requirements for connection components
VDE 0185-561-2 (IEC 62561-2)	Lightning protection system components – Requirements for conductors and earthers
VDE 0185-561-3 (IEC 62561-3)	Lightning protection system components – Requirements for isolating spark gaps
VDE 0185-561-4 (IEC 62561-4)	Lightning protection system components – Requirements for conductor fasteners
VDE 0185-561-5 (IEC 62561-5)	Lightning protection system components – Requirements for earth electrode inspection housings and earth electrode seals
VDE 0185-561-6 (IEC 62561-6)	Lightning protection system components – Requirements for lightning strike counters
VDE 0185-561-7 (IEC 62561-7)	Lightning protection system components – Requirements for earthing enhancing compounds
IEC TS 62561-8	Lightning protection system components – Requirements for components for insulated lightning protection systems
VDE 0675-6-11 (IEC 61643-11)	Surge protective devices for use in low-voltage power systems – Requirements and test methods
VDE 0845-3-1 (IEC 61643-21)	Surge protection for use in telecommunications and signalling networks

Lightning protection and surge protection components



Gradual surge reduction with lightning protection zones



Lightning protection zone concept

The lightning protection zone concept described in international standard IEC 62305-4 (DIN VDE 0185 Part 4) has proved to be practical and efficient. This concept is based on the principle

of gradually reducing surges to a safe level before they reach the terminal device and cause damage. In order to achieve this situation, a building's entire energy network is split into lightning protection zones (LPZ = lightning protection zone). Installed at each

transition from one zone to another is a surge arrester for equipotential bonding. These arresters correspond to the requirement class in question.

Lightning protection zone

LPZ 0 A	Unprotected zone outside the building. Direct lightning strike, no shielding against electromagnetic interference pulses LEMP (Lightning Electromagnetic Pulse).
LPZ 0 B	Through the area protected by the external lightning protection system. No shielding against LEMP.
LPZ 1	Zone inside the building. Low partial lightning energies possible.
LPZ 2	Zone inside the building. Low surges possible.
LPZ 3	Zone inside the building (can also be the metal housing of a consumer). No interference pulses through LEMP or surges present.

Choosing the right surge protective devices

The classification of surge protective devices into types means they can be matched to different requirements with regard to location, protection level and current-carrying capacity. The table provides an overview of the zone

transitions. It also shows which OBO surge protective devices can be installed in the energy supply network and their respective function.

Zone transition	Protection device and device type	Product example	Product figure
LPZ 0 B to LPZ 1	Protection device for lightning protection equipotential bonding in accordance with VDE 0185-305 (IEC 62305) for direct or close lightning strikes. Devices: Type 1+2 (Class I+II), e.g. CCF Compact Max. protection level according to standard: 1.5 kV OBO protection level: < 1.5 kV Installation, e.g. in the main distributor/at building entry	MCF Compact Item no.: 5096987	
LPZ 1 to LPZ 2	Protection device for lightning protection equipotential bonding in accordance with VDE 0185-305 (IEC 62305) for direct or close lightning strikes. Devices: Type 2 (Class II), e.g. V20 Max. protection level according to standard: 1.5 kV OBO protection level: < 1.3 kV Installation, e.g. in the main distributor/at building entry	V20 Item no.: 5095253	
LPZ 2 to LPZ 3	Protection device, designed for surge protection of portable consumers at sockets and power supplies. Devices: Type 3 (Class III), e.g. ÜSM-A Max. protection level according to standard: 1.5 kV OBO protection level: < 1.3 kV Installation, e.g. on the end consumer	ÜSM-A Item no.: 5092451	



BET – testing centre for lightning protection, electrical engineering and support systems



Lightning current generator

BET with countless tasks

Whereas previously only lightning current, environmental and electrical testing had been possible at BET, the BET Test Centre is now also a competent partner for the testing of cable support systems. This combination has made it necessary to revise the meaning of the name. If BET previously stood for "Blitzschutz- und EMV-Technologiezentrum" (Lightning protection and EMC technology centre), since 2009 these letters have meant BET Test Centre for lightning protection, electrical engineering and support systems.

Test generator for lightning current tests

The test generator planned in 1994 and completed in 1996 makes it possible to carry out lightning current tests at up to 200 kA. The generator was planned and constructed in cooperation with Soest Technical College. Due to the intensive planning and scientific support in the construction of the test system, it has worked for 20 years without errors and meets current standardised test requirements.

Testing tasks


The main load of the testing generator is generated through the testing of products from the TBS product division. For this, developmental tests of new developments, modifications to existing OBO products and also comparison tests with competitive products are carried out. These include lightning protection components, surge protective devices and lightning arresters. Tests for lightning protection components are carried out according to DIN EN 62561-1, for spark gaps according to DIN EN 62561-3 and for lightning and surge protective devices according to DIN EN 61643-11. This is only a small amount of the testing standards used for tests in the BET Test Centre.

Certification

In development, manufacture and marketing, the products of OBO Bettermann are subject to high, standardised quality standards and international standards. For decades now, OBO Bettermann has operated an ISO 9001-certified quality management system, which also fulfils the high requirements of the ATEX 2014/34/EU directive for EX products. In addition, OBO has run a certified energy management system according to ISO 50001 and is a long-standing member of Industrieverband Feuerverzinken e.V.

The BET Test Centre is a testing laboratory, recognised and certified by VDE, for the execution of countless tests according to international standards for lightning protection systems.





Types of pulse and their characteristics

Testing types for lightning and surge protection

Both lightning current tests and surge voltage tests can be carried out at up to 20 kV. A hybrid generator is used for these tests, which was also developed as part of a cooperation with the Soest Technical College. EMC testing of cable support systems can also be carried out using this test generator. All kinds of cable routing and cable support systems of up to 8 m length can be tested without any difficulties. Tests for electrical conductivity according to IEC 61537 are also carried out.


Simulation of real environmental conditions

To carry out standardised tests on components intended for external use, they must be pretreated under real environmental conditions. This takes place in a salt spray trough and a sulphur dioxide testing chamber. Depending on the test, the test length and the concentration of the salt spray or sulphur dioxide in the testing chambers may vary. This means that it is possible to conduct tests according to IEC 60068-2-52, ISO 7253, ISO 9227 and EN ISO 6988.

Testing cable support systems

The well-known KTS testing system, newly installed in the BET Test Centre, allows the investigation of the load capacities of any cable support system manufactured by OBO. The basis for this is IEC 61537 and VDE 0639.

In the BET Test Centre, OBO Bettermann has a testing department in which products can be tested according to standards, even during the development phase.



Selection aid, energy technology

24



Selection aid, energy technology

AC combination arrester and surge protection; type 1, type 1+2, type 2 and type 3

		Installation location 1 Installation in the main distributor box / combined distributor Basic protection / type 1, type 2					
Initial situation	Building type	Description	Type	Item no.	Test mark	Product figure	
<ul style="list-style-type: none"> No external lightning protection system Earthing cable connection 	Private building, multiple dwelling	TN-TT Type 2 4 SU Secondary meter zone	V20 3+NPE	5093 38 0 Page: 185	VDE ÖVE UL		
			V10-C 3+NPE	5093 39 1 Page: 187	VDE ÖVE UL		
Industry, commerce	TN-TT Type 2 4 SU Secondary meter zone	V20 3+NPE	5095 25 3 Page: 167	VDE ÖVE UL			
			V20 3+NPE+FS with remote signalling	5095 33 3 Page: 168	VDE ÖVE UL		
External lightning protection system (according to IEC 62305) 	Buildings of lightning protection classes III and IV (e.g. housing, offices and commercial buildings)	TN-TT Type 1 + 2 4 SU Secondary meter zone	V50 3+NPE	5093 52 6 Page: 132	VDE ÖVE UL		
			V50 3+NPE+FS with remote signalling	5093 53 3 Page: 133	VDE ÖVE UL		
Outdoor connection 	Buildings of lightning protection classes I to IV (e.g. industry)	TN-C Type 1+2 6 SU Pre-metered or secondary meter zone	MCF75-3+FS	5096981 Page: 101			
			TN-S Type 1+2 6 SU Pre-metered or secondary meter zone	5096 87 9 Page: 108			

Installation location 2
Installation in the subdistributor
Medium protection / Type 2
Only required if distance \geq 10m

Description	Type	Item no.	Test mark	Product figure
TN/TT Type 2 + 3 2.5 SU	V10 Compact	5093380 Page: 185		
	V10 Compact FS, with remote signalling	5093382 Page: 188		
TN/TT Type 2 4 SU	V20 3+NPE	5095253 Page: 167	VDE ÖVE UL	
	V20 3+NPE+FS with remote signalling	5095333 Page: 168	VDE ÖVE UL	
TN/TT Type 2 4 SU	V20 3+NPE	5095253 Page: 167	VDE ÖVE UL	
	V20 3+NPE+FS with remote signalling	5095333 Page: 168	VDE ÖVE UL	
TN/TT Type 2 4 SU	V20 3+NPE	5095253 Page: 167	VDE ÖVE UL	
	V20 3+NPE+FS with remote signalling	5095333 Page: 168	VDE ÖVE UL	

Installation location 2
Installation before the terminal
Fine protection / type 3

Description	Type	Item no.	Product figure
Plug-in	FC-D	5092 80 0	
	FC-TV-D	5092 80 8	
	FS-SAT-D	5092 81 6	
	FC-TAE-D	5092 82 4	
	FC-ISDN-D	5092 81 2	
	FC-RJ-D	5092 82 8	
	CNS-3-D-D	5092 70 1	
Fixed installation	ÜSM-A	5092 45 1 Page: 206	
	ÜSM-A ST-230 1P+PE	5092 44 1	
	ÜSS 45-o-RW	6117 47 3 Page: 209	
Series installation in distributor	V10 Compact L1/L2/L3/N	5093 38 0 Page: 185	
	VF230-AC/DC	5097 65 0 Page: 302	
	VF230-AC-FS with remote signalling	5097 85 8 Page: 306	





Planning aids, contents lightning and surge protection, photovoltaics

Coordinated protection	28
Four steps to comprehensive protection	29
DC surge protection energy technology, type 2	30
DC combination arrestor, type 1+2 and data protection devices	31



Coordinated protection: The ProtectPlus system kit

A well-thought-out system for the whole electrical infrastructure of a photovoltaic system – that's ProtectPlus. Different components provide comprehensive protection, which allows both the erection engineer and the system operator to sleep in peace.



External lightning protection systems

Lightning currents are intercepted and run safely to the earth with the following systems:

- Air-termination rods and masts
- Insulated lightning protection
- Insulated isCon® conductor
- Flat and round conductors
- Cable brackets
- Connection clamps and connection terminals

Earthing systems

Our products for perfect earthing:

- Flat and round conductors
- Connectors
- Connection terminals
- Earth entries
- Deep, ring and foundation earthers
- Corrosion protection



Equipotential bonding systems

Equipotential bonding systems are the link between external lightning protection, surge protection and earthing. They are available in the following variants:

- For indoor use
- For outdoor use
- For industrial use

Ovvoltage protection systems

A product range for any application:

- Lightning arrestor/combination arrestor
- Surge protection for energy and data technology
- Complete system solutions, terminated and premounted in the housing
- Combination and surge arrestor for photovoltaics, DC side

Cable support systems

Quick-mounting, safe cable routing with:

- Cable trays
- Mesh cable trays
- Cable ladders
- Vertical ladders
- Suspended supports
- Wall and support brackets



Cable routing systems

Tidy cable routing within the building can be achieved using

- Wall and ceiling ducts
- Cable and pipe fastening systems made of plastic and metal
- Screw-in and knock-in systems
- Rail systems

Fire protection systems

Our fire protection system consists of the following components:

- Insulation
- Weatherproof fire protection bandages
- Systems for emergency and escape routes

Four steps to comprehensive protection

Step 1:

Check the separation distance

If the required separation distance cannot be complied with, then the metallic parts must be interconnected to be able to carry lightning current.

Step 2:

Check the protection measures

Measures for lightning protection equipotential bonding are used on the DC and the AC side, e.g. lightning current arrestor (type 1).

Step 3:

Include data cables

Data cables must be included in the protection concept.



Step 4:

Carrying out the equipotential bonding

Local equipotential bonding must be provided on the inverter.

Overview of protection measures

Initial situation	Measure	Separation distance according to DIN EN 62305 maintained	equipotential bonding	Surge protection	Sample product picture
<ul style="list-style-type: none">External lightning protection system (according to DIN EN 62305) 	Adapt the lightning protection system according to IEC 62305	Yes	min. 6 mm ²	DC: Type 2	
		No	min. 16 mm ²	AC: Type 1	
		-	min. 6 mm ²	DC: Type 1	
<ul style="list-style-type: none">No external lightning protection systemEarthing cable connection 	Requirements' testing: LBO, Vds 2010, risk analysis, ...	-	min. 6 mm ²	AC: Type 1	
				DC: Type 2	

Selection aid

Photovoltaic system solutions

Energy technology, type 2, protection of the DC side								
Initial situation	Max. DC voltage	Max. number of MPP per inverter	Max. number of strings per MPP terminal	Connection (DC side)	Version	Type	Item no.	Product figure
<ul style="list-style-type: none"> No external lightning protection system Earthing cable connection <p>The following are required:</p> <ul style="list-style-type: none"> Surge voltage protection, type 2 Lightning protection equipotential bonding 6.5 mm²  	1000 V	1	1In/1Out	MC 4 connector		VG-C DCPH-Y1000	5088 67 2	
		1	2	Terminals	Circuit breaker	VG-C DC-TS1000	5088 66 0	
		1	4	Terminals	4 fuse holders, unequipped	VG-C PV1000KS4	5088 65 4	
		1	10	Terminals		VG-C DCPH-MS1000	5088 69 1 Page: 230	
		2	4	Terminals		VG-CPV1000K 22	5088 56 8	
		2	6	Terminals		VG-CPV 1000K 330	5088 58 2	
		3	6	Terminals		VG-CPV 1000K 333	5088 58 5 Page: 227	

You can find the selection aid for AC combination arrestors and surge protection in the chapter Surge Protection in Energy Technology.

Energy technology, type 1+2, protection of the DC side								
Initial situation	Max. DC voltage	Max. number of MPP per inverter	Max. number of strings per MPP terminal	Connection (DC side)	Version	Type	Item no.	Product figure
<ul style="list-style-type: none"> External lightning protection system according to DIN EN 0185-305 The following are required: <ul style="list-style-type: none"> Lightning and surge protection Type 1+2 Lightning protection equipotential bonding 16 mm² Separating distance could not be maintained 	600 V	1	1 0	Terminal		VG-BC DCPH-MS600	5088 69 3 Page: 232	
	900 V	1	1In/1Out	MC 4 connector		VG-BC DCPH-Y900	5088 67 8	
		1	2	Terminals	Circuit breaker	VG-BC DC-TS900	5088 63 5	
		1	1 0	Terminals		VG-BC DCPH-MS900	5088 69 2 Page: 231	
		2	4	Terminals		VG-BCPV900K 22	5088 56 6 Page: 226	
		2	6	Terminals		VG-BCPV 900K 330	5088 57 6	
		3	2In/1Out	MC 4 connector		VG-BC DCPH900-31	5088 62 9 Page: 229	
		3	6	Terminals		VG-BCPV 900K 333	5088 57 9	




Data technology						
Initial situation		RJ 45	Terminal	Type	Item no.	Product figure
	<ul style="list-style-type: none"> No external lightning protection system Earthing cable connection 	•		ND-CAT6A/EA	5081800 Page: 265	
	<ul style="list-style-type: none"> External lightning protection system (according to DIN EN 62305) 		•	FRD 24 HF	5098575 Page: 309	



Planning aids, surge protection device for data and information technology

Important terms and basic principles	34
Selection aid, HF, video and satellite TV	36
Selection aid, data technology	39
Selection aid, telecommunications	40
Selection aid, measurement and control systems	43
Selection aid, bus systems	46

Surge protection systems for data and information technology



Protection principle based on lightning protection zone concept

Data and information technology systems are used in many different applications. Almost every electronic system used to process information is considered extremely important. Ever increasing volumes of data are being stored and must be accessible at all times at very short notice. It has become even more important to protect these systems too against dangerous surges. In order to prevent failure or even destruction of these systems, they must be integrated into the lightning and surge protection concept.

Planning methods – Basic

principles

These days, communication and IT systems are the lifelines of almost every company. In the worst-case scenario, surge voltages, caused by galvanic, capacitive or inductive couplings in data cables, can destroy IT equipment and communication technology. To avoid such failures, suitable protection measures have to be taken.

In practice, the wide range of standard information, telecommunication and measurement systems often makes the selection of the right surge protection device complex.

The following factors must be taken into account:

- The connection system of the protection device must fit the device to be protected.
- Parameters such as the highest signal level, highest frequency, maximum protection level and the installation environment must be taken into account.
- The protection device may only exert the minimum of impacts, such as attenuation and reflection, on the transmission path.

Data cable protection devices and labelling



LPZ 0B - 2, final code B = Basic protection, red colour coding



LPZ 0B - 3, final code C = Combi Protection, blue colour coding



LPZ 1 - 3, final code: F = fine protection, green colour coding

Basic protection

Basic protection devices are lightning arrestors of class 1 that can directly arrest lightning currents and surge voltages. The single-stage protection circuit contains gas arresters. These devices are installed where the lines enter the buildings. They serve to arrest lightning current with waveform 10/350 µs coupled from outside the building via the data cables.

Combined protection

The combined protection devices limit the transients with gas-discharge protectors or transzorb diodes, which are decoupled through resistors. These correspond to classes 1, 2 and 3 or categories D1 and C2 as defined in the standard DIN EN 61643-21. The devices can be installed as basic protection where the lines enter the building, or as fine protection directly before the terminal device. In the latter case it should be noted that the distance to the device needing protection should not exceed 10 metres. If it does, then a further fine protection device should be installed before the device.

Fine protection

The fine protection devices use transzorb diodes to limit surge impulses. The devices are earthed with powerful gas discharge protectors. The decoupling required for basic and fine protection is achieved when the line section between basic and fine protection device is at least five metres. Fine protection devices should always be installed on the device to be protected itself.

Selection aid, HF, video and satellite TV

Technology	Connection	Protected wires	Frequency range	Type	Gender	Item no.	Protection type
CATV	F	1	0-3.4 GHz	DS-F	plug/connector	5093275	Combination protection
	F	1	0-3.4 GHz	DS-F	connector/connector	5093272	Combination protection
DCF 77	SMA	1	0-3.7 GHz	DS-SMA	connector/connector	5093277	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	plug/connector	5093252	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	connector/connector	5093236	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	plug/plug	5093260	Combination protection
DCS 1800	SMA	1	0-3.7 GHz	DS-SMA	connector/connector	5093277	Combination protection
	N	1	0-3 GHz	DS-N	plug/connector	5093996	Combination protection
	N	1	0-3 GHz	DS-N	connector/connector	5093988	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	plug/connector	5093252	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	connector/connector	5093236	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	plug/plug	5093260	Combination protection
	Jul 16	1	0-3 GHz	DS-7 16	plug/connector	5093171	Combination protection
DOCSIS	F	1	0-3.4 GHz	DS-F	plug/connector	5093275	Combination protection
	F	1	0-3.4 GHz	DS-F	connector/connector	5093272	Combination protection
DVB-T / terrestrial	F	1	0-3.4 GHz	DS-F	plug/connector	5093275	Combination protection
	F	1	0-3.4 GHz	DS-F	connector/connector	5093272	Combination protection
	F	1	0.5-2.8 GHz	TV4+1	connector	5083400	Fine protection
DVB-T2	N	1	0-6 GHz	DS-N-6	plug/connector	5093998	Combination protection
Radio installations	UHF	1	0-1.3 GHz	S-UHF	plug/connector	5093023	Combination protection
	UHF	1	0-1.3 GHz	S-UHF	connector/connector	5093015	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	plug/connector	5093252	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	connector/connector	5093236	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	plug/plug	5093260	Combination protection
	N	1	0-3 GHz	DS-N	plug/connector	5093996	Combination protection
	N	1	0-3 GHz	DS-N	connector/connector	5093988	Combination protection
	SMA	1	0-3.7 GHz	DS-SMA	connector/connector	5093277	Combination protection
	Jul 16	1	0-3 GHz	DS-7 16	plug/connector	5093171	Combination protection
	F	1	0-3.4 GHz	DS-F	plug/connector	5093275	Combination protection
	F	1	0-3.4 GHz	DS-F	connector/connector	5093272	Combination protection
	TNC	1	0-4 GHz	DS-TNC	plug/connector	5093270	Combination protection
GPS	SMA	1	0-3.7 GHz	DS-SMA	connector/connector	5093277	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	plug/connector	5093252	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	connector/connector	5093236	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	plug/plug	5093260	Combination protection
	N	1	0-3 GHz	DS-N	plug/connector	5093996	Combination protection
	N	1	0-3 GHz	DS-N	connector/connector	5093988	Combination protection
	Jul 16	1	0-3 GHz	DS-7 16	plug/connector	5093171	Combination protection
	TNC	1	0-4 GHz	DS-TNC	plug/connector	5093270	Combination protection

Selection aid, HF, video and satellite TV

Technology	Connection	Protected wires	Frequency range	Type	Gender	Item no.	Protection type
GSM 900 / 1800	SMA	1	0–3.7 GHz	DS-SMA	connector/connector	5093277	Combination protection
	BNC	1	0–2.2 GHz	DS-BNC	plug/connector	5093252	Combination protection
	BNC	1	0–2.2 GHz	DS-BNC	connector/connector	5093236	Combination protection
	BNC	1	0–2.2 GHz	DS-BNC	plug/plug	5093260	Combination protection
	N	1	0–3 GHz	DS-N	plug/connector	5093996	Combination protection
	N	1	0–3 GHz	DS-N	connector/connector	5093988	Combination protection
	TNC	1	0–4 GHz	DS-TNC	plug/connector	5093270	Combination protection
	Jul 16	1	0–3 GHz	DS-7 16	plug/connector	5093171	Combination protection
LTE	SMA	1	0–3.7 GHz	DS-SMA	connector/connector	5093277	Combination protection
	N	1	0–3 GHz	DS-N	plug/connector	5093996	Combination protection
	N	1	0–3 GHz	DS-N	connector/connector	5093988	Combination protection
	TNC	1	0–4 GHz	DS-TNC	plug/connector	5093270	Combination protection
	Jul 16	1	0–3 GHz	DS-7 16	plug/connector	5093171	Combination protection
PCS 1900	SMA	1	0–3.7 GHz	DS-SMA	connector/connector	5093277	Combination protection
PCS 1901	BNC	1	0–2.2 GHz	DS-BNC	plug/connector	5093252	Combination protection
PCS 1902	BNC	1	0–2.2 GHz	DS-BNC	connector/connector	5093236	Combination protection
PCS 1903	BNC	1	0–2.2 GHz	DS-BNC	plug/plug	5093260	Combination protection
PCS 1904	N	1	0–3 GHz	DS-N	plug/connector	5093996	Combination protection
PCS 1905	N	1	0–3 GHz	DS-N	connector/connector	5093988	Combination protection
PCS 1906	Jul 16	1	0–3 GHz	DS-7 16	plug/connector	5093171	Combination protection
Satellite TV	F	1	0–3.4 GHz	DS-F	plug/connector	5093275	Combination protection
	F	1	0–3.4 GHz	DS-F	connector/connector	5093272	Combination protection
	F	1	0.5–2.8 GHz	TV4+1	connector	5083400	Fine protection
	F	3	0–2.5 GHz	FC-SAT-D	plug/connector	5092816	Fine protection
C strip	N	1	0–6 GHz	DS-N-6	plug/connector	5093998	Combination protection
Sky DSL	F	1	0–3.4 GHz	DS-F	plug/connector	5093275	Combination protection
	F	1	0–3.4 GHz	DS-F	connector/connector	5093272	Combination protection
TETRA/BOS	SMA	1	0–3.7 GHz	DS-SMA	connector/connector	5093277	Combination protection
	BNC	1	0–2.2 GHz	DS-BNC	plug/connector	5093252	Combination protection
	BNC	1	0–2.2 GHz	DS-BNC	connector/connector	5093236	Combination protection
	BNC	1	0–2.2 GHz	DS-BNC	plug/plug	5093260	Combination protection
	N	1	0–3 GHz	DS-N	plug/connector	5093996	Combination protection
	N	1	0–3 GHz	DS-N	connector/connector	5093988	Combination protection
	Jul 16	1	0–3 GHz	DS-7 16	plug/connector	5093171	Combination protection



Technology	Connection	Protected wires	Frequency range	Type	Gender	Item no.	Protection type
TV	F	1	0-3.4 GHz	DS-F	plug/connector	5093275	Combination protection
	F	1	0-3.4 GHz	DS-F	connector/connector	5093272	Combination protection
	F	3	0-2.5 GHz	FC-TV-D	plug/connector	5092808	Fine protection
UMTS	SMA	1	0-3.7 GHz	DS-SMA	connector/connector	5093277	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	plug/connector	5093252	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	connector/connector	5093236	Combination protection
	BNC	1	0-2.2 GHz	DS-BNC	plug/plug	5093260	Combination protection
	N	1	0-3 GHz	DS-N	plug/connector	5093996	Combination protection
	N	1	0-3 GHz	DS-N	connector/connector	5093988	Combination protection
	TNC	1	0-4 GHz	DS-TNC	plug/connector	5093270	Combination protection
	Jul 16	1	0-3 GHz	DS-7 16	plug/connector	5093171	Combination protection
	BNC	1	0-65 MHz	Coax B-E2 MF-F	plug/connector	5082432	Fine protection
Video/CCTV	BNC	1	0-65 MHz	Coax B-E2 MF-C	plug/connector	5082430	Combination protection
	BNC	1	0-160 MHz	Coax B-E2 FF-F	plug/plug	5082434	Fine protection
	SMA	1	0-3.7 GHz	DS-SMA	connector/connector	5093277	Combination protection
Wi-Fi (2.4 GHz)	N	1	0-3 GHz	DS-N	plug/connector	5093996	Combination protection
	N	1	0-3 GHz	DS-N	connector/connector	5093988	Combination protection
	TNC	1	0-4 GHz	DS-TNC	plug/connector	5093270	Combination protection
	Wi-Fi (> 5 GHz) Standard: a/h, n, ac	N	1	0-6 GHz	DS-N-6	plug/connector	5093998
WiMAX	N	1	0-6 GHz	DS-N-6	plug/connector	5093998	Combination protection

Selection aid, data technology

Technology	Connection	Protected wires	Type	Item no.	Protection type
Arcnet	BNC	1	KoaxB-E2 FF-F	5082 43 4	Fine protection
	BNC	1	KoaxB-E2 MF-F	5082 43 2	Fine protection
	BNC	1	KoaxB-E2 MF-C	5082 43 0	Combination protection
ATM	RJ45	8	ND-CAT6A/EA	5081 80 0	Fine protection
	RJ45	8	RJ45 S-ATM 8-F	5081 99 0	Fine protection
Ethernet	Up to class 6A/EA	RJ45 (PoE)	8	ND-CAT6A/EA	5081 80 0
	Up to class 6 / E	RJ45 (PoE)	8	ND-CAT6/E-F	5081 80 2
		RJ45 (PoE)	8	ND-CAT6/E-B	5081 80 4
	Up to class 5 / D	RJ45	8	RJ45 S-ATM 8-F	5081 99 0
	10 Base 2 / 10 Base 5	BNC	1	KoaxB-E2 FF-F	5082 43 4
		BNC	1	KoaxB-E2 MF-F	5082 43 2
		BNC	1	KoaxB-E2 MF-C	5082 43 0
FDDI, CDDI	RJ45	8	ND-CAT6A/EA	5081 80 0	Fine protection
	RJ45	8	RJ45 S-ATM 8-F	5081 99 0	Fine protection
Industrial Ethernet	RJ45	8	ND-CAT6A/EA	5081 80 0	Fine protection
	RJ45	8	RJ45 S-ATM 8-F	5081 99 0	Fine protection
	Wire-to-terminal connection	20	LSA-B-MAG	5084 02 0	Combination protection
	Wire-to-terminal connection	2	LSA-BF-180	5084 02 4	Combination protection
	Wire-to-terminal connection	2	LSA-BF-24	5084 02 8	Combination protection
Power over Ethernet	RJ45 (PoE)	8	ND-CAT6A/EA	5081 80 0	Fine protection
	RJ45 (PoE)	8	ND-CAT6/E-F	5081 80 2	Fine protection
	RJ45 (PoE)	8	ND-CAT6/E-B	5081 80 4	Combination protection
Token Ring	RJ45	8	ND-CAT6A/EA	5081 80 0	Fine protection
	RJ45	8	RJ45 S-ATM 8-F	5081 99 0	Fine protection
	BNC	1	KoaxB-E2 FF-F	5082 43 4	Fine protection
	BNC	1	KoaxB-E2 MF-F	5082 43 2	Fine protection
	BNC	1	KoaxB-E2 MF-C	5082 43 0	Combination protection
RS232, V24	Wire-to-terminal connection	2	MDP-2 D-24-T	5098 42 2	Combination protection
	Wire-to-terminal connection	4	MDP-4 D-24-EX	5098 43 2	Combination protection
	Wire-to-terminal connection	2	FDB-2 24-M	5098 38 0	Combination protection
	Wire-to-terminal connection	2	FDB-2 24-N	5098 39 0	Combination protection
	Wire-to-terminal connection	2	FRD 24 HF	5098 57 5	Fine protection
	Wire-to-terminal connection	4	MDP-4 D-24-T	5098 43 1	Combination protection
	Wire-to-terminal connection	4	MDP-4 D-24-EX	5098 43 2	Combination protection
	Wire-to-terminal connection	4	ASP-V24T 4	5083 06 0	Fine protection
	Connector	9	SD09-V24 9	5080 05 3	Fine protection
	Connector	15	SD15-V24 15	5080 15 0	Fine protection
VG Any LAN	RJ45	8	ND-CAT6A/EA	5081 80 0	Fine protection
Voice over IP	RJ45	8	ND-CAT6A/EA	5081 80 0	Fine protection
4-wire information technology systems	RJ45	4	RJ45 S-E100 4-B	5081 00 1	Combination protection
	RJ45	4	RJ45 S-E100 4-C	5081 00 3	Combination protection
	RJ45	4	RJ45 S-E100 4-F	5081 00 5	Fine protection

Selection aid, telecommunications



Technology	Connection	Protected wires	Mounting/note	Type	Item no.	Protection type
a/b - analogue	RJ11	4	Various	RJ11-TELE 4-C	5081975	Combination protection
	RJ11	4	Various	RJ11-TELE 4-F	5081977	Fine protection
	RJ45	4	Various	RJ45-TELE 4-C	5081982	Combination protection
	RJ45	4	Various	RJ45-TELE 4-F	5081984	Fine protection
	Wire-to-terminal connection	2	DIN rail	TD-2/D-HS	5081694	Combination protection
	Wire-to-terminal connection	4	Wall mounting	TD-4/I	5081690	Combination protection
	Wire-to-terminal connection	4	Wall mounting	TD-4/I-TAE-F	5081692	Combination protection
	Wire-to-terminal connection	2	Wall mounting	TD-2D-V	5081698	Combination protection
	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	DIN rail	TKS-B	5097976	Basic protection
	TAE/RJ11 / Connector	2	Socket	FC-TAE-D	5092824	Fine protection
ADSL	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	DIN rail	TD-2/D-HS	5081694	Combination protection
	Wire-to-terminal connection	4	Wall mounting	TD-4/I	5081690	Combination protection
	Wire-to-terminal connection	4	Wall mounting	TD-4/I-TAE-F	5081692	Combination protection
	Wire-to-terminal connection	2	Wall mounting	TD-2D-V	5081698	Combination protection
	Wire-to-terminal connection	2	DIN rail	TKS-B	5097976	Basic protection
ADSL2+	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	Wall mounting	TD-2D-V	5081698	Combination protection
	Wire-to-terminal connection	2	DIN rail	TKS-B	5097976	Basic protection
SDSL/SHDSL	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	Wall mounting	TD-2D-V	5081698	Combination protection
	Wire-to-terminal connection	2	DIN rail	TKS-B	5097976	Basic protection
VDSL	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	Wall mounting	TD-2D-V	5081698	Combination protection
	Wire-to-terminal connection	2	DIN rail	TKS-B	5097976	Basic protection

Selection aid, telecommunications

Technology	Connection	Protected wires	Mounting/note	Type	Item no.	Protection type
VDSL2	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	Wall mounting	TD-2D-V	5081698	Combination protection
	Wire-to-terminal connection	2	DIN rail	TKS-B	5097976	Basic protection
ISDN basic connection (U_{k0})	Wire-to-terminal connection	2	DIN rail	TD-2/D-HS	5081694	Combination protection
	Wire-to-terminal connection	4	Wall mounting	TD-4/I	5081690	Combination protection
	Wire-to-terminal connection	4	Wall mounting	TD-4/I-TAE-F	5081692	Combination protection
	Wire-to-terminal connection	20	LSA / can only be used WITH LSA-ALEI or LSA-T-LEI	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA / can only be used WITH LSA-ALEI or LSA-T-LEI	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	DIN rail	TKS-B	5097976	Basic protection
	RJ11	4	Various	RJ11-TELE 4-C	5081975	Combination protection
	RJ11	4	Various	RJ11-TELE 4-F	5081977	Fine protection
	RJ45	4	Various	RJ45-TELE 4-C	5081982	Combination protection
	RJ45	4	Various	RJ45-TELE 4-F	5081984	Fine protection
ISDN basic connection (S_0)	RJ45	8	Various	ND-CAT6A/EA	5081800	Fine protection
	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	LSA	LSA-BF-24	5084028	Combination protection
	RJ11/connector	4	Socket	FC-ISDN-D	5092812	Fine protection
ISDN Primary Rate Interface (S_{2m}/U_{2m})	RJ11	4	Various	RJ11-TELE 4-C	5081975	Combination protection
	RJ11	4	Various	RJ11-TELE 4-F	5081977	Fine protection
	RJ45	4	Various	RJ45-TELE 4-C	5081982	Combination protection
	RJ45	4	Various	RJ45-TELE 4-F	5081984	Fine protection
	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
Datex-P	Spring terminal	4	DIN rail	MDP-4 D-24-T-10	5098433	Combination protection
G.703/G.704	RJ45	8	Various	RJ45-S-ATM 8-F	5081990	Fine protection
	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	LSA	LSA-BF-24	5084028	Combination protection
	Wire-to-terminal connection	2	DIN rail	TKS-B	5097976	Basic protection
	Wire-to-terminal connection	2	DIN rail	TD-2/D-HS	5081694	Combination protection
	Wire-to-terminal connection	4	Wall mounting	TD-4/I	5081690	Combination protection
	Wire-to-terminal connection	4	Wall mounting	TD-4/I-TAE-F	5081692	Combination protection





Technology	Connection	Protected wires	Mounting/note	Type	Item no.	Protection type
E1	RJ45	8	Various	RJ45 S-ATM 8-F	5081990	Fine protection
	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	LSA	LSA-BF-24	5084028	Combination protection
Various telecom systems	Wire-to-terminal connection	20	LSA	LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA	LSA-BF-180	5084024	Combination protection
	Wire-to-terminal connection	2	LSA	LSA-BF-24	5084028	Combination protection
	Wire-to-terminal connection	2	DIN rail	TKS-B	5097976	Basic protection
	Wire-to-terminal connection	2	DIN rail	TD-2/D-HS	5081694	Combination protection
	Wire-to-terminal connection	4	Wall mounting	TD-4/I	5081690	Combination protection
	Wire-to-terminal connection	4	Wall mounting	TD-4/I-TAE-F	5081692	Combination protection
	RJ11	4	Various	RJ11-TELE 4-C	5081975	Combination protection
	RJ11	4	Various	RJ11-TELE 4-F	5081977	Fine protection
	RJ45	4	Various	RJ45-TELE 4-C	5081982	Combination protection
	RJ45	4	Various	RJ45-TELE 4-F	5081984	Fine protection
	RJ45	8	Various	RJ45 S-ATM 8-F	5081990	Fine protection
	RJ45	8	Various	ND-CAT6A/EA	5081800	Fine protection
	RJ11/connector	4	Socket	FC-RJ-D	5092828	Fine protection

Selection aid, measurement and control systems

Interface	Connection	Protected wires	Mounting	#EX icon	FS**	Type	Item no.	Protection rating
RS232, V24	Spring terminal	2	DIN rail			MDP-2 D-24-T	5098422	Combination protection
	Spring terminal	4	DIN rail	✓		MDP-4 D-24-EX	5098432	Combination protection
	Spring terminal	4	DIN rail			MDP-4 D-24-T	5098431	Combination protection
	Spring terminal	4	DIN rail	✓		MDP-4 D-24-EX	5098432	Combination protection
	Wire-to-terminal connection	2	Thread – metric	✓		FDB-2 24-M	5098380	Fine protection
	Wire-to-terminal connection	2	Thread – NPT	✓		FDB-2 24-N	5098390	Fine protection
	Screw terminal	2	DIN rail			FRD 24	5098514	Fine protection
	Screwless terminal	4	Miscellaneous			ASP-V24T 4	5083060	Fine protection
	SUB-D-9	9	Connector			SD09-V24 9	5080053	Fine protection
	SUB-D-15	15	Connector			SD15-V24 15	5080150	Fine protection
RS422, V11	Wire-to-terminal connection	2	Thread – metric	✓		FDB-2 24-M	5098380	Fine protection
	Wire-to-terminal connection	2	Thread – NPT	✓		FDB-2 24-N	5098390	Fine protection
	Screw terminal	2	DIN rail			FRD 24	5098514	Combination protection
	Spring terminal	2	DIN rail			MDP-2 D-24-T	5098422	Combination protection
	Spring terminal	2	DIN rail	✓		MDP-4 D-24-EX	5098432	Combination protection
	Spring terminal	4	DIN rail			MDP-4 D-24-T	5098431	Combination protection
	Spring terminal	4	DIN rail	✓		MDP-4 D-24-EX	5098432	Combination protection
RS485	Spring terminal	2	DIN rail			MDP-2 D-5-T	5098404	Combination protection
	Spring terminal	2	DIN rail	✓		MDP-4 D-5-EX	5098432	Combination protection
	Spring terminal	4	DIN rail			MDP-4 D-5-T	5098411	Combination protection
	Spring terminal	4	DIN rail	✓		MDP-4 D-5-EX	5098432	Combination protection
	Screw terminal	2	DIN rail			FRD 5 HF	5098571	Combination protection
	SUB-D-9	9	Connector			SD-09-V11 9	5080061	Fine protection
Binary signals, ground potential-free	Spring terminal	2	DIN rail			MDP-2 D-24-T	5098422	Combination protection
	Spring terminal	2	DIN rail	✓		MDP-4 D-24-EX	5098432	Combination protection
	Wire-to-terminal connection	2	Thread – metric			FDB-2 24-M	5098380	Combination protection
	Wire-to-terminal connection	2	Thread – NPT			FDB-2 24-N	5098390	Combination protection
	Screw terminal	2	DIN rail			FRD 5 HF	5098571	Combination protection
	Screw terminal	2	DIN rail			FRD 5	5098492	Combination protection
	Screw terminal	2	DIN rail			FLD 5	5098600	Combination protection
Binary signals, common reference potential	Screw terminal	2	DIN rail			FRD 2-24	5098727	Combination protection
	Screw terminal	2	DIN rail			FLD 2-24	5098816	Combination protection

** Remote signalling



Selection aid, measurement and control systems



Interface	Connection	Protected wires	Mounting	#EX icon	FS**	Type	Item no.	Protection type
(0)4-20 mA	Spring terminal	2	DIN rail			MDP-2 D-24-T	5098422	Combination protection
	Spring terminal	2	DIN rail	✓		MDP-4 D-24-EX	5098432	Combination protection
	Spring terminal	4	DIN rail			MDP-4 D-24-T	5098431	Combination protection
	Spring terminal	4	DIN rail	✓		MDP-4 D-24-EX	5098432	Combination protection
	Wire-to-terminal connection	2	Thread – metric	✓		FDB-2 24-M	5098380	Fine protection
	Wire-to-terminal connection	2	Thread – NPT	✓		FDB-2 24-N	5098390	Fine protection
	Wire-to-terminal connection	2	LSA			LSA-B-MAG	5084020	Basic protection
	Wire-to-terminal connection	2	LSA			LSA-BF-24	5084028	Combination protection
	Spring terminal	2	DIN rail			FLD 24	5098611	Fine protection
0-10 V	Spring terminal	2	DIN rail			MDP-2 D-24-T	5098422	Combination protection
	Spring terminal	2	DIN rail	✓		MDP-4 D-24-EX	5098432	Combination protection
	Wire-to-terminal connection	2	Thread – metric	✓		FDB-2 24-M	5098380	Fine protection
	Wire-to-terminal connection	2	Thread – NPT	✓		FDB-2 24-N	5098390	Fine protection
	Screw terminal	2	DIN rail			FLD 24	5098611	Combination protection
Various DC circuits	Ground potential-free	Spring terminal	2	DIN rail		FLD 5	5098600	Combination protection
		Spring terminal	2	DIN rail		FLD 12	5098603	Combination protection
		Spring terminal	2	DIN rail		FLD 24	5098611	Combination protection
		Spring terminal	2	DIN rail		FLD 48	5098630	Combination protection
		Spring terminal	2	DIN rail		FLD 60	5098638	Combination protection
		Spring terminal	2	DIN rail		FLD 110	5098646	Combination protection
	Common reference potential	Spring terminal	2	DIN rail		FLD 2-5	5098867	Combination protection
	Common reference potential	Spring terminal	2	DIN rail		FLD 2-12	5098808	Combination protection
		Spring terminal	2	DIN rail		FLD 2-24	5098816	Combination protection
		Spring terminal	2	DIN rail		FLD 2-48	5098824	Combination protection
		Spring terminal	2	DIN rail		FLD 2-110	5098859	Combination protection
Various frequency-dependent circuits	Ground potential-free	Spring terminal	2	DIN rail		FRD 5 HF	5098571	Combination protection
		Spring terminal	2	DIN rail		FRD 24 HF	5098575	Combination protection
		Spring terminal	2	DIN rail		FRD 5	5098492	Combination protection
		Spring terminal	2	DIN rail		FRD 12	5098506	Combination protection
		Spring terminal	2	DIN rail		FRD 24	5098514	Combination protection
		Spring terminal	2	DIN rail		FRD 48	5098522	Combination protection
		Spring terminal	2	DIN rail		FRD 110	5098557	Combination protection
** Remote signalling								

Selection aid, measurement and control systems

Interface	Connection	Protected wires	Mounting	#EX icon	FS*	Type	Item no.	Protection type
2-pin power supplies 5 V	Spring terminal	4	DIN rail			MDP-4 D-5-T-10	5098413	Combination protection
2-pin power supplies 12 V	Screw terminal	2	DIN rail			VF12-AC-DC	5097453	Fine protection
	Screw terminal	2	DIN rail		✓	VF12-AC/DC-FS	5097454	Fine protection
2-pin power supplies 24 V	Screw terminal	2	DIN rail			VF24-AC/DC	5097607	Fine protection
	Screw terminal	2	DIN rail		✓	VF24-AC/DC-FS	5097820	Fine protection
2-pin power supplies 48 V	Screw terminal	2	DIN rail			VF48-AC/DC	5097615	Fine protection
	Screw terminal	2	DIN rail		✓	VF48-AC/DC-FS	5097822	Fine protection
2-pin power supplies 60 V	Screw terminal	2	DIN rail			VF60-AC/DC	5097623	Fine protection
	Screw terminal	2	DIN rail		✓	VF60-AC/DC-FS	5097824	Fine protection
2-pin power supplies 110 V	Screw terminal	2	DIN rail			VF110-AC/DC	5097631	Fine protection
2-pin power supplies 230 V	Screw terminal	2	DIN rail			VF230-AC/DC	5097650	Fine protection
	Screw terminal	2	DIN rail		✓	VF230-AC-FS	5097858	Fine protection
	Screw terminal	2	DIN rail		✓ **	VF2-230-AC/DC-FS	5097939	Fine protection
PT 100	Spring terminal	2	DIN rail			FLD 24	5098611	Combination protection
	Spring terminal	2	DIN rail			FLD 2-24	5098816	Combination protection
	Spring terminal	4	DIN rail			MDP-4 D-24-T-10	5098433	Combination protection
PT 1000	Spring terminal	2	DIN rail			FLD 24	5098611	Combination protection
	Spring terminal	2	DIN rail			FLD 2-24	5098816	Combination protection
	Spring terminal	4	DIN rail			MDP-4 D-24-T-10	5098433	Combination protection
TTL	Spring terminal	2	DIN rail			FRD 12	5098603	Combination protection
	Spring terminal	2	DIN rail			MDP-2 D-24-T	5098422	Combination protection
	SUB-D-9	9	Connector			SD09-V24 9	5080053	Fine protection
	SUB-D-15	15	Connector			SD15-V24 15	5080150	Fine protection

* Remote signalling, ** Leakage current-free



Selection aid, bus systems



Interface	Connection	Protected wires	Mounting	#EX icon	Testable	FS*	Type	Item no.	Protection type
ADVANT	Spring terminal	4	DIN rail		✓		MDP-4 D-24-T	5098431	Combination protection
ARCNET	RJ45	8	DIN rail				ND-CAT6A/EA	5081800	Fine protection
AS-I	Data cable	Spring terminal	2	DIN rail		✓	MDP-2 D-24-T-10	5098425	Combination protection
	Power supply	Spring terminal	2	DIN rail		✓	VF24-AC/DC	5097607	Fine protection
		Spring terminal	2	DIN rail		✓	VF24-AC/DCFS	5097820	Fine protection
BITBUS	Spring terminal	4	DIN rail		✓		MDP-4 D-24-T	5098431	Combination protection
BLN	Spring terminal	2	DIN rail		✓		MDP-2 D-24-T	5098422	Combination protection
	Spring terminal	2	DIN rail				FRD 24 HF	5098575	Fine protection
	Spring terminal	2	DIN rail						
CANBus	Data cable	Spring terminal	3	DIN rail		✓	MDP-3 D-5-T	5098407	Combination protection
	Power supply	Spring terminal	2	DIN rail		✓	VF24-AC/DC	5097607	Fine protection
		Spring terminal	2	DIN rail		✓	VF24-AC/DCFS	5097820	Fine protection
CAN open	Data cable	Spring terminal	4	DIN rail		✓	MDP-4 D-24-T	5098431	Combination protection
	Power supply	Spring terminal	2	DIN rail		✓	VF24-AC/DC	5097607	Fine protection
		Spring terminal	2	DIN rail		✓	VF24-AC/DCFS	5097820	Fine protection
C-BUS	Spring terminal	2	DIN rail				MDP-2 D-24-T	5098422	Combination protection
	Spring terminal	2	DIN rail				FRD 24 HF	5098575	Combination protection
	Spring terminal	2	DIN rail						
CC-Link	Data cable	Spring terminal	4	DIN rail		✓	MDP-4-D-24-T	5098431	Combination protection
	Power supply	Spring terminal	2	DIN rail		✓	VF24-AC/DC	5097607	Fine protection
		Spring terminal	2	DIN rail		✓	VF24-AC/DCFS	5097820	Fine protection
Data Highway Plus	Spring terminal	4	DIN rail		✓		MDP-4 D-24-T	5098431	Combination protection
Device Net	Data cable	Spring terminal	4	DIN rail		✓	MDP-4 D-24-T	5098431	Combination protection
	Power supply	Spring terminal	2	DIN rail		✓	VF24-AC/DC	5097607	Fine protection
		Spring terminal	2	DIN rail		✓	VF24-AC/DCFS	5097820	Fine protection
Dupline	Spring terminal	2	DIN rail		✓		MDP-2 D-24-T	5098422	Combination protection
	Spring terminal	2	DIN rail				FRD 24 HF	5098575	Combination protection
	Spring terminal	2	DIN rail						
eBUS	Spring terminal	2	DIN rail		✓		MDP-2 D-48-T	5098442	Combination protection
	Spring terminal	2	DIN rail				FRD 48	5098522	Fine protection
	Spring terminal	2	DIN rail						
EIB	Spring terminal	2	DIN rail		✓		MDP-2 D-24-T-10	5098425	Combination protection
	Spring terminal	4	DIN rail		✓		MDP-4 D-24-T-10	5098433	Combination protection
	Spring terminal	2	DIN rail				TKS-B	5097976	Basic protection
ET 200	Spring terminal	2	DIN rail				FRD 5	5098492	Fine protection
	Spring terminal	2	DIN rail		✓		MDP-2 D-5-T	5098404	Combination protection
	Spring terminal	4	DIN rail		✓		MDP-4 D-24-T	5098431	Combination protection
FIPIO/FIPWAY	Spring terminal	4	DIN rail		✓		MDP-4 D-5-T	5098411	Combination protection
	Spring terminal	2	DIN rail		✓		MDP-2 D-48-T	5098450	Combination protection
	Spring terminal	2	DIN rail	✓	✓		MDP-4 D-48-EX	5098452	Combination protection
Foundation Fieldbus	Spring terminal	2	Thread - metric	✓			FDB-2 24-M	5098380	Combination protection
	Spring terminal	2	Thread - NPT	✓			FDB-2 24-N	5098390	Combination protection
	Spring terminal	2	DIN rail		+		FRD 5	5098492	Fine protection
FSK	Spring terminal	2	DIN rail		+		MDP-2 D-5-T	5098404	Combination protection
	Spring terminal	4	DIN rail		+		MDP-4 D-24-T	5098431	Combination protection
Genius	Spring terminal	4	DIN rail						

* Remote signalling

Selection aid, bus systems

Interface	Connection	Protected wires	Mounting	#EX icon	Testable	Type	Item no.	Protection type
HARD	Spring terminal	2	DIN rail			FRD 24	5098514	Combination protection
	Spring terminal	2	DIN rail		✓	MDP-2 D-24-T	5098422	Combination protection
	Spring terminal	4	DIN rail		✓	MDP-4 D-24-T	5098431	Combination protection
	Spring terminal	4	DIN rail	✓		MDP-4 D-24-EX	5098432	Combination protection
	Wire-to-terminal connection	4	Thread – metric	✓		FDB-2 24-M	5098380	Fine protection
	Wire-to-terminal connection	4	Thread – NPT	✓		FDB-2 24-N	5098390	Fine protection
IEC bus	Spring terminal	4	DIN rail		✓	MDP-4 D-5-T	5098411	Combination protection
Interbus Inline (I/O)s	Spring terminal	4	DIN rail		✓	MDP-4 D-24-T	5098422	Combination protection
Interbus Loop	Spring terminal	2	DIN rail		✓	MDP-4 D-24-T-10	5098433	Combination protection
KNX	Spring terminal	2	DIN rail			TKS-B	5097976	Basic protection
LON	Spring terminal	2	DIN rail			FRD 48	5098522	Combination protection
	Spring terminal	2	DIN rail		✓	MDP-2 D-48-T	5098442	Combination protection
LRE	Spring terminal	2	DIN rail			FRD 5	5098492	Combination protection
	Spring terminal	2	DIN rail		✓	MDP-2 D-5-T	5098404	Combination protection
LUXMATE	Spring terminal	4	DIN rail			MDP-4 D-5-T	5098411	Combination protection
M-BUS	Spring terminal	2	DIN rail			FRD 24	5098514	Combination protection
	Spring terminal	2	DIN rail		✓	MDP-2 D-24-T	5098422	Combination protection
Melsec Net 2	BNC	1	Miscellaneous			DS-BNC m/f	5093252	Basic protection
Melsec Net 3	BNC	1	Miscellaneous			DS-BNC f/f	5093236	Basic protection
Melsec Net 4	BNC	1	Miscellaneous			DS-BNC f/m	5093260	Basic protection
MODBUS	Spring terminal	4	DIN rail		✓	MDP-4 D-24-T	5098431	Combination protection
MPI bus	Spring terminal	2	DIN rail			FRD 5	5098492	Combination protection
	Spring terminal	2	DIN rail		✓	MDP-2 D-5-T	5098404	Combination protection
	Spring terminal	4	DIN rail		✓	MDP-4 D-5-T	5098411	Combination protection
	Spring terminal	2	DIN rail			FRD 5	5098492	Combination protection
N1 LAN	Spring terminal	2	DIN rail			MDP-2 D-5-T	5098404	Combination protection
	Spring terminal	20	DIN rail			LSA-B-MAG	5084020	Basic protection
	Spring terminal	2	DIN rail			LSA-BF-24	5084028	Combination protection
	Spring terminal	2	DIN rail			FRD 2-5	5098794	Combination protection
N2 bus	Spring terminal	2	DIN rail		✓	MDP-2 D-5-T	5098404	Combination protection
	Spring terminal	2	DIN rail			FRD 12	5098603	Combination protection
novaNet	Spring terminal	2	DIN rail		✓	MDP-2 D-24-T	5098422	Combination protection
	Spring terminal	2	DIN rail					



Selection aid, bus systems



Interface		Connection	Protected wires	Mounting	#EX icon	Testable	FS*	Type	Item no.	Protection type	
P-BUS, Process Bus, Panel Bus	Data cable	Spring terminal	2	DIN rail				FRD 24 HF	5098575	Combination protection	
		Spring terminal	2	DIN rail		✓		MDP-2 D-24-T	5098422	Combination protection	
	Power supply	Spring terminal	2	DIN rail		✓		VF24-AC/DC	5097607	Fine protection	
		Spring terminal	2	DIN rail		✓	✓	VF24-AC/DC-FS	5097820	Fine protection	
P-NET		Spring terminal	4	DIN rail		✓		MDP-4 D-24-T	5098431	Combination protection	
Procontic CS31		Spring terminal	2	DIN rail				FRD 12	5098603	Combination protection	
		Spring terminal	2	DIN rail		✓		MDP-2 D-24-T	5098422	Combination protection	
Procontic T200		Spring terminal	4	DIN rail		✓		MDP-4 D-24-T	5098431	Combination protection	
Profibus DP		Spring terminal	2	DIN rail		✓		MDP-2 D-5-T	5098404	Combination protection	
		Screw terminal	2	DIN rail				FRD 5 HF	5098571	Combination protection	
		SUB-D-9	9	Connector				SD09-V24 9	5080053	Fine protection	
Profibus PA		Spring terminal	2	DIN rail		✓		MDP-2 D-48-T	5098442	Combination protection	
		Spring terminal	4	DIN rail	✓			MDP-4 D-48-EX	5098452	Combination protection	
		Wire-to-terminal connection	2	Metric thread	✓			FDB-2 24-M	5098380	Fine protection	
		Wire-to-terminal connection	2	Thread – NPT	✓			FDB-2 24-N	5098390	Fine protection	
Profinet		Spring terminal	8	DIN rail				ND-CAT6A/EA	5081800	Fine protection	
SafetyBUS p		Spring terminal	4	DIN rail		✓		MDP-4 D-24-T	5098431	Combination protection	
SDLC		Spring terminal	4	DIN rail		✓		MDP-4 D-24-T	5098431	Combination protection	
SIGMALOOP (SIGMASYS)		Spring terminal	2	DIN rail				FRD 24	5098514	Combination protection	
		Spring terminal	2	DIN rail		✓		MDP-4 D-24-T	5098431	Combination protection	
SIGMANET (SIGMASYS)		Spring terminal	2	DIN rail				FRD 24	5098514	Combination protection	
		Spring terminal	2	DIN rail		✓		MDP-4 D-24-T	5098431	Combination protection	
SINEC L1	SINEC L2	Spring terminal	4	DIN rail		✓		MDP-4 D-5-T	5098411	Combination protection	
* Remote signalling											

Selection aid, bus systems

Interface	Connection	Protected wires	Mounting	#EX icon	Testable	Type	Item no.	Protection type
SINEC L2	Spring terminal	2	DIN rail			FRD 5 HF	5098571	Combination protection
	Spring terminal	2	DIN rail		✓	MDP-4 D-5-T	5098411	Combination protection
	SUB-D-9	9	Connector			SD09-V24 9	5080053	Fine protection
SS97 SINIX	Spring terminal	4	DIN rail		✓	MDP-4 D-24-T	5098431	Combination protection
SUCONET	Spring terminal	4	DIN rail		✓	MDP-4 D-24-T	5098431	Combination protection
	Crimp clamp	20	LSA			LSA-B-MAG	5084020	Basic protection
	Crimp clamp	2	LSA			LSA-BF-24	5084028	Fine protection
TTL	Spring terminal	2	DIN rail			FRD 24	5098514	Combination protection
	Spring terminal	2	DIN rail		✓	MDP-2 D-24-T	5098422	Combination protection
	SUB-D-9	9	Connector			SD09-V24 9	5080053	Fine protection
	SUB-D-15	15	Connector			SD15-V24 15	5080150	Fine protection
U-BUS	Spring terminal	4	DIN rail			2x TKS-B	5097976	Basic protection



Planning aids, protection and spark gaps

Protection and spark gaps/ATEX approval 52

Installation principle for protection and spark gaps 53

Protection and spark gaps/ATEX approval



Task

OBO isolating and protective spark gaps are designed to isolate electrical system components, which under normal operating conditions are not connected together. If lightning strikes cause a potential increase in one of the electrical system components, the isolating spark gap guarantees a conductive connection and therefore equipotential bonding.



Function

As their name suggests, isolating and protective spark gaps comprise a spark gap. This gap transfers from the insulating to the current-permeable condition when an electric arc is ignited by a surge voltage. An isolating spark gap differs from a protective spark gap in its purpose for use. Isolating spark gaps isolate varying earth potentials, while the protective spark gaps are used only in roof standard open-wire lines.

Applications

- For producing an indirect connection between insulating flanges (cathodic corrosion protection).
- For bridging insulating flanges, also in potentially explosive areas (tested in accordance with ATEX Directive 2014/34/EU).
- Avoidance of drag in residual voltages, especially TT systems.
- For lightning equipotential bonding in accordance with DIN VDE 0185-305 (IEC 62305).
- For connecting different earthing systems, the aim being to make optimum use of all earthers for lightning protection equipotential bonding.
- As a measure that saves isolating connections for measuring and test purposes.

Installation principle for protection and spark gaps

Overview				
Application	Description	Type	Item no.	Product figure
Isolating spark gaps for insulating flange	<ul style="list-style-type: none"> e.g. in a gas pressure control station Particularly for Ex areas For bridging of insulating flanges or insulating threaded joints which can carry lightning currents 	EX ISG H EX ISG H350	5240030 5240031	
Spark gaps for potential isolation	<ul style="list-style-type: none"> Several earthing systems in one building, e.g. foundation earther and deep earther Connection via spark gap No electrochemical corrosion Entire earth rod surface is effective in the event of a direct lightning strike 	Type 481	5240085 Page: 443	
Open-wire connection	<ul style="list-style-type: none"> Roof stand spark gap for insulation Largest possible distance between the roof stand of a low voltage free cable and a lightning protection system Distance < 0.5 m: encapsulated spark gap in agreement with the power supply company 	Type 482	5240050 Page: 443	
Coupling of earthing systems	<ul style="list-style-type: none"> Several earthing systems on one building If the operation of special electronic equipment requires a separate earthing system, then this functional earth must be connected to the operating earth Prevention of dangerously high voltage differences An additional throttle is fitted to keep high-frequency voltages away from the functional earthing 	Type FS-V20	5099803 Page: 443	

HINWEIS!

**Isolierter Blitzschutz mit dem
OBO isCon®-System.**

**Änderungen sind nur von einer
Blitzschutzfachkraft
durchzuführen!**



Measuring and testing systems

56

Measuring and testing systems



ISOLAB testing device



Life Control testing unit

Testing surge protection devices within data cables

Often, it is necessary to check the functionality of the surge protection devices within the data cable. Of particular importance is that the actual testing of the protection devices has no negative impact on the data signal.

Testing of the arrestor upper parts V50, V25, V20 and V10

The ISOLAB testing unit allows the checking of the arrestor upper parts V50, V25, V20 and V10. A rotary controller allows the selection of the appropriate OBO Bettermann arrestor. Then, the upper part of the appropriate combination and/or surge arrestor is placed in the appropriate opening in the device. The function of the varistor is then checked by pressing the test button. Besides arrestor testing, the ISOLAB also allows insulation testing according to VDE 0100-610.

The Life Control testing unit, developed by OBO Bettermann, allows testing of the protection devices when installed, without influencing the data signal. A thin testing pin creates the contact with the integrated lightning barrier. The integrated microprocessor displays the test result on the OLED display and also emphasises it with acoustic signals. A connectable LED within the testing pin is an additional feature, allowing orientation, even in the darkest switchgear cabinet. A high-quality testing case for safe transport and the documentation of the testing results are a component part of this innovation from OBO Bettermann.



The LSC I+II lightning current meter records lightning and pulse currents (10/30) (/20) and permanently saves this event together with the date and time, tested to VDE 0185-561-6 Ed.2. (IEC 62561-6 ED. 2)

Testing of lightning protection systems with the PCS system


The peak current sensor (PCS) records and stores pulsed currents in the form of a magnetic card. This is a method of monitoring whether lightning has hit the lightning protection and which maximum lightning current has occurred.

If the PCS system is mounted between the interface from equipotential bonding to earthing system, the coupled lightning current in a building can also be measured. The results can provide information on potential damage in



the electrical installation. The PCS card is mounted by snapping a card holder onto the round conductor at a defined distance. The measuring range of the card is between 3 and 120 kA. The magnetic card reader offers the option of evaluating peak current sensors. The appropriate peak current value is shown on the display.


Alternatively, OBO Bettermann can read it off for you. In this case please contact your OBO Bettermann agency or subsidiary.



Planning aids, equipotential bonding systems

Equipotential bonding planning

60



Path of the lightning current: 1 = 100%, 2 = 50%, 3 = max. 50%

Tasks and function of internal lightning protection

The task of an internal lightning protection system is to prevent dangerous sparking within the building to be protected. Sparking can occur especially when high potential differences with metallic or electrically operated system components occur due to a conductor (arrestor) passing from the lightning current. Electrical energy and information technology systems in particular require special protection, as a direct connection between the external lightning protection system and the building installation exists via the earthing system and the equipotential bonding. In order to avoid damage inside the building, a lightning protection equipotential

bonding in accordance with DIN EN 62305 (IEC 62305) is necessary.

System components to be connected

In addition, the following system components must be connected to the equipotential bonding:

- Metal carcass of the structure
- Metal installations
- External conductive components
- Electrical energy and information technology systems

Installing the equipotential bonding

The equipotential bonding should be installed at the basement or at ground level. The electrical energy

and information technology lines must be connected to the equipotential bonding via type 1 lightning current arrestors. The arrestors must be connected to the equipotential bonding as close as possible to where the lines enter the building. The surge arrestor connection must comply with DIN VDE 0100-534. The following cross-sections apply as minimum dimensions for connections in the lightning protection equipotential bonding (unless larger cross-sections are specified in other standards):

- Copper: 16 mm²
- Aluminium: 25 mm²
- Steel: 50 mm²

Minimum dimensions of cables, protection class I to IV

Material	Cross-section of cables, which interconnect different equipotential bonding busbars or which connect to the earthing system	Cross-section of cables, which connect the internal metallic installations with the equipotential bonding busbar
Copper	16 mm ²	6 mm ²
Aluminium	25 mm ²	10 mm ²
Steel	50 mm ²	16 mm ²


Equipotential bonding systems

Very large surge voltages are caused mainly by lightning strikes on or close to energy systems. Even from several hundred metres away, lightning currents can also cause impermissible surge voltages in conductor loops, through either capacitive, inductive or galvanic coupling. Large surge voltages are coupled over a radius of up to 2 km. Switching operations involving inductive loads create dangerous surge voltages in the medium and low-voltage power networks.

Lightning discharges (LEMP: Lightning Electro Magnetic Impulse)

The international lightning protection standard IEC 62305 describes how direct lightning strikes of up to 200 kA are safely arrested. The current is coupled into the earthing system and, due to the voltage drop at the earthing resistor, half of the lightning current is coupled into the internal installation. The partial lightning current then divides itself among the power lines entering the building (number of cores of power line entering building), while around 5% enters data cables.

The voltage drop at the earthing resistor is calculated from the product of the partial lightning current (i) and the earthing resistance (R). This is then the potential difference between the local earth (equipotential bonding) and the live cables, which are earthed some distance away.



The highest surges are caused by lightning strikes. According to VDE 0185-305 (IEC 62305), lightning strikes are simulated with lightning surge currents of up to 200 kA (10/350 µs).



1	Lightning strike	100 %	$I_{imp} = \text{max } 200 \text{ kA (IEC 62305)}$
2	Earthing system	$\sim 50\%$	$I = 100 \text{ kA (50\%)}$
3	Electrical installation	$\sim 50\%$	$I = 100 \text{ kA (50\%)}$
4	lightning current	$\sim 5\%$	$I = 5 \text{ kA (5\%)}$

Typical distribution of lightning current



Planning aids, earthing systems

Basic principles of earthing	64
Decision-making aid, foundation earthers	66
Selection aid, foundation earth electrodes	67
Selection aid, ring earth electrodes	69

Earthing systems



Installing a foundation earther

The standards specify that each system must include an earthing system.

What do we mean by an "earthing system"?

We can find the required definitions in IEC 60050-826 – Low-voltage electrical installations: Terms.

- "Totality of the electrical connections and equipment used to earth a network, a system or a resource." Also:
- "Conductive element, embedded in the earth or in another specific conductive medium in electrical contact with the earth."

The tasks of an earthing system are:

- Arresting of the lightning current into the earth
- Equipotential bonding between the down-conductors
- Equipotential bonding near conductive walls of the building structure

Consequences of an improperly created earthing system:

- Dangerous surge voltages at the equipotential bonding
- No even potential course on the earthing system
- Destruction of the foundation through insufficient arresting area of the energy-rich lightning current
- Destruction of the foundation through improperly made connections (no terminal connection)
- Electrical decoupling of high amounts of lightning energy

Earther arrangement to VDE 0185-305-3 (IEC 62305-3)

Type A

- Horizontal earth electrodes
- Vertical earth electrodes (earth rods)

Type B

- Ring earth electrodes (surface earthers)
- Foundation earth electrodes


External and internal lightning protection systems

Planning methods

VDE 0185-305-3 (IEC 62305-3) demands continuous lightning protection equipotential bonding. This means individual earthing systems must be connected together to create a global earthing system.


The standard differentiates between type A and type B earthing systems. Type A earth electrodes are vertical or horizontal earthers (earth rods). Type B earth electrodes are any surface earther (ring earthers, foundation earthers). OBO Construct for earthing systems offers digital support in the planning of earthing systems.

Foundation earther – without lightning protection




Functional equipotential bonding conductor and ring earther

- Without lightning protection Insulating foundation



Functional equipotential bonding conductor and ring earther

- With lightning protection Insulating foundation



Earthing material, for use in concrete:

- Surrounded by min. 5 cm of concrete on all sides; ≤ 2 m connect to reinforcement
- Grid width max. 20 x 20 m; with EMC protection to VDE 0185-305-4: 5 x 5 m
- Unreinforced foundation: Material no. 1.4571/1.4404, V4A

Type	Item no.	Description
1	5052	Strip steel 30x3.5 mm FT
2	250 A-FT	Connector, strip steel with reinforcement FT
3	1814 FT	Terminal on reinforcement to Ø 14 mm
3	1814 FT D37	For reinforcements Ø 16–37 mm
4	205 DG L180 V4A	Earthing fixed point with axis
8	ProtectionBall	Protective cap for connection straps

Earthing and connection material, for use in the earth or cleanliness layer


- Material no. 1.4571 / 1.4404, V4A; clamps in earth with corrosion protection strip
- Min. 0.8 m deep, routing outside drainage shaft, frost apron (moist area)
- Grid: Without lightning protection: 20 x 20 m, connection between earth and concrete: Every 20 m, with lightning protection: 10 x 10 m, connection between earth and concrete: Every down-conductor

Type	Item no.	Description
5	RD 10 V4A	Round conductor Ø10 mm V4A
6	250 V4A	Terminal for round conductor and strip steel


Material for equipotential bonding

Type	Item no.	Description
7	1801 VDE	Equipotential busbar, industrial

Decision-making aid to determine the grid width of ring or foundation earthers



Selection aid, foundation earthers

Foundation earther				
Application	Designation	Type	Item no.	Product figure
Foundation earthers for lightning protection measures according to VDE 0185-305-3 (IEC 62305) and for protection measures against electric shocks according to DIN 18014	Flat conductor, galvanised steel, 30 m	5052 DIN 30X3.5	5019 34 5 Page: 380	
	Round conductor, galvanised steel, 80 m	RD 10	5021 10 3 Page: 380	
	Spacer, 250 mm long, galvanised steel	1 81 1	5014 01 8 Page: 400	
	Spacer, 400 mm long, galvanised steel	1811 I	5014 02 6 Page: 400	
	Cross-connector for flat conductors and round conductors, galvanised steel	25 0	5312 90 6 Page: 395	
	Cross-connector for flat conductor, galvanised steel	256 A-DIN 30 FT	5314 65 8 Page: 391	
	Parallel clamp, galvanised steel	259 A FT	5315 51 4 Page: 397	
	Connection terminal for reinforcing steels, galvanised steel	1814 FT	5014 46 8 Page: 398	
	Round conductor, galvanised steel with PVC jacketing, 75 m	RD 10-PVC	5021 16 2 Page: 381	
	Wall penetration, sealed against pressurised water	DW RD10	2360 04 1 Page: 398	
	Wall penetration, sealed against pressurised water	DW FL30x3.5	2360 04 3 Page: 398	

Selection aid, ring earthers for lightning protection measures

Ring earther				
Application	Designation	Type	Item no.	Product figure
Ring earther for lightning protection measures according to VDE 0185-305-3 (IEC 62305) Not suitable for loamy or wet soil!	Flat conductor, galvanised steel, 30 m	5052 DIN 30X3.5	5019 34 5 Page: 380	
	Flat conductor, galvanised steel, 60 m	5052 DIN 30X3.5	5019 34 7 Page: 380	
	Round conductor, galvanised steel, 80 m	RD 10	5021 10 3 Page: 380	
	Cross-connector for flat conductors and round conductors, galvanised steel	252 8-10 FT	5312 31 0 Page: 393	
	Cross-connector for flat conductor, galvanised steel	256 A-DIN 30 FT	5314 65 8 Page: 391	
Ring earther for lightning protection measures according to VDE 0185-305-3 (IEC 62305) Usable universally in many environments.	Flat conductor, stainless steel V4A, 25 m	5052 V4A 30X3.5	5018 73 0 Page: 380	
	Flat conductor, stainless steel V4A, 50 m	5052 V4A 30X3.5	5018 70 6 Page: 380	
	V4A stainless steel round conductor, 50 m	RD 10-V4A	5021 64 2 Page: 382	
	V4A stainless steel round conductor, 80 m	RD 10-V4A	5021 64 7 Page: 382	
	Cross-connector for flat conductors and round conductors, V4A	252 8-10 V4A	5312 31 8 Page: 393	
	Cross-connector for flat conductor, V4A	256 A-DIN 30 V4A	5314 65 9 Page: 392	
	Plastic corrosion protection strip, 10 m	356 50	2360 05 5 Page: 404	



Selection aid, ring earthers for protection measures against electric shocks

Ring earther				
Application	Designation	Type	Item no.	Product figure
Ring earthers for protection measures against electric shocks according to DIN 18014	Flat conductor, stainless steel V4A, 25 m	5052 V4A 30X3.5	5018 73 0 Page: 380	
	Flat conductor, stainless steel V4A, 50 m	5052 V4A 30X3.5	5018 70 6 Page: 380	
	V4A stainless steel round conductor, 50 m	RD 10-V4A	5021 64 2 Page: 382	
	V4A stainless steel round conductor, 80 m	RD 10-V4A	5021 64 7 Page: 382	
	Cross-connector for flat conductors and round conductors, V4A	252 8-10 V4A	5312 31 8 Page: 393	
	Cross-connector for flat conductor, V4A	256 A-DIN 30 V4A	5314 65 9 Page: 392	
	Plastic corrosion protection strip, 10 m	356 50	2360 05 5 Page: 404	



Planning aids, air-termination and down-conductor systems

Lightning protection classes	72
Materials for external lightning protection	73
Installation principle, building with flat roof	74
Installation principle, building with pitched roof	75
Determining the wind load	76

Lightning protection classes

Lightning protection classes and allocation

Before a lightning protection system is planned, the object to be protected must be assigned to one of four lightning protection classes. Efficiency in lightning protection class I is the highest at 98% and in lightning protection class IV the lowest at 81% (see table of hazard parameters). The cost of erecting a lightning protection system (e.g. necessary protection angles, distances from loops, protection profiles, distances from down-conductors) is more involved for lightning protection class I systems than for lightning protection class IV systems.

VdS Directive

The required lightning protection class is determined by assessing the damage risk in accordance with DIN EN 62305-2 (IEC 62305-2), unless specified in regulations or national guidelines, such as special building codes or model or state building codes. Lightning protection is preventive fire protection. Directive VdS 2010 (risk-oriented lightning and surge protection), published by Gesamtverband der Deutschen Versicherungswirtschaft e. V. (GDV) offers an alternative method of determining the lightning protection class.



You can obtain further information from www.vds.de, via OBO Customer Service
+49 (0)2371 7899-2000 or at www.obo.de.

Hazard parameters in dependence of lightning protection classes

Lightning protection class	Peak lightning current value min.	Peak lightning current value max.	Capture probability
I	3 kA	200 kA	98%
II	5 kA	150 kA	95%
II	10 kA	100 kA	88%
IV	16 kA	100 kA	81%

Lightning protection classes based on Directive VdS 2010

Application	Lightning protection class
Computer centres, military applications, nuclear power stations	I
Ex zones in industry and the chemicals sector	II
Photovoltaic systems > 10 kW	III
Museums, schools, hotels with more than 60 beds	III
Hospitals, churches, storage facilities, meeting places accommodating more than 100 to 200 people	III
Administrative buildings, sales points, offices and bank buildings of over 2,000 m ²	III
Residential buildings with more than 20 apartments, multi-storey buildings over 22 m high	III
Photovoltaics (< 10 KW)	III

Materials for external lightning protection



Substances and material

The following materials are preferred for use in external lightning protection systems: hot galvanised steel, rust-proof steel (VA), copper and aluminium.

Corrosion

A risk of corrosion occurs especially when joining different material types. Therefore, no copper parts may be installed above galvanised surfaces or above aluminium parts as copper particles worn away by rain or other environmental influences can penetrate the galvanised surface. In addition, a galvanic element occurs, which accelerates corrosion of the contact surface.

Examples

As you can see from the examples, the copper connection on the steel water pipe is corroded and could become detached. If two different materials that are not recommended need to be joined, bi-metal connectors can be used. The example shows the use of bi-metal connectors on a copper gutter to which an aluminium round conductor is attached. Points at increased risk of corrosion, such as insertion points into the concrete or soil, must be


corrosion-protected. A suitable coating must be applied as corrosion protection to connection points in the ground. Aluminium must not be placed directly (without a distance) on, in or under plaster, mortar or concrete or in the earth – the potential consequences of doing so are shown in our example. In the "Material combinations" table, possible metal combinations are evaluated with regard to contact corrosion in air.

Material combinations without increased risk of corrosion

	Steel, galvanised	Aluminium	Copper	Stainless steel	Titanium	Tin
Steel, galvanised	Yes	Yes	No	Yes	Yes	Yes
Aluminium	Yes	Yes	No	Yes	Yes	Yes
Copper	No	No	Yes	Yes	No	Yes
Stainless steel	Yes	Yes	Yes	Yes	Yes	Yes
Titanium	Yes	Yes	No	Yes	Yes	Yes
Tin	Yes	Yes	Yes	Yes	Yes	Yes

Installation principle, building with flat roof

In buildings with flat roofs, the grid method is generally used. Roof structures such as PV systems, air-conditioning units, roof dome lights and ventilators are protected with additional air-termination rods.



Planning aids, air-termination and down-conductor systems

1	Terminal block
2	Bridging component
3	Roof conductor holder
4	Cable bracket
5	Insulated spacer
6	Air-termination system stand
7	Air-termination rod
8	Fire protection bandage over insulated parapet cover
9	Expansion piece
10	Vario quick connector

Installation principle, building with a pitched/gabled roof

The exposed points, e.g. the ridge, chimneys and any roof structures, must be protected with air-termination systems.



1	Roof conductor holder for ridge tiles
2	Vario quick connector
3	Roof conductor holder
4	Round conductor
5	Air-termination rod
6	Cable bracket
7	Gutter clamp



The wind load describes the effect on buildings and installed systems. It must be taken into account during planning.

Determining the wind load

For decades, wind load has been an important consideration for OBO Bettermann in relation to external lightning protection. Today's calculation models and air-termination rod systems are the result of numerous studies and years of R&D experience.

The previous German standards in this area – DIN 1055:2005 Part 4: Wind loads and Part 5: Snow and ice loads, and DIN 4131: Steel antenna mounts – dealt with all load assumptions for mounts in Germany.

The Eurocodes (EC) are the result of European standardisation in the construction field. EC 0 to EC 9 cover the documents in the series DIN EN 1990 to 1999. These are supplemented by the various national annexes (NA). The NAs contain provisions that go beyond the Eurocode rules, i.e. the provisions that were previously part of the national standards.

Following the publication of the national annexes to the ECs, the old standards became invalid, following appropriate coexistence phases.



Old standard	New standard
Eurocode 1: DIN EN 1991-1-4:2010-12: Parts 1-4: General effects; wind loads + DIN EN 1991-1-4/NA: 2010-12	Eurocode 1: DIN EN 1991-1-4:2010-12: Parts 1-4: General effects; wind loads + DIN EN 1991-1-4/NA: 2010-12
DIN EN 1991-1-3: 2010-12 -; Parts 1-3: General effects; snow loads + DIN EN 1991-1-3/NA: 2010-12	DIN EN 1991-1-3: 2010-12 -; Parts 1-3: General effects; snow loads + DIN EN 1991-1-3/NA: 2010-12
Eurocode 3: DIN EN 1993-3-1: 2010-12: Parts 3-1: Towers, masts and chimneys – Towers and masts + DIN EN 1993-3-1/NA: 2010-12	Eurocode 3: DIN EN 1993-3-1: 2010-12: Parts 3-1: Towers, masts and chimneys – Towers and masts + DIN EN 1993-3-1/NA: 2010-12

Example of German national standards for the calculation of wind load

1st step: Determining the wind zone

The second factor that needs to be known when determining the wind load is the wind load zone in which the object is located.

The standards contain no statements regarding the following aspects:

- Framework masts and towers with non-parallel main legs,
- Guyed masts and chimneys,
- Cable-stayed and suspension bridges,
- Torsional vibrations.

Zone	Wind speed in m/s	Speed pressure in kN/m ²
1	22.5	0.32
2	25.0	0.39
3	27.5	0.47
4	30.0	0.56



Basic speeds and speed pressures

Wind zones in Germany according to DIN EN 1991-1-4 NA

2nd step: Determining the terrain category (TC)


Terrain-specific loads and dynamic pressures are an important element in calculating wind loads.

Terrain category (TC)	Definition
Terrain category I	Open sea; lakes with at least 5 km of open water in the wind direction; even, flat land without obstacles
Terrain category II	Terrain with hedges, individual farmsteads, buildings or trees, e.g. agricultural area
Terrain category III	Suburbs, industrial or commercial areas; forests
Terrain category IV	Urban areas in which at least 15% of the area is built up with buildings whose average height is higher than 15 m

Table 2.10: Terrain categories according to DIN EN 1991-1-4

3rd step: Determining the maximum gust speed

The tilt and slip resistance of air-termination rods must always be determined on a project-by-project basis. The reference height is the building height and two thirds of the length of the air-termination rod. The maximum gust speed at the project location must be determined.



Air-termination rod with stand

Gust speed in wind zone I				
Reference height in metres	TC I in kph	TC II in kph	TC III in kph	TC IV in kph
0	112	105	100	93
5	122	108	100	93
10	136	124	103	93
16	136	124	111	93
20	139	128	115	98
30	145	134	122	106
40	149	139	128	112
70	157	148	139	126
100	162	155	147	135

Gust speeds, wind zone I

Gust speed in wind zone II				
Reference height in metres	TC I in kph	TC II in kph	TC III in kph	TC IV in kph
0	124	117	111	104
5	136	120	111	104
10	145	131	114	104
16	152	138	123	104
20	155	142	127	109
30	161	149	136	118
40	165	154	142	125
70	174	165	155	139
100	180	172	163	150

Gust speeds, wind zone II

Gust speed in wind zone III				
Reference height in metres	TC I in kph	TC II in kph	TC III in kph	TC IV in kph
0	137	129	122	114
5	149	132	122	114
10	159	144	126	114
16	167	152	135	114
20	170	156	140	119
30	177	164	149	129
40	182	170	156	137
70	192	181	170	153
100	198	189	180	165

Gust speeds, wind zone III

Gust speed in wind zone IV				
Reference height in metres	TC I in kph	TC II in kph	TC III in kph	TC IV in kph
0	149	140	133	124
5	163	144	133	124
10	174	157	137	124
16	182	166	148	125
20	186	170	153	130
30	193	179	163	141
40	198	185	170	150
70	209	198	185	167
100	216	206	196	180

Gust speeds, wind zone IV

4th step: Determining what concrete blocks are required

Based on the maximum gust speed, the number and size (10 or 16 kg) of concrete blocks required can be determined for the air-termination rod used. The value in the tables must lie above the maximum gust speed for the location.

An example

The maximum gust speed at the location is 142 km/h.

A tapered pipe air-termination rod of type 101 VL2500 and height 2.5 m is used.

Because the value in Table 2.15 must be higher than the maximum gust speed at the location (i.e. in this case more than 142 km/h), the next possible value is 164. Three concrete blocks, each of weight 16 kg, must therefore be used.

Number of concrete blocks for tapered pipe air-termination rods

Air-termination rod height in m	1.5	2	2.5	3	3.5	4	Concrete blocks required
Type	101 VL1500	101 VL2000	101 VL2500	101 VL3000	101 VL3500	101 VL4000	
Item no.	5401980	5401983	5401986	5401989	5401993	5401995	
Wind speed kph	117	-	-	-	-	-	1 x 10 kg
	164	120	95	-	-	-	2 x 10 kg
	165	122	96	-	-	-	1 x 16 kg
	-	170	135	111	95	-	2 x 16 kg
	-	208	164	136	116	102	3 x 16 kg

Number of concrete blocks for air-termination rod, one end rounded

Air-termination rod height in m	1	1.5	2	2.5	3	Concrete blocks required
Type	101 ALU-1000	101 ALU-1500	101 ALU-2000	101 ALU-2500	101 ALU-3000	
Item no.	5401771	5401801	5401836	5401852	5401879	
Wind speed kph	97	-	-	-	-	1 x 10 kg
	196	133	103	-	-	1 x 16 kg
	-	186	143	117	100	2 x 16 kg
	-	-	173	142	121	3 x 16 kg

Number of concrete blocks for air-termination rod, one end rounded with connection strap

Air-termination rod height in m	1	1.5	Concrete blocks required
Type	101 A-L 100	101 A-L 150	
Item no.	5401808	5401859	
Wind speed kph	100	-	1 x 10 kg
	192	129	1 x 16 kg
	-	177	2 x 16 kg
	-	214	3 x 16 kg

Number of concrete blocks for insulated VA and AI air-termination rods

Air-termination rod height in m	4	6	4	6	Concrete blocks required
Material	VA	VA	AI	AI	
Item no.	5408942	5408946	5408943	5408947	
Item no. of appropriate air-termination rod stand	5408968	5408969	5408966	5408967	
Wind speed kph	120	94	120	92	3 x 16 kg
	161	122	163	122	6 x 16 kg
	194	145	197	147	9 x 16 kg
	222	165	227	168	12 x 16 kg
	246	182	252	187	15 x 16 kg

Number of concrete blocks for insulated air-termination rods with exit

Air-termination rod height in m	4	6	8	10	Concrete blocks required
Item no.	5408938	5408940	5408888	5408890	
Item no. of appropriate air-termination rod stand	5408930	5408932	5408902	5408902	
Wind speed kph	110	85	93	82	3 x 16 kg
	148	111	116	102	6 x 16 kg
	178	132	134	119	9 x 16 kg
	204	151	151	133	12 x 16 kg
	227	167	166	146	15 x 16 kg

Number of concrete blocks for isFang air-termination rod with VA tripod stand

Air-termination rod height in m	4	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	Required concrete blocks
Air-termination rod item no.	5402 864	5402 866	5402 868	5402 870	5402 872	5402 874	5402 876	5402 878	5402 880	
Item no. of appropriate air-termination rod stand	5408 968	5408 968	5408 968	5408 968	5408 969	5408 969	5408 969	5408 969	5408 969	
Wind speed kph	143	124	110	99	104	96	89	83	78	3 x 16 kg
	193	168	148	133	138	127	117	109	102	6 x 16 kg
	232	202	178	159	165	151	139	129	121	9 x 16 kg
	266	231	203	182	188	172	159	147	138	12 x 16 kg
	296	257	226	202	208	191	176	163	152	15 x 16 kg





Planning aids, insulated lightning protection

isFang air-termination rod system	84
OBO isCon® system	85
Air-termination and down-conductor system	88
Installation principle, Ex areas	89
Ex areas	90

isFang air-termination rod system

Quickly and simply installed

The OBO isFang modular air-termination rod system can offer a fast and freely terminable solution for insulated air-termination rod systems, as well as high air-termination rods for the largest possible protection angle.

Insulated variant

The insulated air-termination rods protect electrical and metallic roof structures, taking the calculated separating distance (s), according to VDE 0185-305-3 (IEC 62305-3), into account. An insulated section of 1.5 metres made of fibre-glass reinforced plastic (GFK) ensures sufficient distance to all roof structures. Even complex building structures can be protected by the comprehensive system accessories.

Aluminium variant

The 3-part air-termination rods of between 4 and 8 metres and made of aluminium complement the conventional air-termination system made of air-termination rod and block, which is used for heights of up to 4 metres. Various brackets for mounting on walls, pipes and corner pipes, as well as two tripod stands with different spreading widths, are available to fasten the various air-termination rods.



isCon®

The high voltage-resistant, insulated isCon® down conductor is the modern solution for planners and erectors of lightning protection systems, in order to maintain the necessary separation distances safely according to VDE 0185-305-3 (IEC/EN 62305-3).

As an innovative international provider of complete lightning and surge protection systems, OBO has adjusted its product range according to the different demands of our customers in the area of insulated lightning protection.

The result: We can now offer the appropriate isCon® conductor system with external certification according to the most recent testing norms (VDE V 0185-561-8/IEC TS 62561-8) for any lightning protection project.



BASIC



$s_e \leq 45 \text{ cm}$



PROFESSIONAL



$s_e \leq 75 \text{ cm}$



EX

PROFESSIONAL+



$s_e \leq 75 \text{ cm}$



PREMIUM



$s_e \leq 90 \text{ cm}$



isCon®



Technical data



BASIC

$s_e \leq 45 \text{ cm}$ 150 kA

$\varnothing 20 \text{ mm}$



Flat roof/
2 storeys



PROFESSIONAL

$s_e \leq 75 \text{ cm}$ 150 kA

$\varnothing 20 \text{ mm}$



Industrial
buildings



PROFESSIONAL+

$s_e \leq 75 \text{ cm}$ 150 kA

$\varnothing 23 \text{ mm}$



Chemicals
industry



PREMIUM

$s_e \leq 90 \text{ cm}$ 200 kA

$\varnothing 23 \text{ mm}$



Tower
blocks

Product safety and quality

The isCon® down-conductors comply with the requirements of VDE 0185-561-2 (IEC/EN 62561-2) thanks to their normative cable diameter. Numerous lightning current tests according to VDE 0185-561-1 (IEC/EN 62561-1) as well as to IEC TS 62561-8 with up to 200 kA (10/350) ensure the safe use in all lightning protection classes.

The surface-discharge-free isCon® Professional+ down-conductor is certified for the use externally in EX areas. Moreover, the isCon® Professional+ down-conductor with the additional grey outer sheath ensures protection against dangerous touch voltages to VDE 0185-305-3 (IEC/EN 62305-3).



OBO isCon® system



1	Weakly conductive EVA (ethylene vinyl acetate copolymer), UV-resistant
2	Conductive PEX (cross-linked polyethylene)
3	Insulating PEX (cross-linked polyethylene)
4	35 mm ² copper cable

Structure of the high-voltage-resistant OBO isCon® Professional + insulated down conductor

In complex installations, the required separation distance can often no longer be implemented with conventional down conductors, as the structural conditions do not permit the required distances between the air-termination systems and the electrical installations. Insulated lightning protection systems with the OBO isCon® conductors can be implemented to maintain the required separation distance.

Tested to IEC TS 62561-8: Up to 90 cm separation distance in the air and 180 cm in solid materials, and up to 200 kA lightning current.

This means that installation is possible directly on metallic and electrical structures. There is no direct arcing between the down conductor and the building to be protected.

Total flexibility on the construction site

The OBO isCon® conductors can be used flexibly. The isCon® conductor is supplied on disposable cable rolls. The user can cut it to the exact size they require and terminate it as necessary. This means: No ordering of pre-terminated cables, but rather flexible working according to actual conditions on the construction site. Special knowledge is required to be able to carry out the planning and routing of the isCon® conductors correctly. This knowledge is imparted by the current installation instructions, but can also be deepened in special OBO workshops.

OBO isCon® system: Air-termination system and down conductor



The air-termination system

The routing of the air-termination system is planned taking DIN EN 62305-3 (VDE 0185-305-3) Section 5.2 into account. The area to be protected must be designed specially according to the height and arrangement of the air-termination system.

The down-conductor

Only the connection element may be connected to the air-termination or forwarding down-conductor of the external lightning protection. The cable must be located in the protection area of the air-termination system and be fastened at a maximum distance of one metre using the installation material indicated. If cables are routed in the building, then specified protection measures, such as fire insulation, must be taken into account.

Separation distance

Calculation of the separation distance according to DIN EN 62305-3 (VDE 0185-305-3) Section 6.3 at the point the isCon® cable is connected. The length (l) should be measured from the connection point of the isCon® conductor to the next level of the lightning protection equipotential bonding (e.g. earthing system). Check whether the calculated separating distance (s) is less than the specified equivalent separating distance of the isCon® conductor.

Maximum lengths of the isCon® down-conductors

			Basic	Professional Professional Plus	Premium
I	Max. lightning current peak value	Number of down-conductors	Length at $s \leq 0.45$ m in air	Length at $s \leq 0.75$ m in air	Length at $s \leq 0.90$ m in air
		1	-	-	11,25
		2	8,52	14,20	17,05
II	150 kA	3 and more	12,78	21,31	25,57
		1	7,50	12,50	15,00
		2	11,36	18,94	22,73
III	100 kA	3 and more	17,05	28,41	34,09
		1	11,25	18,75	22,50
		2	17,05	28,41	34,09
		3 and more	25,57	42,61	51,14

An exact calculation of the separation distance verifies the possible use of the isCon® conductor.


NOTE: The values in the table apply to all type B earth rods and to those type A earth rods in which the earth resistance of the neighbouring earth electrodes does not differ by more than a factor of 2. If the earth resistance of individual electrodes deviates by more than a factor of 2, then $k_c = 1$ should be assumed.

Source: Table 12 DIN EN 62305-3:2011



Installation principle for isCon® in potentially explosive areas

In the Ex zones 1 and 21, after the first potential connection, the OBO isCon® Professional + should be connected at regular distances (0.5 metres) using a metallic conductor bracket (e.g. isCon H VA or PAE) to the equipotential bonding. If there is a lightning strike, lightning current may not flow through the equipotential bonding and it must be in the protection angle of the lightning protection system.



1	isCon® Professional + conductor
2	isFang air-termination rod 4 m with external isCon® conductor
3	isFang air-termination rod 6 m with external isCon® conductor
4	Potential connection

OBO isCon® system: Ex areas



Installation in potentially explosive areas

When planning and running a lightning protection system through Ex zones, the following rules must particularly be taken into account:

- DIN EN 62305-3 – Appendix D – "Additional information for lightning protection systems for structure in areas with the risk of explosion"
- VDE 0185-305-3 – Supplementary sheet 2 – "Additional information for special structures"

For Ex systems with Ex zone 2 and 22, supplementary sheet 2 (VDE 0185-305-3, Point 4.3) states that an Ex atmosphere will only occur in rare, unforeseen circumstances. Therefore, it is possible to position interception units in Ex zone 2 and 22, taking Appendix D in DIN EN 62305-3 (VDE 0185-305-3) into account.

In the Ex zones 1 and 21, after the first potential connection, the OBO isCon® Professional + conductor should be connected at regular distances (0.5 metres) using a metallic cable bracket (e.g. isCon® H VA or PAE) to the equipotential bonding. If there is a lightning strike, lightning current may not flow through the equipotential bonding and it must be in the protection angle of the lightning protection system.

Secure screw connectors against loosening.



OBO isCon® system: application examples



Application example: soft-covered roofs

Soft-covered roofs, for example with straw, thatch or reeds, require increased protection against lightning strikes and the resulting risk of fire.

A separate lightning protection system incorporating the isCon® Professional or Basic conductor is recommended in order to comply with the aesthetic expectations of builders and architects. The air-termination system is implemented using air-termination rods, which allow the conductor to be routed in their interior (type isFang IN). The grey variant of the isCon® conductor guarantees a high degree of protection and should be used for soft roofs. In this way, the conductor can be routed under the soft roof.

Observe the OBO isCon® system manual for detailed mounting instructions.



Application example: mobile telecommunications system

Installations such as mobile telecommunications systems must be included in the lightning protection concept, particularly in the case of refitting work.

Spatial restrictions, as well as the influence of transmission signals, can be overcome by constructing the lightning protection system using an isCon® conductor. Simple inclusion in the existing lightning protection system as well as separate lightning protection can be implemented simply and in accordance with the standards.



Aesthetic aspects

In easily visible areas, as well as wherever aesthetics are important, we recommend routing the isCon® conductor in air-termination rods. Equipotential bonding after the first 1.5 metres takes place in the rod. The entire retaining pipe is earthed, guaranteeing comprehensive equipotential bonding. A simple and visually perfect installation solution.

Test marks

	Lightning current-tested
	Lightning current-tested, Class H (100 kA)
	ELEKTROTECHNICKÝ ZKUŠEBNÍ ÚSTAV, Czech Republic
	ATEX certificate for explosive areas
	Russia, GOST The State Committee for Standards
	KEMA-KEUR, Netherlands
	Indication of metric products
	MAGYAR ELEKTROTECHNIKAI ELLENŐRZŐ INTÉZET Budapest, Hungary
	Österreichischer Verband für Elektrotechnik, Austria
	Underwriters Laboratories Inc., USA
	Eidgenössisches Starkstrominspektorat, Switzerland
	Underwriters Laboratories Inc., USA
	Verband der Elektrotechnik, Elektronik, Informationstechnik e.V., Germany
	German Association of Electricians, tested safety
	5-year warranty
	Halogen-free; without chlorine, fluorine and bromine
	INMETRO, Brazil



Pictogram explanation

Lightning protection classes

Type 1	Protection device to DIN EN 61643-11 or IEC 61643-11
Type 1+2	Combination protection device made of type 1 and type 2
Type 2	Protection device to DIN EN 61643-11 or IEC 61643-11
Type 2+3	Protection device to DIN EN 61643-11 or IEC 61643-11
Type 3	Protection device to DIN EN 61643-11 or IEC 61643-11

Lightning protection zone

LPZ 0→1	Transition from LPZ 0 to LPZ 1
LPZ 0→2	Transition from LPZ 0 to LPZ 2
LPZ 0→3	Transition from LPZ 0 to LPZ 3
LPZ 1→2	Transition from LPZ 1 to LPZ 2
LPZ 1→3	Transition from LPZ 1 to LPZ 3
LPZ 2→3	Transition from LPZ 2 to LPZ 3

Applications

FS	Remote signalling
AS	Acoustic signalling
ISDN	Integrated Service Digital Network, ISDN applications
DSL	Digital Subscriber Line, DSL applications
Analog TK	Analogue telecommunication
Cat 5	Category 5 TwisterPair
Cat 6	Channel Performance to American EIA/TIA standard
MSR	Measuring, controlling and regulating systems
TV	TV applications
SAT	SAT-TV applications
Mu	MultiBase base
LifeControl	LifeControl
EX	Intrinsically safe protection device for areas with a risk of explosions
Class Ei	Channel Performance to ISO / IEC 11801
PoE	Power over Ethernet
230/400 V System	230/400 V system
IP 54	Protection rating IP 54
IP 65	Protection rating IP 65

Metals

Alu	Aluminium
VA	Stainless steel, rustproof 1.4301
VA	Stainless steel, rustproof 1.4401
VA	Stainless steel, rustproof 1.4404
VA	Stainless steel, rustproof 1.4571
Cu	Copper
CuZn 37	Brass
St	Steel
TG	Malleable iron
Zn	Die-cast zinc

Plastics

GFK	Fibre-glass-reinforced plastic
PETR	Petrolatum
PA	Polyamide
PC	Polycarbonate
PE	Polyethylene
PP	Polypropylene
PS	Polystyrene

Surfaces

FS	Strip galvanised
F	Hot-dip galvanised
G	Electrogalvanised
FT	Hot-dip galvanised
Cu	Copper-plated
N	Nickel-plated
ZD	Galvanised, Deltatone 500

Metallic materials

Alu — Aluminium

VA (1.4301) — Stainless steel, rustproof 1.4301

VA (1.4401) — Stainless steel, rustproof 1.4401

VA (1.4404) — Stainless steel, rustproof 1.4404

VA (1.4571) — Stainless steel, rustproof 1.4571

Cu — Copper

CuZn — Brass

St — Steel

TG — Malleable iron

Electrogalvanised

Zn — Die-cast zinc



Plastic materials

GFK — Fibre-glass-reinforced plastic

Temperature resistance:

minus 50 to 130 °C.

Resistant to

High chemical resistance

Corrosion resistance

UV light resistance

PETR — Petrolatum

PA — Polyamide

Temperature resistance:

permanently up to approx. 90 °C, briefly up to about 130 °C and to about minus 40 °C*.

Chem. resistance generally as for polyethylene.

Resistant to

Petrol, benzene, diesel oil, acetone, solvents for paints and lacquers, oils and greases.

Unstable with

Bleach, most acids, chlorine.

Risk of stress cracks

Low in air-humid conditions; only with some aqueous salt solutions.

Highly desiccated parts (high temperature and extremely low air humidity) are highly sensitive to fuels and various solvents.

PA/PE — Polyamide/polyethylene

PC — Polycarbonate

Temperature resistance:

permanently up to approx. 110 °C (in water 60 °C), briefly up to 125 °C, and to below minus 35 °C.

Resistant to

Petrol, turpentine, most weak acids.

Unstable with

Acetone, benzene, chlorine, methylene chloride, most concentrated acids.

Risk of stress cracks

Relatively low.

Media which can cause tension cracking include benzene, aromatic hydrocarbons, methanol, butanol, acetone, turpentine.

PE — Polyethylene

Temperature resistance:

hard types permanently up to about 90 °C, briefly up to about 105 °C, soft types permanently up to about 80 °C, briefly up to about 100 °C and to about minus 40 °C*.

Resistant to

Alkalies and inorganic acids.

Conditionally resistant to

Acetone, organic acids, petrol, benzene, diesel oil, most oils.

Unstable with

Chlorine, hydrocarbons, oxidising acids.

Risk of stress cracks

Relatively high.

Stress cracks can be caused by, among other things, acetone, various alcohols, formic acid, ethanol, petrol, benzene, butyric acid, acetic acid, formaldehyde, various oils, petroleum, propanol, nitric acid, hydrochloric acid, sulphuric acid, soap solutions, turpentine, trichloroethylene, citric acid.

PP — Polypropylene

Temperature resistance:

permanently up to approx. 90 °C, briefly up to about 110 °C and to about minus 30 °C*.

Chem. resistance generally as for polyethylene.

Resistant to

Alkalies and inorganic acids.

Conditionally resistant to

Acetone, organic acids, petrol, benzene, diesel oil, most oils.

Unstable with

Chlorine, hydrocarbons, oxidising acids.

Risk of stress cracks

Low, only with some acids such as chromic acid, hydrofluoric acid and hydrochloric acid, as well as nitrogen oxide.

PS — Polystyrene

Temperature resistance:

Because of its relatively high sensitivity to the effects of chemicals, its use is not recommended at temperatures above normal room temperature, about 25 °C.

Resistance to cold: to about minus 40 °C*.

Resistant to

Alkalies, most acids, alcohol.

Conditionally resistant to

Oils and greases.

Unstable with

Butyric acid, concentrated nitric acid, concentrated acetic acid, acetone, ether, petrol and benzene, solvents for paints and lacquers, chlorine, diesel fuel.

Risk of stress cracks

Relatively high.

Stress cracks can be caused by, amongst other things, acetone, ether, petrol, cyclohexane, heptane, methanol, propanol and the softeners used in some PVC cable mixes.

*The minus values apply only for parts in the quiescent condition with no severe impact stress.

There is no plastic that is resistant to every chemical. The agents listed are only a small selection. Plastic parts are especially at risk in the presence of chemicals and high temperatures. Stress cracks may occur. If in doubt, please consult us and/or ask for a detailed chemical resistance table.

Stress crack formation: Stress cracks may occur if plastic parts under tension are exposed to chemicals at the same time. Parts made of polystyrene and polyethylene are particularly susceptible. Stress cracks may even be caused by agents to which the plastic in question is resistant in the absence of stress. Typical examples of parts under constant stress when used as intended: Grip clips, intermediate connectors of cable glands, ribbon clips.

Tested lightning protection components

Tightening torques

M5 = 4 Nm

M6 = 6 Nm

M8 = 12 Nm

M10 = 20 Nm

Detailed data can be provided on request.



Brief glossary of overvoltage protection

100% response lightning impulse voltage

The 100% response lightning impulse voltage is the value of the lightning impulse voltage 1.2/50 µs, causing the arrester to switch. With this testing voltage, the surge protection device must respond ten times to ten loads.

Arrestor

Arrestors are resources, which primarily consist of voltage-dependent resistors and/or spark gaps. Both elements can be switched in series or in parallel or used individually. Arrestors are used to protect other electrical resources and electrical systems against surge voltages.

Arrestor measured voltage V_c

For arrestors without a spark gap, the measured voltage is the maximum permitted effective value of the mains voltage on the arrester terminals. The measured voltage may constantly be applied to the arrester without changing its operational characteristics.

Back-up fuse before the arrestors

There must be a back-up fuse before the arrestors. If the upstream fuse is greater than the maximum approved back-up fuse of the arrester elements (see technical data of the device), the arrester must be protected selectively with the required value.

Cut-off unit

The cut-off unit cuts the arrester off from the mains or the earthing system if it is overloaded, thus preventing a fire risk and also signalling the switch-off of the protection device.

Equipotential bonding

Electrical connection, which brings the bodies of electrical resources and other conductive parts to the same or almost the same potential.

Equipotential busbar (PAS)

A terminal or rail, intended to connect the protective conductor, the equipotential bonding conductor and, if necessary, the conductor for function earthing with the earthing cable and the earthers.

Error current protection unit (RCD)

Resource for protection against electric shocks and fire protection (e.g. FI protection switches).

Lightning protection equipotential bonding system

The lightning protection equipotential bonding is a key measure in reducing the risk of fire and explosion on the room or building to be protected. The lightning protection equipotential bonding is achieved using equipotential bonding cables or arrestors, which connect the external lightning protection system, metallic parts of the building or room, the installation, the other conductive parts and the electrical energy and telecommunications systems.

Lightning protection system (LPS)

A lightning protection system (LPS) is considered as the entire system used to protect a room or building against the impact of a lightning strike. This includes both internal and external lightning protection.

Lightning protection zone (LPZ)

Lightning protection zones are those areas in which the electromagnetic environment of the lightning is to be defined and mastered. At the zone transitions, all cables and metallic parts must be integrated into the equipotential bonding system.

Lightning surge current (I_{imp})

A lightning surge current (lightning current carrying capacity per path) is a standardised surge current curve of the shape 10/350 µs. With its parameters

- Peak value
- Charge
- Specific energy

it represents the load from natural lightning currents. Type 1 lightning current arrestors (previously requirement class B) must be able to arrest such lightning currents without being destroyed.

Line follow current quenching (I_f)

The follow current – also called network follow current – is the current which flows through the surge protection device after an arresting operation and is supplied by the network. The follow current is considerably different from the continuous operating current. The level of the network follow current is dependent on the feed line from the transformer to the arrester.

Nominal current (I_n)

The nominal current is the maximum permitted operating current which may be run continually through the appropriately labelled connection terminals.

Nominal discharge surge current (I_n)

Peak value of the current flowing through the arrester with the wave shape 8/20. It is used to classify the testing of surge arrestors of type 2 (formerly requirements Class C).

Nominal frequency (f_n)

The nominal frequency is that frequency for which a resource is measured, by which it is called and upon which other nominal parameters refer.

Nominal voltage (V_n)

The rated voltage is the voltage value for which a resource is designed. In so doing it might be a direct voltage value or the effective value of a sine-form alternating voltage.

Surge protection device (SPD)

A device intended for the limitation of transient surge voltages and arresting of surge voltages. It contains at least one non-linear construction element. In general speech, surge protection devices are also termed arrestors.

Protection level (Up)

The protection level is the highest current voltage value on the terminals of the surge protection device before response.

Residual voltage (V_{res})

The peak voltage value, occurring via the terminals of the surge protection device during or immediately after the arresting surge current has flowed.

Short-circuit resistance

The surge protection device must be able to conduct the short-circuit current, until it is either interrupted by the device itself or by an internal or external cut-off unit or by mains-side over-current protection (e.g. back-up fuse).

Response time (t_a)

The response time primarily characterises the response behaviour of the individual protection elements used in arrestors. Depending on the slope du/dt of the surge voltage or di/dt of the surge current, the response times may vary within specific limits.

SPD

Surge protection device.

Surge arrester, type 1

Arrestors, which, due to their special structure, are able to arrest lightning currents or partial lightning currents during direct strikes.

Surge arrester, type 2

Arrestors, which are able to arrest surged voltages caused by remote or nearby strikes or switching actions.

Surge arrester, type 3

Arrestors, used for surge protection of individual consumers or consumer groups and are employed directly on sockets.

Surge voltage

A surge voltage is a voltage occurring briefly between conductors or between a conductor and the earth, which exceeds the highest permissible operating voltage value by a long way, but does not have the operating frequency. It can be created by storms or by earthing or shortcircuits.

Temperature range

The operating temperature specifies within which temperature limits the perfect function of the surge protection device is guaranteed.

Transmission frequency (f_g)

The transmission frequency specifies up to which frequency the insertion damping of the employed resource is less than 3 dB.

Volume resistance per path, series resistance

The volume resistance per path specifies the ohmic resistance increase of the conductor path per wire caused by the use of the surge protection device.





Diese Anlage ist mit
Überspannungsschutzgeräten
ausgerüstet.

OBO
BETTERMANN

Bei Isolationsmessungen bitte die OBO
Schutzmodule herausziehen bzw.
abklemmen.

System contains overvoltage protection
devices. Please remove or disconnect the
OBO protectors during isolation tests.

	Combination arrester MCF Compact	100
	MCD combination arrester	108
	V50 combination arrester	115
	Accessories, upper parts and bases	134

LightningController Compact - MCF100




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF100-3+NPE+FS	255	3+N/PE	IP20	1	93.500	5096987


Combination arrester, lightning current and surge arrester, type 1+2

- Protection level $\leq 1.5 \text{ kV}$
- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 100 kA (10/350), 3+NPE
- Line following current quenching 50 kA Ipeak, arrester backup fuse to 315 A gL/gG
- Fulfils the requirements of VDE-AR-N 4100 for use in pre-meter area
- Encapsulated, non-extinguishing spark gap arrester for use in distributor housings

Application: Industrial systems and buildings with external lightning protection of the highest class I to IV.



Dimensions



Connection options

MCF100-3+NPE+FS

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μs)	I_n / I_{n-N} 35 kA
Maximum discharge current (8/20 μs)	I_{max} 50 kA
Lightning surge current (10/350 μs)	I_{imp} 25 kA
Lightning surge current (10/350)	I_{total} 100 kA
Arrestor surge current (8/20 μs) [total]	I_{total} 100 kA
Protection level [L-N]	U_p 1.5 kV
Max. mains-side overcurrent protection	315 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{op} -40 - +80 °C
Protection rating	IP20
Approvals	VDE, UL
Conductor cross-section, flexible (fine-wire)	1.5 - 25 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 3 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

LightningController Compact - MCF75



Type	AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF75-3+FS	255	3	IP20	1	75.000	5096981


Combination arrester, lightning current and surge arrester, type 1+2

- Protection level $\leq 1.5 \text{ kV}$
- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 75 kA (10/350), 3-pole
- Line following current quenching 50 kA Ipeak, arrester backup fuse to 315 A gL/gG
- Fulfils the requirements of VDE-AR-N 4100 for use in pre-meter area
- Encapsulated, non-extinguishing spark gap arrester for use in distributor housings

Application: Industrial systems and buildings with external lightning protection of the highest class I to IV.




Dimensions



MCF75-3+FS

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 255 V
Nominal discharge current (8/20 μs)	I_n / I_{N-N} 35 kA
Maximum discharge current (8/20 μs)	I_{max} 50 kA
Lightning surge current (10/350 μs)	I_{imp} 25 kA
Lightning surge current (10/350)	I_{total} 75 kA
Arrestor surge current (8/20 μs) [total]	I_{total} 75 kA
Combined voltage protection level [L-PEN]	U_n / I_{PEN} 1.5 kV
Max. mains-side overcurrent protection	315 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	VDE, UL
Conductor cross-section, flexible (fine-wire)	1.5 - 25 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 3 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options



LightningController - MCF25-NAR-TNC





Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF25-NAR-TNC	255	3	IP20	1	100.800	5096950
MCF25-NAR-TNC+FS	255	3	IP20	1	102.000	5096953


Combination arrester, type 1+2, for mounting on 40 mm bus bars, for TN-C systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 25 kA (10/350) 3-pole
- Fulfils the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100

Application: Building with outside cable infeed.



Connection options



MCF25-NAR-TNC

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{mp} 8.5 kA
Lightning surge current (10/350)	I_{total} 25 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Combined voltage protection level [L-PEN]	$U_o / L-PEN$ 1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$ 442 V
Max. mains-side overcurrent protection	160 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm²

MCF25-NAR-TNC+FS

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{mp} 8.5 kA
Lightning surge current (10/350)	I_{total} 25 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Combined voltage protection level [L-PEN]	$U_o / L-PEN$ 1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$ 442 V
Max. mains-side overcurrent protection	160 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm²
FM contacts	Changeover
Switching power AC	250V/ 2A
Switching power DC	250V/ 0,1A
Connection cross-section, FM terminals	0,5 - 1,5 mm²

LightningController - MCF30-NAR-TT



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF30-NAR-TT	255	3+N/PE	IP20	1	107.504	5096961
MCF30-NAR-TT+FS	255	3+N/PE	IP20	1	107.600	5096963


Combination arrester, type 1+2, for mounting on 40 mm bus bars, for TN-S and TT systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 30 kA (10/350) 3+NPE
- Fulfils the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100


Application: Building with outside cable infeed.



Dimensions



Connection options



MCF30-NAR-TT

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_{n/20\mu s}$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 7.5 kA
Lightning surge current (10/350)	I_{total} 30 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.5 kV
Protection level [N-PE]	$U_{p/N-PE}$ 1.5 kV
Combined voltage protection level [L-PE]	$U_{p/L-PE}$ 2.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_{T/L-N, 120\text{ min}}$ 442 V
TOV voltage [N-PE] – withstand mode – 200 ms	$U_{T/N-PE, 200\text{ ms}}$ 1200 V
Max. mains-side overcurrent protection	160 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm²

MCF30-NAR-TT+FS

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_{n/20\mu s}$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 7.5 kA
Lightning surge current (10/350)	I_{total} 30 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.5 kV
Protection level [N-PE]	$U_{p/N-PE}$ 1.5 kV
Combined voltage protection level [L-PE]	$U_{p/L-PE}$ 2.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_{T/L-N, 120\text{ min}}$ 442 V
TOV voltage [N-PE] – withstand mode – 200 ms	$U_{T/N-PE, 200\text{ ms}}$ 1200 V
Max. mains-side overcurrent protection	160 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm²
FM contacts	Changeover
Switching power AC	250V/ 2A
Switching power DC	250V/ 0,1A
Connection cross-section, FM terminals	0,5 - 1,5 mm²

LightningController - MCF38-NAR-TNC




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF38-NAR-TNC	255	3	IP20	1	100.800	5096971
MCF38-NAR-TNC+FS	255	3	IP20	1	102.000	5096973

Combination arrester, type 1+2, for mounting on 40 mm bus bars, for TN-C systems


- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 38 kA (10/350) 3-pole
- Fulfils the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100

Application: Building with lightning protection or outside cable infeed.

Dimensions



Connection options



MCF38-NAR-TNC

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 38 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Combined voltage protection level [L-PEN]	$U_o / L-PEN$ 1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$ 442 V
Max. mains-side overcurrent protection	160 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm²

MCF38-NAR-TNC+FS

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 38 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Combined voltage protection level [L-PEN]	$U_o / L-PEN$ 1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$ 442 V
Max. mains-side overcurrent protection	160 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm²
FM contacts	Changeover
Switching power AC	250V/ 2A
Switching power DC	250V/ 0,1A
Connection cross-section, FM terminals	0,5 - 1,5 mm²

LightningController - MCF50-NAR-TT



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF50-NAR-TT	255	3+N/PE	IP20	1	106.700	5096975
MCF50-NAR-TT+FS	255	3+N/PE	IP20	1	107.500	5096977


Combination arrester, type 1+2, for mounting on 40 mm bus bars, for TN-S and TT systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 50 kA (10/350) 3+NPE
- Fulfils the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100


Application: Building with lightning protection or outside cable infeed.



Dimensions



Connection options



MCF50-NAR-TT

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 255 V
Nominal discharge current (8/20 μ s)	I_n / I_{N-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.5 kV
Protection level [N-PE]	$U_p / N-PE$ 1.5 kV
Combined voltage protection level [L-PE]	$U_p / L-PE$ 2.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / I_{N-N}, 120 \text{ min}$ 442 V
TOV voltage [N-PE] – withstand mode – 200 ms	$U_T / N-PE, 200 \text{ ms}$ 1200 V
Max. mains-side overcurrent protection	160 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm²

MCF50-NAR-TT+FS

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 255 V
Nominal discharge current (8/20 μ s)	I_n / I_{N-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.5 kV
Protection level [N-PE]	$U_p / N-PE$ 1.5 kV
Combined voltage protection level [L-PE]	$U_p / L-PE$ 2.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / I_{N-N}, 120 \text{ min}$ 442 V
TOV voltage [N-PE] – withstand mode – 200 ms	$U_T / N-PE, 200 \text{ ms}$ 1200 V
Max. mains-side overcurrent protection	160 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm²
FM contacts	Changeover
Switching power AC	250V/ 2A
Switching power DC	250V/ 0,1A
Connection cross-section, FM terminals	0,5 - 1,5 mm²

LightningController – MCF75-NAR-TNC




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF75-NAR-TNC	255	3	IP20	1	100.800	5096982
MCF75-NAR-TNC+FS	255	3	IP20	1	102.000	5096983

Combination arrester, type 1+2, for mounting on 40 mm bus bars, for TN-C systems


- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 75 kA (10/350) 3-pole
- Fulfils the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 315 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100

Application: Building with lightning protection or outside cable infeed.

Dimensions



Connection options



MCF75-NAR-TNC

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 25 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 25 kA
Lightning surge current (10/350)	I_{total} 75 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 75 kA
Combined voltage protection level [L-PEN]	$U_o / L-PEN$ 1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$ 442 V
Max. mains-side overcurrent protection	315 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm²

MCF75-NAR-TNC+FS

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 25 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 25 kA
Lightning surge current (10/350)	I_{total} 75 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 75 kA
Combined voltage protection level [L-PEN]	$U_o / L-PEN$ 1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$ 442 V
Max. mains-side overcurrent protection	315 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm²
FM contacts	Changeover
Switching power AC	250V/ 2A
Switching power DC	250V/ 0,1A
Connection cross-section, FM terminals	0,5 - 1,5 mm²

Voltage tap for MCF-NAR series




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF-NAR-SMG	—	—	IP20	1	5.850	5096900

Adapter for voltage tap in power-side connection compartment

- Simple and space-saving voltage taps for the termination point meter position (APZ) and the space for additional applications (RfZ)
- With spring contacts for easy connection of wires
- Includes 2 plug sockets
- Safety screw to prevent unwanted loosening
- Replaceable 5 A fine-wire fuse with a breaking capacity of 50 kA
- Fuse holder 6.3 x 32 mm



Dimensions



Connection options

Nominal voltage AC (50/60 Hz)	U _n	230 V
Nominal frequency	f	50 Hz
Operating temperature range	T _u	-40 - +80 °C
Protection rating		IP20
Conductor cross-section, flexible (fine-wire)		0.75 - 2.5 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		0.75 - 2.5 mm ²

Combination arrester, 3-pole + NPE



Type	Nominal voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 50-B 3+1	255	3 + NPE	1	168.000	5096879

Combination arrester, type 1+2, 4-pole, for use in TT and TN-S networks.


Completely pre-terminated and ready for connection, consisting of:

3x MCD 50-B: Coordinated lightning current arrester, type 1+2 to EN 61643-11 and 1x MCD 125-B/NPE: Coordinated N-PE spark gap, type 1+2 to EN 61643-11. For interface 0 to 2 (LPZ) in accordance with lightning protection zone concept to IEC 61312-1 and/or VDE 0185-305.


- Lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 50 kA (10/350) per pole and up to 125 kA (10/350) in total
- Protection level < 1.7 kV allows device protection
- Short-circuit resistance 10 kA, arrester backup fuse to 500 A gL/gG
- Suitable for use in pre-meter area according to VDE-AR-N 4100
- Encapsulated, non-extinguishing spark gaps

Application: Industrial systems and buildings with external lightning protection of the classes I to IV.

Dimensions



Connection options



MCD 50-B 3+1

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	125 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrester surge current (8/20) [total]	$I_{total\ 8/20}$	125 kA
Protection level	U_p	< 1,7 kV
Protection level (N-PE)		< 1,5 kV
Response time	t_A	<100 ns
Follow current quenching capacity leff	$I_{fi\ eff}$	10 kA
Follow current quenching capacity (eff) [N-PE]	I_{fi}	0.1 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		8
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²

Combination arrester, 3-pole + NPE with function display



Type	V	Highest continuous voltage	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 50-B 3+1-OS	255		3 + NPE	1	172.000	5096836

Combination arrester, type 1+2, 4-pole, with visual function display, for use in TN-S and TT networks.

Completely pre-terminated and ready for connection, consisting of:

3x MCD 50-B_OS: Type 1+2 (Class B) coordinated lightning current arrester EN 61643-11.
1x MCD 125-B/NPE: Coordinated N-PE spark gap, type 1+2 EN 61643-11 for use in TN-S and TT systems.


Interface 0 to 1 according to lightning protection zone concept according to IEC 61312-1 and VDE 0185-305.

- Lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 50 kA (10/350) per pole and up to 125 kA (10/350) in total
- Protection level < 1.7 kV allows device protection
- Short-circuit resistance 10 kA, arrester backup fuse to 500 A gL/gG
- Power consumption < 26 mW/pole
- Encapsulated, non-extinguishing spark gap

Application: Industrial systems and buildings with external lightning protection of Classes I to IV.




Dimensions



MCD 50-B 3+1-OS

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0-2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	125 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	125 kA
Protection level	U_p	< 1.7 kV
Protection level (N-PE)		< 1.5 kV
Response time	t_A	<100 ns
Follow current quenching capacity leff	$I_{fi\ eff}$	10 kA
Follow current quenching capacity (eff) [N-PE]	I_{fi}	0.1 kA
Maximum back-up fuse		500 A
Temperature range	θ	-40 - +85 °C
Division unit TE (17.5 mm)		8
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm²
Connection cross-section, multi-wire		10 - 35 mm²
Connection cross-section, flexible		10 - 25 mm²

Connection options



Combination arrester, 1-pole




Type	V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 50-B	255	1-pole	1	34.400	5096849

Combination arrester, type 1+2, for use in TN and TT networks


- Lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 50 kA (10/350) per pole and up to 150 kA (10/350) in total
- Protection level < 1.7 kV allows device protection
- Short-circuit resistance 10 kA, arrester backup fuse to 500 A gL/gG
- Suitable for use in pre-meter area
- Encapsulated, non-extinguishing spark gaps

Application: Industrial systems and buildings with external lightning protection of the highest class I to IV.

Dimensions



Connection options



MCD 50-B

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	50 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrester surge current (8/20) [total]	$I_{total\ 8/20}$	50 kA
Protection level	U_o	< 1.7 kV
Response time	t_A	<100 ns
Follow current quenching capacity I_{eff}	$I_{fi\ eff}$	10 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		2
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm²
Connection cross-section, multi-wire		10 - 35 mm²
Connection cross-section, flexible		10 - 25 mm²



Combination arrester, 1-pole with function display

Highest
contin-
ous
voltageType
MCD 50-B-OS | 255 | Version
V | 1-polePack
Piece | 1 | 34.800 | Weight
kg/100 pc. | Item no.
5096852

Combination arrester, type 1+2, 1-pole, for use in TN and TT networks:


MCD 50-B-OS: Coordinated lightning current arrester, type 1+2 to EN 61643-11 with visual function display. For interface 0 to 2 (LPZ) in accordance with lightning protection zone concept to IEC 61312-1 and/or DIN VDE 0185-305.

- Arresting capacity 50 kA (10/350 µs) per pole
- Power consumption < 26 mW/pole
- Protection level < 1.7 kV, allows device protection
- Line follow current quenching 25 kA Ipeak
- Incl. plug caps for labelling the connections
- Encapsulated, non-extinguishing spark gap
- Can be used in standard distributor housings.


Application: Compact surge protection concepts and installations in a distributor.



Dimensions



Connection options



MCD 50-B-OS

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imn}	50 kA
Lightning surge current (10/350)	I_{total}	50 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrestor surge current (8/20) [total]	$I_{total\ 8/20}$	50 kA
Protection level	U_D	< 1.7 kV
Response time	t_A	<100 ns
Follow current quenching capacity leff	$I_{f\ eff}$	10 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		2
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm²
Connection cross-section, multi-wire		10 - 35 mm²
Connection cross-section, flexible		10 - 25 mm²

Combination arrester, 1-pole NPE



Type	Nominal voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 125-B NPE	255	NPE	1	46.500	5096865


Combination arrester, type 1+2, N+PE for use in TN-S and TT networks.

MCD 125-B/NPE: Coordinated N-PE spark gap, type 1+2 to EN 61643-11. For interface 0 to 2 (LPZ) in accordance with lightning protection zone concept to IEC 61312-1 and/or VDE 0185-305.


- Arresting capacity 125 kA (10/350 µs)
- Conforms to VDE-AR-N 4100
- Incl. plug caps for labelling the connections
- Protection level < 1.5 kV, allows device protection
- Encapsulated, non-extinguishing spark gap

Application: Industrial systems and buildings with external lightning protection of Classes I to IV.

Dimensions



Connection options



MCD 125-B NPE

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	125 kA
Lightning surge current (10/350)	I_{total}	125 kA
Nominal discharge current (8/20)	I_n	125 kA
Arrestor surge current (8/20) [total]	$I_{total\ 8/20}$	125 kA
Protection level (N-PE)		< 1,5 kV
Response time	t_A	<100 ns
Follow current quenching capacity (eff) [N-PE]	I_f	0.1 kA
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		2
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²

Protection set PS 2-B+C TNC



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
PS 2-B+C TNC	255	2-pole	1	105.800	5089736
PS 2-B+C TNC+FS	255	2-pole	1	106.300	5089738


Protection set, lightning and surge arrester combination, type 1+2

- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 50 kA (10/350) per pole
- Arrester, connectable, including connecting bridges, labelled connection terminals
- Encapsulated, non-extinguishing arrester for use in distributor housings

Application: Mobile telecommunications systems and industrial systems with special requirements.



Dimensions



Connection options

PS 2-B+C TNC

Nominal voltage	U_N	230 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	100 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	100 kA
Maximum discharge current (8/20 µs)	I_{max}	100 kA
Protection level	U_p	1.3 kV
Response time	t_A	<25 ns
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		7
Protection rating		IP20
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²

PS 2-B+C TNC+FS

Nominal voltage	U_N	230 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	100 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	100 kA
Maximum discharge current (8/20 µs)	I_{max}	100 kA
Protection level	U_p	1.3 kV
Response time	t_A	<25 ns
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		7
Protection rating		IP20
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²

Coordinated Lightning Controller, plug-in arrester



Highest continuous voltage

Type V Version

MCD 50-B 0 | 255 | 1-pole

LPZ 0→2

230/400 V System



Pack Piece Weight kg/100 pc. Item no.

| 1 | 19.200 |


5096822

Combination arrester, lightning current arrester, type 1+2, upper part.

- Protection level < 1.7 kV, allows device protection
- Line current quenching capacity 10 kA
- Encapsulated, non-extinguishing spark gap

Application: Industrial systems and buildings with external lightning protection of Classes I to IV.

Coordinated Lightning Controller, plug-in arrester with function display



Highest continuous voltage

Type V Version

MCD 50-B 0-OS | 255 | 1-pole

Type 1+2

LPZ 0→2

230/400 V System



Pack Piece Weight kg/100 pc. Item no.

| 1 | 19.500 |

5096827

Combination arrester, type 1+2, plug-in arrester with visual display.

- Lightning current arresting capacity 50 kA (10/350)
- Power consumption < 26 mW/pole
- Protection level < 1.7 kV
- Line current quenching capacity 10 kA
- Encapsulated, non-extinguishing spark gap

Application: Installations of surge protection devices, type 1+2, in a distribution.

Combination arrester V50 in 150 V, type 1+2

Combination arrester V50, 1-pole 150 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1-150	150	1	IP20	1	15.400	5093440

PA Polyamide


Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.



Dimensions



Connection options



V50-1-150

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_C 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{N-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Protection level [L-N]	U_p 0.8 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.4 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.5 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Combination arrestor V50, with RS, 150 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1+FS-150	150	1	IP20	1	15.600	5093446


PA Polyamide

Lightning current combination arrestor, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrestor with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Dimensions



Connection options



V50-1+FS-150

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_c 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{n-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Protection level [L-N]	U_p 0.8 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.4 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.5 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG





Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-3-150	150	3	IP20	1	43.500	5093442

PA Polyamide

Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

**Dimensions****Connection options****V50-3-150**

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_c 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{N-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 37.5 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_p 0.8 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.4 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.5 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Combination arrestor V50, 3-pole with FS 150 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-3+FS-150	150	3	IP20	1	43.900	5093448


PA Polyamide

Lightning current combination arrestor, type 1+2


- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrestor with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Dimensions



Connection options



V50-3+FS-150

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_c 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{N-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 37.5 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_n 0.8 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.4 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.5 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Combination arrestor V50, 1-pole + NPE 150 V

LPZ
0→2Type
1+2

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1+NPE-150	150	1+N/PE	IP20	1	29.300	5093452

PA Polyamide


Lightning current combination arrestor, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrestor with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.



Dimensions



Connection options



V50-1+NPE-150

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U _n 120 V
Maximum continuous voltage AC	U _c 150 V
Nominal discharge current (8/20 µs)	I _n / I _N 30 kA
Maximum discharge current (8/20 µs)	I _{max} 50 kA
Lightning surge current (10/350 µs)	I _{imp} 12.5 kA
Lightning surge current (10/350)	I _{total} 25 kA
Arrestor surge current (8/20 µs) [total]	I _{total} 80 kA
Protection level [L-N]	U _n 0.8 kV
Combined voltage protection level [L-PE]	U _n / I _{PE} 2.1 kV
Residual voltage [L-N] @ 1 kA	U _{res} 0.4 kV
Residual voltage [L-N] @ 5 kA	U _{res} 0.5 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T _{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Combination arrestor V50, 1-pole + NPE with FS 150 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1+NPE+FS-150	150	1+N/PE	IP20	1	29.600	5093460


PA Polyamide

Lightning current combination arrester, type 1+2


- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Dimensions



Connection options



V50-1+NPE+FS-150

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_c 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Protection level [L-N]	U_n 0.8 kV
Combined voltage protection level [L-PE]	U_n / I_{PF} 2.1 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.4 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.5 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{op} -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0.5 A
Switching power DC	230 V; 0.1 A / 75 V; 0.5 A
Connection cross-section, FM terminals	0.5 - 1.5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Combination arrestor V50, 3-pole + NPE 150 V

LPZ
0→2Type
1+2

Highest continuous voltage AC V Pole version Protection rating

Type	Pack	Weight	Item no.
	Piece	kg/100 pc.	
V50-3+NPE-150 150	1	55.800	5093454

PA Polyamide


Lightning current combination arrestor, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrestor with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.




Dimensions



V50-3+NPE-150

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_C 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 0.8 kV
Combined voltage protection level [L-PE]	$U_{p / I-PE}$ 2.1 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,4 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.5 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options



Combination arrestor V50, 3-pole + NPE with FS 150 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-3+NPE+FS-150	150	3+N/PE	IP20	1	56.300	5093462


PA Polyamide

Lightning current combination arrestor, type 1+2


- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrestor with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Dimensions



Connection options



V50-3+NPE+FS-150

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_c 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_n 0.8 kV
Combined voltage protection level [L-PE]	U_n / I_{L-PE} 2.1 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.4 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.5 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0.5 A
Switching power DC	230 V; 0.1 A / 75 V; 0.5 A
Connection cross-section, FM terminals	0.5 - 1.5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

LPZ
0→2Type
1+2

5



KEUR



us

Combination arrestor V50, 1-pole 280 V

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1-280	280	1	IP20	1	16.400	5093500

PA Polyamide


Lightning current combination arrestor, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrestor with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.



Dimensions



Connection options



V50-1-280

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U _n 230 V
Maximum continuous voltage AC	U _C 280 V
Nominal discharge current (8/20 µs)	I _n / I _N 30 kA
Maximum discharge current (8/20 µs)	I _{max} 50 kA
Lightning surge current (10/350 µs)	I _{imp} 12.5 kA
Protection level [L-N]	U _p 1.3 kV
Residual voltage [L-N] @ 1 kA	U _{res} 0.7 kV
Residual voltage [L-N] @ 5 kA	U _{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T _u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Combination arrestor V50, 1-pole with FS 280 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1+FS-280	280	1	IP20	1	16.600	5093502


PA Polyamide

Lightning current combination arrestor, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrestor with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Dimensions



Connection options



V50-1+FS-280

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{n-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

LPZ
0→2Type
1+2

5

KEMA
KEUR

ÖVE



cULus

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-3-280	280	3	IP20	1	46.500	5093511


Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling


Application: Lightning current equipotential bonding for buildings of class III and IV.



Dimensions



Connection options

**V50-3-280**

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{N-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 37.5 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Combination arrestor V50, 3-pole with FS 280 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-3+FS-280	280	3	IP20	1	46.900	5093516

Lightning current combination arrester, type 1+2


- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Dimensions



Connection options



V50-3+FS-280

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μs)	I_n / I_{L-N} 30 kA
Maximum discharge current (8/20 μs)	I_{max} 50 kA
Lightning surge current (10/350 μs)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 37.5 kA
Arrestor surge current (8/20 μs) [total]	I_{total} 120 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

LPZ
0→2Type
1+2

5



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-4-280	280	4	IP20	1	61.000	5093513


Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.




Dimensions

**V50-4-280**

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U _n 230 V
Maximum continuous voltage AC	U _c 280 V
Nominal discharge current (8/20 µs)	I _n / I _{-N} 30 kA
Maximum discharge current (8/20 µs)	I _{max} 50 kA
Lightning surge current (10/350 µs)	I _{imp} 12.5 kA
Lightning surge current (10/350)	I _{total} 50 kA
Arrester surge current (8/20 µs) [total]	I _{total} 160 kA
Protection level [L-N]	U _p 1.3 kV
Residual voltage [L-N] @ 1 kA	U _{res} 0.7 kV
Residual voltage [L-N] @ 5 kA	U _{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T _u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options



Combination arrestor V50, 4-pole with FS 280 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-4+FS-280	280	4	IP20	1	61.500	5093518

Lightning current combination arrester, type 1+2


- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Dimensions



Connection options



V50-4+FS-280

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 160 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

LPZ
0→2Type
1+2

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1+NPE-280	280	1+N/PE	IP20	1	30.300	5093522


Lightning current combination arrestor, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrestor with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling


Application: Lightning current equipotential bonding for buildings of class III and IV.



Dimensions



Connection options

**V50-1+NPE-280**

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{N-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 25 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.3 kV
Combined voltage protection level [L-PE]	$U_{p / I-PE}$ 2.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Combination arrestor V50, 1-pole + NPE with FS 280 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1+NPE+FS-280	280	1+N/PE	IP20	1	30.600	5093531

Lightning current combination arrester, type 1+2


- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Dimensions



Connection options



V50-1+NPE+FS-280

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{N-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350 μ s)	I_{total} 25 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_n 1.3 kV
Combined voltage protection level [L-PE]	U_n / I_{N-PE} 2.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0.5 A
Switching power DC	230 V; 0.1 A / 75 V; 0.5 A
Connection cross-section, FM terminals	0.5 - 1.5 mm²
Conductor cross-section, flexible (fine-wire)	21 - 16 AWG
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

LPZ
0→2Type
1+2

Type	AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-2+NPE-280	280	2+N/PE	IP20	1	44.300	5093524


Lightning current combination arrestor, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrestor with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling


Application: Lightning current equipotential bonding for buildings of class III and IV.



Dimensions



Connection options


**V50-2+NPE-280**

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 37.5 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.3 kV
Combined voltage protection level [L-PE]	U_p / I_{-PE} 2.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG


Combination arrestor V50, 3-pole + NPE 280 V



Dimensions



Connection options



V50-3+NPE-280

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{n-N} 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_n 1.3 kV
Combined voltage protection level [L-PE]	U_n / I_{n-PE} 2.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-3+NPE+FS-280	280	3+N/PE	IP20	1	59.300	5093533


Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling


Application: Lightning current equipotential bonding for buildings of class III and IV.



Dimensions



Connection options

**V50-3+NPE+FS-280**

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U _n 230 V
Maximum continuous voltage AC	U _C 280 V
Nominal discharge current (8/20 µs)	I _n / I _N 30 kA
Maximum discharge current (8/20 µs)	I _{max} 50 kA
Lightning surge current (10/350 µs)	I _{imp} 12.5 kA
Lightning surge current (10/350)	I _{total} 50 kA
Arrester surge current (8/20 µs) [total]	I _{total} 80 kA
Protection level [L-N]	U _p 1.3 kV
Combined voltage protection level [L-PE]	U _p / I _{-PF} 2.5 kV
Residual voltage [L-N] @ 1 kA	U _{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U _{res} 0.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T _{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Combination arrester V50, 3-pole + NPE with FS 280 V

Combination arrester V50 upper part, type 1+2

Plug-in arrester V50 150 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-0-150	150	1	IP20	1	7.660	5093505

Combination arrester, type 1+2

- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current discharge capacity of 12.5 kA (10/350) per pole
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)

Plug-in arrester V50 280 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-0-280	280	1	IP20	1	8.500	5093508

Combination arrester, type 1+2

- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current discharge capacity of 12.5 kA (10/350) per pole
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)


Plug-in arrester NPE-C50



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
C50-0-255	255	N/PE	IP20	1	7.215	5095609

Cover NPE, lightning current combination arrester, type 1+2

- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current discharge capacity up to 50 kA (10/350) in total
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic according to UL 94 V-0





MCF 35-1+FS-440

UL 1449 6th
5088 874
Lightning protection
for 400/690V
power supply systems
U_L = 440 V
I_L = 35 kA
I_L = 35 kA
U_L = 2.5 kV
SPD L-PE/N [II]
I_L = 400 A g.-g.

CE 0589

0589-P1-0446
Schnellauslösevorrichtung
fast-lock device
NEM 0.039

OBO Bittermann

OBO

MCF 35-1+FS-440

UL 1449 6th
5088 974
Lightning protection
for 400/690V
power supply systems
U_L = 440 V
I_L = 35 kA
I_L = 35 kA
U_L = 2.5 kV
SPD L-PE/N [II]
I_L = 400 A g.-g.

CE 0589

0589-P1-0446
Schnellauslösevorrichtung
fast-lock device
NEM 0.039

OBO Bittermann

OBO

MCF 35-1+FS-440

UL 1449 6th
5088 974
Lightning protection
for 400/690V
power supply systems
U_L = 440 V
I_L = 35 kA
I_L = 35 kA
U_L = 2.5 kV
SPD L-PE/N [II]
I_L = 400 A g.-g.

CE 0589

0589-P1-0446
Schnellauslösevorrichtung
fast-lock device
NEM 0.039

OBO Bittermann

OBO

Surge protection device for energy technology, arrester, type 1 (industry)



Lightning arrestor MCF 35

138



Accessories MCF

140

Lightning arrester MCF 35, 400/690 V for power networks

Lightning arrester MCF 35, 400/690 V, 1-pole with IR



CE **EAC** **400 V** Type 1 LPZ 0→1

Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCF 35-1+FS-440	440	1-pole	1	98.000	5096974


AIG Die-cast aluminium

Lightning arrester type 1

- For lightning protection equipotential bonding to DIN EN 62305 (IEC 62305)
- Lightning current arresting capacity 35 kA (10/350) per pole
- Follow current extinguishing 50 kA_{eff}, arrester back-up fuse up to 400 A gL/gG
- Encapsulated, non-extinguishing spark gap arrester for use in distributor housings
- Cut-off unit with visual indicator
- Remote signalling with potential-free changeover contact

Application: Without exception for 400/690 V network systems

Dimensions



Connection options



MCF 35-1+FS-440

Nominal voltage	U_N	400 V
Max. continuous operating voltage	U_C	440 V
SPD to EN 61643-11		Type 1
SPD to IEC 61643-11		Class I
Impulse discharge current (10/350)	I_{imp}	35 kA
Nominal discharge current (8/20)	I_n	35 kA
Protection level	U_o	2,5 kV
Follow current quenching capacity leff	$I_{fi\ eff}$	50 kA
Maximum back-up fuse		400 A
Protection rating		IP20
Response time	t_A	< 100 ns
Temperature range	ϑ	-40 - +85 °C

Lightning arrestor MCF 35, 400/690 V, 3-pole with IR

400
VType
1LPZ
0→1

Type	V	Highest continuous voltage	Version	Pack	Weight	Item no.
MCF 35-P3+FS-440		440	3-pole	1	400.000	5096976

AIG Die-cast aluminium


Lightning arrestor type 1

- Fully assembled 3-pole connection unit
- For lightning protection equipotential bonding according to DIN EN 62305 (IEC 62305)
- Lightning current arresting capacity 35 kA (10/350) per pole
- Line following current quenching 50 kAeff, arrestor back-up fuse up to 400 A gL/gG
- Encapsulated, non-extinguishing spark gap arrestor for use in distributor housings
- Cut-off unit with visual indicator
- Remote signalling with potential-free changeover contact
- For finished mounting on busbars and walls

Application: Without exception for 400/690 V power systems




Dimensions



MCF 35-P3+FS-440

Nominal voltage	U_N	400 V
Max. continuous operating voltage	U_C	440 V
SPD to EN 61643-11		Type 1
SPD to IEC 61643-11		Class I
Impulse discharge current (10/350)	I_{mn}	35 kA
Nominal discharge current (8/20)	I_n	35 kA
Protection level	U_p	2,5 kV
Follow current quenching capacity eff	$I_{fi\ eff}$	50 kA
Maximum back-up fuse		400 A
Protection rating		IP20
Response time	t_A	< 100 ns
Temperature range	ϑ	-40 - +85 °C

Connection options



Accessories MCF




Version

Type	Version	Pack	Weight	Item no.
MCF-MS-P1 1-pole		1	19.600	5096992

A2 Stainless steel, rustproof 1.4301

Mounting plate 1-pole


- Mounting plate for installation of the arrestor MCF 35-1+FS-440
- Prefabricated hole pattern for mounting the arrestor on busbars
- Required screws for installation the arrestor enclosed



Mounting plate, 1-pole

Accessories MCF

Mounting plate, 1-pole, M10



Version

Type**MCF-MS-M10 | 1-pole**


A2 Stainless steel, rustproof 1.4301

Pack Piece Weight kg/100 pc. **Item no.**1 14.200 **5096990**

Mounting plate with threaded connector M10

- Mounting plate with threaded M10 connector to install the arrester MCF 35-1+FS-440
- M10 bolts for direct installation of the arrester on busbars
- Required screws for installation enclosed

Mounting plate, 3-pole



Version


Type**MCF-MS-P3 | 3-pole**

A2 Stainless steel, rustproof 1.4301

Pack Piece Weight kg/100 pc. **Item no.**1 99.800 **5096994**

Mounting plate 3-pole

- Mounting plate 3-pole for installation of the arrester MCF 35-1+FS-440
- Prefabricated hole pattern for mounting the arrester on busbars
- Suitable for wall mounting
- Required screws for installation enclosed



Diese Anlage ist mit
Überspannungsschutzgeräten
ausgerüstet.



Bei Isolationsmessungen bitte die OBO
Schutzmodule herausziehen bzw.
abklemmen.

System contains overvoltage protection
devices. Please remove or disconnect the
OBO protectors during isolation tests.

Merk-Nr. 4100 8383



V20 Überspannungsableiter Typ 2

V20 surge arrester type 2



Surge arrestor V20

144



Surge arrester V20 in 75 V, type 2

Surge arrester V20, 1-pole 75 V




Type	AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1-75	75	1	IP20	1	11.500	5095141

Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-1-75

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 60 V
Maximum continuous voltage AC	U_c 75 V
Nominal discharge current (8/20 μ s)	$I_{n / L-N}$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 40 kA
Protection level [L-N]	U_n 0.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.3 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.4 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	25 kA
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Type
2LPZ
1→2

5



OVE



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1+NPE-75	75	1+N/PE	IP20	1	22.900	5095221


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options



V20-1+NPE-75

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 60 V
Maximum continuous voltage AC	U_C 75 V
Nominal discharge current (8/20 μ s)	$I_n / I_{\cdot N}$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_p 0.5 kV
Combined voltage protection level [L-PE]	$U_{p \cdot I-PE}$ 1.2 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.3 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.4 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 75 V, type 2

Surge arrester V20, 2-pole, 75 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2-75	75	2	IP20	1	22.800	5095142

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-2-75

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 60 V
Maximum continuous voltage AC	U_c 75 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_n 0.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.3 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.4 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1-150	150	1	IP20	1	11.900	5095151


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options

**V20-1-150**

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_C 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 40 kA
Protection level [L-N]	U_p 0.8 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.5 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.6 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 150 V, type 2, for TN-S networks

Surge arrester V20, 2-pole, 150 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2-150	150	2	IP20	1	23.600	5095152

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-2-150

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_c 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_n 0.8 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.5 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.6 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Type
2LPZ
1→2

5

c^W_{us}

Surge arrester V20, 2-pole + NPE, 150 V

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2+NPE-150	150	2+N/PE	IP20	1	32.800	5095232


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options



V20-2+NPE-150

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_C 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_p 0.8 kV
Combined voltage protection level [L-PE]	$U_{p / I-PE}$ 1.2 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.5 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.6 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 150 V, type 2, for TN-S networks

Surge arrester V20, 2-pole + NPE and FS, 150 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2+NPE+FS-150	150	2+N/PE	IP20	1	33.200	5095322

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-2+NPE+FS-150

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_c 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{N-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_n 0.8 kV
Combined voltage protection level [L-PE]	U_n / I_{PF} 1.2 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.5 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.6 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{op} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0.5 A
Switching power DC	230 V; 0.1 A / 75 V; 0.5 A
Connection cross-section, FM terminals	0.5 - 1.5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20, 3-pole, 150 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3-150	150	3	IP20	1	33.000	5095153


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options



V20-3-150


SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_C 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_p 0.8 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.5 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.6 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 150 V, type 2


Surge arrester V20, 1-pole+ NPE, 150 V



Dimensions



Connection options



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1+NPE-150	150	1+N/PE	IP20	1	23.300	5095231

Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

V20-1+NPE-150

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_c 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_n 0.8 kV
Combined voltage protection level [L-PE]	U_n / I_{PF} 1.2 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.5 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.6 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{op} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Type 2

LPZ
1→2

5

c^W us

EUR

Surge arrester V20, 3-pole + NPE, 150 V

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3+NPE-150	150	3+N/PE	IP20	1	42.700	5095233


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.




Dimensions



V20-3+NPE-150

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U _n 120 V
Maximum continuous voltage AC	U _C 150 V
Nominal discharge current (8/20 µs)	I _n / I _N 20 kA
Maximum discharge current (8/20 µs)	I _{max} 40 kA
Arrestor surge current (8/20 µs) [total]	I _{total} 60 kA
Protection level [L-N]	U _p 0.8 kV
Combined voltage protection level [L-PE]	U _p / I _{-PF} 1.2 kV
Residual voltage [L-N] @ 1 kA	U _{res} 0.5 kV
Residual voltage [L-N] @ 5 kA	U _{res} 0.6 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T _{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options



Surge arrester V20 in 150 V, type 2

Surge arrester V20, 3-pole+ NPE and FS, 150 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3+NPE+FS-150	150	3+N/PE	IP20	1	43.300	5095321

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-3+NPE+FS-150

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 120 V
Maximum continuous voltage AC	U_c 150 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_n 0.8 kV
Combined voltage protection level [L-PE]	U_n / I_{PF} 1.2 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.5 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0.6 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{op} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0.5 A
Switching power DC	230 V; 0.1 A / 75 V; 0.5 A
Connection cross-section, FM terminals	0.5 - 1.5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Type
2LPZ
1→2cTMus

Surge arrestor V20, 1-pole, 280 V

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1-280	280	1	IP20	1	12.900	5095161


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options



V20-1-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U _n 230 V
Maximum continuous voltage AC	U _C 280 V
Nominal discharge current (8/20 µs)	I _n / I _N 20 kA
Maximum discharge current (8/20 µs)	I _{max} 40 kA
Arrestor surge current (8/20 µs) [total]	I _{total} 40 kA
Protection level [L-N]	U _p 1.3 kV
Residual voltage [L-N] @ 1 kA	U _{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U _{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T _u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 280 V, type 2

Surge arrester V20, 1-pole with remote signalling, 280 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1+FS-280	280	1	IP20	1	13.100	5095281

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-1+FS-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 40 kA
Protection level [L-N]	U_n 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, flexible (fine-wire)	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Type
2LPZ
1→2

5

cUL us

OVE



KEMA

Surge arrester V20, 2-pole, 280 V

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2-280	280	2	IP20	1	25.600	5095162


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options



V20-2-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 280 V, type 2, for TN-S networks

Surge arrester V20, 2-pole with remote signalling, 280 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2+FS-280	280	2	IP20	1	25.900	5095282

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-2+FS-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_n 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Type 2

LPZ
1→2

Surge arrester V20, 2-pole + NPE, 280 V

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2+NPE-280	280	2+N/PE	IP20	1	34.600	5095252


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options



V20-2+NPE-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{N-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_p 1.3 kV
Combined voltage protection level [L-PE]	U_{p+I-PE} 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 280 V, type 2, for TN-S networks

Surge arrester V20, 2-pole + NPE and remote signalling, 280 V



CE EAC

Type 2 LPZ 1→2



FS




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2+NPE+FS-280	280	2+N/PE	IP20	1	34.800	5095332

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-2+NPE+FS-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_n 1.3 kV
Combined voltage protection level [L-PE]	U_n / I_{PF} 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{op} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20, 3-pole, 280 V

Type
2LPZ
1→2

5

cUL us

OVE



KEMA

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3-280	280	3	IP20	1	36.000	5095163


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options



V20-3-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 280 V, type 2, for TN-C networks

Surge arrester V20, 3-pole with remote signalling, 280 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3+FS-280	280	3	IP20	1	36.400	5095283

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-3+FS-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Type
2LPZ
1→2

Surge arrester V20, 4-pole, 280 V

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-4-280	280	4	IP20	1	47.000	5095164


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.




Dimensions



V20-4-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U _n 230 V
Maximum continuous voltage AC	U _C 280 V
Nominal discharge current (8/20 µs)	I _n / I _N 20 kA
Maximum discharge current (8/20 µs)	I _{max} 40 kA
Arrestor surge current (8/20 µs) [total]	I _{total} 160 kA
Protection level [L-N]	U _p 1.3 kV
Residual voltage [L-N] @ 1 kA	U _{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U _{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T _u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options



Surge arrester V20 in 280 V, type 2, TN-S networks

Surge arrester V20, 4-pole with remote signalling, 280 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-4+FS-280	280	4	IP20	1	47.500	5095284

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-4+FS-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 160 kA
Protection level [L-N]	U_n 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Type 2

LPZ 1→2



Surge arrester V20, 1-pole + NPE, 280 V

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1+NPE-280	280	1+N/PE	IP20	1	24.300	5095251


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options



V20-1+NPE-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_p 1.3 kV
Combined voltage protection level [L-PE]	$U_{p \text{ / I-PE}}$ 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 280 V, type 2, TN-S and TT networks

Surge arrester V20, 1-pole + NPE and remote signalling, 280 V



CE EAC

Type 2
LPZ 1→2

FS



KEMA EUR


Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1+NPE+FS-280	280	1+N/PE	IP20	1	24.600	5095331

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-1+NPE+FS-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_n 1.3 kV
Combined voltage protection level [L-PE]	U_n / I_{PF} 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{op} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0.5 A
Switching power DC	230 V; 0.1 A / 75 V; 0.5 A
Connection cross-section, FM terminals	0.5 - 1.5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Type 2

LPZ 1→2



Surge arrester V20, 3-pole + NPE, 280 V

Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3+NPE-280	280	3+N/PE	IP20	1	45.800	5095253


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.




Dimensions



V20-3+NPE-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U _n 230 V
Maximum continuous voltage AC	U _C 280 V
Nominal discharge current (8/20 µs)	I _n / I _N 20 kA
Maximum discharge current (8/20 µs)	I _{max} 40 kA
Arrestor surge current (8/20 µs) [total]	I _{total} 60 kA
Protection level [L-N]	U _p 1.3 kV
Combined voltage protection level [L-PE]	U _p / I _{-PF} 1.5 kV
Residual voltage [L-N] @ 1 kA	U _{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U _{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T _{II} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options



Surge arrester V20 in 280 V, type 2, TN-S and TT networks

Surge arrester V20, 3-pole + NPE and remote signalling, 280 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3+NPE+FS-280	280	3+N/PE	IP20	1	46.300	5095333

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-3+NPE+FS-280

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	I_n / I_{-N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_n 1.3 kV
Combined voltage protection level [L-PE]	U_n / I_{PF} 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0.8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_{op} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0.5 A
Switching power DC	230 V; 0.1 A / 75 V; 0.5 A
Connection cross-section, FM terminals	0.5 - 1.5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1-440	440	1	IP20	1	13.600	5095201


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options

**V20-1-440**

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 400 V
Maximum continuous voltage AC	U_C 440 V
Nominal discharge current (8/20 μ s)	I_n / I_{N} 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 40 kA
Protection level [L-N]	U_p 2 kV
Residual voltage [L-N] @ 1 kA	U_{res} 1.5 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1.8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 550 V, type 2

Surge arrester V20, 1-pole, 550 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1-550	550	1	IP20	1	14.300	5095211

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-1-550

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 400 V
Maximum continuous voltage AC	U_c 550 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 15 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 40 kA
Protection level [L-N]	U_n 2.4 kV
Residual voltage [L-N] @ 1 kA	U_{res} 1.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 2.1 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2-550	550	2	IP20	1	27.000	5095212


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options

**V20-2-550**

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 400 V
Maximum continuous voltage AC	U_C 550 V
Nominal discharge current (8/20 μ s)	I_n / I_{N} 15 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 2.4 kV
Residual voltage [L-N] @ 1 kA	U_{res} 1.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 2.1 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 550 V, type 2, for TN-S networks

Surge arrester V20, 2-pole with remote signalling, 550 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2+FS-550	550	2	IP20	1	27.300	5095312

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-2+FS-550

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 480 V
Maximum continuous voltage AC	U_c 550 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 15 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_n 2.4 kV
Residual voltage [L-N] @ 1 kA	U_{res} 1.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 2.1 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20, 3-pole, 550 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3-550	550	3	IP20	1	38.100	5095213


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.



Dimensions



Connection options



V20-3-550

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 400 V
Maximum continuous voltage AC	U_C 550 V
Nominal discharge current (8/20 μ s)	I_n / I_{N} 15 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_p 2.4 kV
Residual voltage [L-N] @ 1 kA	U_{res} 1.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 2.1 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Surge arrester V20 in 550 V, type 2, for TN-C networks

Surge arrester V20, 3-pole with remote signalling, 550 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3+FS-550	550	3	IP20	1	38.500	5095313

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-3+FS-550

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 480 V
Maximum continuous voltage AC	U_c 550 V
Nominal discharge current (8/20 μ s)	I_n / I_{n-N} 15 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_n 2.4 kV
Residual voltage [L-N] @ 1 kA	U_{res} 1.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 2.1 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-4-550	550	4	IP20	1	49.800	5095214


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.




Dimensions

**V20-4-550**

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 400 V
Maximum continuous voltage AC	U_C 550 V
Nominal discharge current (8/20 μ s)	I_n / I_{N} 15 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 160 kA
Protection level [L-N]	U_p 2.4 kV
Residual voltage [L-N] @ 1 kA	U_{res} 1.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 2.1 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options



Surge arrester V20 in 550 V, type 2, for TN-S networks

Surge arrester V20, 4-pole with remote signalling, 550 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-4+FS-550	550	4	IP20	1	50.300	5095314

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Dimensions



Connection options



V20-4+FS-550

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 480 V
Maximum continuous voltage AC	U_c 550 V
Nominal discharge current (8/20 μ s)	I_n / I_{L-N} 15 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrestor surge current (8/20 μ s) [total]	I_{total} 160 kA
Protection level [L-N]	U_n 2.4 kV
Residual voltage [L-N] @ 1 kA	U_{res} 1.7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 2.1 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG




Type	AC V	Pole	Protec-	Pack	Weight	Item no.
			version	Piece	kg/100 pc.	
V20-0-75	75	1	IP20	1	3.600	5095360

Surge arrester, type 2

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)



Dimensions



Plug-in arrester V20 75 V




Type	AC V	Pole	Protec-	Pack	Weight	Item no.
			version	Piece	kg/100 pc.	
V20-0-150	150	1	IP20	1	4.160	5095362

Surge arrester, type 2

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)



Dimensions



Surge arrester V20 upper parts, type 2

Plug-in arrester V20 280 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-0-280	280	1	IP20	1	5.000	5095364

Surge arrester, type 2

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)

Dimensions




V20 cover 440 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-0-440	440	1	IP20	1	5.660	5095370

Surge arrester, type 2

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)



V20-0-440



SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 400 V
Maximum continuous voltage AC	U_c 440 V
Protection level	U_p 2 kV
Nominal discharge current (8/20 μ s)	$I_{n / L-N}$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Operating temperature range	T_{op} -40 - +80 °C
Protection rating	IP20
Approvals	UL



Plug-in arrester V20 550 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-0-550	550	1	IP20	1	6.360	5095372

Surge arrester, type 2

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)

**V20-0-550**

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 400 V
Maximum continuous voltage AC	U_c 550 V
Protection level	U_p 2.4 kV
Nominal discharge current (8/20 μ s)	$I_{n/L-N}$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL



Plug-in arrester V20 1000 V



Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-0-1000	1000	1	IP20	1	6.960	5095378

Surge arrester, type 2

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)

**V20-0-1000**

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 750 V
Maximum continuous voltage AC	U_c 1000 V
Protection level	U_p 4.2 kV
Nominal discharge current (8/20 μ s)	$I_{n/L-N}$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	—

NPE discharge gap C20 in 280 V, type 2

Plug-in arrester C20 280 V




Type	Highest continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
C20-0-255	255	N/PE	IP20	1	3.680	5095600

N-PE surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)

Dimensions




Application: Equipotential bonding in main and sub-distributors.

Connection options



C20-0-255

SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Protection level [N-PE]	$U_p / N-PE$ 1.3 kV
Nominal discharge current (8/20 μ s)	I_n / L_N 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Operating temperature range	T_{op} -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA



Keller 1 Wash.	Keller 2 Traktor	Keller 3 Licht	Keller 4 Stekdosen	Keller 5 Heizung und Pumpe	Keller 6 Garage	EG/DG DG 1 Licht	EG/DG/DG 2 Stekdosen
-------------------	---------------------	-------------------	-----------------------	----------------------------------	--------------------	---------------------	-------------------------



Front 1	Front 2	Front 3					
---------	---------	---------	--	--	--	--	--



Surge protection energy technology, arrester, type 2+3

	Surge arrestor V10 Compact	184
	Accessories, upper parts and bases V10	193
	Compact surge protection	194

Surge arrester V10 Compact

Surge arrester V10 Compact 150 V



LPZ
1→3
Type
2+3
5




Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V10 COMPACT 150	150	3 + NPE	1	15.800	5093378

Surge protection device, compact module, type 2+3


- Surge protection in sub-distributors to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 60 kA (8/20) in total
- Integrated 3+1 solution for TN and TT network systems on 45 mm module width
- High-performance varistor technology
- Incl. thermal and dynamic cut-off unit and visual function display

Application: Sub/storey distribution as well as device protection in rotational current systems.

Dimensions



Connection options



V10 COMPACT 150

Nominal voltage	U_N	130 V
Max. continuous operating voltage	U_C	150 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	60 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_n	< 0,7 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		63 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		1.5
Protection rating		IP20
Connection cross-section, rigid		2.5 - 10 mm ²
Connection cross-section, multi-wire		2.5 - 10 mm ²
Connection cross-section, flexible		2.5 - 10 mm ²

Surge arrester V10 Compact 255 V



Type	V	Highest continuous voltage	Version	Pack Piece	Weight kg/100 pc.	Item no.
V10 COMPACT 255	255		3 + NPE	1	15.800	5093380


Surge protection device, compact module, type 2+3

- Surge protection in sub-distributors to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 60 kA (8/20) in total
- Integrated 3+1 solution for TN and TT network systems on 45 mm module width
- High-performance varistor technology
- Incl. thermal and dynamic cut-off unit and visual function display


Application: Sub/storey distribution as well as device protection in rotational current systems.



Dimensions



Connection options

**V10 COMPACT 255**

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	60 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_n	< 1,1 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		63 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		1.5
Protection rating		IP20
Connection cross-section, rigid		2.5 - 10 mm ²
Connection cross-section, multi-wire		2.5 - 10 mm ²
Connection cross-section, flexible		2.5 - 10 mm ²

Surge arrestor V10 Compact

Surge arrester V10 Compact 385 V




Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V10 COMPACT 385	385	3 + NPE	1	16.800	5093384

Surge protection device, compact module, type 2+3


- Surge protection in sub-distributors to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 60 kA (8/20) in total
- Integrated 3+1 solution for TN and TT network systems on 45 mm module width
- High-performance varistor technology
- Incl. thermal and dynamic cut-off unit and visual function display

Application: Sub/storey distribution as well as device protection in rotational current systems.

Dimensions



Connection options



V10 COMPACT 385

Nominal voltage	U_N	385 V
Max. continuous operating voltage	U_C	385 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	60 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_n	< 1,5 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		63 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		1.5
Protection rating		IP20
Connection cross-section, rigid		2.5 - 10 mm ²
Connection cross-section, multi-wire		2.5 - 10 mm ²
Connection cross-section, flexible		2.5 - 10 mm ²

Surge arrester V10 Compact with audible signalling 255 V

LPZ
1→3Type
2+3Highest
contin-
ous
voltage

Type	V	Version	Designation	Pack	Weight	Item no.
V10 COMPACT-AS	255	3 + NPE	with acoustic signalling	1	15.800	5093391


Surge protection device, compact module, type 2+3

- Surge protection in sub-distributors to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 60 kA (8/20) in total
- Integrated 3+1 solution for TN and TT network systems on 45 mm module width
- High-performance varistor technology
- Including thermic and dynamic cut-off unit and visual function display
- ...-AS version with additional acoustic defect signalling (switchable)

Application: Sub/storey distribution as well as device protection in rotational current systems.




Dimensions

**V10 COMPACT-AS**

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	60 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_p	< 1,1 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		63 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		1.5
Protection rating		IP20
Connection cross-section, rigid		2.5 - 10 mm ²
Connection cross-section, multi-wire		2.5 - 10 mm ²
Connection cross-section, flexible		2.5 - 10 mm ²

Connection options



Surge arrester V10 Compact

Surge arrester V10 Compact with remote signalling 255 V




Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V10 COMPACT-FS 255	3 + NPE		1	17.300	5093382

Surge protection device, compact module, type 2+3


- Surge protection in subdistributors to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 60 kA (8/20) in total
- Integrated 3+1 solution for TN and TT network systems on 45 mm module width
- High-performance varistor technology
- Including thermic and dynamic cut-off unit and visual function display
- ...-FS version with potential-free changeover contact for remote signalling

Application: Sub/storey distribution as well as device protection in rotational current systems.

Dimensions



Connection options



V10 COMPACT-FS

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	60 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_n	< 1,1 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		63 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		1.5
Protection rating		IP20
Connection cross-section, rigid		2.5 - 10 mm ²
Connection cross-section, multi-wire		2.5 - 10 mm ²
Connection cross-section, flexible		2.5 - 10 mm ²

Upper part, surge arrester V10 280 V



Highest
contin-
uous
voltage

Type
V
V10-C 1-280

Version
280 | 1-pole

Pack
Piece
| 1 | 10.000 | **5093415**

Weight
kg/100 pc.


Surge arrester, type 2+3

- Surge protection in sub-distributors to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 20 kA (8/20) per pole
- Arrester, connectable with dynamic cut-off unit and visual function display
- High-performance varistor technology
- Base with multiple connection terminals


Application: Equipotential bonding in sub-distributors and device protection



Dimensions



Connection options

**V10-C 1-280**

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	280 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	10 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_p	< 1,1 kV
Response time	t_A	<25 ns
Maximum back-up fuse		125 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		1
Protection rating		IP20
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²

Surge arrester V10, 280 V

Surge arrester V10 3-pole + NPE 280 V




Type	V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V10-C 3+NPE	280	3 + NPE	1	37.800	5094920

Surge arrester, type 2+3


- Complete unit consisting of cover and base, pre-mounted and ready for connection
- Suitable for TN-S and TT network systems
- Incl. thermal and dynamic cut-off unit
- With visual display of defects
- High current conductivity and long service life
- Labelled connections

Application example: Residential buildings, single-family homes

Dimensions



Connection options



V10-C 3+NPE

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	280 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	40 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_n	< 1,1 kV
Response time	t_A	<25 ns
Maximum back-up fuse		125 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		4
Protection rating		IP20
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²

Surge arrester V10 3-pole + NPE with remote signalling 280 V

LPZ
1→3Type
2+3

FS



Highest
contin-
ous
voltage

Type

V10-C 3+NPE+FS

| 280

V

|

3 + NPE

Version

Pack
Piece | 1 | 37.900

kg/100 pc.

Item no.

5094931


Surge arrester, type 2+3

- Complete unit consisting of cover and base, pre-mounted and ready for connection
- Suitable for TN-S and TT network systems
- Incl. thermal and dynamic cut-off unit
- With visual display of defects
- Version ...-FS with remote signalling and potential-free NO contact for function monitoring
- High current conductivity and long service life
- Labelled connections


Application example: Residential buildings, single-family homes



Dimensions



Connection options



V10-C 3+NPE+FS

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	280 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	40 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_p	< 1,1 kV
Response time	t_A	<25 ns
Maximum back-up fuse		125 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		4
Protection rating		IP20
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²

Surge arrester V10, 280 V

Surge arrester V10 1-pole + NPE 280 V




Type	Nominal voltage U _N	Highest continuous voltage U _C	Version	Pack Piece	Weight kg/100 pc.	Item no.
V10-C 1+NPE-280	280	280	1 + NPE	1	22.200	5093418

Surge arrester, type 2+3


- Complete unit consisting of cover and base, pre-mounted and ready for connection
- Suitable for TN-S and TT network systems
- Incl. thermal and dynamic cut-off unit
- With visual display of defects
- High current conductivity and long service life
- Labelled connections

Application example: Residential buildings, single-family homes

Dimensions



Connection options



V10-C 1+NPE-280

Nominal voltage	U _N	230 V
Max. continuous operating voltage	U _C	280 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I _n	10 kA
Arrestor surge current (8/20) [total]	I _{Total 8/20}	20 kA
Maximum discharge current (8/20 µs)	I _{max}	20 kA
Protection level	U _n	< 1,1 kV
Response time	t _A	< 25 ns
Maximum back-up fuse		125 A
Temperature range	θ	-40 - +80 °C
Division unit TE (17.5 mm)		2
Protection rating		IP20
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 35 mm ²

Plug-in arrester V10 150 V



Type	V	Highest continuous voltage	Version	Pack Piece	Weight kg/100 pc.	Item no.
V10-C 0-150	150		1-pole	1	2.900	5093400


Surge arrester, type 2+3 to EN 61643-11

- Plug-in cover; cover can be separated from base without tools
- Incl. thermal and dynamic cut-off unit and visual display of defects
- High current conductivity and long service life


**V10-C 0-150**

Nominal voltage	U_N	150 V
Max. continuous operating voltage	U_C	150 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	10 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_p	< 0,7 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		125 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		1
Protection rating		IP20

Dimensions



Connection options



Surge protection for LED systems

Surge protection for LED systems 230V




Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-LED 230	255	1+NPE	1	3.500	5092480

Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids.
Appropriate for the protection of LED lighting.


- With visual function display
- Small size for the installation in the pole or in the LED lamp head
- 1+NPE protective circuit with a maximum discharge capacity of 20 kA
- Surge limitation under 1,300 V or 1,000 V @ 5 kA
- Available with or without cut-off function of the lamp in case of malfunction

Application: Universally deployable in all lighting systems

Dimensions



Connection options



ÜSM-LED 230

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_p	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m

Surge protection for LED systems 230 V IP65

LPZ
1→3Type
2+3

5

Highest
contin-
ous
voltage
V

Version

Pack

Piece

Weight

kg/100 pc.

Item no.

ÜSM-LED 230-65 | 255 | 1+NPE

| 25 | 7.500

| 5092478


Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids.
Appropriate for the protection of LED lighting and the LED driver.

- With visual function display
- Small size for the installation in the mast connection box
- IP65 and with 25 cm connection cable
- 1+NPE protective circuit with a maximum discharge capacity of 20 kA
- Surge limitation under 1,300 V or 1,000 V @ 5 kA
- Available with or without cut-off function of the lamp in case of malfunction


Application: Universally deployable in all lighting systems



Dimensions



Connection options



ÜSM-LED 230-65

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_p	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP65
Connecting cable length		0.25 m

Surge protection for LED systems

Surge protection for LED systems 440 V




Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-LED 440	440	1+NPE	1	4.500	5092482

Surge protection module type 2+3 to DIN EN 61643-11 for 440 V power grids.
Appropriate for the protection of LED lighting.


- With visual function display
- Small size for the installation in the pole or in the LED lamp head
- 1+NPE protective circuit with a maximum discharge capacity of 20 kA
- Surge limitation under 1,800 V
- Available with or without cut-off function of the lamp in case of malfunction

Application: Universally deployable in all lighting systems

Dimensions



Connection options



ÜSM-LED 440

Nominal voltage	U_N	440 V
Max. continuous operating voltage	U_C	440 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_n	1,8 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m

Surge protection for LED systems ÜSM-20-230I1P+PE

LPZ
1→3Type
2+3

5

Highest
contin-
ous
voltage

Type	V	Version	Pack	Weight	Item no.
ÜSM-20-230I1P+PE 255 1-pole + NPE for PC I			1	4.100	5092431


Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids.
Appropriate for the protection of LED lighting.

- With function display and switch-off of the load circuit when a SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- 1+NPE protective circuit with a maximum discharge capacity of 20 kA
- Reduction of overvoltage to under 1,300 V or 1,000 V @ 5 kA
- With or without luminaire switch-off in case of defect


Application: In the cable transition box, junction boxes, cable duct to underfloor systems



Dimensions



Connection options



ÜSM-20-230I1P+PE

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_p	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m

Surge protection for LED systems

Surge protection for LED systems ÜSM-20-230I1PE65




Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-20-230I1PE65	255	1-pole + NPE for PC I	1	8.300	5092433

Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids.
Appropriate for the protection of LED lighting.


- With function display and switch-off of the load circuit when a SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- 1+NPE protective circuit with a maximum discharge capacity of 20 kA
- Reduction of overvoltage to under 1500 V or 1000 V @ 5 kA
- With or without luminaire switch-off in case of defect

Application: In the cable transition box, junction boxes, cable duct to underfloor systems

Dimensions



Connection options



ÜSM-20-230I1PE65

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_p	1,5 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP65
Connecting cable length		0.25 m

Surge protection module ÜSM-10-230I2P+PE

LPZ
1→3Type
2+3

Highest
contin-
ous
voltage

Type	V	Version	Pack	Weight	
			Piece	kg/100 pc.	Item no.
ÜSM-10-230I2P+PE			1	4.400	5092426

Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids.


Appropriate for the protection of electronic devices and LED drivers.

- For luminaires with 2 phases (power reduction)
- With function display and switch-off of the load circuit when a SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- Protective circuit with a maximum arresting capacity of 10 kA
- Reduction of overvoltage to under 1,300 V (protection level)
- For LED luminaires with PE connection


Application: In the cable transition box, junction boxes, cable duct to underfloor systems



Dimensions



Connection options

**ÜSM-10-230I2P+PE**

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	5 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	10 kA
Maximum discharge current (8/20 μ s)	I_{max}	10 kA
Protection level	U_p	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m

Surge protection for LED systems

Surge protection module ÜSM-10-230I2P-0




Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-10-230I2P-0	255	2-pole without NPE for SK II	1	4.100	5092424

Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids.
Appropriate for the protection of electronic devices and LED drivers.


- For luminaires with 2 phases (power reduction)
- With function display and switch-off of the load circuit when a SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- Protective circuit with a maximum arresting capacity of 10 kA
- Reduction of overvoltage to under 1,300 V (protection level)
- For protection insulated luminaires (PC II) without PE connection

Application: In the cable transition box, junction boxes, cable duct to underfloor systems

Dimensions



Connection options



ÜSM-10-230I2P-0

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	5 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	— kA
Maximum discharge current (8/20 μ s)	I_{max}	10 kA
Protection level	U_p	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m

Surge protection module ÜSM-10-230I1P+PE

LPZ
1→3Type
2+3

Highest
contin-
uous
voltage

Type	V	Version	Pack	Weight	Item no.
ÜSM-10-230I1P+PE 255 1-pole + NPE for PC I			1	3.500	5092422

Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids.


Appropriate for the protection of electronic devices and LED drivers.

- With function display and switch-off of the load circuit when a SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- Use in the LED luminaire head upstream of the electronic LED driver
- Protective circuit with a maximum arresting capacity of 10 kA
- Reduction of overvoltage to under 1,300 V (protection level)
- For LED luminaires with PE connection


Application: In the cable transition box, junction boxes, cable duct to underfloor systems



Dimensions



Connection options



ÜSM-10-230I1P+PE

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	5 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	10 kA
Maximum discharge current (8/20 μ s)	I_{max}	10 kA
Protection level	U_p	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m

Surge protection for LED systems

Surge protection module ÜSM-10-230I1P-0




Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-10-230I1P-0	255	1-pole without NPE for PC II	1	3.200	5092420

Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids.
Appropriate for the protection of electronic devices and LED drivers.


- With function display and switch-off of the load circuit when a SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- Protective circuit with a maximum arresting capacity of 10 kA
- Reduction of overvoltage to under 1,300 V (protection level)
- For protection insulated luminaires (PC II) without PE connection

Application: In the cable transition box, junction boxes, cable duct to underfloor systems

Dimensions




Connection options



ÜSM-10-230I1P-0

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	5 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	— kA
Maximum discharge current (8/20 μ s)	I_{max}	10 kA
Protection level	U_p	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m




OBO
REINHOLD BOHNENBERGER

Blitzbarriere **VF** **24** **AC/DC**



OK



Replace

U_N : 24 V

I_L : 20 A

$I_{n(8/20)}$: 700 A

$I_{max(8/20)}$: 2 kA

U_p : ≤ 130 V

IP20 CE

Art.-Nr. 5097 60 7

theben

13 03

OFF

13:41

MENU



Surge protection Energy technology, type 3 arrester



Fine power protection, fixed installation

206



Fine power protection, fixed installation

Surge protection module 230 V




Type	Signalling on device	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-A	Acoustic	Acoustic operating display	1	1.500	5092451

Surge protection module type 3 to DIN EN 61643-11.


- With audible defect signal
- With low construction height
- Halogen-free plastic (UL 94 V-0)
- Y circuit

Application: Universally applicable for all installation systems.

Dimensions



Connection options



ÜSM-A

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	3 kA
Protection level (L-N)		< 1.3 kV
Protection level (N-PE)		< 1.5 kV
Maximum back-up fuse		16 A
Response time	t_A	< 25 ns
Temperature range	ϑ	-15 - +60 °C
Maximum discharge current (8/20 µs)	I_{max}	6 kA
Rated current	I_i	16 A

Surge protection module 150 V



Type	Signalling on device	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-A-150	Acoustic	Acoustic operating display	1	1.500	5092466


Surge protection module type 3 to DIN EN 61643-11.

- With audible defect signal
- With low construction height
- Halogen-free plastic (UL 94 V-0)
- Y circuit


Application: Universally applicable for all installation systems.



Dimensions



Connection options



ÜSM-A-150

Nominal voltage	U_N	150 V
Max. continuous operating voltage	U_C	170 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	3 kA
Protection level (L-N)		< 1,3 kV
Protection level (N-PE)		< 1,5 kV
Maximum back-up fuse		16 A
Response time	t_A	< 25 ns
Temperature range	ϑ	-15 - +60 °C
Maximum discharge current (8/20 µs)	I_{max}	6 kA
Rated current	I_i	16 A

Fine power protection, fixed installation

Surge protection device 230 V for through wiring





Type Signalling
ÜSM-A-2 on device Version
ÜSM-A-2 | Acoustic | V connection

Pack Piece Weight
 | 1 | 2.200 | kg/100 pc. **Item no.**
5092460

Surge protection device type 3 to DIN EN 61643-11 for 230 V networks.

- With acoustic defect signal
- With 2 strands for continuous wiring
- With low construction height
- Halogen-free plastic (UL 94 V-0)
- Y circuit

Application: Universally applicable for all installation systems.

Dimensions**Connection options****ÜSM-A-2**

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	3 kA
Protection level (L-N)		< 1.3 kV
Protection level (N-PE)		< 1.5 kV
Maximum back-up fuse		16 A
Response time	t_A	< 25 ns
Temperature range	ϑ	-15 - +60 °C
Maximum discharge current (8/20 µs)	I_{max}	6 kA
Rated current	I_i	16 A

Fine power protection for Modul 45 with acoustic function display



Type	Signalling on device	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSS 45-O-RW	Visual	Visual function display	1	2.411	6117473


Surge protection / network fine protection, type 3, according to EN 61643-11 for installation in Rapid 45 trunking, device installation trunking and underfloor systems.

- Version-O with acoustic function display
- Quick and easy mounting
- Low construction width of 22.5 mm

Application: The surge protection device secures downstream and nearby sockets.




Dimensions

**ÜSS 45-O-RW**

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	2.5 kA
Protection level (L-N)		< 1.5 kV
Protection level (N-PE)		< 1.5 kV
Maximum back-up fuse		16 A
Response time	t_A	25 ns
Temperature range	ϑ	-25 - +45 °C

Connection options



Fine power protection, fixed installation

Surge protection module for Modul 45 with audible signalling




Type	Signalling on device	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSS 45-A-RW	Acoustic	Acoustic function display	1	2.800	6117465

Surge protection / network fine protection, type 3, according to EN 61643-11 for installation in Rapid 45 trunking, device installation trunking and underfloor systems.


- Version-A with acoustic function display (switchable signal tone)
- Quick and easy mounting
- Low construction width of 22.5 mm

Application: The surge protection device secures downstream and nearby sockets.

Dimensions



Connection options



ÜSS 45-A-RW

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	2.5 kA
Protection level (L-N)		< 1,5 kV
Protection level (N-PE)		< 1,5 kV
Maximum back-up fuse		16 A
Response time	t_A	25 ns
Temperature range	θ	-25 - +45 °C

Surge protection module ÜSM 10

LPZ
1→3Type
2+3

5

Highest
contin-
ous
voltage

Type

ÜSM-10-230I1PE25 | 255

V Version

Pack
Piece

kg/100 pc.

Item no.
5092440

Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids.
Appropriate for the protection of LED lighting.

- With function display and switch-off of the load circuit when a SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- 1+NPE protective circuit with a maximum discharge capacity of 10 kA
- Reduction of overvoltage to under 1300 V or 1000 V @ 5 kA
- With or without luminaire switch-off in case of defect

Application: In the cable transition box, junction boxes, cable duct to underfloor systems


ÜSM-10-230I1PE25

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	5 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	10 kA
Maximum discharge current (8/20 µs)	I_{max}	10 kA
Protection level	U_o	1,5 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m



Dimensions

Connection options





Photovoltaic systems

	Lightning current and surge arrester, type 1+2, photovoltaic systems 1,500 V DC	214
	Lightning current and surge arrester, type 1+2, photovoltaic systems 1,000 V DC	216
	Lightning current and surge arrester, type 1+2, photovoltaic systems 600 V DC	218
	Surge arrester, type 2, photovoltaics 1,500 V DC	220
	Surge arrester, type 2, photovoltaics 1,000 V DC	223
	Surge arrester, type 2, photovoltaics 600 V DC	224
	Photovoltaic system solution with 2/3 MPP trackers	226
	Photovoltaic system solution with fuses	228
	Photovoltaic upper parts	234
	Photovoltaic bases	234

PV complete block 1500 V DC



CE LPZ 0→2 Type 1+2


Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T1+2-1500	1500	Y configuration	1	49.200	5094240

Type 1+2 combination arrestor for lightning and surge protection of PV systems.


- Lightning protection equipotential bonding according to IEC 62305 (VDE 0185-305)
- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity to 12.5 kA (10/350) and 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Lightning current and surge protection devices for PV systems.

Dimensions



Connection options



V-PV-T1+2-1500

U max DC	U_c DC	1500 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	6.25 kA
Nominal discharge current (8/20)	I_n	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	40 kA
Protection level	U_b	< 4,5 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - 80 °C
Protection rating		IP20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 35 mm ²

CE LPZ 0→2 Type 1+2 5 years

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T1+2-1500FS	1500	Y configuration + RS	1	49.600	5094242


Type 1+2 combination arrestor for lightning and surge protection of PV systems.

- Lightning protection equipotential bonding according to IEC 62305 (VDE 0185-305)
- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity to 12.5 kA (10/350) and 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling


Application: Lightning current and surge protection devices for PV systems.



Dimensions



Connection options



V-PV-T1+2-1500FS

U max DC	U _c DC	1500 V
SPD to EN 61643-11	Type 1+2	
Lightning protection zone LPZ	0→2	
Impulse discharge current (10/350)	I _{imp}	6.25 kA
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 µs)	I _{max}	40 kA
Protection level	U _o	< 4,5 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - 80 °C
Protection rating		IP20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 35 mm ²



PV complete block 1000 V DC



CE LPZ 0→2 Type 1+2

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T1+2-1000	1000	Y configuration	1	40.700	5094230

Type 1+2 combination arrestor according to EN 50539-11 for lightning and surge protection of PV systems.

- Lightning protection equipotential bonding according to IEC 62305 (VDE 0185-305)
- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity to 12.5 kA (10/350) and 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Lightning current and surge protection devices for PV systems.

Dimensions**Connection options****V-PV-T1+2-1000**

U max DC	U_c DC	1000 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	6.25 kA
Nominal discharge current (8/20)	I_n	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	40 kA
Protection level	U_b	< 3,3 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - 80 °C
Protection rating		IP20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 35 mm ²



PV complete block 1000 V DC with remote signalling

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T1+2-1000FS	1000	Y configuration + RS	1	41.200	5094232

Type 1+2 combination arrester according to EN 50539-11 for lightning and surge protection of PV systems.

- Lightning protection equipotential bonding according to IEC 62305 (VDE 0185-305)
- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity to 12.5 kA (10/350) and 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Lightning current and surge protection devices for PV systems.

**Dimensions****Connection options****V-PV-T1+2-1000FS**

U max DC	U_c DC	1000 V
SPD to EN 61643-11	Type 1+2	
Lightning protection zone LPZ	0→2	
Impulse discharge current (10/350)	I_{imp}	6.25 kA
Nominal discharge current (8/20)	I_n	20 kA
Maximum discharge current (8/20 µs)	I_{max}	40 kA
Protection level	U_o	< 3.3 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - 80 °C
Protection rating		IP20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm²
Connection cross-section, multi-wire		2.5 - 35 mm²
Connection cross-section, flexible		2.5 - 35 mm²



PV combination arrester V50, 600 V DC

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V50-B+C 3-PH600	600	3-pole for PV systems	1	41.000	5093623

V50 combination arrester, type 1+2, for photovoltaic systems

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit to VDE 0100-712 (EN 50539-12)
- Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 12.5 kA (10/350) and 50 kA (8/20) per pole
- Low DC protection level: < 2.6 kV and Voc max = 600 V DC
- With visual function display for use in distributor housings

Application: PV systems with lightning protection system

Dimensions**Connection options****V50-B+C 3-PH600**

U max DC	U_c DC	600 V
SPD to EN 61643-11	Type	1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	12.5 kA
Nominal discharge current (8/20)	I_n	30 kA
Maximum discharge current (8/20 µs)	I_{max}	50 kA
Protection level	U_b	< 2,6 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		3
Connection cross-section, rigid		2.5 - 35 mm²
Connection cross-section, multi-wire		2.5 - 35 mm²
Connection cross-section, flexible		2.5 - 25 mm²

PV combination arrester V50, 600 V DC with remote signallingType
1+2LPZ
0→2U max
DC

V Version

Pack Piece

Weight kg/100 pc.

Item no.

Type V50-B+C 3PHFS600 | 600 | 3-pole for PV systems with FS

| 1 | 49.600 |



5093625

V50 combination arrester, type 1+2, for photovoltaic systems

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit to VDE 0100-712 (EN 50539-12)
- Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 12.5 kA (10/350) and 50 kA (8/20) per pole
- Low DC protection level: < 2.6 kV and Voc max = 600 V DC
- With visual function display for use in distributor housings



Application: PV systems with lightning protection system

Dimensions**Connection options****V50-B+C 3PHFS600**

U max DC	U_c DC	600 V
SPD to EN 61643-11	Type	1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	12.5 kA
Nominal discharge current (8/20)	I_n	30 kA
Maximum discharge current (8/20 µs)	I_{max}	50 kA
Protection level	U_o	< 2,6 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²

Surge arrestor, type 2, photovoltaics 1,500 V DC

PV complete block 1500 V DC



CE Type 2 LPZ 1→2

U max
DC
Type V Version
V-PV-T2-1500 | 1500 | Y configuration


Pack Weight
Piece kg/100 pc. **Item no.**
| 1 | 33.800 | **5094210**

Type 2 surge protection for PV plants.


- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity of 20 kA per pole and up to 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Surge protection devices for PV systems.

Dimensions



Connection options



V-PV-T2-1500

U max DC	U_c DC	1500 V
SPD to EN 61643-11	Type 2	
Lightning protection zone LPZ	1→2	
Nominal discharge current (8/20)	I_n	20 kA
Maximum discharge current (8/20 µs)	I_{max}	40 kA
Protection level	U_p	< 4,5 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - 80 °C
Protection rating		IP20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 35 mm ²

PV complete block 1500 V DC with remote signalling



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T2-1500+FS	1500	Y configuration + RS	1	34.400	5094212


Type 2 surge protection for PV plants.

- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity of 20 kA per pole and up to 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling


Application: Surge protection devices for PV systems.



Dimensions



Connection options



V-PV-T2-1500+FS

U max DC	U _c DC	1500 V
SPD to EN 61643-11	Type 2	
Lightning protection zone LPZ	1-2	
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 µs)	I _{max}	40 kA
Protection level	U _p	< 4.5 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - 80 °C
Protection rating		IP20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 35 mm ²

Surge arrestor, type 2, photovoltaics 1000 V DC

PV surge protection V20, 1000 V DC




Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V20-C 3-PH-1000	1000	3-pole for PV systems	1	36.500	5094608

V20 surge arrestor, type 2, for photovoltaic systems


- Complete unit, consisting of plug-in varistor arrestor with cut-off unit
- Error-resistant Y circuit to VDE 0100-712 (EN 50539-12)
- Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- V20-C 3-PH-1000 tested to EN 50539-11 (VDE / KEMA)
- Arresting capacity to 40 kA (8/20) per pole
- Low DC protection level: < 4.0 kV and Voc max = 1,000 V DC
- With visual status display for use in distributor housings

Application: PV systems with or without separate lightning protection system

Dimensions



Connection options



V20-C 3-PH-1000

U max DC	U_c DC	1000 V
SPD to EN 61643-11		Type 2
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	20 kA
Maximum discharge current (8/20 µs)	I_{max}	40 kA
Protection level	U_p	< 4,0 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		3
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²

PV surge protection V20, 1000 V DC with remote signalling

Type
2LPZ
1→2

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V20-C 3PHFS-1000	1000	3-pole for PV systems with FS	1	44.500	5094574


V20 surge arrester, type 2, for photovoltaic systems

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit to VDE 0100-712 (EN 50539-12)
- Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- V20-C 3-PH-1000 tested to EN 50539-11 (VDE / KEMA)
- Arresting capacity to 40 kA (8/20) per pole
- Low DC protection level: < 4.0 kV and Voc max = 1,000 V DC
- With visual status display for use in distributor housings


Application: PV systems with or without separate lightning protection system



Dimensions



Connection options



V20-C 3PHFS-1000

U max DC	U _c DC	1000 V
SPD to EN 61643-11	Type 2	
Lightning protection zone LPZ	1→2	
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 µs)	I _{max}	40 kA
Protection level	U _p	< 4.0 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²

Surge arrestor, type 2, photovoltaics 600 V DC

PV surge protection V20, 600 V DC




Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V20-C 3PH-600	600	3-pole for PV systems	1	33.500	5094605

V20 surge arrestor, type 2, for PV systems


- Complete unit, consisting of plug-in varistor arrestor with cut-off unit
- Error-resistant Y circuit for use according to VDE 0100-712 (EN 50539-12)
- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 40 kA (8/20) per pole
- Low DC protection level: < 2.6 kV (Voc max = 600 V DC)
- Arrestor, connectable with thermodynamic cut-off unit and visual function display
- Encapsulated, zinc oxide varistor arrestor for use in distributor housings

Application: PV systems with or without separate lightning protection system

Dimensions



Connection options



V20-C 3PH-600

U max DC	U_c DC	600 V
SPD to EN 61643-11	Type	2
Lightning protection zone LPZ	1→2	
Nominal discharge current (8/20)	I_n	20 kA
Maximum discharge current (8/20 µs)	I_{max}	40 kA
Protection level	U_p	< 2,6 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		3
Connection cross-section, rigid		2.5 - 35 mm²
Connection cross-section, multi-wire		2.5 - 35 mm²
Connection cross-section, flexible		2.5 - 25 mm²

PV surge protection V20, 600 V DC with remote signalling

Type
2LPZ
1→2U max
DC

V

Version

Pack
PieceWeight
kg/100 pc.

Item no.

Type	V20-C 3PHFS-600	U max DC V	3-pole for PV systems; Y circuit with FS	Pack Piece	Weight kg/100 pc.	Item no.
		600		1	41.500	5094576


V20 surge arrester, type 2, for PV systems

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit for use according to VDE 0100-712 (EN 50539-12)
- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 40 kA (8/20) per pole
- Low DC protection level: < 2.6 kV (Voc max = 600 V DC)
- Arrester, connectable with thermodynamic cut-off unit and visual function display
- Encapsulated, zinc oxide varistor arrester for use in distributor housings


Application: PV systems with or without separate lightning protection system



Dimensions



Connection options



V20-C 3PHFS-600

U max DC	U _c DC	600 V
SPD to EN 61643-11	Type 2	
Lightning protection zone LPZ	1→2	
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 µs)	I _{max}	40 kA
Protection level	U _p	< 2.6 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²


PV system solution, type 1+2, for inverter with 2 MPP trackers, 900 V DC



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BCPV900K 22	900	For two MPP and with terminal connection	1	220.000	5088566


System solution for photovoltaic inverter with 2 separate MPP trackers

- Varistor arrester, connectable with disconnecting device in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 4.0 kV (Uoc max = 1,000 V DC with V20-C/0-500PV)
- Low DC protection level: < 3.0 kV (Uoc max = 900 V DC with V25-B+C/0-450PV)
- Per protection device, there are 4 terminals up to 6 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for the use outside, including cable gland kit



Dimensions

For DC protection of the inverter in photovoltaic systems.
If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!



Connection options

VG-BCPV900K 22



U max DC	U _c DC	900 V
SPD to EN 61643-11	Type	1+2
Lightning protection zone LPZ		0-2
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 µs)	I _{max}	60 kA
Protection level	U _p	< 3,0 kV
Response time	t _A	< 25 ns
Temperature range	θ	-30 - 90 °C
Protection rating		IP66

PV system solution, type 2, for inverter with 3 MPP trackers, 1000 V DCType
2LPZ
1→2

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-CPV 1000K 333	1000	For three MPP and with terminal connection	1	528.000	5088585

System solution for photovoltaic inverter with 3 separate MPP trackers

- Varistor arrestor, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-450PV)
- Per protection device there are 6 terminals up to 6 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP65), UV-resistant for use outside, including cable gland kit

**Dimensions****Connection options****VG-CPV 1000K 333**

U max DC	U_c DC	1000 V
SPD to EN 61643-11	Type 2	
Lightning protection zone LPZ	1→2	
Nominal discharge current (8/20)	I_n	20 kA
Maximum discharge current (8/20 µs)	I_{max}	40 kA
Protection level	U_p	< 4.0 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP65

Photovoltaic housing with 4 fuses 10 A



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-C DCPH1000-4S	1000	Type 2 in housing with 4 PV fuses (10 A)	1	200.000	5088651


System solution for photovoltaic fuses for photovoltaic inverters with 1 MPP tracker

- Error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 4.0 kV (Voc max = 1,000 V DC with V20-C/0-500PV)
- Item no.: 5088651: (+) poles protected via 4 photovoltaic fuses 10 x 38 mm 10 A, 1,000 V DC protected
- Item no.: 5088654: (+) poles protected via 4 photovoltaic fuses 10 x 38 mm (unequipped), 1,000 V DC protected
- 4 (-) poles via terminal up 6 mm² switched in parallel in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP65), weather-resistant for use outside, including cable gland kit


For DC protection of the inverter in photovoltaic systems.

If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Dimensions



Connection options



VG-C DCPH1000-4S

U max DC	U _c DC	1000 V
SPD to EN 61643-11	Type 2	
Lightning protection zone LPZ	1→2	
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 µs)	I _{max}	40 kA
Protection level	U _p	< 4,0 kV
Response time	t _A	< 25 ns
Connection cross-section, rigid		0.5 - 6 mm ²
Connection cross-section, flexible		0.5 - 6 mm ²
Temperature range	θ	-40 - +80 °C
Protection rating		IP 65

PV housing for inverter with 3 MPP trackers, type 1+2, 900 V DCType
1+2LPZ
0→2U max
DC

Type

VG-BC DCPH900-31

V

Version

Pack
Piece
kg/100 pc.

Weight

Item no.

For three MPP and
with MC4 connection



1

542.000

5088629

System solution with MC4 connector for photovoltaic inverter with 3 separate MPP trackers

- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 4.0 kV (Voc max = 1,000 V DC with V20-C/0-500PV)
- Low DC protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-450PV)
- Two PV string inputs (MC4 plug connector) at one MPP inverter input, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP65), UV-resistant for use outside, including cable gland kit

**VG-BC DCPH900-31**

U max DC	U_c DC	900 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	7 kA
Nominal discharge current (8/20)	I_n	30 kA
Maximum discharge current (8/20 µs)	I_{max}	60 kA
Protection level	U_o	< 3,0 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP65

PV system solution housing

PV housing for inverter with 1 MPP tracker, type 2




Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-C DCPH-MS1000	1000	Type 2 in housing with terminals	1	154.000	5088691

System solution for photovoltaic inverter with 1 separate MPP tracker

- Varistor arrester, connectable with disconnecting device in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 4.0 kV (Uoc max = 1000 V DC with V20-C/0-500PV)
- Low DC protection level: < 3.0 kV (Uoc max = 900 V DC with V25-B+C/0-450PV)
- Per protection device, there are 3 terminals up to 16 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for the use outside, including cable gland kit


Dimensions



For DC protection of the inverter in photovoltaic systems.

If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Connection options



VG-C DCPH-MS1000

U max DC	U _c DC	1000 V
SPD to EN 61643-11	Type	2
Lightning protection zone LPZ	1→2	
Impulse discharge current (10/350) I _{imp}	— kA	
Nominal discharge current (8/20) I _n	20 kA	
Maximum discharge current (8/20 µs) I _{max}	40 kA	
Protection level U _b	< 4,0 kV	
Response time t _A	< 25 ns	
Connection cross-section, rigid	0.5 - 6 mm ²	
Connection cross-section, flexible	0.5 - 6 mm ²	
Temperature range θ	-40 - +80 °C	
Protection rating	IP 65	



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BC DCPH-MS900	900	Type 1+2 in housing with terminals	1	160.000	5088692

System solution for photovoltaic inverter with 1 MPP tracker


- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 2.6 kV (Voc max = 600 V DC with V50-B+C/0-300PV / V20-C/0-300PV)
- Low DC protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-450PV)
- Low DC protection level: < 4.0 kV (Voc max = 1000 V DC with V20-C/0-500PV)
- For each protection device, there are 3 terminals up to 16 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems.


If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!



Dimensions



Connection options



VG-BC DCPH-MS900

U max DC	U _c DC	900 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I _{imp}	7 kA
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 µs)	I _{max}	50 kA
Protection level	U _o	< 3,0 kV
Response time	t _A	< 25 ns
Connection cross-section, rigid		0.5 - 6 mm ²
Connection cross-section, flexible		0.5 - 6 mm ²
Temperature range	θ	-40 - +80 °C
Protection rating		IP 65



PV housing for inverter with 1 MPP tracker, type 1+2



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BC DCPH-MS600	600	Type 1+2 in housing with terminals	1	159.000	5088693


System solution for photovoltaic inverter with 1 MPP tracker

- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 2.6 kV (Voc max = 600 V DC with V50-B+C/0-300PV / V20-C/0-300PV)
- Low DC protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-450PV)
- Low DC protection level: < 4.0 kV (Voc max = 1000 V DC with V20-C/0-500PV)
- For each protection device, there are 3 terminals up to 16 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for use outside, including cable gland kit


For DC protection of the inverter in photovoltaic systems.

If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Dimensions



Connection options



VG-BC DCPH-MS600

U max DC	U _c DC	600 V
SPD to EN 61643-11	Type	1+2
Lightning protection zone LPZ	0→2	
Impulse discharge current (10/350)	I _{imp}	12.5 kA
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 µs)	I _{max}	50 kA
Protection level	U _b	< 2,6 kV
Response time	t _A	< 25 ns
Connection cross-section, rigid		0.5 - 6 mm ²
Connection cross-section, flexible		0.5 - 6 mm ²
Temperature range	θ	-40 - +80 °C
Protection rating		IP 65

PV system solution, type 1+2, with MC4 connector for inverter with 1 MPP tracker, 900 V DC

Type
1+2LPZ
0→2

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BC900S1	900	For one MPP and with MC4 connection	1	105.000	5088564

System solution, type 1+2, with MC4 connector for photovoltaic inverter with 1 MPP tracker


- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Type 1+2 combination arrester for lightning protection equipotential bonding to EN 62305 (VDE 0185-305)
- Low DC voltage protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-450PV)
- One PV string input (MC4 plug connector) at one MPP inverter input, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for use outside

For DC protection of the inverter of photovoltaic systems.


If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!



Dimensions



Connection options

**VG-BC900S1**

U max DC	U_c DC	900 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	7 kA
Nominal discharge current (8/20)	I_n	30 kA
Maximum discharge current (8/20 µs)	I_{max}	50 kA
Protection level	U_p	< 3,0 kV
Response time	t_A	< 25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP66

PV lightning and surge protection upper parts

PV CombiController V50, plug-in arrester, type 1+2




Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V50-B+C 0-300PV	300	1-pole, PV upper part with Y base to 600 V DC	1	8.200	5093726

CombiController cover – type 1+2, combination arrester for photovoltaic systems

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 12.5 kA (10/350) and 50 kA (8/20) per pole
- Low DC voltage protection level: < 1.3 kV per pole (Y circuit: 2.6 kV and Voc max = 600 V DC)
- Plug-in arrester with thermodynamic cut-off unit and visual function display
- Encapsulated, zinc oxide varistor arrester for use in distributor housings
- High current carrying capacity with long lifespan

Application: PV systems with lightning protection system



V50-B+C 0-300PV

U max DC	U _c DC	300 V
SPD to EN 61643-11	Type	1+2
SPD to IEC 61643-11	Class	I+II
Lightning protection zone LPZ	0-2	
Nominal discharge current (8/20)	I _n	30 kA
Impulse discharge current (10/350)	I _{imp}	12.5 kA
Maximum discharge current (8/20 µs)	I _{max}	50 kA
Protection level	U _p	< 1.3 kV
Response time	t _A	<25 ns
Maximum back-up fuse		125 A
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1



PV lightning and surge protection bases

PV base, 3-pole in Y circuit



Type	Version	Pack Piece	Weight kg/100 pc.	Item no.
V20-C U-3PH-Y	3-pole Y circuit for PV	1	17.000	5096647

Base for photovoltaic systems up to Voc = 1000 V (Y-circuit)



V20-C U-3PH-Y

Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		3
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²

PV base, 3-pole in Y circuit with remote signalling

Type
1+2Type
2LPZ
0→1LPZ
1→2

FS



Version

Type

V20-C U-3PH-Y-FS | 3-pole Y circuit for photovoltaic systems with FS

Pack

Piece

Weight
kg/100 pc.

Item no.



| 1 | 25.000 |

5096646

Base for photovoltaic systems up to Voc = 1000 V (Y circuit)

- Suitable for V 50-B+C and V25-B+C covers, type 1+2, combination arrester
- Suitable for V 20-C covers, type 2, surge arresters
- Protection circuit against transverse and longitudinal voltages
- Y circuit
- Low DC voltage protection level: < 4.0 kV (Voc max = 1000 V DC with V20-C/0-440)
- Low DC voltage protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-385)
- Low DC voltage protection level: < 2.6 kV (Voc max = 600 V DC with V50-B+C/0-280)
- FS with remote signalling and potential-free changeover contact for function monitoring
- Labelled connections

Application: In photovoltaic systems between PH modules and inverters.



V20-C U-3PH-Y-FS

Temperature range	9 -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	4
Connection cross-section, rigid	2.5 - 35 mm ²
Connection cross-section, multi-wire	2.5 - 35 mm ²
Connection cross-section, flexible	2.5 - 25 mm ²



bleiter

Net-Defender

	Surge protection for telecommunication systems	238
	Surge protection for LSA-Plus systems	245
	Coaxial protection devices for high-frequency applications	251
	Surge protection for network technology and CCTV camera systems	265
	MCR protection 2-pole power supply	297
	MCR protection FRD/FLD/TKS-B lightning protection barriers	308
	MCR protection MDP, in series terminal format	325

Combination protection device TD-2d-V for VDSL systems



Highest continuous voltage AC V

Maximum continuous voltage DC V

ISDN

DSL

Analog

TK

LPZ 0→3

5



Type TD-2d-V | Number of poles 2 | Connection system Terminal

Pack Piece | Weight kg/100 pc.

9.500

Item no.

5081698


Plastic

Data cable protection device for telecommunications equipment


- Low protection level at a high current load
- "Push-in" clamps for quick installation
- Bandwidth-optimised for secure transmission up to 225 MHz
- Surface mounting

Application: Ideal for all DSL systems, IP connections, ISDN or analogue telecommunications

Dimensions



Connection options



TD-2d-V

Maximum continuous voltage AC	U_C	125 V
Maximum continuous voltage DC	U_C	180 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		2
Rated current	I_r	0.5 A
Capacity (wire-wire)		<10 pF
Capacity (wire-earth)		<20 pF
Series resistance per wire		2,2 Ω ± 5 %
Impulse durability wire-wire		C2: 15 kV / 7,5 kA (8/20μs)
Impulse durability wire-earth		C2: 15 kV / 7,5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		22,5 kA
Total discharge current (10/350)		D1: 7,5 kA
Protection level wire-wire		<350 V
Protection level wire-earth		<600 V
Frequency range		0 - 225 MHz
Insertion loss	S_{21}	≤3 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Surface-mounted
Connection system		Terminal
Protection rating		IP54
Shielding connection available		Yes
Connection cross-section, flexible		0.14 - 1 mm²
Connection cross-section, multi-wire		0.14 - 1 mm²
Connection cross-section, rigid		0.08 - 1.5 mm²
Testing standard		IEC 61643-21

Combination protection device TD-4/I for ISDN and DSL systems



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
TD-4/I	120	170	4	Terminal	1	11.000	5081690

Plastic


Data cable protection device for telecommunications equipment

- Low protection level at a high current load
- "Push-in" terminals for quick installation
- Bandwidth-optimised for secure transmission
- Surface mounting
- Visual function display


Application: DSL systems, IP connections, ISDN or analogue telecommunications



Dimensions



Connection options



TD-4/I

Maximum continuous voltage AC	U _c	120 V
Maximum continuous voltage DC	U _c	170 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		4
Rated current	I _r	0.2 A
Capacity (wire-wire)		<50 pF
Capacity (wire-earth)		<10 pF
Series resistance per wire		9 Ω ± 10 %
Impulse durability wire-wire		C2: 18 kV / 9 kA (8/20μs)
Impulse durability wire-earth		C2: 18 kV / 9 kA (8/20μs)
Impulse discharge current (10/350) I _{imp}		2.5 kA
Total discharge current (8/20)		25 kA
Total discharge current (10/350)		D1: 12.5 kA
Protection level wire-wire		<300 V
Protection level wire-earth		<650 V
Protection level, shield-earth (S-PE)		850 V
Frequency range		0 - 100 MHz
Insertion loss	S ₂₁	≤3 dB
Temperature range	θ	-40 - +80 °C
Installation type		Surface-mounted
Connection system		Terminal
Protection rating		IP54
Shielding connection available		Yes
Connection cross-section, flexible		0.14 - 0.75 mm ²
Connection cross-section, multi-wire		0.14 - 0.75 mm ²
Connection cross-section, rigid		0.14 - 0.75 mm ²
Testing standard		IEC 61643-21

Combination protection device TD-2/D-HS for ISDN and DSL systems




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
TD-2/D-HS	120	170	2	Terminal	1	4.800	5081694

Plastic


Data cable protection devices for telecommunication systems

- Low protection level at high current load
- Screwless terminals or connectable
- Bandwidth-optimised for secure transmission
- Quick mounting onto DIN rail for a telephone line
- Visual function display

Application: DSL systems, ISDN or analogue telecommunication



Dimensions



Connection options

TD-2/D-HS

Maximum continuous voltage AC	U_C	120 V
Maximum continuous voltage DC	U_C	170 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		2
Rated current	I_I	0.2 A
Capacity (wire-wire)		<50 pF
Capacity (wire-earth)		<50 pF
Series resistance per wire		9 Ω ± 10 %
Impulse durability wire-wire		C2: 18 kV / 9 kA (8/20μs)
Impulse durability wire-earth		C2: 18 kV / 9 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 5 kA kA
Protection level wire-wire		<300 V
Protection level wire-earth		<650 V
Frequency range		0 - 75 MHz
Insertion loss	S_{21}	≤3 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		No
Connection cross-section, flexible		0.14 - 2.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Testing standard		IEC 61643-21

Combination protection device TELE 4-C for ISDN RJ11



Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
RJ11-TELE 4-C	Combi protection, 4 wires	RJ11	1	14.000	5081975


Data line protection device for analogue telecommunications systems

- In aluminium housing
- With 2-stage protection circuit
- Simple mounting
- Incl. 150 mm connection cable with RJ11 and/or RJ45 connectors
- Optimised bandwidth for TC systems
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: For analogue telecommunication systems




Dimensions



RJ11-TELE 4-C

Maximum continuous voltage AC	U_c	120 V
Maximum continuous voltage DC	U_c	170 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		4
Series resistance per wire		$8,2 \Omega \pm 10\%$
Total discharge current (8/20)		4 kA
Total discharge current (10/350)		1,5 kA
Protection level wire-wire		<300 V
Protection level wire-earth		<600 V
Protection level, wire-earth at 1 kV/μs (C3)	U_b	<245 V
Frequency range		0 - 12 MHz
Insertion loss	S_{21}	≤ 3 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ11
Protection rating		IP40
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Connection options



Surge protection for telecommunication systems

Fine protection device TELE 4-F for ISDN RJ11




Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
RJ11-TELE 4-F	Fine protection, 4 wires	RJ11	1	14.000	5081977

Data line protection device for analogue telecommunications systems


- In aluminium housing
- With 2-stage protection circuit
- Simple mounting
- Incl. 150 mm connection cable with RJ11 and/or RJ45 connectors
- Optimised bandwidth for TC systems
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: For analogue telecommunication systems

Dimensions



Connection options



RJ11-TELE 4-F

Maximum continuous voltage AC	U_c	120 V
Maximum continuous voltage DC	U_c	170 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Number of poles		4
Series resistance per wire		$2,2 \Omega \pm 10\%$
Total discharge current (8/20)		4 kA
Protection level wire-wire		<300 V
Protection level wire-earth		<600 V
Protection level, wire-earth at 1 kV/μs (C3)	U_p	<245 V
Frequency range		0 - 18 MHz
Insertion loss	S_{21}	≤ 3 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ11
Protection rating		IP40
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Combination protection device TELE 4-C for ISDN RJ45



Type	Version	Connec-tion system	Pack Piece	Weight kg/100 pc.	Item no.
RJ45-TELE 4-C	Combi protection, 4 wires	RJ45	1	14.000	5081982


Data line protection device for analogue telecommunications systems

- In aluminium housing
- With 2-stage protection circuit
- Simple mounting
- Incl. 150 mm connection cable with RJ11 and/or RJ45 connectors
- Optimised bandwidth for TC systems
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: For analogue telecommunication systems




Dimensions



RJ45-TELE 4-C

Maximum continuous voltage AC	U_c	120 V
Maximum continuous voltage DC	U_c	170 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		4
Series resistance per wire		$8,2 \Omega \pm 10\%$
Total discharge current (8/20)		4 kA
Total discharge current (10/350)		1,5 kA
Protection level wire-wire		<300 V
Protection level wire-earth		<600 V
Protection level, wire-earth at 1 kV/μs (C3)	U_b	<245 V
Frequency range		0 - 12 MHz
Insertion loss	S_{21}	≤ 3 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ45
Protection rating		IP40
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Connection options



Surge protection for telecommunication systems

Fine protection device TELE 4-F for ISDN RJ45




Type	Version	Connec-tion system	Pack Piece	Weight kg/100 pc.	Item no.
RJ45-TELE 4-F	Fine protection, 4 wires	RJ45	1	14.000	5081984

Data line protection device for analogue telecommunications systems


- In aluminium housing
- With 2-stage protection circuit
- Simple mounting
- Incl. 150 mm connection cable with RJ11 and/or RJ45 connectors
- Optimised bandwidth for TC systems
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: For analogue telecommunication systems

Dimensions



Connection options



RJ45-TELE 4-F

Maximum continuous voltage AC	U_c	120 V
Maximum continuous voltage DC	U_c	170 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Number of poles		4
Series resistance per wire		$2,2 \Omega \pm 10\%$
Total discharge current (8/20)		4 kA
Protection level wire-wire		<300 V
Protection level wire-earth		<600 V
Protection level, wire-earth at 1 kV/μs (C3)	U_p	<245 V
Frequency range		0 - 18 MHz
Insertion loss	S_{21}	≤ 3 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ45
Protection rating		IP40
Earthing via:		Connection cable
Testing standard		IEC 61643-21

LSA basic protection magazine



Type	Installation type	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
LSA-B-MAG	LSA-Plus, connectable	20	1	8.600	5084020


LSA basic protection magazine for use in multi-core data cable systems, MCR systems and telephone switchboards.

- Basic protection
- Equipped with 20 gas arresters
- Max. voltage: 180 V

Application: Directly on LSA-Plus separating strips or connection rails (e.g. OBO LSA-A-LEI (5084 00 8) or OBO LSA-T-LEI (5084 01 2)).




Dimensions

**LSA-B-MAG**

Maximum continuous voltage AC	U_c	120 V
Maximum continuous voltage DC	U_c	180 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		20
Rated current	I_r	1 A
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		1 kA
Protection level @ C1		<750 V
Temperature range	ϑ	-40 - +80 °C
Installation type		LSA-Plus, connectable
Connection system		Other
Protection rating		IP20
Testing standard		IEC 61643-21

Connection options



Surge protection for LSA-Plus systems

Combination protection device LSA BF 180



Type	Installation type	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
LSA-BF-180	LSA-Plus, connectable	2	1	0.500	5084024


LSA basic and fine protection, for application in MCR systems



- Basic and fine protection
- Coarse protection using fail-safe technology.
- With PTC protection components against overcurrent.
- Max. voltage: 180 V


Application: Directly on LSA-Plus separating strip or connection rails with earthing rail (e.g. OBO LSA-A-LEI (5084 00 8) or OBO LSA-T-LEI (5084 01 2), and OBO LSA-E (5084 03 2))

Dimensions



Connection options

1 DA (TC) => 1 line



LSA-BF-180

Maximum continuous voltage AC	U_c	120 V
Maximum continuous voltage DC	U_c	180 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		2
Rated current	I_r	0.12 A
Impulse durability wire-wire		C2: 5 kV / 2,5 kA (8/20μs)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)		5 kA
Total discharge current (10/350)		0,5 kA
Protection level wire-wire		<300 V
Protection level wire-earth		<300 V
Temperature range	ϑ	-40 - +80 °C
Installation type		LSA-Plus, connectable
Connection system		Other
Protection rating		IP20
Testing standard		IEC 61643-21



Type	Installation type	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
LSA-BF-24	LSA-Plus, connectable	2	1	0.500	5084028


LSA basic and fine protection, for application in MCR systems

- Basic and fine protection
- Coarse protection using fail-safe technology.
- With PTC protection components against overcurrent.
- Max. voltage: 24 V


Application: Directly on LSA-Plus separating strip or connection rails with earthing rail (e.g. OBO LSA-A-LEI (5084 00 8) or OBO LSA-T-LEI (5084 01 2), and OBO LSA-E (5084 03 2))



Dimensions



Connection options



LSA-BF-24

Maximum continuous voltage AC	U_c	15 V
Maximum continuous voltage DC	U_c	24 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0-3
Number of poles		2
Rated current	I_r	0.12 A
Impulse durability wire-wire		C2: 5 kV / 2,5 kA (8/20μs)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)		5 kA
Total discharge current (10/350)		0.5 kA
Protection level wire-wire		<70 V
Protection level wire-earth		<70 V
Temperature range	ϑ	-40 - +80 °C
Installation type		LSA-Plus, connectable
Connection system		Other
Protection rating		IP20
Testing standard		IEC 61643-21


LSA connection strip



Type	Colour	Pack Piece	Weight kg/100 pc.	Item no.
LSA-A-LEI	Grey	1	5.100	5084008


LSA connection strip 2/10 for attaching 10 double-cores.

- For use with protection element LSA-B-MAG
- Fastening to mounting trough LSA-M
- Colour: Grey
- Clampable cross-section 0.14–0.5 (AWG 26–20)



Surge protection for LSA-Plus systems

LSA separating strip



Colour

Type


LSA-T-LEI | White

Pack	Weight	Item no.
Piece	kg/100 pc.	
1	5.400	5084012


LSA separating strip 2/10 for attaching up to 10 double-cores.

- For use with protection element LSA-BF-180; LSA-BF-24; LSA-B-MAG
- Fastening to mounting trough LSA-M
- Colour: White
- Clampable cross-sections 0.14–0.5 mm² (AWG 26–20)

Dimensions



LSA earthing strip



Colour

Type


LSA-E-LEI | Red

Pack	Weight	Item no.
Piece	kg/100 pc.	
1	6.500	5084016

LSA earthing strip, 40-pole for connecting earthing cables or screens to the earth connection.

- Complete with connection line, green-yellow, 1.5 mm²
- Colour: Red

Dimensions






Type	Pack	Weight	
LSA-E	Piece	kg/100 pc.	Item no.
	1	1.275	5084032

Earth rail as earth connection between surge protectors LFS-BF... (1 DA) and distributor connector LSA-...-LEI.



Dimensions




LSA installation trough




Type	Pack	Weight	
LSA-M	Piece	kg/100 pc.	Item no.
Steel	1	7.800	5084036

Installation trough for 5 connection rails or separating strips Grid 22.5 mm.
Depth: 22 mm; 30 mm; 50 mm



Dimensions



Surge protection for LSA-Plus systems

LSA simple tool




Type
LSA-TOOL

Pack	Weight
Piece	kg/100 pc.
1	0.600
Item no. 5084040	

Simple tool for the soldering, bolting and stripping-free connection of cores, without cutter.



Dimensions



LSA protective housing



Colour
Type
LSA-G | Light grey


Pack	Weight
Piece	kg/100 pc.
1	57.500
Item no. 5084048	

PA Polyamide
Protective housing for a LSA 10 DA bar

- Protective housing for 10 wire pairs
- Housing can be locked
- Incl. key
- 4x cable fixing
- Light grey



Dimensions



Coaxial protection devices for S-UHF connection: female/female




Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
S-UHF W/W	UHF	0 - 1,3 GHz	1	7.000	5093015

Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 µs)
- Simple installation (adapter plug), m = male/f = female connector
- Various plug combinations
- With UHF connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation




Dimensions

**S-UHF W/W**

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_r	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20µs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20µs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 1,3 GHz
Insertion loss	S_{21}	≤0,2 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		UHF
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Connection options



Coaxial protection devices for S-UHF connection: male/female





CE LPZ 0→2

Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
S-UHF M/W	UHF	0 - 1,3 GHz	1	7.000	5093023

Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 µs)
- Simple installation (adapter plug), m = male/f = female connector
- Various plug combinations
- With UHF connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

Dimensions**Connection options****S-UHF M/W**

Maximum continuous voltage AC	U_C	130 V
Maximum continuous voltage DC	U_C	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_r	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20µs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20µs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 1,3 GHz
Insertion loss	S_{21}	≤0,2 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		UHF
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Coaxial protection device for BNC connection: male/female




Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-BNC M/W	BNC	0 - 2,2 GHz	1	6.500	5093252

Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 µs)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With BNC connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation




Dimensions

**DS-BNC M/W**

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_r	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20µs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20µs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 2,2 GHz
Insertion loss	S_{21}	≤0,95 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		BNC
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Connection options



Coaxial protection device for BNC connection: female/female




Type	Connection system	Frequency range
DS-BNC W/W	BNC	0 - 2,2 GHz

Pack Piece Weight
kg/100 pc. Item no.
1 6.000 5093236


Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 µs)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With BNC connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

Dimensions



Connection options



DS-BNC W/W

Maximum continuous voltage AC	U_C	130 V
Maximum continuous voltage DC	U_C	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_L	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20µs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20µs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 2,2 GHz
Insertion loss	S_{21}	≤0,95 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		BNC
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Coaxial protection device for BNC connection: male/male




Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-BNC M/M	BNC	0 - 2,2 GHz	1	7.000	5093260

Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 µs)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With BNC connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation




Dimensions

**DS-BNC M/M**

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_r	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20µs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20µs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 2,2 GHz
Insertion loss	S_{21}	≤0,95 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		BNC
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Connection options



Coaxial protection device for N connection: male/female




Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-N M/W N		0 - 3 GHz	1	12.200	5093996

Coaxial data cable protection devices




- High pulsed current carrying capacity 2 x 2.5 kA (10/350)
- Simple mounting (adapter plug), m = plug/f = female connector
- Optimised transmission behaviour
- 5-year guarantee
- With N connector
- Including OBO M25 Quick clip for simple installation

Dimensions



Connection options



DS-N M/W

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_r	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 3 GHz
Insertion loss	S_{21}	≤0,62 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		N
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Coaxial protection device for N connection: female/female







Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-N W/W N	N	0 - 3 GHz	1	11.500	5093988

Coaxial data cable protection devices


- High pulsed current carrying capacity 2 x 2.5 kA (10/350)
- Simple mounting (adapter plug), m = plug/f = female connector
- Optimised transmission behaviour
- 5-year guarantee
- With N connector
- Including OBO M25 Quick clip for simple installation



Dimensions



Connection options



DS-N W/W

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_r	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 3 GHz
Insertion loss	S_{21}	≤0,62 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		N
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Coaxial protection device for N connection up to 6 GHz: Male/female




Type	Connec-tion system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-N-6 M/W N		0 - 6 GHz	1	7.830	5093998

Coaxial data cable protection devices for transmission and reception technology


- With N-Connector, male/female
- High impulse current load capacity: 2.5 kA (10/350)
- Simple mounting (adapter), m = connector, w = socket
- Low protection level at high current loads
- Optimum transmission behaviour:
 - Low reflection behaviour
 - Bandwidth-optimised for secure transmission up to 6 GHz
- Available in 50 Ω technology

Application: For example: SAT-TV C band, WiMAX, WLAN applications, DVB-T2

Dimensions



Connection options



DS-N-6 M/W

Maximum continuous voltage AC	U_c	50 V
Maximum continuous voltage DC	U_c	70 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_r	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imn}	2.5 kA
Protection level		<750 V
Frequency range		0 - 6 GHz
Insertion loss	S_{21}	≤0,1 dB
Return loss	S_{11}	≥22 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		N
Protection rating		IP65/67
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Coaxial protection device for TNC connection: male/female




Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-TNC M/W	TNC	0 - 4 GHz	1	7.953	5093270

Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 µs)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With TNC connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation




Dimensions



DS-TNC M/W

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_r	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20µs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20µs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 4 GHz
Insertion loss	S_{21}	≤0,5 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		TNC
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Connection options



Coaxial protection device for 7/16 connection: male/female




Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-7 16 M/W	7/16	0 - 3 GHz	1	35.500	5093171

Coaxial data protection device


- Basic protection
- Simple mounting (adapter)
- Optimum transmission
- High pulse load capacity
- With 7/16 connector

Application: to protect mobile telephony applications.

Dimensions



Connection options



DS-7 16 M/W

Maximum continuous voltage AC	U_C	130 V
Maximum continuous voltage DC	U_C	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_L	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 3 GHz
Insertion loss	S_{21}	≤0,95 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		7/16
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Coaxial protection device for F connection: male/female




Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-F M/W	F	0 - 3,4 GHz	1	9.000	5093275


Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 µs)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With F connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

Application: Protection of TV and SAT systems, multi-switches, receivers and DVB-T(2)

**Dimensions****DS-F M/W**

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		1
Rated current	I_r	5 A
Wave resistance	Z_L	75 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20µs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20µs)
Impulse discharge current (10/350)	I_{imp}	1 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		2 kA
Protection level		<800 V
Frequency range		0 - 3,4 GHz
Insertion loss	S_{21}	≤0,9 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		F
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Connection options

Coaxial protection device for F connection: female/female




Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-F W/W F	F	0 - 3,4 GHz	1	9.000	5093272


Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 µs)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With F connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

Dimensions



Application: Protection of TV and SAT systems, multi-switches, receivers and DVB-T(2)



DS-F W/W

Maximum continuous voltage AC	U_C	130 V
Maximum continuous voltage DC	U_C	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_L	5 A
Wave resistance	Z_L	75 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20µs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20µs)
Impulse discharge current (10/350)	I_{imp}	1 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		2 kA
Protection level		<800 V
Frequency range		0 - 3,4 GHz
Insertion loss	S_{21}	≤0,9 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		F
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Coaxial protection device for SMA connection: female/female



Type	Connec-tion system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-SMA W/W	SMA	0 - 3,7 GHz	1	7.500	5093277


Coaxial data cable protection devices

- High pulse current carrying capacity 2 x 2.5 kA (10/350)
- Simple mounting (adapter connector), m = connector, f = socket
- Optimised transmission behaviour
- 5-year guarantee
- With SMA connector
- Including OBO Multi-Quick clip 25-28 for simple installation
- 50 Ω technology


Application: Radio and data technology with SMA connector



Dimensions



Connection options

**DS-SMA W/W**

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_r	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 3,7 GHz
Insertion loss	S_{21}	≤0,2 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		SMA
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Coaxial protection device for SAT and cable multi-switch




Type	Connection system	Frequency range	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
TV 4+1 F		0,5 - 2,8 GHz F		1	37.000	5083400

Coaxial data line protection for TV reception systems


- Protects up to four SAT lines
- Protects one terrestrial line, e.g. DVB-T.
- Simple mounting using screws and holder
- With F-connector
- Optimum transmission behaviour with 75 Ohm technology.

Application: Protection of TV and SAT systems, multi-switches, receivers and DVB-T receivers

Dimensions



Connection options



TV 4+1

Maximum continuous voltage Vc SAT inputs	U _C	22 V
Maximum continuous voltage Vc terrestrial input	U _C	70 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1-3
Number of poles		5
Rated current	I _I	2 A
Wave resistance	Z _L	75 Ω
Nominal discharge current SAT inputs	I _n	300 A
Lightning impulse current terrestrial input	I _{imp}	1 kA
Protection level SAT inputs at In	U _p	<45 V
Protection level Terrestrial input at In		<500 V
Frequency range		0,5 - 2,8 GHz
Insertion loss	S ₂₁	<3 dB
Return loss	S ₁₁	>30 dB
Temperature range	θ	-40 - +80 °C
Installation type		Surface-mounted
Connection system		F
Protection rating		IP10
Shielding connection available		Yes
Shield connection		Direct
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Surge protection for high-speed networks up to 10 GBit (Class EA/CAT6A)



Type	Version	Connec- tion system	Pack Piece	Weight kg/100 pc.	Item no.
ND-CAT6A/EA	Fine protection, 8 wires + shield	RJ45 8(8)	1	16.600	5081800


Data cable protection device for high-speed networks

- High-quality RJ45 sockets
- Low protection level at high current load
- Earthing via DIN rail or connection cable
- Support of Power over Ethernet ++ (PoE++/4PPoE) to 1 A in accordance with IEEE 802.3
- Tested transmission quality in networks up to 1 GBit/s (Class E) or CAT6
- Fast installation through plug-in version
- Incl. DIN rail fastening set and earthing cable

Application example: 1 GBit Ethernet, 10/100 MBit Ethernet, PoE applications, IP camera systems, ISDN S0 interfaces




Dimensions



ND-CAT6A/EA

Maximum continuous voltage AC	U_c	41 V
Maximum continuous voltage DC	U_c	58 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Channel performance ISO/IEC		Class EA
Channel performance Ansi/EA		CAT 6A
Number of poles		8
Rated current	I_r	1 A
Impulse durability wire-wire		C1: 0,3 kV / 0,15 kA (8/20μs)
Impulse durability wire-earth		C2: 2 kV / 1 kA (8/20μs)
Total discharge current (8/20)		7 kA
Protection level wire-wire		<120 V
Protection level wire-earth		<700 V
Frequency range		>500 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ45 8(8)
Protection rating		IP10
Shielding connection available		Yes
Shield connection		Direct
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connection options



Surge protection for high-speed networks up to 1 GBit (Class ND-CAT6/E-B)




Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
ND-CAT6/E-B	Basic protection, 8 wires + shield	RJ45 8(8)	1	16.220	5081804

Alu Aluminium


Data cable protection device for high-speed networks

- High-quality RJ45 sockets
- Low protection level at high current load
- Earthing via DIN rail or connection cable
- Support of Power over Ethernet ++ (PoE++/4PPoE) to 1 A in accordance with IEEE 802.3
- Tested transmission quality in networks up to 1 GBit/s (Class E) or CAT6
- Fast installation through plug-in version
- Incl. DIN rail fastening set and earthing cable

Dimensions



Application example: 1 GBit Ethernet, 10/100 MBit Ethernet, PoE applications, IP camera systems, ISDN S0 interfaces



ND-CAT6/E-B

Maximum continuous voltage AC	U_c	46 V
Maximum continuous voltage DC	U_c	65 V
Category		Type 1 / D1
Lightning protection zone LPZ		0→1
Channel performance ISO/IEC		Class E
Channel performance Ansi/EA		CAT 6
Number of poles		8
Rated current	I_r	1 A
Impulse durability wire-wire		C2: 3 kV / 1,5 kA (8/20μs)
Impulse durability wire-earth		C2: 3 kV / 1,5 kA (8/20μs)
Total discharge current (8/20)		10 kA
Protection level wire-wire		<1100 V
Protection level wire-earth		<900 V
Frequency range		>250 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ45 8(8)
Protection rating		IP10
Shielding connection available		Yes
Shield connection		Direct
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Surge protection for high-speed networks up to 1 GBit (Class ND-CAT6/E-F)



Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
ND-CAT6/E-F	Fine protection, 8 wires + shield	RJ45 8(8)	1	16.380	5081802

Alu: Aluminium


Data cable protection device for high-speed networks

- High-quality RJ45 sockets
- Low protection level at high current load
- Earthing via DIN rail or connection cable
- Support of Power over Ethernet ++ (PoE++/4PPoE) to 1 A in accordance with IEEE 802.3
- Tested transmission quality in networks up to 1 GBit/s (Class E) or CAT6
- Fast installation through plug-in version
- Incl. DIN rail fastening set and earthing cable

Application example: 1 GBit Ethernet, 10/100 MBit Ethernet, PoE applications, IP camera systems, ISDN S0 interfaces




Dimensions



ND-CAT6/E-F

Maximum continuous voltage AC	U_c	41 V
Maximum continuous voltage DC	U_c	58 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Channel performance ISO/IEC		Class E
Channel performance Ansi/EA		CAT 6
Number of poles		8
Rated current	I_r	1 A
Impulse durability wire-wire		C1: 0,3 kV / 0,15 kA (8/20μs)
Impulse durability wire-earth		C2: 3 kV / 1,5 kA (8/20μs)
Total discharge current (8/20)		5 kA
Protection level wire-wire		<40 V
Protection level wire-earth		<900 V
Frequency range		>250 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ45 8(8)
Protection rating		IP10
Shielding connection available		Yes
Shield connection		Direct
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connection options




 Surge protection for network technology



Fine protection 8-F for Ethernet networks (Class D/CAT 5)



Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
RJ45 S-ATM 8-F	Fine protection, 8 wires + shield	RJ45 8(8)	1	14.000	5081990

Universal data cable protection device for network technology and telecommunication systems

- In aluminium housing
- Protection for 8 cores
- With two-stage protective circuit
- Simple mounting
- With RJ45 Western connector
- Incl. 150 mm connection cable with RJ45 connectors
- Cat 5e network technology, 10BaseT, 100BaseT, 1000BaseT
- DIN rail mounting with accessories DLS-BS (5082 38 2)

Application: For analogue, ISDN, DSL systems, Ethernet Twisted Pair.


Dimensions


Connection options

RJ45 S-ATM 8-F

Maximum continuous voltage AC	U_c	4.2 V
Maximum continuous voltage DC	U_c	6.2 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Channel performance ISO/IEC		Class D
Channel performance Ansi/EA		CAT 5e
Number of poles		8
Rated current	I_L	1 A
Impulse durability wire-wire		C2: 3 kV / 1,5 kA (8/20μs)
Impulse durability wire-earth		C2: 3 kV / 1,5 kA (8/20μs)
Total discharge current (8/20)		7,5 kA
Protection level wire-wire		<40 V
Protection level wire-earth		<900 V
Frequency range		>155 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ45 8(8)
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Combination arrestor for 10Base2-/10Base5 networks



Type	Version	Connec-tion system	Pack Piece	Weight kg/100 pc.	Item no.
KOAX B-E2 MF-C	Combi protection	BNC	1	10.300	5082430


Data line protection device for coaxial Ethernet network systems

- In aluminium housing
- BNC connector m/f
- Simple mounting with adapter plug
- Two-stage protection circuit
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: Protecting video signals; cameras and/or CCTV units, Cheapernet, 10BASE2, 10BASE5




Dimensions



KOAX B-E2 MF-C

Maximum continuous voltage AC	U_c	4.2 V
Maximum continuous voltage DC	U_c	6.2 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		1
Rated current	I_r	0.3 A
Series resistance per wire		4.7 $\Omega \pm 10\%$
Wave resistance	Z_w	75 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp}	1 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		2 kA
Protection level wire-wire		<75 V
Protection level wire-earth		<600 V
Frequency range		0 - 68 MHz
Insertion loss	S_{21}	≤ 1.7 dB
Return loss	S_{11}	≥ 14 dB
Temperature range	θ	-20 - +80 °C
Installation type		Connector/cable adapter
Connection system		BNC
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Connection options



Surge protection for network technology

Fine protection for 10Base2-/10Base5 networks




Type	Version	Connec-tion system	Pack Piece	Weight kg/100 pc.	Item no.
KOAX B-E2 MF-F	Fine protection	BNC	1	9.800	5082432

Data line protection device for coaxial Ethernet network systems


- In aluminium housing
- BNC connector m/f
- Simple mounting with adapter plug
- Two-stage protection circuit
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: Protecting video signals; cameras and/or CCTV units, Cheapernet, 10BASE2, 10BASE5

Dimensions



Connection options



KOAX B-E2 MF-F

Maximum continuous voltage AC U_c	4.2 V
Maximum continuous voltage DC U_c	6.2 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1→3
Number of poles	1
Rated current I_r	1 A
Wave resistance Z_L	75 Ω
Impulse durability wire-wire	C1: 1 kV / 0,5 kA (8/20μs)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20μs)
Total discharge current (8/20)	10 kA
Protection level wire-wire	<40 V
Protection level wire-earth	<600 V
Frequency range	0 - 70 MHz
Insertion loss S_{21}	≤1 dB
Return loss S_{11}	≥14 dB
Temperature range ϑ	-20 - +80 °C
Installation type	Connector/cable adapter
Connection system	BNC
Protection rating	IP40
Shielding connection available	Yes
Shield connection	Direct
Earthing via:	Connection cable
Testing standard	IEC 61643-21

Data cable protection device for coaxial TV / camera systems



Type	Version	Connec- tion system	Pack Piece	Weight kg/100 pc.	Item no.
KOAX B-E2 FF-F	Fine protection	BNC	1	14.400	5082434


Data cable protection device for coaxial TV / camera systems

- In aluminium housing
- BNC connector socket/socket
- Simple mounting with adapter plug
- Two-stage protection circuit
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: Protection of CCTV, video signals; cameras and/or TV systems




Dimensions



KOAX B-E2 FF-F

Maximum continuous voltage AC	U_c	4.2 V
Maximum continuous voltage DC	U_c	6.2 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Number of poles		1
Rated current	I_r	1 A
Wave resistance	Z_L	75 Ω
Impulse durability wire-wire		C1: 1 kV / 0,5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Total discharge current (8/20)		10 kA
Protection level wire-wire		<40 V
Protection level wire-earth		<600 V
Frequency range		0 - 160 MHz
Insertion loss	S_{21}	≤1,7 dB
Return loss	S_{11}	≥14 dB
Temperature range	θ	-20 - +80 °C
Installation type		Connector/cable adapter
Connection system		BNC
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Connection options



Fastening set for DIN profile rail




Version

Type	Version	Pack	Weight	Item no.
		Piece	kg/100 pc.	
DLS-BS	For mounting: • Coax B-E2/... • Coax N-E5/... • RJ 11-Tele/4... • RJ 45 S...	1	5.000	5082382

DLS-BS: The fastening set is designed for a hat profile rail and wall mounting and can be used for the data cable protection devices listed below:

- Coax N-E5/...
- Coax B-E2/...
- RJ 11-Tele/4...
- RJ 45 S...

Dimensions



Basic protection for 4-wire information technology systems with RJ45



Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
RJ45 S-E100 4-B	Basic protection, 4 wires + shield	RJ45	1	14.000	5081001


Data line protection device for IT systems

- In aluminium housing
- RJ45 connector
- Incl. 150 mm connection cable with RJ45 connectors
- Simple mounting using adapter
- 2-stage protection circuit
- DIN rail mounting with DLS-BS accessories (5082 38 2)


Application: Twisted Pair, control circuits, RJ45 communication cables



Dimensions



Connection options



RJ45 S-E100 4-B

Maximum continuous voltage AC	U_c	120 V
Maximum continuous voltage DC	U_c	170 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		4
Rated current	I_i	1 A
Impulse durability wire-wire		C2: 3 kV / 1,5 kA (8/20μs)
Impulse durability wire-earth		C2: 3 kV / 1,5 kA (8/20μs)
Impulse discharge current (10/350)	I_{im}	0.5 kA
Total discharge current (8/20)		7.5 kA
Total discharge current (10/350)		2.5 kA
Protection level wire-wire		<700 V
Protection level wire-earth		<850 V
Frequency range		0 - 463 MHz
Insertion loss	S_{21}	≤3 dB
Temperature range	θ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ45
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Indirect
Earthing via:		Connection cable
Testing standard		IEC 61643-21


Combination arrestor for 4-wire information technology systems with RJ45




Type	Version	Connec-tion system	Pack Piece	Weight kg/100 pc.	Item no.
RJ45 S-E100 4-C	Combined protection, 4 wires + shield	RJ45	1	14.000	5081003

Data line protection device for IT systems

- In aluminium housing
- RJ45 connector
- Incl. 150 mm connection cable with RJ45 connectors
- Simple mounting using adapter
- 2-stage protection circuit
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Dimensions

Application: Twisted Pair, control circuits, RJ45 communication cables

Connection options**RJ45 S-E100 4-C**

Maximum continuous voltage AC	U_C	4.2 V
Maximum continuous voltage DC	U_C	6.2 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→2
Number of poles		4
Rated current	I_L	0.3 A
Series resistance per wire		$4.7 \Omega \pm 10\%$
Impulse durability wire-wire		C2: 3 kV / 1,5 kA (8/20μs)
Impulse durability wire-earth		C2: 3 kV / 1,5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp}	1.5 kA
Total discharge current (8/20)		7.5 kA
Total discharge current (10/350)		2.5 kA
Protection level wire-wire		<70 V
Protection level wire-earth		<850 V
Frequency range		0 - 109 MHz
Insertion loss	S_{21}	≤ 3 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ45
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Indirect
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Fine protection for 4-wire information technology systems with RJ45



Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
RJ45 S-E100 4-F	Fine protection, 4 wires + shield	RJ45	1	14.000	5081005


Data line protection device for IT systems

- In aluminium housing
- RJ45 connector
- Incl. 150 mm connection cable with RJ45 connectors
- Simple mounting using adapter
- 2-stage protection circuit
- DIN rail mounting with DLS-BS accessories (5082 38 2)


Application: Twisted Pair, control circuits, RJ45 communication cables



Dimensions



Connection options

**RJ45 S-E100 4-F**

Maximum continuous voltage AC	U_c	4.2 V
Maximum continuous voltage DC	U_c	6.2 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		2→3
Number of poles		4
Rated current	I_i	1 A
Impulse durability wire-wire		C1: 1 kV / 0,5 kA (8/20μs)
Impulse durability wire-earth		C1: 1 kV / 0,5 kA (8/20μs)
Impulse discharge current (10/350)	I_{im}	— kA
Total discharge current (8/20)		2,5 kA
Total discharge current (10/350)		— kA
Protection level wire-wire		<40 V
Protection level wire-earth		<750 V
Frequency range		0 - 100 MHz
Insertion loss	S_{21}	≤3 dB
Temperature range	θ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		RJ45
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Indirect
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Combined protection device 2in1 for CCTV camera systems




Type	Maximum continuous voltage (L-N) V	Maximum discharge current (8/20 µs) kA	Pack Piece	Weight kg/100 pc.	Item no.
PND-2in1-C-OS	255	10	1	27.000	5081070

Combination protection device for IP-based TV/camera systems


- Protection of power and data interface in a single device
- In aluminium housing
- Simple mounting with adapter plug
- Two-stage protection circuit
- Three-pole power connection for the power interface
- RJ45 connection for the data interface
- With LED operation display (OS)
- Incl. DIN rail fastening set

Dimensions



Application: Protection of CCTV, video signals, (IP) cameras and/or TV systems

Connection options



PND-2in1-C-OS

Temperature range	0	-20 - +80 °C
Installation type		Installation
Protection rating		IP20
Earthing via:		Connection cable / DIN rail
Lightning protection zone LPZ		1-3
Power		
SPD to IEC 61643-11		Class II+III
SPD to EN 61643-11		Type 2+3
Maximum continuous voltage (L-N)	U_c	255 V
Rated current	I_r	16 A
Protection level	U_p	<1,3 kV
Idle voltage	U_{OC}	10 kV
Nominal discharge current (8/20 µs)	$I_n / I_{N,N}$	5 kA
Maximum discharge current (8/20 µs)	I_{max}	10 kA
Network		
Maximum continuous voltage AC	U_c	5.65 V
Maximum continuous voltage DC	U_c	8 V
Category		Type 1+2+3 / D1+C2+C1
Impulse durability wire-wire		C1: 0,3 kV / 0,15 kA (8/20µs)
Impulse durability wire-earth		C2: 3 kV / 1,5 kA (8/20µs)
Protection level wire-wire		<40 V
Protection level wire-earth		<450 V
Frequency range		0 - 100 MHz
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21



Type	Maximum continuous voltage (L-N) V	Maximum discharge current (8/20 µs) kA	Pack Piece	Weight kg/100 pc.	Item no.
PND-3in1-C-OS	255	10	1	29.900	5081072

Combination protection device for coaxial TV/camera systems



- Protection of power and data interfaces in a single device
- In aluminium housing
- Simple mounting with adapter
- Two-stage protection circuit
- Three-pole power connection for the power interface
- With LED operation display (OS)
- Incl. DIN rail fastening set



Application: Protection of CCTV, video signals, cameras and/or TV systems

PND-3in1-C-OS

Lightning protection zone LPZ	1→3
Earthing via:	Connection cable / DIN rail
Protection rating	IP20
Power	
SPD to IEC 61643-11	Class II+III
SPD to EN 61643-11	Type 2+3
Maximum continuous voltage (L-N) U_c	255 V
Rated current I_L	16 A
Protection level U_p	<1,3 kV
Nominal discharge current (8/20 µs) $I_{n/8-20\mu s}$	5 kA
Maximum discharge current (8/20 µs) I_{max}	10 kA
Data	
Maximum continuous voltage AC U_c	5.65 V
Maximum continuous voltage DC U_c	8 V
SPD to IEC 61643-21	Class I+II / D1+C2
Category	Type 1+2 / D1+C2
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20µs)
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20µs)
Impulse current (10/350) I_{imp}	1 kA
Protection level wire-earth	<450 V
Protection level wire-wire	<65 V
Frequency range	0-100 MHz
Video	
Maximum continuous voltage AC U_c	5.65 V
Maximum continuous voltage DC U_c	8 V
SPD to IEC 61643-21	Class I+II / D1+C2
Category	Type 1+2 / D1+C2
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20µs)
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20µs)
Impulse current (10/350) I_{imp}	1 kA
Protection level wire-wire	<90 V
Protection level wire-earth	<150 V
Frequency range	0-100 MHz
Screen connection	Yes
Screening	Direct
Temperature range ϑ	-20 - +80 °C

Dimensions**Connection options**



Surge protection for serial interfaces

Fine protection for 9-pole RS232 interface




Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
SD09-V24 9	18	SUB-D-9; V24 RS232	1	6.000	5080053

Data cable protection device for serial interfaces


- Various connection technologies available
- Low voltage protection level

Application: PLC, alarm systems, controllers

Dimensions



Connection options



SD09-V24 9

Max. continuous operating voltage	U_c 18 V
Category	Type 3 / C1
Lightning protection zone LPZ	2-3
Number of poles	9
Impulse durability wire-wire	0,34 kA (8/20μs)
Impulse durability wire-earth	0,34 kA (8/20μs)
Protection level wire-wire	<50 V
Protection level wire-earth	<50 V
Protection level, wire-earth at 1 kV/μs (C3)	U_n <25 V
Temperature range	-40 - +80 °C
Installation type	Connector/cable adapter
Connection system	D-Sub 9-pin
Protection rating	IP40
Shielding connection available	Yes
Shield connection	Direct
Testing standard	IEC 61643-21

Fine protection for 15-pole RS232 interface



Highest
contin-
ous
voltage

Type V Version

SD15-V24 15 | 18 | SUB-D-15; V24 RS232

Pack
Piece
kg/100 pc.

5080150


Data cable protection device for serial interfaces

- Various connection technologies available
- Low voltage protection level

Application: PLC, alarm systems, controllers




Dimensions

**SD15-V24 15**

Max. continuous operating voltage	U_c	18 V
Category		Type 3 / C1
Lightning protection zone LPZ		2-3
Number of poles		15
Impulse durability wire-wire		0,34 kA (8/20μs)
Impulse durability wire-earth		0,34 kA (8/20μs)
Protection level wire-wire		<50 V
Protection level wire-earth		<50 V
Protection level, wire-earth at 1 kV/μs (C3)	U_n	<25 V
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		D-Sub 15-pin
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Connection options





Surge protection for serial interfaces

Fine protection for 9-pole RS485 interface




Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
SD09-V11 9	7.5	SUB-D-9; V11 RS485	1	2.951	5080061

Data cable protection device for serial interfaces


- Various connection technologies available
- Low voltage protection level

Application: PLC, alarm systems, controllers

Dimensions



Connection options



SD09-V11 9

Max. continuous operating voltage	U_c 7.5 V
Category	Type 3 / C1
Lightning protection zone LPZ	2-3
Number of poles	9
Impulse durability wire-wire	0,75 kA (8/20μs)
Impulse durability wire-earth	0,75 kA (8/20μs)
Protection level wire-wire	<100 V
Protection level wire-earth	<100 V
Protection level, wire-earth at 1 kV/μs (C3)	U_n <10 V
Temperature range	-40 - +80 °C
Installation type	Connector/cable adapter
Connection system	D-Sub 9-pin
Protection rating	IP40
Shielding connection available	Yes
Shield connection	Direct
Testing standard	IEC 61643-21



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2-5-D	4.2	6	2	1	6.500	5080301


Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Direct shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Installation width from 12.5 mm
- High system availability – no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Dimensions



Connection options

PDP-2-5-D

Maximum continuous voltage AC	U_c	4.2 V
Maximum continuous voltage DC	U_c	6 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		2
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2.5 kA
Protection level wire-wire		100 V
Protection level wire-earth		850 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2-pole, direct earthing




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2-12-D	12	16	2	1	6.500	5080303

Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Direct shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Installation width from 12.5 mm
- High system availability – no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.

Dimensions



Connection options

PDP-2-12-D

Maximum continuous voltage AC	U_c	12 V
Maximum continuous voltage DC	U_c	16 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		2
Nominal load current AC	I_n	0.43 A
Nominal load current DC	I_n	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		130 V
Protection level wire-earth		850 V
Frequency range		0 - 100 MHz
Temperature range	θ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2-pole, direct earthing



Type	Highest voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2-24-D	21	30	2	1	6.500	5080305


Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Direct shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Installation width from 12.5 mm
- High system availability – no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Dimensions



Connection options

PDP-2-24-D

Maximum continuous voltage AC	U_c	21 V
Maximum continuous voltage DC	U_c	30 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		2
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		150 V
Protection level wire-earth		850 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2-pole, direct earthing




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2-48-D	37	52	2	1	6.500	5080307

Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Direct shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Installation width from 12.5 mm
- High system availability – no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.

Dimensions



Connection options

PDP-2-48-D

Maximum continuous voltage AC	U_c	37 V
Maximum continuous voltage DC	U_c	52 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		2
Nominal load current AC	I_n	0.43 A
Nominal load current DC	I_n	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		170 V
Protection level wire-earth		850 V
Frequency range		0 - 100 MHz
Temperature range	θ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2-pole, indirect earthing



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2-5-I	4.2	6	2	1	6.600	5080309


Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Indirect shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Small installation width of 12.5 mm
- High system availability - no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Dimensions



Connection options

PDP-2-5-I

Maximum continuous voltage AC	U_c	4.2 V
Maximum continuous voltage DC	U_c	6 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		2
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		100 V
Protection level wire-earth		1600 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Indirect
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2-pole, indirect earthing




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2-12-I	12	16	2	1	6.600	5080311

Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Indirect shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Small installation width of 12.5 mm
- High system availability - no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.

Dimensions



Connection options

PDP-2-12-I

Maximum continuous voltage AC	U_c	12 V
Maximum continuous voltage DC	U_c	16 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		2
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		130 V
Protection level wire-earth		1600 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Indirect
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2-24-I	21	30	2	1	6.600	5080313


Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Indirect shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Small installation width of 12.5 mm
- High system availability - no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Dimensions



Connection options

PDP-2-24-I

Maximum continuous voltage AC	U_c	21 V
Maximum continuous voltage DC	U_c	30 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		2
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		150 V
Protection level wire-earth		1600 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Indirect
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2-pole, indirect earthing




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2-48-I	37	52	2	1	6.600	5080315

Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Indirect shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Small installation width of 12.5 mm
- High system availability - no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.

Dimensions



Connection options

PDP-2-48-I

Maximum continuous voltage AC	U_c	37 V
Maximum continuous voltage DC	U_c	52 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		2
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		170 V
Protection level wire-earth		1600 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Indirect
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21






Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2x2-5-D	4.2	6	—	1	7.200	5080317


Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Direct shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Installation width from 12.5 mm
- High system availability – no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Dimensions



Connection options

PDP-2x2-5-D

Maximum continuous voltage AC	U_c	4.2 V
Maximum continuous voltage DC	U_c	6 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Version		2x2-pole
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		100 V
Protection level wire-earth		850 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2x2-pole, direct earthing




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2x2-12-D	12	16	—	1	7.200	5080319

Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Direct shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Installation width from 12.5 mm
- High system availability – no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Dimensions

Connection options

PDP-2x2-12-D

Maximum continuous voltage AC	U_c	12 V
Maximum continuous voltage DC	U_c	16 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Version		2x2-pole
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		130 V
Protection level wire-earth		850 V
Frequency range		0 - 100 MHz
Temperature range	θ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2x2-24-D	21	30	—	1	7.200	5080321


Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Direct shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Installation width from 12.5 mm
- High system availability – no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Dimensions



Connection options

PDP-2x2-24-D

Maximum continuous voltage AC	U_c	21 V
Maximum continuous voltage DC	U_c	30 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Version		2x2-pole
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		150 V
Protection level wire-earth		850 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2x2-pole, direct earthing




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2x2-48-D	37	52	—	1	7.200	5080323

Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Direct shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Installation width from 12.5 mm
- High system availability – no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Connection options

PDP-2x2-48-D

Maximum continuous voltage AC	U_c	37 V
Maximum continuous voltage DC	U_c	52 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Version		2x2-pole
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		170 V
Protection level wire-earth		850 V
Frequency range		0 - 100 MHz
Temperature range	θ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2x2-pole, indirect earthing



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2x2-5-I	4.2	6	—	1	7.300	5080325


Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Indirect shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Small installation width of 12.5 mm
- High system availability - no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Dimensions



Connection options

PDP-2x2-5-I

Maximum continuous voltage AC	U_c	4.2 V
Maximum continuous voltage DC	U_c	6 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Version		2x2-pole
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		100 V
Protection level wire-earth		1600 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Indirect
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2x2-pole, indirect earthing




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2x2-12-I	12	16	-	1	7.300	5080327

Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Indirect shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Small installation width of 12.5 mm
- High system availability - no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.

Dimensions



Connection options

PDP-2x2-12-I

Maximum continuous voltage AC	U_c	12 V
Maximum continuous voltage DC	U_c	16 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Version		2x2-pole
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		130 V
Protection level wire-earth		1600 V
Frequency range		0 - 100 MHz
Temperature range	θ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Indirect
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2x2-pole, indirect earthing



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2x2-24-I	21	30	—	1	7.300	5080329


Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Indirect shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Small installation width of 12.5 mm
- High system availability - no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Dimensions



Connection options

PDP-2x2-24-I

Maximum continuous voltage AC	U_c	21 V
Maximum continuous voltage DC	U_c	30 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Version		2x2-pole
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		150 V
Protection level wire-earth		1600 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Indirect
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

Connectable data cable protection, 2x2-pole, indirect earthing




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2x2-48-I	37	52	-	1	7.300	5080331

Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Indirect shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Small installation width of 12.5 mm
- High system availability - no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.

Dimensions



Connection options

PDP-2x2-48-I

Maximum continuous voltage AC	U_c	37 V
Maximum continuous voltage DC	U_c	52 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Version		2x2-pole
Nominal load current AC	I_L	0.43 A
Nominal load current DC	I_L	0.6 A
Series resistance per wire		$1,2 \Omega \pm 5\%$
Impulse durability wire-wire		10 kV / 5 kA
Impulse durability wire-earth		10 kV / 5 kA
Total discharge current (8/20)		20 kA
Total discharge current (10/350)		2,5 kA
Protection level wire-wire		170 V
Protection level wire-earth		1600 V
Frequency range		0 - 100 MHz
Temperature range	θ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Indirect
Connection cross-section, flexible		0.14 - 1.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Connection cable / DIN rail
Testing standard		IEC 61643-21

MCR protection for 2-pole power supply, 12 V



Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF12-AC DC	13.5	1	9.000	5097453


Surge protection device / fine protection type 3 to EN 61643-11

- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit


Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.



Dimensions



Connection options



VF12-AC DC

U max AC	U_c AC	13.5 V
U max DC	U_c DC	18 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	0.7 kA
Maximum discharge current (8/20 μ s)	I_{max}	2 kA
Rated current	I_L	20 A
Protection level wire-wire		<110 V
Protection level wire-earth		<1200 V
Response time	t_A	<25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, flexible		0.14 - 2.5 mm ²

MCR protection for 2-pole power supply

MCR protection for 2-pole for power supply, 24 V




Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF24-AC/DC 34		1	8.000	5097607

Surge protection device / fine protection type 3 to EN 61643-11


- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit

Dimensions



Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.

Connection options



VF24-AC/DC

U max AC	U_c AC	34 V
U max DC	U_c DC	46 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	0,7 kA
Maximum discharge current (8/20 µs)	I_{max}	2 kA
Rated current	I_L	20 A
Protection level wire-wire		<130 V
Protection level wire-earth		<1200 V
Response time	t_A	<25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, flexible		0.14 - 2.5 mm²



Highest
contin-
ous
voltage
V

Type

VF48-AC/DC | 60

Pack
Piece
kg/100 pc.

Weight
Item no.

| 1 | 8.000 | **5097615**


Surge protection device / fine protection type 3 to EN 61643-11

- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit


Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.



Dimensions



Connection options



VF48-AC/DC

U max AC	U_c AC	60 V
U max DC	U_c DC	80 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	0.7 kA
Maximum discharge current (8/20 μ s)	I_{max}	2 kA
Rated current	I_L	20 A
Protection level wire-wire		<220 V
Protection level wire-earth		<1200 V
Response time	t_A	<25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, flexible		0.14 - 2.5 mm ²

MCR protection for 2-pole power supply

MCR protection for 2-pole power supply, 60 V




Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF60-AC/DC 80		1	8.000	5097623

Surge protection device / fine protection type 3 to EN 61643-11


- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit

Dimensions



Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.

Connection options



VF60-AC/DC

U max AC	U_c AC	80 V
U max DC	U_c DC	110 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	0,7 kA
Maximum discharge current (8/20 µs)	I_{max}	2 kA
Rated current	I_L	20 A
Protection level wire-wire		<280 V
Protection level wire-earth		<1200 V
Response time	t_A	<25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, flexible		0.14 - 2.5 mm²



Highest
contin-
ous
voltage
V

Type

VF110-AC DC | 150

Pack
Piece | 1 | 8.000 | **Item no.** 5097631


Surge protection device / fine protection type 3 to EN 61643-11

- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit


Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.



Dimensions



Connection options




VF110-AC DC

U max AC	U_c AC	150 V
U max DC	U_c DC	200 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	2 kA
Maximum discharge current (8/20 μ s)	I_{max}	6.5 kA
Rated current	I_L	20 A
Protection level wire-wire		<500 V
Protection level wire-earth		<1400 V
Response time	t_A	<25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, flexible		0.14 - 2.5 mm ²

MCR protection for 2-pole power supply

MCR protection for 2-pole for power supply, 230 V




Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF230-AC/DC	255	1	8.000	5097650

Surge protection device / fine protection type 3 to EN 61643-11


- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit

Dimensions



Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.

Connection options



VF230-AC/DC

U max AC	U_c AC	255 V
U max DC	U_c DC	350 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	2.5 kA
Maximum discharge current (8/20 μ s)	I_{max}	7 kA
Rated current	I_L	20 A
Protection level wire-wire		<1000 V
Protection level wire-earth		<1400 V
Response time	t_A	<25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, flexible		0.14 - 2.5 mm ²

MCR protection for 2-pole power supply with remote signalling, 12 V AC/DC



Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF12-AC/DC-FS	13.5	1	6.400	5097454


Surge protection / fine power protection, type 3, to EN 61643-11 with remote signalling

- With remote signalling, potential-free changeover contact, for function monitoring
- Suitable for DC and AC systems
- With visual function display
- With easy mounting, screwless connection terminals
- In space-saving 17.5 mm grid
- Y circuit


Application: Universal use on 35 mm DIN profile rails in any standard distributor housing.



Dimensions



Connection options



VF12-AC/DC-FS

U max AC	U_c AC	13.5 V
U max DC	U_c DC	18 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	0.7 kA
Maximum discharge current (8/20 µs)	I_{max}	2 kA
Rated current	I_r	20 A
Protection level wire-wire		<110 V
Protection level wire-earth		<1200 V
Response time	t_A	<25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, flexible		0.14 - 2.5 mm²

MCR protection for 2-pole power supply with remote signalling

MCR protection for 2-pole power supply with remote signalling, 24 V AC/DC



Highest
contin-
ous
voltage
V


Type	VF24-AC/DC-FS 34	Pack Piece	Weight kg/100 pc.	Item no.
		1	6.620	5097820

Surge protection / fine power protection, type 3, to EN 61643-11 with remote signalling


- With remote signalling, potential-free changeover contact, for function monitoring
- Suitable for DC and AC systems
- With visual function display
- With easy mounting, screwless connection terminals
- In space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rails in any standard distributor housing.

Dimensions



Connection options



VF24-AC/DC-FS

U max AC	U _c AC	34 V
U max DC	U _c DC	46 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I _n	0,7 kA
Maximum discharge current (8/20 µs)	I _{max}	2 kA
Rated current	I _i	20 A
Protection level wire-wire		<160 V
Protection level wire-earth		<1200 V
Response time	t _A	<25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, flexible		0.14 - 2.5 mm ²

MCR protection for 2-pole power supply with remote signalling, 12 V AC/DC



Highest
contin-
ous
voltage
Type
V

VF48-AC/DC-FS | 60

Pack
Piece | 1 | 6.630
Weight
kg/100 pc. | 5097822


Surge protection / fine power protection, type 3, to EN 61643-11 with remote signalling

- With remote signalling, potential-free changeover contact, for function monitoring
- Suitable for DC and AC systems
- With visual function display
- With easy mounting, screwless connection terminals
- In space-saving 17.5 mm grid
- Y circuit


Application: Universal use on 35 mm DIN profile rails in any standard distributor housing.



Dimensions



Connection options



VF48-AC/DC-FS

U max AC	U_c AC	60 V
U max DC	U_c DC	80 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	0.7 kA
Maximum discharge current (8/20 µs)	I_{max}	2 kA
Rated current	I_r	20 A
Protection level wire-wire		<220 V
Protection level wire-earth		<1200 V
Response time	t_A	<25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, flexible		0.14 - 2.5 mm²

MCR protection for 2-pole power supply with remote signalling

MCR protection for 2-pole power supply with remote signalling, 230 V AC



Highest
contin-
ous
voltage
V


Type
VF230-AC-FS | 255

Pack
Piece | 1 | 6.910
Weight
kg/100 pc. | **5097858**


Surge protection / fine power protection, type 3, to EN 61643-11 with remote signalling

- With remote signalling, potential-free changeover contact, for function monitoring
- Suitable for AC systems
- With visual function display
- With easy mounting, screwless connection terminals
- In space-saving 17.5 mm grid
- Y circuit

Dimensions



Connection options



VF230-AC-FS

U max AC	U_c AC	255 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	2,5 kA
Maximum discharge current (8/20 µs)	I_{max}	7 kA
Rated current	I_l	20 A
Protection level wire-wire		<1060 V
Protection level wire-earth		<1400 V
Response time	t_A	<25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, flexible		0.14 - 2.5 mm ²

MCR protection for 2-pin for power supply with leak current-free remote signalling, 230 V AC/DC



Type	U max AC V	U max DC V	Pack Piece	Weight kg/100 pc.	Item no.
VF2-230-AC/DC-FS	255	350	1	6.000	5097939


Type 3 surge protection/fine network protection to EN 61643-11 with leak current-free remote signalling

- With remote signalling: potential-free NC contact for function monitoring
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- Y circuit


Application: Universal use on 35 mm DIN profile rails in any standard distributor housing.



Dimensions



Connection options



VF2-230-AC/DC-FS

U max AC	U_c AC	255 V
U max DC	U_c DC	350 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	2.5 kA
Maximum discharge current (8/20 µs)	I_{max}	7 kA
Rated current	I_r	20 A
Protection level wire-wire		< 1000 V
Protection level wire-earth		< 1400 V
Response time	t_A	<25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, flexible		0.14 - 2.5 mm²

Combination protection for two-core systems with HF applications 5 V




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 5 HF 4	4	6	2	Terminal	1	4.400	5098571

Surge protection for use in measuring, control and regulation systems.


- Basic, medium and fine protection
- Two-stage protection circuit with high lightning current carrying capacity
- High transmission frequency up to 100 MHz
- Suitable for all bus systems (e.g. Profibus)
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid

Dimensions



Application: Multipurpose use on any 35 mm DIN profile rail in every commercially available distribution housing.

Connection options



FRD 5 HF

Maximum continuous voltage AC	U_c	4 V
Maximum continuous voltage DC	U_c	6 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0-3
Number of poles		2
Rated current	I_r	0.45 A
Series resistance per wire		$2,2 \Omega \pm 10\%$
Impulse durability wire-wire		C2: 18 kV / 9 kA (8/20μs)
Impulse durability wire-earth		C2: 18 kV / 9 kA (8/20μs)
Total discharge current (8/20)		18 kA
Total discharge current (10/350)		D1: 6 kA
Protection level wire-wire		<90 V
Protection level wire-earth		<650 V
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Division unit TE (17.5 mm)		1
Protection rating		IP20
Connection cross-section, flexible		0.14 - 2.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Terminal
Testing standard		IEC 61643-21
Approvals		UL

Combination protection for two-core systems with HF applications

24 V



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 24 HF	19	28	2	Terminal	1	4.400	5098575


Surge protection for use in measuring, control and regulation systems.

- Basic, medium and fine protection
- Two-stage protection circuit with high lightning current carrying capacity
- High transmission frequency up to 100 MHz
- Suitable for all bus systems (e.g. Profibus)
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid


Application: Multipurpose use on any 35 mm DIN profile rail in every commercially available distribution housing.



Dimensions



Connection options



FRD 24 HF

Maximum continuous voltage AC	U_c 19 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	2
Rated current	I_L 0.45 A
Series resistance per wire	$2.2 \Omega \pm 10\%$
Impulse durability wire-wire	C2: 18 kV / 9 kA (8/20μs)
Impulse durability wire-earth	C2: 18 kV / 9 kA (8/20μs)
Total discharge current (8/20)	18 kA
Total discharge current (10/350)	D1: 6 kA
Protection level wire-wire	<120 V
Protection level wire-earth	<650 V
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm²
Connection cross-section, multi-wire	0.14 - 2.5 mm²
Connection cross-section, rigid	0.14 - 2.5 mm²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

MCR protection for two-core systems

Basic protection for two-core systems with HF applications 120 V




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
TKS-B 120	120	170	2	Terminal	1	4.400	5097976

Basic protection for measuring, control and regulation technology and telecommunication systems.


- Basic protection for lightning protection equipotential bonding
- High impulse arresting capacity 6 kA (10/350)
- With easy-to-mount, screwless connection terminals
- In a space-saving 17.5 mm grid

Dimensions



Application: Universal use on 35 mm DIN rails in standard distributor housings.

Connection options



TKS-B

Maximum continuous voltage AC	U_c	120 V
Maximum continuous voltage DC	U_c	170 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		2
Rated current	I_r	20 A
Impulse durability wire-wire		C2: 18 kV / 9 kA
Impulse durability wire-earth		C2: 18 kV / 9 kA
Total discharge current (8/20)		18 kA
Total discharge current (10/350)		D1: 6 kA
Protection level wire-wire		<950 V
Protection level wire-earth		<600 V
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail
Connection system		Terminal
Division unit TE (17.5 mm)		1
Protection rating		IP20
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Medium and fine protection FRD for two-core systems 5 V



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 5 5	5	8	2	Terminal	1	5.100	5098492


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for double core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With ohmic decoupling in the longitudinal branch


Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.



Dimensions



Connection options



FRD 5

Maximum continuous voltage AC	U_c 5 V
Maximum continuous voltage DC	U_c 8 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	2
Rated current	I_r 0.2 A
Series resistance per wire	$15 \Omega \pm 10\%$
Impulse durability wire-wire	C1: 1 kV / 0.5 kA (8/20μs)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20μs)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<15 V
Protection level wire-earth	<600 V
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Medium and fine protection FRD for two-core systems 12 V




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 12 9	9	13	2	Terminal	1	5.100	5098506

Surge protection for use in measurement and control technology


- Medium and fine protection
- Standard design for double core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With ohmic decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.

Dimensions



Connection options



FRD 12

Maximum continuous voltage AC	U_c	9 V
Maximum continuous voltage DC	U_c	13 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0-3
Number of poles		2
Rated current	I_r	0.2 A
Series resistance per wire		$15 \Omega \pm 10\%$
Impulse durability wire-wire		C1: 1 kV / 0.5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 3 kA
Protection level wire-wire		<30 V
Protection level wire-earth		<600 V
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Division unit TE (17.5 mm)		1
Protection rating		IP20
Connection cross-section, flexible		0.14 - 2.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Terminal
Testing standard		IEC 61643-21
Approvals		UL

Medium and fine protection FRD for two-core systems 24 V

Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 24	19	28	2	Terminal	1	5.100	5098514


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for double core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With ohmic decoupling in the longitudinal branch


Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.



Dimensions



Connection options



FRD 24

Maximum continuous voltage AC	U_c 19 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	2
Rated current	I_r 0.2 A
Series resistance per wire	$15 \Omega \pm 10\%$
Impulse durability wire-wire	C2: 5 kV / 2.5 kA (8/20μs)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20μs)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<60 V
Protection level wire-earth	<600 V
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm²
Connection cross-section, multi-wire	0.14 - 2.5 mm²
Connection cross-section, rigid	0.14 - 2.5 mm²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Medium and fine protection FRD for two-core systems 48 V




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 48	37	53	2	Terminal	1	5.100	5098522

Surge protection for use in measurement and control technology


- Medium and fine protection
- Standard design for double core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With ohmic decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.

Dimensions



Connection options



FRD 48

Maximum continuous voltage AC	U_c	37 V
Maximum continuous voltage DC	U_c	53 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		2
Rated current	I_r	0.2 A
Series resistance per wire		$15 \Omega \pm 10\%$
Impulse durability wire-wire		C2: 5 kV / 2.5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 3 kA
Protection level wire-wire		<140 V
Protection level wire-earth		<600 V
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Division unit TE (17.5 mm)		1
Protection rating		IP20
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		Terminal
Testing standard		IEC 61643-21
Approvals		UL

Medium and fine protection FRD for two-core systems 110 V



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 110	86	122	2	Terminal	1	5.100	5098557


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for double core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With ohmic decoupling in the longitudinal branch


Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.



Dimensions



Connection options



FRD 110

Maximum continuous voltage AC	U_c 86 V
Maximum continuous voltage DC	U_c 122 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	2
Rated current	I_r 0.2 A
Series resistance per wire	$15 \Omega \pm 10\%$
Impulse durability wire-wire	C2: 5 kV / 2.5 kA (8/20μs)
Impulse durability wire-earth	C2: 10 kV / 5 kA
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<300 V
Protection level wire-earth	<600 V
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Medium and fine protection FRD 2 for two-core systems 24 V




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 2-24 19	19	28	2	Terminal	1	5.100	5098727

Surge protection for use in measurement and control technology


- Medium and fine protection
- Standard design for double core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With ohmic decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.

Dimensions



Connection options



FRD 2-24

Maximum continuous voltage AC	U_c	19 V
Maximum continuous voltage DC	U_c	28 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Number of poles		2
Rated current	I_r	0.2 A
Series resistance per wire		$15 \Omega \pm 10\%$
Impulse durability wire-wire		C2: 5 kV / 2,5 kA (8/20μs)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)		5 kA
Total discharge current (10/350)		— kA
Protection level wire-wire		<120 V
Protection level wire-earth		<60 V
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Division unit TE (17.5 mm)		1
Protection rating		IP20
Connection cross-section, flexible		0.14 - 2.5 mm²
Connection cross-section, multi-wire		0.14 - 2.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		Terminal
Testing standard		IEC 61643-21

Medium and fine protection FLD for two-core systems 5 V



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection	Pack Piece	Weight kg/100 pc.	Item no.
FLD 5 5	5	8	2	Terminal	1	5.200	5098600


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch


Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.



Dimensions



Connection options



FLD 5

Maximum continuous voltage AC	U_c 5 V
Maximum continuous voltage DC	U_c 8 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_r 1 A
Series inductivity per wire	120 μ H ± 20 %
Impulse durability wire-wire	C1: 1 kV / 0,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<15 V
Protection level wire-earth	<600 V
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Medium and fine protection FLD for two-core systems 12 V



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 12 9	13	13	2	Terminal	1	5.200	5098603


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch


Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.



Dimensions



Connection options



FLD 12

Maximum continuous voltage AC	U_c	9 V
Maximum continuous voltage DC	U_c	13 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0-3
Number of poles		2
Rated current	I_r	1 A
Series inductivity per wire		120 μ H \pm 20 %
Impulse durability wire-wire		C1: 1 kV / 0,5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 3 kA
Protection level wire-wire		<30 V
Protection level wire-earth		<600 V
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Division unit TE (17.5 mm)		1
Protection rating		IP20
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		Terminal
Testing standard		IEC 61643-21
Approvals		UL

Medium and fine protection FLD for two-core systems 24 V



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection	Pack Piece	Weight kg/100 pc.	Item no.
FLD 24	19	28	2	Terminal	1	5.200	5098611


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch


Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.



Dimensions



Connection options



FLD 24

Maximum continuous voltage AC	U_c 19 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	2
Rated current	I_r 1 A
Series inductivity per wire	120 μ H \pm 20 %
Impulse durability wire-wire	C2: 5 kV / 2,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<60 V
Protection level wire-earth	<600 V
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Medium and fine protection FLD for two-core systems 48 V




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 48	37	53	2	Terminal	1	5.200	5098630

Surge protection for use in measurement and control technology


- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.

Dimensions



Connection options



FLD 48

Maximum continuous voltage AC	U_c	37 V
Maximum continuous voltage DC	U_c	53 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0-3
Number of poles		2
Rated current	I_r	1 A
Series inductivity per wire		120 μ H \pm 20 %
Impulse durability wire-wire		C2: 5 kV / 2,5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 3 kA
Protection level wire-wire		<140 V
Protection level wire-earth		<600 V
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Division unit TE (17.5 mm)		1
Protection rating		IP20
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		Terminal
Testing standard		IEC 61643-21
Approvals		UL

Medium and fine protection FLD for two-core systems 110 V

LPZ
0→3

MSR



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 110	86	122	2	Terminal	1	5.200	5098646


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch


Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.



Dimensions



Connection options



FLD 110

Maximum continuous voltage AC	U_c 86 V
Maximum continuous voltage DC	U_c 122 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_r 1 A
Series inductivity per wire	120 μ H ± 20 %
Impulse durability wire-wire	C1: 1 kV / 0,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<300 V
Protection level wire-earth	<600 V
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

MCR protection for two-core systems

Medium and fine protection FLD 2 for two-core systems 12 V




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 2-12 9	13	13	2	Terminal	1	5.100	5098808

Surge protection for use in measurement and control technology


- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.

Dimensions



Connection options



FLD 2-12

Maximum continuous voltage AC	U_c	9 V
Maximum continuous voltage DC	U_c	13 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Number of poles		2
Rated current	I_r	1 A
Series inductivity per wire		120 μ H ± 10 %
Impulse durability wire-wire		C1: 1 kV / 0,5 kA (8/20 μ s)
Impulse durability wire-earth		C1: 1 kV / 0,5 kA (8/20 μ s)
Total discharge current (8/20)		1 kA
Total discharge current (10/350)		— kA
Protection level wire-wire		<60 V
Protection level wire-earth		<30 V
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Division unit TE (17.5 mm)		1
Protection rating		IP20
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		Terminal
Testing standard		IEC 61643-21
Approvals		UL



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 2-24	19	28	2	Terminal	1	5.100	5098816


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch


Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.



Dimensions



Connection options



FLD 2-24

Maximum continuous voltage AC	U_c 19 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1→3
Number of poles	2
Rated current	I_r 1 A
Series inductivity per wire	120 μ H ± 10 %
Impulse durability wire-wire	C1: 1 kV / 0,5 kA (8/20 μ s)
Impulse durability wire-earth	C1: 1 kV / 0,5 kA (8/20 μ s)
Total discharge current (8/20)	1 kA
Total discharge current (10/350)	— kA
Protection level wire-wire	<120 V
Protection level wire-earth	<60 V
Temperature range	θ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

MCR protection for two-core systems

Medium and fine protection FLD 2 for two-core systems 110 V




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 2-110	86	122	2	Terminal	1	5.100	5098859

Surge protection for use in measurement and control technology


- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.

Dimensions



Connection options



FLD 2-110

Maximum continuous voltage AC	U_c	86 V
Maximum continuous voltage DC	U_c	122 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Number of poles		2
Rated current	I_r	1 A
Series inductivity per wire		120 μ H \pm 10 %
Impulse durability wire-wire		C2: 5 kV / 2,5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)		5 kA
Total discharge current (10/350)		- kA
Protection level wire-wire		<500 V
Protection level wire-earth		<300 V
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Division unit TE (17.5 mm)		1
Protection rating		IP20
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		Terminal
Testing standard		IEC 61643-21
Approvals		UL

Series protection device, 2-pole, 5 V version



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection	Pack Piece	Weight kg/100 pc.	Item no.
MDP-2 D-5-T	7	10	2	Terminal	1	6.000	5098404


Lightning barrier with test function; 5 V version

- Nominal load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High frequency range of 0–100 MHz
- UL-listed (4DG1)


Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options



MDP-2 D-5-T

Maximum continuous voltage AC	U_c 7 V
Maximum continuous voltage DC	U_c 10 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_r 0.58 A
Series resistance per wire	$2,35 \Omega \pm 5\%$
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20μs)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)	5 kA
Total discharge current (10/350)	D1: 1 kA
Protection level wire-wire	<35 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm²
Connection cross-section, multi-wire	0.14 - 1.5 mm²
Connection cross-section, rigid	0.14 - 2.5 mm²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 3-pole, 5 V version




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-3 D-5-T	7	10	3	Terminal	1	6.000	5098407


Lightning barrier with test function; 5 V version

- Nominal load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High frequency range of 0–100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options

MDP-3 D-5-T

Maximum continuous voltage AC	U_c	7 V
Maximum continuous voltage DC	U_c	10 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0-3
Number of poles		3
Rated current	I_r	0.58 A
Series resistance per wire		$2.35 \Omega \pm 5\%$
Impulse durability wire-wire		C1: 0.5 kV / 0.25 kA (8/20μs)
Impulse durability wire-earth		C2: 5 kV / 2.5 kA (8/20μs)
Total discharge current (8/20)		7.5 kA
Total discharge current (10/350)		D1: 1.5 kA
Protection level wire-wire		<35 V
Protection level wire-earth		<800 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm²
Connection cross-section, multi-wire		0.14 - 1.5 mm²
Connection cross-section, rigid		0.14 - 2.5 mm²
Earthing via:		DIN rail
Testing standard		IEC 61643-21
Approvals		UL

Series protection device, 4-pole, 5 V version



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-5-T	7	10	4	Terminal	1	6.000	5098411


Lightning barrier with test function; 5 V version

- Nominal load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High frequency range of 0–100 MHz
- UL-listed (4DG1)


Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options



MDP-4 D-5-T

Maximum continuous voltage AC	U_c 7 V
Maximum continuous voltage DC	U_c 10 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	4
Rated current	I_r 0.58 A
Series resistance per wire	$2,35 \Omega \pm 5\%$
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20μs)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 2 kA
Protection level wire-wire	<35 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm²
Connection cross-section, multi-wire	0.14 - 1.5 mm²
Connection cross-section, rigid	0.14 - 2.5 mm²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 2-pole, 24 V version




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-2 D-24-T	20	28	2	Terminal	1	6.000	5098422


Lightning barrier with test function; 24 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options

MDP-2 D-24-T

Maximum continuous voltage AC	U_c	20 V
Maximum continuous voltage DC	U_c	28 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0-3
Number of poles		2
Rated current	I_r	0.58 A
Series resistance per wire		$2,35 \Omega \pm 5\%$
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20μs)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)		5 kA
Total discharge current (10/350)		D1: 1 kA
Protection level wire-wire		<55 V
Protection level wire-earth		<800 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 1.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		DIN rail
Testing standard		IEC 61643-21
Approvals		UL

Series protection device, 3-pole, 24 V version



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-3 D-24-T	20	28	3	Terminal	1	6.000	5098427


Lightning barrier with test function; 24 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)


Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options



MDP-3 D-24-T

Maximum continuous voltage AC	U_c 20 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	3
Rated current	I_r 0.58 A
Series resistance per wire	2,35 $\Omega \pm 5\%$
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	7,5 kA
Total discharge current (10/350)	D1: 1,5 kA
Protection level wire-wire	<55 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 4-pole, 24 V version




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-24-T	20	28	4	Terminal	1	5.800	5098431


Lightning barrier with test function; 24 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options

MDP-4 D-24-T

Maximum continuous voltage AC	U_c	20 V
Maximum continuous voltage DC	U_c	28 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		4
Rated current	I_r	0.58 A
Series resistance per wire		$2,35 \Omega \pm 5\%$
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20μs)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 2 kA
Protection level wire-wire		<55 V
Protection level wire-earth		<800 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 1.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		DIN rail
Testing standard		IEC 61643-21
Approvals		UL

Series protection device, 2-pole, 48 V version



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-2 D-48-T	41	58	2	Terminal	1	6.000	5098442


Lightning barrier with test function; 48 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)


Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options

**MDP-2 D-48-T**

Maximum continuous voltage AC	U_c 41 V
Maximum continuous voltage DC	U_c 58 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	2
Rated current	I_r 0.58 A
Series resistance per wire	$2,35 \Omega \pm 5\%$
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20μs)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)	5 kA
Total discharge current (10/350)	D1: 1 kA
Protection level wire-wire	<95 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm²
Connection cross-section, multi-wire	0.14 - 1.5 mm²
Connection cross-section, rigid	0.14 - 2.5 mm²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 3-pole, 48 V version




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-3 D-48-T	41	58	3	Terminal	1	6.000	5098446


Lightning barrier with test function; 48 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options

MDP-3 D-48-T

Maximum continuous voltage AC	U_c	41 V
Maximum continuous voltage DC	U_c	58 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0-3
Number of poles		3
Rated current	I_r	0.58 A
Series resistance per wire		$2,35 \Omega \pm 5\%$
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20μs)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)		7,5 kA
Total discharge current (10/350)		D1: 1,5 kA
Protection level wire-wire		<95 V
Protection level wire-earth		<800 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail 35 mm
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 1.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		DIN rail
Testing standard		IEC 61643-21
Approvals		UL

Series protection device, 4-pole, 48 V version



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-48-T	41	58	4	Terminal	1	5.800	5098450


Lightning barrier with test function; 48 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)


Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options

**MDP-4 D-48-T**

Maximum continuous voltage AC	U_c 41 V
Maximum continuous voltage DC	U_c 58 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	4
Rated current	I_r 0.58 A
Series resistance per wire	2,35 Ω ± 5 %
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20μs)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 2 kA
Protection level wire-wire	<95 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	-40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm²
Connection cross-section, multi-wire	0.14 - 1.5 mm²
Connection cross-section, rigid	0.14 - 2.5 mm²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 4-pole, 5 V version




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-5-T-10	7	10	4	Terminal	1	7.200	5098413

Lightning barrier with test function; 5 V version


- Rated load current 10 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.

Dimensions



Connection options



MDP-4 D-5-T-10

Maximum continuous voltage AC	U_c	7 V
Maximum continuous voltage DC	U_c	10 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0-3
Number of poles		4
Rated current	I_r	10 A
Series resistance per wire		—
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20μs)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 2 kA
Protection level wire-wire		<45 V
Protection level wire-earth		<800 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 1.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		DIN rail
Testing standard		IEC 61643-21
Approvals		UL



MSR

LPZ
0→3

5



LISTED

Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-2 D-12-T-10	10.5	15	2	Terminal	1	6.000	5098415


Lightning barrier with test function; 12 V version

- Rated load current 10 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)


Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options

**MDP-2 D-12-T-10**

Maximum continuous voltage AC	U_c 10.5 V
Maximum continuous voltage DC	U_c 15 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_s 10 A
Series resistance per wire	—
Impulse durability wire-wire	C1: 0.5 kV / 0.25 kA (8/20μs)
Total discharge current (8/20)	5 kA
Total discharge current (10/350)	D1: 1 kA
Protection level wire-wire	<55 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	θ -40 - +80 °C
Installation type	DIN rail
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm²
Connection cross-section, multi-wire	0.14 - 1.5 mm²
Connection cross-section, rigid	0.14 - 2.5 mm²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 4-pole, 12 V version




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-12-T-10	10.5	15	4	Terminal	1	6.000	5098419


Lightning barrier with test function; 12 V version

- Rated load current 10 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options

MDP-4 D-12-T-10

Maximum continuous voltage AC	U_c	10.5 V
Maximum continuous voltage DC	U_c	15 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		4
Rated current	I_r	10 A
Series resistance per wire		—
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20μs)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 2 kA
Protection level wire-wire		<55 V
Protection level wire-earth		<800 V
Frequency range		0 - 100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 1.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		DIN rail
Testing standard		IEC 61643-21
Approvals		UL



MSR

LPZ
0→3

Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Connection of system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-2 D-24-T-10	20	28	2	Terminal	1	6.000	5098425


Lightning barrier with test function; 24 V version

- Rated load current 10 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)


Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options

**MDP-2 D-24-T-10**

Maximum continuous voltage AC	U_c 20 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_s 10 A
Series resistance per wire	—
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20μs)
Total discharge current (8/20)	5 kA
Total discharge current (10/350)	D1: 1 kA
Protection level wire-wire	<70 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	θ -40 - +80 °C
Installation type	DIN rail
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Accessories for MCR protection

Earthing strip



Type
VB-MDP 10-MD

Pack	Weight
Piece	kg/100 pc.
1	2.300
Item no. 5098470	


Cu Copper

Connecting bridge for 8 mm lightning barriers

- Length of bridge can be adjusted
- Material: Copper
- Allows quick equipotential bonding

Application: Parallel switching of the MDP lightning barriers

Dimensions



Replacement connector for VF remote signalling




Version
Type
VF-FS | 3-pole


Pack	Weight
Piece	kg/100 pc.
25	0.320
Item no. 5098475	

Replacement telephony connector, 3-pin version, for VF variant



Dimensions








	Series protection device, 4-pole, 5 V	342
	Series protection device, 4-pole, 24 V	343
	Series protection device, 4-pole, 48 V	344
	MCR protection, 2-pole 24 V	345
	MCR protection, 3-pole 24 V	346


Series protection device, 4-pole, 5 V version



Dimensions



Connection options



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-5-EX	7	10	4	1	5.800	5098412

Lightning barrier for intrinsically safe measuring circuits

- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- High frequency range of 0–100 MHz
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4 (BVS 11 ATEX E 131 X)
- UL-listed (4UM2)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.

MDP-4 D-5-EX

Maximum continuous voltage AC	U_c	7 V
Maximum continuous voltage DC	U_c	10 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		4
Rated current	I_s	0.58 A
Series resistance per wire		$2,35 \Omega \pm 5\%$
Impulse durability wire-wire		C1: 0,5 KV / 0,25 kA (8/20μs)
Impulse durability wire-earth		C2: 5 KV / 2,5 kA (8/20μs)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 2 kA
Protection level wire-wire		< 35 V
Protection level wire-earth		<800 V
Frequency range		0-100 MHz
Temperature range	ϑ	-40 → +80 °C
Installation type		DIN rail
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 1.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		DIN rail
EX approval		II 2(1)G Ex ia [ia Ga] IIC T4 Gb
Testing standard		IEC 61643-21
Approvals		UL



Series protection device, 4-pole, 24 V version



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-24-EX	20	28	4	1	5.800	5098432


Lightning barrier for intrinsically safe measuring circuits

- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- High frequency range of 0–100 MHz
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4 (BVS 11 ATEX E 131 X)
- UL-listed (4UM2)


Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.



Dimensions



Connection options




MDP-4 D-24-EX

Maximum continuous voltage AC	U_c 20 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	4
Rated current	I_r 0.58 A
Series resistance per wire	2,35 $\Omega \pm 5\%$
Impulse durability wire-wire	C1: 0,5 KV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 KV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 2 kA
Protection level wire-wire	< 55 V
Protection level wire-earth	< 800 V
Frequency range	0-100 MHz
Temperature range	-40 - +80 °C
Installation type	DIN rail
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
EX approval	II 2(1)G Ex ia [ia Ga] IIC T4 Gb
Testing standard	IEC 61643-21
Approvals	UL


Series protection device, 4-pole, 48 V version



Dimensions



Connection options



Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-48-EX	41	58	4	1	5.800	5098452

Lightning barrier for intrinsically safe measuring circuits

- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- High frequency range of 0–100 MHz
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4 (BVS 11 ATEX E 131 X)
- UL-listed (4UM2)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.

MDP-4 D-48-EX

Maximum continuous voltage AC	U_c	41 V
Maximum continuous voltage DC	U_c	58 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		4
Rated current	I_s	0.58 A
Series resistance per wire		$2,35 \Omega \pm 5\%$
Impulse durability wire-wire		C1: 0.5 KV / 0.25 kA (8/20μs)
Impulse durability wire-earth		C2: 5 KV / 2.5 kA (8/20μs)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 2 kA
Protection level wire-wire		< 95 V
Protection level wire-earth		< 800 V
Frequency range		0-100 MHz
Temperature range	ϑ	-40 → +80 °C
Installation type		DIN rail
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 1.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		DIN rail
EX approval		II 2(1)G Ex ia [ia Ga] IIC T4 Gb
Testing standard		IEC 61643-21
Approvals		UL

Protection for field devices, 2-pole, 24 V, metric



Type	Highest voltage AC V	Maximum continuous voltage DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
FDB-2 24-M	22	32	2-pole; metric	1	18.500	5098380


Petrol Field Protector FDB for intrinsically safe measuring circuits and bus systems




- Different connection technologies available (metric/NPT)
- Low protection level at high current load
- Easy mounting on field devices
- Negligible internal capacitance and inductance
- Stainless steel housing with pressure-resistant encapsulation
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)

Application: Flow sensors, temperature sensors

Dimensions



Connection options



FDB-2 24-M

Maximum continuous voltage AC	U _c	22 V
Maximum continuous voltage DC	U _c	32 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Number of poles		2
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20μs)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)		10 kA
Protection level wire-wire		<80 V
Protection level wire-earth		<800 V
Temperature range	θ	-20 - +70 °C
Installation type		Screw-on
Protection rating		IP65/67
Mounting of input / output		M20 x 1.5 external thread
Mounting of field / device side:		Connection cable 1.5 mm ² Length ~ 250 mm
Earthing via:		Connection cable
Housing material		V2A
EX approval		II 2(1)G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)
Testing standard		IEC 61643-21

Protection for field devices, 3-pole, 24 V, metric




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
FDB-3 24-M	22	32	3-pole; metric	1	19.000	5098382

Petrol Field Protector FDB for intrinsically safe measuring circuits and bus systems


- Different connection technologies available (metric/NPT)
- Low protection level at high current load
- Easy mounting on field devices
- Negligible internal capacitance and inductance
- Stainless steel housing with pressure-resistant encapsulation
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)

Application: Flow sensors, temperature sensors

Dimensions



Connection options



FDB-3 24-M

Maximum continuous voltage AC U_c	22 V
Maximum continuous voltage DC U_c	32 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1→3
Number of poles	3
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20μs)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)	10 kA
Protection level wire-wire	<80 V
Protection level wire-earth	<800 V
Temperature range	-20 - +70 °C
Installation type	Screw-on
Protection rating	IP65/67
Mounting of input / output	M20 x 1.5 external thread
Mounting of field / device side:	Connection cable 1.5 mm ² Length ~ 250 mm
Earthing via:	Connection cable
Housing material	V2A
EX approval	II 2(1)G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)
Testing standard	IEC 61643-21



Protection for field devices, 2-pole, 24 V, NPT



Type	Highest voltage AC V	Maximum continuous voltage DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
FDB-2 24-N	22	32	2-pole; NPT	1	19.000	5098390


Petrol Field Protector FDB for intrinsically safe measuring circuits and bus systems




- Different connection technologies available (metric/NPT)
- Low protection level at high current load
- Easy mounting on field devices
- Negligible internal capacitance and inductance
- Stainless steel housing with pressure-resistant encapsulation
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)

Application: Flow sensors, temperature sensors

Dimensions



Connection options



FDB-2 24-N

Maximum continuous voltage AC	U _c	22 V
Maximum continuous voltage DC	U _c	32 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Number of poles		2
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20µs)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20µs)
Total discharge current (8/20)		10 kA
Protection level wire-wire		<80 V
Protection level wire-earth		<800 V
Temperature range	θ	-20 - +70 °C
Installation type		Screw-on
Protection rating		IP65/67
Mounting of input / output		1/2" NPT
Mounting of field / device side:		Connection cable 1.5 mm ² Length ~ 250 mm
Earthing via:		Connection cable
Housing material		V2A
EX approval		II 2(1)G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)
Testing standard		IEC 61643-21

Protection for field devices, 3-pole, 24 V, NPT




Type	Highest continuous voltage AC V	Maximum continuous voltage DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
FDB-3 24-N	22	32	3-pole; NPT	1	19.500	5098392

Petrol Field Protector FDB for intrinsically safe measuring circuits and bus systems


- Different connection technologies available (metric/NPT)
- Low protection level at high current load
- Easy mounting on field devices
- Negligible internal capacitance and inductance
- Stainless steel housing with pressure-resistant encapsulation
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)

Application: Flow sensors, temperature sensors

Dimensions




Connection options



FDB-3 24-N

Maximum continuous voltage AC	U_c	22 V
Maximum continuous voltage DC	U_c	32 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1→3
Number of poles		3
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20μs)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20μs)
Total discharge current (8/20)		10 kA
Protection level wire-wire		<80 V
Protection level wire-earth		<800 V
Temperature range	ϑ	-20 - +70 °C
Installation type		Screw-on
Protection rating		IP65/67
Mounting of input / output		1/2" NPT
Mounting of field / device side:		Connection cable 1.5 mm ² Length ~ 250 mm
Earthing via:		Connection cable
Housing material		V2A
EX approval		II 2(1)G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)
Testing standard		IEC 61643-21







Isolating spark gap

352

EX ISG H spark gap




Type	Pack Piece	Weight kg/100 pc.	Item no.
EX ISG H	1	41.360	5240030

Hotmelt

- Spark gap to VDE 0185-561-3 (IEC 62561-3)
- Ex certificate to ATEX
- Labelling to EN 60079-0/-1: II 2 G Ex db IIC T6 Gb
- Labelling to EN 60079-0/-31: II 2 D Ex td IIIC T80 °C Db IP67
- Ex certificate to IECEx
- Labelling to IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to IEC 60079-0/-31: Ex td IIIC T80 °C Db IP67
- Ex certificate to INMETRO
- Labelling to ABNT NBR IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to ABNT NBR IEC 60079-31: Ex td IIIC T80 °C Db IP67

Dimensions



Application: In potentially explosive areas zone 1/21 and 2/22, indirect bridging of insulating flanges and insulating glands, e.g. in cathodic, corrosion-protected (KKS) systems.

ES ISG H spark gap, with one cable




Type	Pack Piece	Weight kg/100 pc.	Item no.
EX ISG H 350	1	57.260	5240031

Hotmelt

- Spark gap to VDE 0185-561-3 (IEC 62561-3)
- Ex certificate to ATEX
- Labelling to EN 60079-0/-1: II 2 G Ex db IIC T6 Gb
- Labelling to EN 60079-0/-31: II 2 D Ex td IIIC T80 °C Db IP67
- Ex certificate to IECEx
- Labelling to IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to IEC 60079-0/-31: Ex td IIIC T80 °C Db IP67
- Ex certificate to INMETRO
- Labelling to ABNT NBR IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to ABNT NBR IEC 60079-31: Ex td IIIC T80 °C Db IP67

Dimensions



Application: In potentially explosive areas zone 1/21 and 2/22, indirect bridging of insulating flanges and insulating glands, e.g. in cathodic, corrosion-protected (KKS) systems.



EX ISG H spark gap, with 2 cables


Type	Pack	Weight	
	Piece	kg/100 pc.	Item no.
EX ISG H 350 2L	1	74.155	5240033

Hotmelt

- Spark gap to VDE 0185-561-3 (IEC 62561-3)
- Ex certificate to ATEX
- Labelling to EN 60079-0/-1: II 2 G Ex db IIC T6 Gb
- Labelling to EN 60079-0/-31: II 2 D Ex td IIIC T80 °C Db IP67
- Ex certificate to IECEx
- Labelling to IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to IEC 60079-0/-31: Ex td IIIC T80 °C Db IP67
- Ex certificate to INMETRO
- Labelling to ABNT NBR IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to ABNT NBR IEC 60079-31: Ex td IIIC T80 °C Db IP67



Dimensions



EX ISG H spark gap, jacketed




Type	Pack	Weight	
	Piece	kg/100 pc.	Item no.
EX ISG H KU	1	210.300	5240032

Hotmelt

- Spark gap to VDE 0185-561-3 (IEC 62561-3)
- Ex certificate to ATEX
- Labelling to EN 60079-0/-1: II 2 G Ex db IIC T6 Gb
- Labelling to EN 60079-0/-31: II 2 D Ex td IIIC T80 °C Db IP67
- Ex certificate to IECEx
- Labelling to IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to IEC 60079-0/-31: Ex td IIIC T80 °C Db IP67
- Ex certificate to INMETRO
- Labelling to ABNT NBR IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to ABNT NBR IEC 60079-31: Ex td IIIC T80 °C Db IP67




Dimensions



Application: In potentially explosive areas zone 1/21 and 2/22, indirect bridging of insulating flanges and insulating glands, e.g. in cathodic, corrosion-protected (KKS) systems.

Connection clamp AB EX ISG straight




Type	Drill hole Ø mm	Version	Pack Piece	Weight kg/100 pc.	Item no.
AB EX ISG S M10	11	For M10 bolt	2	9.000	5240360
AB EX ISG S M12	14	For M12 bolt	2	8.900	5240362
AB EX ISG S M16	18	For M16 bolt	2	8.600	5240366
AB EX ISG S M20	22	For M20 bolt	2	8.200	5240370
AB EX ISG S M24	26	For M24 bolt	2	7.800	5240374

St Steel

FT Hot-dip galvanised

Connection clamp for mounting the OBO Ex spark gap, type EX ISG, on insulating flanges and insulating pieces.

Connection clamp AB EX ISG, angled




Type	Drill hole Ø mm	Version	Pack Piece	Weight kg/100 pc.	Item no.
AB EX ISG SW M10	11	For M10 bolt	2	10.900	5240380
AB EX ISG SW M12	14	For M12 bolt	2	10.800	5240382
AB EX ISG SW M16	18	For M16 bolt	2	10.500	5240386
AB EX ISG SW M20	22	For M20 bolt	2	10.100	5240390
AB EX ISG SW M24	26	For M24 bolt	2	9.700	5240394

St Steel

FT Hot-dip galvanised

Connection clamp for mounting the OBO Ex spark gap, type EX ISG, on insulating flanges and insulating pieces.


Connection cable – AL EX ISG



Type	Dimen- sion mm	Pack Piece	Weight kg/100 pc.	Item no.
AL EX ISG 100	100	1	9.600	5240102
AL EX ISG 200	200	1	12.300	5240104
AL EX ISG 300	300	1	15.200	5240106

Cu Copper

UV-resistant connection cable (copper 25 mm²) for mounting the OBO Ex spark gap, type EX ISG, on insulating flanges and insulating pieces. With cable shoe for M10 bolts on both sides, on one side with M10 screw, nuts and spring ring.



HINWEIS!

**Isolierter Blitzschutz mit dem
OBO isCon®-System.**

**Änderungen sind nur von einer
Blitzschutzfachkraft
durchzuführen!**



Measuring and testing systems

	Testing unit for lightning barriers	358
	Magnetic card PCS	358
	Magnetic card holder PCS-H	358
	Card reader PCS-CS..	359
	Lightning current meter LSC	359

Testing unit for lightning barriers



Type
LFC

Pack	Weight
Piece	kg/100 pc.
1	164.500
Item no. 5096786	

OBO Life Control allows function control of the MDP lightning barriers. The lightning barriers can be checked while installed. Life Control will not have any influences on the measuring signal. Life Control possesses an integrated OLED with visual and acoustic defect signalling. A separate LED inside the testing pin is also integrated. Life Control is delivered in a case, complete with a CD and instructions.

Magnetic card PCS




Type
PCS

Pack	Weight
PU	kg/100 PUs
1	5.000
Item no. 5091438	

Peak Current Sensor (PCS) card for recording pulsed/lightning currents. A continuous check of whether lightning has struck the lightning protection system and how high the most recent lightning current was in kA can thus be carried out in the simplest manner by the system operator, specialist lightning protection company or by a surveyor. Here, the printed maintenance circuit and the labelling panels support the maintenance work of the entire lightning protection system which must be performed at defined intervals according to VDE 0185-305-3 (IEC/EN 62305-3).

- Contents = 10 units
- Digital evaluation via the PCS card reading device
- Can be used in addition to the OBO lightning current meter LSC I+II
- With separate labelling panels: "Erected by", "Tested by", "Card code"
- Integrated maintenance circuit (year/month)

Magnetic card holder PCS-H




Type
PCS-H

Pack	Weight
PU	kg/100 PUs
1	31.000
Item no. 5091527	

Magnetic card holder for mounting PCS cards.

- Sealable holder
- For installing on round conductor Rd 8-10
- Simple holder installation by means of clamp
- 1 PU = 10 pieces

Magnetic card and holder MK-B



Type
MK-B

Pack	Weight
PU	kg/100 PUs
1	31.000
Item no. 5091322	


PCS magnetic card to record pulse/lightning currents including holder

- Holder can be leaded
- For mounting on round conductor Rd 8-10
- Simple holder mounting through clamping
- 1 PU = 10 units

Card reader PCS-CS..



Type	Country version	Nom. voltage V	Measuring range	Measuring tolerances	Pack Piece	Weight kg/100 pc.	Item no.
PCS-CS-D	EN	230	3 - 120 kA	< 2 kA (< 2%)	1	750.000	5091683
PCS-CS-GB	GB	230	3 - 120 kA	< 2 kA (< 2%)	1	750.000	5091691



Magnetic card reader for reading and analysing PCS cards.

- Inc. rechargeable battery for 4 h continuous, no-mains operation
- Large, clear display

Lightning strike counter





Type	Measuring range	Pack Piece	Weight kg/100 pc.	Item no.
LSC I+II	1 kA - 100 kA	1	32.500	5091722

Plastic

The LSC I+II lightning current meter measures and permanently saves pulse currents, together with the date and time. This ensures constant monitoring in order to notice if any lightning has struck the lightning protection system. Should this be the case, then the lightning protection system must be maintained according to VDE 0185-305 (IEC 62305).

- Saving and display of time and date
- Usable both inside and outside due to its protection class of IP65
- Cable clip for round conductor or flat conductor
- Direct mounting on the conductor or the PE conductor of the surge protection device
- Long lifespan of the internal lithium batteries
- LCD display
- Internal battery
- Tested according to VDE 0185-561-6 (IEC 62561-6)





Equipotential bonding systems

	Equipotential busbars for indoor use	362
	Equipotential busbars for outdoor areas	364
	Equipotential busbars for industrial areas	365
	Equipotential busbars for Ex area	368
	Earthing pipe	371
	Earthing clamps	372



Equipotential busbar rail for indoors, VDE-tested



Colour

Type
1801 VDE | GreyPack
Piece kg/100 pc. Item no.

1 | 55.000 | 5015650

CuZn Brass


Equipotential busbar for equipotential bonding to DIN VDE 0100-410/-540 as well as lightning protection equipotential bonding to DIN VDE 0185-305

- According to VDE 0618, Part 1
- With 10 x 10 mm clamping rail made of nickel-plated brass
- With contact-secure series terminals made of electrogalvanised steel
- Cover and rail stands made of grey polystyrene
- Sealable/labellable cover
- Lightning current carrying capacity 100 kA (10/350)
- Tension clamp with screw lock against self-loosening (e.g. required in industry)

Connection options:

- 7 single or multi-wire cables 2.5–25 mm² or fine-wire cables to 16 mm² (max. Ø 7 mm)
- 2 single or multi-wire cable 25–95 mm² or fine-wire cables to 70 mm² (max. Ø 13.5 mm)
- 1 flat conductor 30 x 3.5 mm

Dimensions



Earthing pipe clamp for EX Zone 1/21, 2/22



For pipe Ø

Dimensions L

Lightning current carrying capacity

Type	mm	mm	kA	Pack Piece	Weight kg/100 pc.	Item no.
EX BES 28	6 - 28	215	H/100	1	30.580	5057630
EX BES 300	28 - 300	1170	H/100	1	35.800	5057640
EX BES 500	300 - 500	1800	H/100	1	39.430	5057645

For ignition spark-free protection/functional equipotential bonding according to DIN VDE 0100-410/-540 and ignition spark-free lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305) in systems according to VDE 0165-1 (IEC/EN 60079-14).

- For pipes of 6-500 mm external diameter
- Use in potentially explosive areas, Ex zone 1 and 2/21 and 22
- Tested according to explosion group IIC
- Lightning current carrying capacity class H (100 kA) to VDE 0185-561-1 (IEC/EN 62561-1)
- UV-stabilised and halogen-free plastic hood
- Secured with bolts against self-loosening to VDE 0185-305-3, Supplementary Sheet 2
- Suitable for indoor and outdoor applications

Equipotential busbar with plastic base plate



Lightning current carrying capacity

Type kA

1809 | H/100

Pack
Piece kg/100 pc. Item no.

1 | 23.000 | 5015073

CuZn Brass

Equipotential busbar for equipotential bonding according to DIN VDE 0100-410/-540 and lightning protection equipotential bonding according to DIN VDE 0185-305

- Base plate and cover hood made of polystyrene, grey
- Sealable / labellable cover
- Contact strip made of nickel-plated brass
- Screws and crossbar made of electrogalvanised steel
- Capable of carrying lightning current 100 kA (10/350)

Connection options:

- 7 x single or multi-core cables to 25 mm² or fine-core cables to 16 mm²
- 1 x round cable Rd 8-10
- 1 x flat strip to FL30 or round cable Rd 8-10





Equipotential busbar with metal base plate



Lightning current carrying capacity	
Type	kA
1809 M H/100	

CuZn Brass

Equipotential busbar with metal foot for equipotential bonding according to DIN VDE 0100-410/-540 and lightning protection equipotential bonding according to DIN VDE 0185-305



- Cover hood from polystyrene, grey

- Sealable/labellable cover

- Base plate made of strip-galvanised steel

- Contact strip made of nickel-plated brass

- Screws and crossbar made of electrogalvanised steel

- Capable of carrying lightning current 100 kA (10/350)

Connection options:

- 7x single or multi-core cables to 25 mm² or fine-core cables to 16 mm²

- 1x round cable Rd 8–10


- 1x flat strip to FL30 or round cable Rd 8–10

Equipotential busbar OBO Green



Lightning current carrying capacity	
Type	kA
1809 NR H/100	

CuZn Brass



Natural product protects against natural influences.

The OBO Green equipotential busbar is a solution manufactured from cellulose acetate CA for the installation of the equipotential bonding according to DIN VDE 0100-410/-540 and lightning protection equipotential bonding according to DIN VDE 0185-305. The basic material is widely used in the paper industry.

- Base plate and cover hood made of CA, white

- Sealable and labellable cover

- Contact strip made of nickel-plated brass

- Bolts and crossbar made of electrogalvanised steel

- Capable of carrying lightning current 100 kA (10/350)

Connection options:

- 7x single or multi-wire cables to 25 mm² or fine-wire cables to 16 mm²

- 1x round cable Rd 8–10


- 1x flat strip to FL 30 or round cable Rd 8–10

Equipotential bonding rail for small systems



Colour	
Type	
1809 BG Grey	

CuZn Brass



Connection options:

- 3 x multi-core cables to 6 mm²

- 2 x multi-core cables to 16 mm²

Equipotential busbar for outside installation



Lightning current carrying capacity

Type Colour kA

1809 A Black N/50

Pack	Weight	
Piece	kg/100 pc.	Item no.
1	23.000	5015111

A2 Stainless steel, rustproof 1.4301


Equipotential busbar for equipotential bonding according to DIN VDE 0100-410/-540 and lightning protection equipotential bonding according to DIN VDE 0185-305

- Cover hood and base plate made of polystyrene
- Colour: Black, UV-resistant
- Screws and crossbar made of VA
- Capable of carrying lightning current 50 kA (10/350)

Connection options:

- 7 x single or multi-core cables to 25 mm² or fine-core cables to 16 mm²
- 1 round conductor Rd 8-10
- 1 flat strip to FL30 or round conductor Rd 8-10

Dimensions



Equipotential busbar for outside installation



Lightning current carrying capacity

Type Colour kA

1809 AM Black H/100

Pack	Weight	
Piece	kg/100 pc.	Item no.
1	23.000	5015105

A2 Stainless steel, rustproof 1.4301


Equipotential busbar for equipotential bonding according to DIN VDE 0100-410/-540 and lightning protection equipotential bonding according to DIN VDE 0185-305

- Cover hood made of polystyrene
- Base plate made of steel, zinc-iron surface
- Colour: Black, UV-resistant
- Screws and crossbar made of VA
- Capable of carrying lightning current 100 kA (10/350)

Connection options:

- 7 single or multi-wire cables to 25 mm² or fine-wire cables to 16 mm²
- 1 round conductor Rd 8-10
- 1 flat strip to FL30 or round conductor Rd 8-10

Dimensions




Equipotential busbar, solid version

Type	Pack Piece	Weight kg/100 pc.	Item no.
1810	1	173.000	5015057

S Steel

F Hot galvanised

- Base plate and screw-on cover made of strip-galvanised steel
- Sealable / labellable cover
- Contact strip made of strip-galvanised steel
- Screws and crossbar made of steel, hot-dip galvanised or electrogalvanised



Connection options:

- 6 cables 6-16 mm²
- 1 round conductor Rd 8-10
- 1 flat conductor to FL 40
- 2 cable shoe M8

Equipotential busbar for industrial application

Equipotential busbar BigBar for industrial application




Type	Number of connections	Width mm	Length mm	Height mm	Pack Piece	Weight kg/100 pc.	Item no.
1802 5 VA	5	40	246	5	1	90.000	5015854
1802 DC 5+5 VA	10	40	605	85	1	237.000	5015876

A2 Stainless steel, rustproof 1.4301

- Main potential equalisation to VDE 0100 Part 410 and Part 540, and also lightning protection potential equalisation to VDE 0185-305 (IEC 62305)
- Insulation feet
- Quick, simple assembly of connection conductors to the contact rail using lock bolts M10
- The high-grade stainless steel versions (V2A) are suitable for outdoor use
- Complete with anchors and bolts for wall mounting
- With lock washer (DIN 137) for bolt locking against loosening (e.g. required in industry and explosion-protected areas)



Dimensions



Equipotential busbar BigBar for industrial application




Type	Number of connections	Width mm	Length mm	Height mm	Pack Piece	Weight kg/100 pc.	Item no.
1802 10 VA 10	10	40	408.5	5	1	138.210	5015866

A2 Stainless steel, rustproof 1.4301

- Main potential equalisation to VDE 0100 Part 410 and Part 540, and also lightning protection potential equalisation to VDE 0185-305 (IEC 62305)
- Insulation feet
- Quick, simple assembly of connection conductors to the contact rail using lock bolts M10
- The high-grade stainless steel versions (V2A) are suitable for outdoor use
- Complete with anchors and bolts for wall mounting
- With lock washer (DIN 137) for bolt locking against loosening (e.g. required in industry and explosion-protected areas)

Dimensions



Equipotential busbar BigBar for industrial application




Type	Number of connections	Width mm	Length mm	Height mm	Pack Piece	Weight kg/100 pc.	Item no.
1802 5 CU	5	40	246	5	1	80.000	5015830
1802 6 CU	6	40	278.5	5	1	98.400	5015832
1802 8 CU	8	40	343.5	5	1	116.550	5015836
1802 10 CU	10	40	408.5	5	1	180.000	5015842
1802 12 CU	12	40	473.5	5	1	152.850	5015844
1802 14 CU	14	40	538.5	5	1	171.000	5015847
1802 20 CU	20	40	733.5	5	1	225.450	5015849
1802 DC 5+1 CU	6	40	505	85	1	209.000	5015870
1802 DC 5+5 CU	10	40	605	85	1	251.000	5015874


Cu Copper

Main equipotential busbar to VDE 0100 Part 410 and Part -540, and also lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)

- Insulation feet
- Quick, simple mounting of connection cables using lock bolts M10
- Complete with anchors and bolts for wall mounting
- With lock washer (DIN 137) for bolt locking against loosening (e.g. required in industry and explosion-protected areas)



Cover for BigBar equipotential busbar



Type	Number of connections	Pack Piece	Weight kg/100 pc.	Item no.
1802 AH 5	5	1	25.800	5015880
1802 AH 10	10	1	34.299	5015884

A2 Stainless steel, rustproof 1.4301


- Complete with all mounting components
- Labellable

Quick connector, cover Rd 8–10 mm

Type	Fit mm	Dimen- sion A mm	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 VA-OT	Rd 8-10 40		100	3.130	5311554

A2 Stainless steel, rustproof 1.4301

- For round conductor Rd 8-10
- Suitable for M10 bolts




Quick connector, cover Rd 8–10 mm

Type	Fit mm	Dimen- sion A mm	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 CU-OT	Rd 8-10 40		100	3.580	5311530

Cu Copper

- For round conductor fastening RD 8-10
- Suitable for M10 bolts



Earthing connection bar


Type	Dimen- sion L mm	Dimen- sion A mm	Dimen- sion B mm	Dimen- sion G mm	Pack Piece	Weight kg/100 pc.	Item no.
1805 2 FT	200	110	51	155	1	54.800	5016029
1805 4 FT	302	212	153	257	1	77.000	5016037
1805 6 FT	404	314	255	359	1	97.100	5016045

St Steel

FT Hot-dip galvanised

1805/...: For connecting different earthing systems

- With 2 mounting holes Ø 11 mm
- 1805/2: With 4 attaching holes
- 1805/4: With 8 attaching holes
- 1805/6: With 12 attaching holes




Earthing connection bar

Type	Dimen- sion L mm	Dimen- sion A mm	Dimen- sion B mm	Dimen- sion G mm	Pack Piece	Weight kg/100 pc.	Item no.
1805 2 VA	200	110	51	155	1	54.800	5016096
1805 4 VA	302	212	153	257	1	77.000	5016118
1805 6 VA	404	314	255	359	1	97.100	5016126

A4 Stainless steel, rustproof 1.4571

1805/...: For connecting different earthing systems

- With 2 mounting holes Ø 11 mm
- 1805/2: With 4 attaching holes
- 1805/4: With 8 attaching holes
- 1805/6: With 12 attaching holes




Vario quick connector

Type	Fit mm	Dimen- sion A mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 VA	Rd 8-10 40		H/100	10	10.700	5311551

A2 Stainless steel, rustproof 1.4301

- For T, cross and parallel connectors
- Quick installation using hexagonal bolt M10 x 30, high-grade stainless steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)



Equipotential busbar for EX zone 1/21, 2/22




Type	Number of connections	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
EX PAS 5	5	H/100	1	152.000	5015265
EX PAS 10	10	H/100	1	214.000	5015270

A2 Stainless steel, rustproof 1.4301

For ignition spark-free protection/functional equipotential bonding to DIN VDE 0100-410/-540 as well as ignition spark-free lightning protection equipotential bonding to VDE 0185-305 (IEC 62305) in systems to VDE 0165-1 (IEC/EN 60079-14)

- Use in potentially explosive areas, Ex zone 1 and 2/21 and 22
- Tested according to explosion group IIC
- Lightning current carrying capacity class H (100 kA) to VDE 0185-561-1 (IEC/EN 62561-1)
- UV-stabilised and halogen-free insulation feet
- With spring washer for locking screws against self-loosening to VDE 0185-305-3 Supplementary sheet 2
- Suitable for indoor and outdoor applications

Dimensions



Equipotential busbar BigBar for industrial application




Type	Number of connections	Width mm	Length mm	Height mm	Pack Piece	Weight kg/100 pc.	Item no.
1802 5 VA	5	40	246	5	1	90.000	5015854
1802 10 VA	10	40	408.5	5	1	138.210	5015866

A2 Stainless steel, rustproof 1.4301

- Main potential equalisation to VDE 0100 Part 410 and Part 540, and also lightning protection potential equalisation to VDE 0185-305 (IEC 62305)
- Insulation feet
- Quick, simple assembly of connection conductors to the contact rail using lock bolts M10
- The high-grade stainless steel versions (V2A) are suitable for outdoor use
- Complete with anchors and bolts for wall mounting
- With lock washer (DIN 137) for bolt locking against loosening (e.g. required in industry and explosion-protected areas)

Dimensions





Equipotential busbar BigBar for industrial application

Type	Number of connections	Width mm	Length mm	Height mm	Pack Piece	Weight kg/100 pc.	Item no.
1802 5 CU	5	40	246	5	1	80.000	5015830
1802 6 CU	6	40	278.5	5	1	98.400	5015832
1802 8 CU	8	40	343.5	5	1	116.550	5015836
1802 10 CU	10	40	408.5	5	1	180.000	5015842
1802 12 CU	12	40	473.5	5	1	152.850	5015844
1802 14 CU	14	40	538.5	5	1	171.000	5015847
1802 20 CU	20	40	733.5	5	1	225.450	5015849


Cu Copper

Main equipotential busbar to VDE 0100 Part 410 and Part -540, and also lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)

- Insulation feet
- Quick, simple mounting of connection cables using lock bolts M10
- Complete with anchors and bolts for wall mounting
- With lock washer (DIN 137) for bolt locking against loosening (e.g. required in industry and explosion-protected areas)



Dimensions




Cover for BigBar equipotential busbar

Type	Number of connections	Pack Piece	Weight kg/100 pc.	Item no.
1802 AH 5	5	1	25.800	5015880
1802 AH 10	10	1	34.299	5015884

A2 Stainless steel, rustproof 1.4301

- Complete with all mounting components
- Labelable




Quick connector, cover Rd 8–10 mm

Type	Fit mm	Dimen- sion A mm	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 VA-OT	Rd 8-10	40	100	3.130	5311554

A2 Stainless steel, rustproof 1.4301

- For round conductor Rd 8-10
- Suitable for M10 bolts




Quick connector, cover Rd 8–10 mm


Type	Fit mm	Dimen- sion A mm	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 CU-OT	Rd 8-10	40	100	3.580	5311530

Cu Copper

- For round conductor fastening RD 8-10
- Suitable for M10 bolts



Vario quick connector




Type	Fit mm	Dimen- sion A mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 VA	Rd 8-10 40	H/100		10	10.700	5311551

A2 Stainless steel, rustproof 1.4301

- For T, cross and parallel connectors
- Quick installation using hexagonal bolt M10 x 30, high-grade stainless steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Connector, Rd 8–10 mm with pressure trough




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5001 N-VA	Rd 8-10 N/50		10	6.800	5304176

A2 Stainless steel, rustproof 1.4301

- With 1 fix contact clamping screw, nut and serrated washer
- Including pre-mounted pressure sump, steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Connector, Rd 8–10 mm, double, with pressure trough




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5002 N-VA	Rd 8-10 N/50		10	16.200	5304270

A2 Stainless steel, rustproof 1.4301

- With 2 Fix-Kontakt clamping bolts, nuts and serrated washers
- With pre-mounted pressure trough made of VA
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)

Vario quick connector Rd 8-10x16



Type	Fit mm	Dimen- sion A mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10X16 VA	8-10X16 40	H/100		10	16.300	5311590


A2 Stainless steel, rustproof 1.4301

- For T, intersection and parallel connections with adapter plates
- Quick mounting using an M10 x 30 bolt, made from rustproof stainless steel
- With sprung washer to DIN 137
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)



Earthing pipe clamp VA

Type	For pipe Ø	For dimen- sion L	For pipe Ø	Pack Piece	Weight kg/100 pc.	Item no.
	inch	mm	mm			
927 1	3/8-11/2	200	17.2 - 48	10	7.780	5057515
927 2	3/8-4	395	17.2 - 114	10	8.550	5057523
927 4	3/8-6	555	17.2 - 165	10	8.022	5057558




A2 Stainless steel, rustproof 1.4301

- For pipes of Ø 3/8 - 6"
- Connection options: Max. 2 cables 2.5-25 mm²
- Round conductor Rd 8
- Clip element, bolts and tightening strap made of rustproof stainless steel (VA)

Earthing pipe clamp, nickel-plated

Type	For Dimen- sion L	For pipe Ø	Pack Piece	Weight kg/100 pc.	Item no.
	mm	mm			
927 0	109.5	8 - 22	10	5.000	5057507




CuZn Brass

N Nickel-plated

- For pipe Ø 8-22 mm
- Connection options: max. 2 conductors 2.5-10 mm²
- Clip elements and screws from nickel-plated brass
- Tightening strip from high-grade stainless steel (V2A)

Clamp lock for earthing pipe clamp

Type	Pack Piece	Weight kg/100 pc.	Item no.
927 SCH-K-VA	20	4.700	5057930




A2 Stainless steel, rustproof 1.4301

- Connection option: max. 2 conductors 2.5-25 mm²
- Possible to connect round conductor Rd 8

Installation strip for earthing pipe clamp

Type	Dimen- sion B	Dimen- sion H	Pack m	Weight kg/100 m	Item no.
	mm	mm			
927 BAND-VA	23	0.3	40	6.000	5057922




A2 Stainless steel, rustproof 1.4301

- 40 m roll
- Ready for transport and installation in unroll pack

Earthing clamps

Earthing clamp, type 925




Type	Dimension A mm	Clamping range D mm	Dim. X mm	For pipe Ø inch	Shipping box Piece	Pack Piece	Weight kg/100 pc.	Item no.
925 1/4	48	11.5 - 13.5	2	1/4	300	25	4.100	5040035
925 3/8	52	15.2 - 17.2	2	3/8	300	25	4.360	5040051
925 1/2	56	19.3 - 21.3	2	1/2	300	25	4.788	5040078
925 3/4	62	24.9 - 26.9	2	3/4	250	25	5.316	5040094
925 1	70	31.7 - 33.7	2	1	250	25	5.956	5040116
925 1 1/4	81	40.4 - 42.4	2	1 1/4	300	25	7.744	5040132
925 1 1/2	88	46.3 - 48.3	2	1 1/2	240	20	9.615	5040159

St Steel

G Electrogalvanised

- For pipes 1/4"-1½" or Ø 11.5-48.3 mm
- Connection options: conductors to 16 mm² with connecting terminal, riveted with brass and 1 cylinder screw M5 x 12
- To 1½" with 2 cylinder screws M6 x 16 (G)

Earthing terminal for fastening on earthing strap



CE

Shipping box

Type Piece

928 | 240

Pack Piece Weight kg/100 pc. Item no.


| 10 | 5.700 | 5040507

CuZn Brass

N Nickel-plated

- For use in bathtubs or shower tubs etc.
- Connection option: conductors to 16 mm²
- Clamping element with threaded connection M6, 1 hexagonal nut M6, 1 serrated dimension washer and 1 cylinder screw M5 x 8
- Clamping element, nut and screws from copper-plated brass
- Serrated washer from stainless steel; 2 washers from galvanised steel

Earthing clamp, type 942



Type	Dimension A mm	Clamping range D mm	Dim. X mm	For pipe Ø inch	Shipping box Piece	Pack Piece	Weight kg/100 pc.	Item no.
942 11	44	8 - 11	3.5	1/8	420	10	4.480	5038014
942 15	50	13 - 15	3	1/4	320	10	4.800	5038030
942 18	52	16 - 18	2	3/8	200	10	5.170	5038057
942 22	55	19 - 22	3	1/2	180	10	5.550	5038073
942 28	63	24 - 28	3	3/4	180	10	6.170	5038081
942 35	71	30 - 35	5	1	120	10	8.570	5038111
942 43	81	39 - 43	5	1 1/4	100	10	9.740	5038138
942 49	86	44 - 49	5	1 1/2	100	10	10.540	5038154


Cu Copper

N Nickel-plated

- For pipes 1/8-1 1/2" or Ø 8-49 mm
- Connection options: Cables up to 25 mm²
- With connection clip and cylinder bolt M6 x 16 made of brass, nickel-plated
- Clip cover and base made of copper, nickel-plated

Earthing clamp, type 950


Type	Dimension A mm	Clamping range D mm	Dim. X Ø mm	For pipe Ø inch	Shipping box Piece	Pack Piece	Weight kg/100 pc.	Item no.
950 Z 1/4	45	12 - 14	2	1/4	300	10	5.830	5050030
950 Z 3/8	50	15.5 - 17.5	2	3/8	180	10	6.020	5050057
950 Z 1/2	54	20 - 22.5	2.5	1/2	120	10	7.000	5050073
950 Z 3/4	61	25 - 28	3	3/4	120	10	7.620	5050081
950 Z 1	66	31.5 - 34.5	3	1	150	10	8.410	5050111
950 Z 1 1/4	78	40.5 - 43.5	3	1 1/4	160	10	10.030	5050138
950 Z 1 1/2	84	46.5 - 49.5	3	1 1/2	150	10	10.410	5050154
950 Z 1 3/4	88	51 - 54	3	1 3/4	100	10	10.251	5050170
950 Z 2	96	58.5 - 61.5	3	2	80	10	12.150	5050197

Zn Die-cast zincG Electrogalvanised

- For pipes Ø 1/4"-2"
- Connection options: conductors to 35 mm² or round conductors to Ø 6 mm
- With captive pressure strip, 2 cylinder screws M6 x 16 and 1 hex-head screw M6 x 16 from galvanised steel, top and bottom part of clip from die-cast zinc

Earthing clamp, type 952

Type	Dimension A mm	Clamping range D mm	Dim. X Ø mm	For pipe Ø inch	Shipping box Piece	Pack Piece	Weight kg/100 pc.	Item no.
952 Z 1/2	65	18.5 - 21.5	3	1/2	50	5	24.880	5052076
952 Z 3/4	71	24 - 27	3	3/4	50	5	26.780	5052092
952 Z 1	77	30.5 - 33.5	3	1	50	5	28.560	5052114
952 Z 1 1/4	87	39.5 - 42.5	3	1 1/4	50	5	32.200	5052130
952 Z 1 1/2	94	45.5 - 48.5	3	1 1/2	20	5	34.720	5052157
952 Z 2	105	57 - 60	3	2	30	5	38.520	5052181

St SteelFT Hot-dip galvanised


- For pipes 1/2-2" or Ø 11.5-60 mm
- Connection options: conductors 16-70 mm² and/or round conductors to Rd 10 with captive pressure strip from stainless steel
- With 2 hexagonal bolts M6 x 16 and 2 hexagonal bolts M6 x 20 from hot-dip galvanised steel
- Top section of clip with cast contact point from die-cast zinc, bottom section of clip from hot-dip galvanised steel

Earthing terminal type 951

Type	Shipping box Piece	Pack Piece	Weight kg/100 pc.	Item no.
951	120	10	5.400	5051509

A2 Stainless steel, rustproof 1.4301

- Longitudinal and transverse conductor routing
- With 1 attaching hole Ø 9 mm
- With 2 cylinder bolts M6 x 16




Quick connector, cover Rd 8–10 mm

Type	Fit mm	Dimension A mm	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 ST-OT	Rd 8-10	40	100	3.240	5311503


St SteelFT Hot-dip galvanised

- For round conductor fastening RD 8-10
- Suitable for M10 bolts



Earthing clamps

Quick connector, cover Rd 8–10 mm




Type	Fit	Pack	Weight	
	mm	Piece	kg/100 pc.	Item no.
249 8-10 ALU-OT	44	100	2.100	5311585

Alu Aluminium

- For round conductor fastening RD 8–10
- Suitable for M10 bolts

Quick connector, cover Rd 8–10 mm




Type	Fit	Pack	Weight	
	mm	Piece	kg/100 pc.	Item no.
249 8-10 VA-OT	Rd 8-10 40	100	3.130	5311554

A2 Stainless steel, rustproof 1.4301

- For round conductor Rd 8–10
- Suitable for M10 bolts

Quick connector, cover Rd 8–10 mm




Type	Fit	Pack	Weight	
	mm	Piece	kg/100 pc.	Item no.
249 8-10 CU-OT	Rd 8-10 40	100	3.580	5311530

Cu Copper

- For round conductor fastening RD 8–10
- Suitable for M10 bolts

Quick connector, cover Rd 16 mm




Type	Fit	Pack	Weight	
	mm	Piece	kg/100 pc.	Item no.
249 VA-OT	16	100	5.700	5311573

A2 Stainless steel, rustproof 1.4301

- For round conductor fastening RD 16
- Suitable for M10 bolts

Earth connection terminal for round conductor and flat conductor




Type	Shipping box	Pack	Weight	
	Piece	Piece	kg/100 pc.	Item no.
937 50	100	10	11.750	5043018

St Steel

FT Hot-dip galvanised

- For round and flat conductors
- Fit: cable 50 mm² x max. FL 40
- Rd 8 x max. FL 40
- With 2 hexagonal bolts M6 x 20 (F)

Earthing terminal for cables and flat conductors



Type	Shipping box	Pack	Weight	
	Piece	Piece	kg/100 pc.	Item no.
939	150	25	5.932	5043107

St Steel

G Electrogalvanised


- For cables to 16 mm² and flat conductors
- Fit: cable to 16 mm² x max. FL 30
- With riveted brass connection terminal and one cylinder bolt, M5 x 12, with two cylinder bolts, M6 x 16

Type
470 4-16

CuZn Brass

N Nickel-plated


- Seat: 4-8 mm x 4-8 mm
- With 4 cylinder bolts M4 x 16

 Pack | Weight
 Piece kg/100 pc. **Item no.**
50 | 2.856 | **5064015****CE**

Type	Dimen- sion L mm	Dimen- sion I mm	Cross- section mm ²	Thread
EKL 25 M6	22	8	25	M6
EKL 35 M6	26	10	35	M6

CuZn Brass

Earthing terminal for fastening the equipotential bonding wire to the cable support system.

 Pack | Weight
 Piece kg/100 pc. **Item no.**
50 | 3.100 | **6404006**50 | 4.800 | **6404014****CE** 11-12

Type	Clamping range D mm	Pack Piece	Weight kg/100 pc.	Item no.
2056N SAS 8 A2	4 - 8	50	2.900	1167006
2056N SAS 12 A2	8 - 12	50	3.700	1167014
2056N SAS 16 A2	12 - 16	50	4.200	1167022
2056N SAS 22 A2	16 - 22	50	4.850	1167030
2056N SAS 28 A2	22 - 28	50	6.600	1167049


A2 Stainless steel, rustproof 1.4301

2B Bright, reworked

For electrical connection of the braided shield of stripped cables.

Delivery complete with counter-trough; pressure trough and VA counter-trough.

A cable screen for protection against electromagnetic influences, can also contribute towards equipotential bonding as both ends are connected to the reference potential.

Clamp clip for screen connection

Pre-tensioning tool


Type	Dimen- sion L mm	Dimen- sion b mm	Pack Piece	Weight kg/100 pc.	Item no.
927 BES VSW 25 153	73		1	14.700	5057690


A2 Stainless steel, rustproof 1.4301

To tension earthing pipes and earthing pipe clamps.



Dimensions








Earthing systems

	Conductor material	380
	Earth rods and plates	383
	Connection material	389
	Holders and accessories	403

Galvanised steel flat conductor for earth



Type	Dimension W x H mm	Cross-section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
5052 DIN 20X2.5	20 x 2,5	50	122	50	122	41.000	5019340
5052 DIN 25X3	25 x 3	75	84	50	84	59.700	5019342
5052 DIN 30X3	30 x 3	90	71	50	71	70.650	5019344
5052 DIN 30X3.5	30 x 3,5	105	30	25	30	84.000	5019345
5052 DIN 30X3.5	30 x 3,5	105	60	50	60	84.000	5019347
5052 DIN 30X4	30 x 4	120	52	50	52	97.000	5019350
5052 DIN 40X4	40 x 4	160	40	51	40	128.000	5019355
5052 DIN 40X5	40 x 5	200	30	50	30	162.000	5019360

St Steel

FT Hot-dip galvanised

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Meets the requirements of VDE 0185-305 (IEC 62305)
- Zinc coating: ≥ 500 g/m² (approx. 70 µm in mean value)
- For lightning protection, earthing systems and ring equipotential bonding

Stainless steel flat conductor




Type	Dimension W x H mm	Cross-section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
5052 V2A 30X3.5	30 x 3,5	105	50	42	50	82.500	5018501
5052 V4A 30X3.5	30 x 3,5	105	50	42	50	82.425	5018706
5052 V4A 30X3.5	30 x 3,5	105	25	21	25	82.425	5018730

A2 Stainless steel, rustproof 1.4301 A4 Stainless steel, rustproof 1.4571/1.4404

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)
- According to the foundation earther standard DIN 18014, V4A is required in the earth
- For use in areas at risk of corrosion
- For lightning protection, earthing systems and ring equipotential bonding

Protective cap for connection lugs, reflective

Fit
Type mm


Pack Piece Weight kg/100 pc. Item no.

ProtectionBall	RD 8-10/ FL 25/ 30/ 40	25	2.050	5018014
----------------	------------------------	----	-------	---------

PE Polyethylene

- For snapping onto round conductors or flat conductors
- Noticeable, reflective label
- For accident protection during the construction phase

Round conductor, galvanised steel



Type	Nominal size Ø mm	Cross-section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-FT	8	50	125	50	125	40.000	5021081
RD 10	10	78	80	50	80	63.000	5021103

St Steel

FT Hot-dip galvanised

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)
- RD 10 can also be used in the earth
- Zinc coating: ≥ 350 g/m² (approx. 50 µm in mean value)

Round conductor, galvanised steel with PVC jacketing



Type	Colour	Dimen- sion d mm	Dimen- sion D mm	Cross- section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 10-PVC	Black	10	13	78	75	50	75	67.000	5021162


SI Steel

FT Hot-dip galvanised

• Corresponds to the requirements according to VDE 0185-305 (IEC 62305)

• Zinc coating: ≥ 350 g/m² (approx. 50 µm in mean value)

• With PVC jacketing



Round conductor, aluminium



Type	Nominal size Ø mm	Cross- section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-ALU	8	50	150	20	150	13.500	5021286
RD 8-ALU-T	8	50	150	20	150	13.500	5021294
RD 10-ALU	10	78	95	20	95	21.000	5021308

Alu Aluminium

• According to DIN EN 62561-2 (VDE 0185-561-2)


• Corresponds to the requirements of VDE 0185-305 (IEC 62305)

• RD 8 ALU: Semi-hard (E-AlMgSi0.5 corresponds to DIN 48801)

• RD 8 ALU-T: Can be subjected to torsion (E-AlMgSi0.5 corresponds to DIN 48801)

• RD 10 ALU: Pure aluminium (E-Al corresponds to DIN 48801)

• AL and ALMgSi may not be routed directly on, in or under plaster, mortar or concrete, nor routed in the earth



Round conductor, aluminium, with PVC sheathing




Type	Nominal size Ø mm	Cross- section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-PVC	8/11	50	100	20	100	20.000	5021332

Alu Aluminium

• Meets the requirements of VDE 0185-305 (IEC 62305)

• With PVC jacketing (halogen-free)

• Suitable for routing on, in or under plasterwork, mortar or concrete



Round conductor, stainless steel A2



Type	Nominal size Ø mm	Cross- section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-V2A	8	50	125	50	125	40.000	5021235
RD 10-V2A	10	78	80	50	80	63.000	5021239
RD 10-V2A	10	78	50	32	50	63.000	5021227


A2 Stainless steel, rustproof 1.4301

• According to DIN EN 62561-2 (VDE 0185-561-2)

• Corresponds to the requirements of VDE 0185-305 (IEC 62305)


• RD 10-V4A for applications in the earth

• According to the foundation earther standard DIN 18014, V4A is required in the earth



Conductor material

Round conductor, stainless steel A4




Type	Nominal size Ø mm	Cross-section mm²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-V4A	8	50	125	50	125	40.000	5021644
RD 10-V4A 20	10	78	20	12	20	63.000	5021640
RD 10-V4A	10	78	80	50	80	63.000	5021647
RD 10-V4A	10	78	50	32	50	63.000	5021642

A4 Stainless steel, rustproof 1.4571/1.4404

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)
- RD 10-V4A for applications in the earth
- According to the foundation earther standard DIN 18014, V4A is required in the earth

Round conductor, copper




Type	Nominal size Ø mm	Cross-section mm²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-CU	8	50	100	45	100	45.000	5021480
RD 8-CU 25	8	50	55	25	55	45.000	5021484
RD 10-CU	10	78	50	35	50	70.000	5021502

Cu Copper

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)

Round conductor, copper sheathed




Type	Nominal size Ø mm	Cross-section mm²	Pack m	Weight kg/100 m	Item no.
RD 8-ST CU	8	50	100	40.000	5021380

St Steel

Cu Copper-plated

- According to IEC/ EN 62561-2 (VDE 0185-561-2)
- Meets the requirements of VDE 0185-305 (IEC 62305)
- Copper layer thickness: Min. 250 µm

Copper cable




Type	Dimension D mm	Individual wires	Cross-section mm²	Normal ring ca. m	Normal ring ca. kg	Weight kg/100 m	Item no.
S 11-CU	10.5	19x Ø 2,1	70	50	30	58.600	5021654
S 9-CU	9	19x Ø 1,8	50	100	45	45.000	5021652

Cu Copper

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)

Copper cable Tin-plated



Type	Dimension D mm	Individual wires	Cross-section mm²	Normal ring ca. m	Normal ring ca. kg	Weight kg/100 m	Item no.
S-11-CU SN	10.5	19x Ø 2,1	70	50	30	58.600	5021656

Cu Copper

Sn Tin-plated

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)




Earth rod for standard applications

Type	Length mm	Outer-Ø mm	Short-circuit current (50 Hz) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
219 20 ST FT	1000	20	7.9	H/100	5	250.000	5000742

St Steel

FT Hot-dip galvanised

- High corrosion resistance
- Zinc support approx. 130 µm
- With peg and bore for linking together
- Round pegs with two knurls
- Conforms to the requirements according to VDE 0185-305 (IEC 62305)
- Short-circuit current Ik (50 Hz), time 1 s, temp. max. 300 °C: 7.9 kA



Earth rod for standard applications




Type	Length mm	Outer-Ø mm	Short-circuit current (50 Hz) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
219 25 ST FT	1500	25	12.3	H/100	5	573.000	5000769

St Steel

FT Hot-dip galvanised

- High corrosion resistance
- Zinc support approx. 130 µm
- With peg and bore for linking together
- Round pegs with three knurls
- Conforms to the requirements according to VDE 0185-305 (IEC 62305)
- Short-circuit current Ik (50 Hz), time 1 s, temp. max. 300 °C: 12.3 kA



Earth rod BP




Type	Length mm	Outer-Ø mm	Short-circuit current (50 Hz) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
219 20 BP FT	1500	20	7.9	H/100	5	360.000	5000947
219 25 BP FT	1500	25	12.3	H/100	5	573.000	5000955

St Steel

FT Hot-dip galvanised

- "BP" system (Bundespost)
- Very good contacting properties with soft metal inlay in the bore hole
- With peg and bore for linking together
- FT version with zinc coating approx. 130 µm
- Conforms to the requirements according to VDE 0185-305 (IEC 62305)




Earth rod BP




Type	Length mm	Outer-Ø mm	Short-circuit current (50 Hz) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
219 20 BP V4A	1000	20	4.2	H/100	5	250.000	5000858
219 20 BP V4A	1500	20	4.2	H/100	5	365.000	5000866

A4 Stainless steel, rustproof 1.4401

- "BP" system (Bundespost)
- Very good contacting properties with soft metal inlay in the bore hole
- With peg and bore for linking together
- Conforms to the requirements according to VDE 0185-305 (IEC 62305)
- Short circuit current Ik (50 Hz), time 1 s, max. temp. 300 °C: 4.5 kA (219 20 BP V4A)



Earth rod BP with copper sheath



Short-circuit current (50 HZ) Lightning current


Type	Length mm	Outer-Ø mm	(1 s;≤300 °C) kA	carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
219 20 BP CU	1500	20	7.9	H/100	5	365.400	5000500

St Steel

Cu Copper-plated

- "BP" system (Bundespost)
- Made of steel with a copper jacket of min. 0.25 mm
- Very good contacting properties with soft metal inlay in the bore hole
- With peg and bore for linking together
- Tensile strength min. 600 N/mm²
- Conforms to the requirements according to VDE 0185-305 (IEC 62305)

Earth rod BS with copper sheath




Type	Length mm	Outer-Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
219 16 CU	1200	14.2	5	192.000	5000481

St Steel

Cu Copper-plated

- Made of steel with a copper jacket of min. 0.25 mm
- With thread for linking together
- Tensile strength min. 600 N/mm²
- Meets the requirements of VDE 0185-305 (IEC 62305)

Driving spike for ST and BP earth rod




Type	For earth rods Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
1819 20BP	20	5	3.768	3041212
1819 25BP	25	5	6.700	3041956

TG Malleable iron

FT Hot-dip galvanised

- Suitable for ST and BP system

Impact head for ST, BP and OMEX earth rods




Type	For earth rods Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
1820 20	St 20	1	62.600	3042200
1820 25	St 25	1	70.000	3042251

St Steel

- Suitable for ST, BP and OMEX systems
- Hardened
- DIN 48852, Form SP

Impact head for earth rod with thread



Type	For earth rods Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
1820 16	14.2	5	5.800	3042270

A2 Stainless steel, rustproof 1.4301


- Suitable for earth rods, type 2019 16 CU

Coupling for earth rod with thread

Type	For earth rods Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
2019 16	14.2	10	8.000	5001190

CuSn Red bronze

- Suitable for earth rods, type 2019 16 CU




Hammer insert type 2500, for earth rod

Type	For earth rods Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
2500 20	20	1	120.000	3043207
2500 25	25	1	140.000	3043258

St Steel

- Manufactured by Cobra BBM 47 SPA-Super, Tex11 and COBRA 248
- Fits earth rod system ST, BP and OMEX
- Hardened




Hammer insert type 2510, for earth rod

Type	For earth rods Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
2510 20	20	1	300.000	3043312

St Steel

- Manufactured by Atlas Copco, type FB 60 S-Super
- Fits earth rod system ST, BP and OMEX
- Hardened




Hammer insert type 2520, for earth rod

Type	For earth rods Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
2520 20	20	1	197.000	3043703
2520 25	25	1	197.000	3043754

St Steel

- Manufactured by Wacker BHF 25, BHF 30S, EHU 25/220
- Fits earth rod system ST, BP and OMEX
- Hardened




Hammer insert type 2530, for earth rod


Type	For earth rods Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
2530 20	20	1	125.000	3043401
2530 25	25	1	125.000	3043452

St Steel

- Manufactured by Bosch USH 10, HSH 10
- Fits earth rod system ST, BP and OMEX
- Hardened



Hammer insert type 2531, for earth rod




For
earth
rods
Type
Ø mm
2531 20 | 20

St Steel

- Make: Bosch GSH 27, USH 27 (WAF 28 mm)
- Suitable for ST, BP and OMEX earth rod systems
- Hardened

Pack
Piece
kg/100 pc.
Item no.
1 | 200.000 | 3043908

Hammer insert type 2535, for earth rod




For
earth
rods
Type
Ø mm
2535 20 | 20
2535 25 | 25

St Steel

- Manufactured by Hilti TE 52/42, TE 72/60, TE 92
- Fits earth rod system ST, BP and OMEX
- Hardened

Pack
Piece
kg/100 pc.
Item no.
1 | 58.000 | 3043916
1 | 100.000 | 3044912

Hammer insert type 2536, for earth rod



For
earth
rods
Type
Ø mm
2536 20 | 20
2536 25 | 25

St Steel

- Fits earth rod system ST, BP and OMEX
- For vibration hammers with SDS- Max/TEY- mounting
- Hardened

Pack
Piece
kg/100 pc.
Item no.
1 | 55.000 | 3044904
1 | 61.000 | 3044831

Hammer insert for LightEarth earth rod



Seat systems

Type

Type	Seat systems	Pack Piece kg/100 pc.	Weight kg/100 pc. Item no.
LE HAMMER-W	Wacker	1 132.000 3043606	
LE HAMMER-H	Hilti	1 76.000 3043610	
LE HAMMER-B	Bosch	1 87.000 3043614	
LE HAMMER-SDS-M	SDS-max	1 76.000 3043602	
LE HAMMER-AC	Atlas Copco	1 76.000 3043618	
LE HAMMER-B-II	Other	1 200.000 3043628	

St Steel

- Suitable for LightEarth system
- 3043606 for Wacker (BHF 25, BHF 30S)
- 3043610 for Hilti (TE 52/42, TE72/60, TE92)
- 3043614 for Bosch (USH 10, HSH 10)
- 3043602 for SDS-Max
- 3043618 for Atlas Copco (Hexagon seat)
- 3043628 for Bosch GSH27/UH27 (11304) / HS28 (12314)
Hitachi H65SD
Makita HM 1500B / HM1800
- Hardened

Air-termination/earth entry rod, rounded-off on both ends



Nominal
Length size Ø
Type mm mm
101 A-1500 | 1500 | 16

St Steel

FT Hot-dip galvanised

- Full material Ø 16 mm
- Rounded on both ends
- Suitable for FangFix stand system


Pack
Piece
kg/100 pc.
Item no.
10 | 240.000 | 5400155

Air-termination/earth entry rod, rounded-off on both ends

Type	Length mm	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
200 V4A-1500	1500	16	10	242.000	5420504
200 V4A-2000	2000	16	10	320.000	5420539

A4 Stainless steel, rustproof 1.4571

- Full material Ø 16 mm
- Both ends rounded



Air-termination/earth entry rod, rounded-off on both ends

Type	Length mm	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 A-CU	1500	16	10	272.100	5400627

Cu Copper

- Full material Ø 16 mm
- Both ends rounded




Air-termination/earth entry rod with connection tabs

Type	Length mm	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 F1500	1500	16	10	240.000	5424151
101 F2000	2000	16	10	320.000	5424208

St Steel

FT Hot-dip galvanised

- With 2 attaching holes Ø 12 mm
- One end rounded




Connection lug/earth entry rod made of stainless steel



Type	Nominal size Ø mm	Cross-section mm²	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
AF RD 10 V4A	10	75	2000	5	123.600	5430720

A4 Stainless steel, rustproof 1.4571/1.4404

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)
- RD 10-V4A for applications in the earth
- According to the foundation earther standard DIN 18014, V4A is required in the earth




Earth entry rod, tapered and partially insulated

Type	Length mm	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
204 KS-2000	2000	16/10	1	230.000	5430011
204 KS-2500	2500	16/10	1	310.000	5430062

St Steel

FT Hot galvanised

- 16 mm earth entry with 10 mm connection
- With mounted heat-shrinkable sleeve (corrosion protection)




Earth entry rod with separating piece and connector

Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
204 KL-1500	Rd 8-10	10	260.700	5430151


St Steel

FT Hot-dip galvanised

- With separating piece type 223 DIN and connector type 5002 DIN



Profile earthing rod with connecting lug




Type	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
213 1000 DIN	1000	5	240.500	5003008
213 1500 DIN	1500	5	364.500	5003016
213 2000 DIN	2000	5	488.400	5003024
213 2500 DIN	2500	3	612.400	5003032
213 3000 DIN	3000	3	736.400	5003040

St Steel

FT Hot-dip galvanised

- Cross-profile 50 x 50 x 3 mm
- With connecting strap
- 1 through hole Ø 13 mm
- 2 through holes Ø 11 mm
- Round conductor fastening e.g. with type 5001 DIN-FT possible
- For the construction of earthing systems e.g. antenna or earthing of building site distribution boards

Profile earth rod with connection strap/hand protection




Type	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
213 1000 DIN HS	1000	5	300.000	5003081

St Steel

FT Hot-dip galvanised

- Cross-profile 50 x 50 x 3 mm
- Hand protection Ø 100 mm
- With connecting strap
- 1 gland hole Ø 13 mm
- 2 gland holes Ø 11 mm
- Round conductor fastening e.g. with type 5001 DIN-FT possible
- For the construction of earthing systems e.g. antennas or earthing of building site distribution boards

Profile earth rod connection with strip steel lug




Type	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
213 1500 M	1500	3	527.600	5003261
213 2000 M	2000	3	651.600	5003288
213 2500 M	2500	3	783.800	5003296
213 3000 M	3000	3	899.500	5003318

St Steel

FT Hot-dip galvanised

- With 2 m strip steel section FL 30 x 3.5
- With 2 through holes Ø 11 mm
- For the construction of earthing systems e.g. antenna or earthing of building site distribution boards

Profile earth rod connection with round conductor lug



Type	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
213 1500 F	1500	3	486.900	5003776
213 2000 F	2000	3	610.900	5003784

St Steel

FT Hot-dip galvanised

- With 2 m round conductor lugs Rd 10
- For the construction of earthing systems e.g. antenna or earthing of building site distribution boards


Type	Dimension B x L x S mm	Pack Piece	Weight kg/100 pc.	Item no.
1816 F-500X1000	500 x 1000 x 3	1	1,329.300	5009227
1816 F-1000X1000	1000 x 1000 x 3	1	2,700.000	5009235

St Steel

FT Hot-dip galvanised

- With 3 m strip steel section FL30 x 3.5
- With 2 attaching holes Ø 11 mm

Earthing plate




Type	Length mm	Width mm	Height mm	Pack Piece	Weight kg/100 pc.	Item no.
1816 CU 6	600	600	3	1	403.000	5009250
1816 CU 9	900	900	3	1	605.000	5009256


Cu Copper

- To reduce the step and contact voltage
- In accordance with IEC 62561-2 and IEC 62305-3

Earth mats



Connection material




Connection clamp for earth rod to round conductors Rd 8–10

Type	For earth rods Ø mm	Dimen- sion A mm	Dimen- sion B mm	Pack Piece	Weight kg/100 pc.	Item no.
2710 20 FT	20	84	114	5	39.900	5001218
2710 25 FT	25	89	119	5	42.300	5001226

St Steel

FT Hot-dip galvanised

- ST, BP, OMEX and LightEarth system
- On round conductor Rd 8-10
- Incl. connector, type 5001 DIN




Connection clamp for earth rod on flat conductor

Type	For earth rods Ø mm	Dimen- sion A mm	Short-circuit current (50 Hz) kA (1 s; ≤ 300 °C)	Dimen- sion B mm	Pack Piece	Weight kg/100 pc.	Item no.
2730 25 FT	25	89	8.5	119	5	38.800	5001412
2730 20 FT	20	84	7.9	114	5	35.900	5001404

St Steel

FT Hot-dip galvanised

- ST, BP, OMEX and LightEarth systems
- On flat conductors
- Including hex-head screw for attaching flat conductors




Connection clamp for earth rod on flat conductor

Type	For earth rods Ø mm	Dimen- sion A mm	Dimen- sion B mm	Pack Piece	Weight kg/100 pc.	Item no.
2730 20 VA	20	84	114	5	33.764	5001366

A2 Stainless steel, rustproof 1.4301

- ST, BP, OMEX and LightEarth systems
- On flat conductors
- Including hex-head screw for attaching flat conductors

Connection clamp for earth rod, universal




Type	Dimen- sion A mm	For earth rods Ø mm	Fit mm	Short-circuit current (50 HZ) (1 s;≤300 °C) kA	Pack Piece	Weight kg/100 pc.	Item no.
2760 20 FT	101	20	Rd 8-10/FL40	7.9	5	28.335	5001641
2760 B-20 FT	101	20	Rd 8-10/FL40	7.9	20	32.400	5001749
2760 25 FT	110	25	Rd 8-10/FL40	8.5	5	38.400	5001668

St Steel

FT Hot-dip galvanised

- Suitable for attaching round conductors Rd 8-10 or flat conductors to FL 40
- With separator plate
- Installed with 2 hexagonal bolts M10 x 30 and 2 hexagonal nuts M10

Connection clamp for earth rod, universal




Type	Dimen- sion A mm	For earth rods Ø mm	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
2760 20 VA	101	20	Rd 8-10/FL40	5	32.400	5001617
2760 B-20 VA	101	20	Rd 8-10/FL40	20	32.400	5001625
2760 20 V4A	101	20	Rd 8-10/FL40	5	32.400	5001633
2760 25 V4A	110	25	Rd 8-10/FL40	5	32.400	5001672

A2 Stainless steel, rustproof 1.4301 A4 Stainless steel, rustproof 1.4404

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Suitable for connecting round conductors Rd 8-10 or flat conductors to FL 40
- With adapter plate
- Mounted with 2 hexagonal bolts M10 x 30 and 2 hexagonal nuts M10

Connection clamp for earth rod or cables




Type	For earth rods Ø mm	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
2745 20 MS	20	7-12,5/S95 mm ²	5	16.000	5001560

CuZn Brass

Cu Copper-plated

- For earth rods Ø 20 or conductors of 95 mm²
- For round conductor attachments Rd 7-12.5 with hexagonal bolts M10 x 25

Connection clip



Type	For earth rods Ø mm	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
2745 16 25	—	Rd 14,2/ FL max. 26 x 12	10	12.000	5001590
2745 16 30	—	Rd 14,2/ FL max. 40 x 12	10	19.000	5001592
2745 16 70	—	Rd 14,2/ Rope 16-70 mm ²	10	6.400	5001594

CuAl Aluminium bronze CuSn Red bronze


- For connection of the copper-plated earth rod, type 219 16 CU, to conductor material
- Type A terminal



Type	Fit Ø mm	Fit mm	For earth rods	Pack Piece	Weight kg/100 pc.	Item no.
2740 16	14.2	14.2	FL/ Rd	10	12.900	5001511
2740 16 KL	14.2	14.2	Rd 8-10/FL max. 26	10	17.500	5001513

CuSn Red bronze

- Suitable for connecting round conductors Rd 8-10 or flat conductors with earth rod 219 16 CU



Cross-connector for flat conductor




Type	Fit mm	Dimen- sion A mm	Dimen- sion B mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
255 A-FL30 FT	max. FL30	52	52	H/100	20	11.500	5314534

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Max FL 30 x FL 30
- Without adapter plate
- Mounted with 4 hexagonal bolts M6 x 20 (F)



Cross-connector for flat conductor, with intermediate plate




Type	Fit mm	Dimen- sion A mm	Dimen- sion B mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
255 30	max. FL30	52	52	H/100	20	16.650	5314518

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Max FL 30 x FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M6 x 20 (F)



DIN cross-connector for flat conductor





Type	Fit mm	Dimen- sion A mm	Dimen- sion B mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
256 A-DIN 30 FT	max. FL30	60	60	H/100	10	27.800	5314658
256 A-DIN 40 FT	max. FL40	80	80	H/100	10	35.436	5314666


St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Max. FL 30 x FL 30 or max. FL 40 x FL 40
- Without adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)



DIN cross-connector for flat conductor




Type	Fit	Dimen-	Dimen-	Lightning current	Pack	Weight	Item no.
	mm	sion A	sion B	carrying capacity	Piece	kg/100 pc.	
256 A-DIN 30 VA	max. FL30	60	60	H/100	10	27.800	5314720
256 A-DIN 30 V4A	max. FL30	60	60	H/100	10	26.400	5314659

A2 Stainless steel, rustproof 1.4301 A4 Stainless steel, rustproof 1.4571

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Max. FL 30 x FL 30
- Without adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

DIN cross-connector for flat conductor, with intermediate plate




Type	Fit	Dimen-	Dimen-	Lightning current	Pack	Weight	Item no.
	mm	sion A	sion B	carrying capacity	Piece	kg/100 pc.	
256 DIN 30 FT	max. FL30	60	60	H/100	10	35.860	5314615
256 DIN 40 FT	max. FL40	80	80	H/100	10	54.650	5314623

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Max. FL 30 x FL 30 or max. FL 40 x FL 40
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

DIN cross-connector for flat conductor, with intermediate plate




Type	Fit	Dimen-	Dimen-	Lightning current	Pack	Weight	Item no.
	mm	sion A	sion B	carrying capacity	Piece	kg/100 pc.	
256 DIN 30 V4A	max. FL30	60	60	H/100	10	29.100	5314616

A4 Stainless steel, rustproof 1.4571

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Max. FL 30 x FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

Cross-connector Rd 8-10



Type	Fit	Lightning current		Pack	Weight
	mm	carrying capacity	Piece	kg/100 pc.	Item no.
253 8X8	Rd 8-10	H/100	25	30.700	5312604

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)


Cross-connector round/round without intermediate plate



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
253 8-10 V4A	Rd 8-10	H/100	25	23.650	5312582
253 S3 V4A	Rd 8-10	H/100	3400	25.900	5312594

A4 Stainless steel, rustproof 1.4401 A4 Stainless steel, rustproof 1.4571/1.4404

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)



Cross-connector with intermediate plate for Rd 8-10




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10 FT	Rd 8-10	H/100	25	33.530	5312310

SI Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)




Cross-connector with intermediate plate for Rd 8-10



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10 V4A	Rd 8-10	H/100	10	33.530	5312318

A4 Stainless steel, rustproof 1.4571

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8




Cross-connector with intermediate plate for Rd 8-10




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10 CU	Rd 8-10	H/100	10	38.940	5312418

Cu Copper

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8



Cross-connector for Rd 8–10 x Rd 16




Type	Fit	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	kA	Piece	kg/100 pc.	
253 10X16	Rd 8-10 x 16	H/100	25	29.800	5312809

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 16 / FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)

Cross-connector with intermediate plate for Rd 8–10 x Rd 16




Type	Fit	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	kA	Piece	kg/100 pc.	
252 8-10X16 FT	Rd 8-10 x 16	H/100	25	38.800	5312345

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 16 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

Cross-connector with intermediate plate for Rd 8–10 x Rd 16




Type	Fit	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	kA	Piece	kg/100 pc.	
252 8-10x16 V4A	Rd 8-10 x 16	H/100	10	39.000	5312346

A4 Stainless steel, rustproof 1.4571

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 16 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

Cross-connector with intermediate plate for Rd 8–10 x Rd 16



Type	Fit	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	kA	Piece	kg/100 pc.	
252 8-10X16 CU	Rd 8-10 x 16	H/100	10	43.985	5312442

Cu Copper

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 16 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8





Cross-connector for round and flat conductors

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10XFL30 FT	8-10 x FL30	H/100	25	28.500	5312655
252 S4 FT	8-10 x FL30	H/100	3600	25.000	5312302

St Steel

FT Hot-dip galvanised



- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10XFL30V4A	8-10 x FL30	H/100	10	28.500	5312656

A4 Stainless steel, rustproof 1.4571

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8





Cross-connector for flat conductors and round conductors

Type	Fit mm	Short-circuit current (50 Hz) (1 s;≤300 °C) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
250	Rd 8-10/FL30	5.6	N/50	25	10.260	5312906

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10
- Fit: Rd 8-10 x FL 30
- Fit: FL 30 x FL 30
- Mounted with 2 hexagonal bolts M8 x 20 (F)




Cross-connector for flat conductors and round conductors

Type	Fit mm	Short-circuit current (50 Hz) (1 s;≤300 °C) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
250 VA	Rd 8-10/FL30 H/100		1.4	25	10.260	5312922
250 V4A	Rd 8-10/FL30 H/100		1.4	10	10.260	5312925

A2 Stainless steel, rustproof 1.4301 A4 Stainless steel, rustproof 1.4571

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10
- Fit: Rd 8-10 x FL 30
- Fit: FL 30 x FL 30
- Mounted with 2 hexagonal bolts M8 x 20



Cross-connector for flat conductors and round conductors with threaded bolt M10x45



Type	Fit mm	Short-circuit current (50 Hz) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 GB 10x45	8-10 x FL30	4.2	H/100	10	34.800	5312657

A2 Stainless steel, rustproof 1.4301


FT/VA Hot-dip galvanised/stainless steel 1.4301

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)

- Fit: Rd 8-10 x FL 30

- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

Diagonal clamp for flat conductors and round conductors



Type	Fit mm	Short-circuit current (50 Hz) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
250 A-FT	Rd 6-22/max. FL50	7.3	H/100	25	28.800	5313015
250 AS-FT	Rd 6-22/max. FL50	7.3	H/100	25	26.000	5313031
250 A	Rd 6-22/max. FL50	7.3	H/100	25	28.800	5313058

St Steel

FT Hot-dip galvanised


- For reinforced steels Ø 6-22 mm and flat conductor 50 x 4

- Installed with screws M10 x 40

- AS version with screws M10 x 20

- Simple installation with open slot

Diagonal clamp for flat conductors and round conductors



Type	Dimen- sion L mm	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
250 A-VA	40	Rd 6-22/max. FL50	H/100	10	28.800	5313023

A2 Stainless steel, rustproof 1.4301


- For reinforced steels Ø 6-22 mm and flat conductor 50 x 4

- Installed with screws M10 x 40

- AS version with screws M10 x 20

- Simple installation with open slot

Diagonal connector for round cable



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
2760 S8 V4A	Rd 8-10	H/100	3600	20.600	5313012
2760 8-10 V4A	Rd 8-10	H/100	25	21.364	5313013

A4 Stainless steel, rustproof 1.4401 A4 Stainless steel, rustproof 1.4571/1.4404

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)

- To connect round cables 8–10 mm

- Mounted with 2 truss-head bolts M10 x 30 and 2 hexagonal bolts M10




Type	Dimen- sion L mm	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
250 A-BO	25	Rd 6-22/max. FL50	H/100	25	30.994	5313066

SI Steel

FT Hot galvanised

- For reinforced steels Ø 6-22 mm and flat conductor 50 x 4
- Installed with screws M10 x 25
- Simple installation with open slot
- With flange-welded bolts M10 x 40, inc. 2 washers and 2 nuts



Parallel clamp for the connecting of reinforcing steels




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
259 A ST	Ø 10-20	H/100	25	18.800	5315557
259 A FT	Ø 10-20	H/100	25	18.800	5315514

SI Steel

FT Hot-dip galvanised

- For connecting reinforced steels Ø 10–20 mm
- Mounted with M10 x 40 bolts




Parallel clamp for the connecting of reinforcing steels



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
259 A VA	Ø 10-20	H/100	10	15.880	5315522

A2 Stainless steel, rustproof 1.4301

- For connecting reinforced steels Ø 10–20 mm
- Mounted with M10 x 40 bolts



Variable earthing terminal




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
1813 KL	FL30 x Rd 8-10	H/100	50	18.000	5014425

SI Steel

FT Hot-dip galvanised

- Suitable for connection for Rd 10 x FL 30, FL 30 x FL 30
- Quick mounting using a hexagonal bolt M10 x 20 (F)



Connection terminal for round conductors




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
1818	Rd 8-10	N/50	10	17.600	5012015


SI Steel

FT Hot-dip galvanised

- For connecting round conductor Rd 8-10
- With 1 hexagonal bolt M12 x 40, 1 hexagonal nut M12 and 1 lock washer, stainless steel



VARIO earthing terminal for reinforced steels



Type Fit
mm Lightning current
carrying capacity
kA

1814 ST	FL30x5 x Rd8-14	N/50
1814 FT	FL30x5 x Rd8-14	N/50


Pack Piece	Weight kg/100 pc.	Item no.
25	20.000	5014476
25	20.000	5014468

St Steel

FT Hot-dip galvanised

- For reinforced steels with diameters 8-14 mm and FL 30 x 5
- Simple mounting through open slot
- Side suspension possible

VARIO earthing terminal for reinforced steels



Type Fit
mm Lightning current
carrying capacity
kA

1814 FT D14	FL30x3-4mm /Rd 8-10 x Rd 6-14	N/50
--------------------	-------------------------------	------


Pack Piece	Weight kg/100 pc.	Item no.
25	15.340	5014471

St Steel

FT Hot-dip galvanised

- For reinforced steel with 6-14 mm diameter and round cables and flat conductors
- Rapid installation using open slot and only one M10 screw

Sealing sleeve for round conductors



Type Fit
mm


DW RD10	RD 10
----------------	-------

Pack Piece	Weight kg/100 pc.	Item no.
1	13.000	2360041

TPE Thermoplastic elastomer

- Sealing sleeve for penetrations of waterproof foundation plates/walls (e.g. white trough)
- For mounting on connection lugs with stainless steel tightening straps
- With pressurised water testing to 5 bar
- According to DIN EN 62561-5 (VDE 0185-561-5)

Sealing sleeve for flat conductors



Type Fit
mm


DW FL30x3,5	FL 30x3,5
--------------------	-----------

Pack Piece	Weight kg/100 pc.	Item no.
1	18.000	2360043

TPE Thermoplastic elastomer

- Sealing sleeve for penetrations of waterproof foundation plates/walls (e.g. white trough)
- For mounting on connection lugs with stainless steel tightening straps
- With pressurised water testing to 5 bar
- According to DIN EN 62561-5 (VDE 0185-561-5)

Earthing fixed point with double thread



Type Thread Short-circuit current (50 Hz) (1 s;≤300 °C) Lightning current carrying capacity kA kA

205 DG V4A	M10/M12	6.2	H/100
-------------------	---------	-----	-------

Pack Piece	Weight kg/100 pc.	Item no.
10	14.800	5420020

A4 Stainless steel, rustproof 1.4404

- For connection to earthing systems, arresters and reinforcements
- Contact plate: Ø 80 mm made of stainless steel, rustproof (V4A)
- Double thread M10/M12
- Incl. plastic cover for simple installation




Earthing fixed point with axis and double thread

Type	Thread	Short-circuit current (50 Hz) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
205 DG L180 FT	M10/M12	4.9	H/100	10	23.900	5420024

SI Steel

FT Hot-dip galvanised

- For connection to earthing systems, arresters and reinforcements
- Contact plate: Ø 80 mm made of stainless steel, rustproof (V4A)
- Clamping bolt Ø 10 mm
- Incl. plastic cover for simple installation




Earthing fixed point with axis and double thread



Type	Thread	Short-circuit current (50 Hz) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
205 DG L180 V4A	M10/M12	3.3	H/100	10	23.900	5420022

A4 Stainless steel, rustproof 1.4404

- For connection to earthing systems, arresters and reinforcements
- Contact plate: Ø 80 mm made of stainless steel, rustproof (V4A)
- Clamping bolt Ø 10 mm
- Incl. plastic cover for simple installation




Connection and end piece

Type	Dimension D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
5011	11	10	7.064	5304997

SI Steel

FT Hot-dip galvanised

- For attaching to steel structures or bolting to fixed earthing terminals
- For attachments: Round conductor Rd 8-10 and flat conductor FL 30 x 3.5
- 2 attaching holes Ø 11 mm
- 1 attaching holes Ø D mm




Connection and end piece


Type	Dimension D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
5011 VA M10	11	10	7.064	5334934
5011 VA M12	13	10	7.048	5334942

A4 Stainless steel, rustproof 1.4571

- For attaching to steel structures or bolting to fixed earthing terminals
- For attachments: Round conductor Rd 8-10 and flat conductor FL 30 x 3.5
- 2 attaching holes Ø 11 mm
- 1 attaching holes Ø D mm



Wedge connector




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
1813 DIN	10/FL30 x FL30	H/100	5	21.144	5014212

St Steel

FT Hot-dip galvanised

- DIN 48834, Form A
- Suitable for connecting Rd 10 x FL 30, FL 30 x FL 30
- Quick installation with high contact force

Spacer




Type	Fit mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
1811	10/FL30 x 3,5	250	25	19.000	5014018
1811 L	10/FL30 x 3,5	400	25	31.500	5014026

St Steel

FT Hot-dip galvanised

- For professional laying of round conductors and flat conductors according to DIN VDE 0185-305 (IEC 62305)
- DIN 48833
- Suitable for mounting round conductors Rd 10 or flat conductors FL 30 x 3.5

Expansion piece




Type	Pack Piece	Weight kg/100 pc.	Item no.
1807	1	27.000	5016142

Alu Aluminium

- For expansion joints, for a connection of the foundation earth electrode outside the concrete
- To VDE 0185-561-2 (IEC 62561-2)
- 2 hexagonal nuts M10 x 30, 2 steel washers, hot galvanised and 2 serrated washers made of rustproof steel

Earthing connection bar



Type	Dimen- sion L mm	Dimen- sion A mm	Dimen- sion B mm	Dimen- sion G mm	Pack Piece	Weight kg/100 pc.	Item no.
1805 2 FT	200	110	51	155	1	54.800	5016029
1805 4 FT	302	212	153	257	1	77.000	5016037
1805 6 FT	404	314	255	359	1	97.100	5016045

St Steel

FT Hot-dip galvanised

1805/...: For connecting different earthing systems

- With 2 mounting holes Ø 11 mm
- 1805/2: With 4 attaching holes
- 1805/4: With 8 attaching holes
- 1805/6: With 12 attaching holes




Earthing connection bar

Type	Dimen- sion L mm	Dimen- sion A mm	Dimen- sion B mm	Dimen- sion G mm	Pack Piece	Weight kg/100 pc.	Item no.
1805 2 VA	200	110	51	155	1	54.800	5016096
1805 4 VA	302	212	153	257	1	77.000	5016118
1805 6 VA	404	314	255	359	1	97.100	5016126

A4 Stainless steel, rustproof 1.4571

1805/...: For connecting different earthing systems

- With 2 mounting holes Ø 11 mm
- 1805/2: With 4 attaching holes
- 1805/4: With 8 attaching holes
- 1805/6: With 12 attaching holes




Cable bracket for flat conductor

Type	Pack Piece	Weight kg/100 pc.	Item no.
113 BZ-FL	100	6.280	5230446
113 B-Z-HD-FL	100	7.000	5230462

Zn Die-cast zinc

G Electrogalvanised

- With female thread M8 or through hole for wood screws
- For flat conductor FL 30
- Sliding over-piece for quick installation




Cable bracket for Rd 8-10 and FL 30

Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
835	Rd 8/10/ FL 30x3,5	1	8.907	5033209

St Steel

FT Hot-dip galvanised

- For round conductor Rd 8-10 and flat conductor FL 30 x 3.5
- Supplied with hexagonal wood bolt 6 x 70 and straddling dowel 910/N




Cable bracket with Cu crossbar Rd 8-10 mm

Type	Material	Surface	Pack Piece	Weight kg/100 pc.	Item no.
113 B-Z16	Zn	VZ	100	6.000	5412706

Zn Die-cast zinc

VZ Galvanised




Spacer clip for flat conductor with fastening hole Ø 6.5

Type	Fit mm	Dimen- sion B mm	Pack Piece	Weight kg/100 pc.	Item no.
831 30	max. FL30	54	25	3.580	5032032
831 40	max. 40 mm flach	65	25	3.894	5032040


St Steel

FT Hot-dip galvanised

- Fit: FL 30 and FL 40
- With mounting hole Ø 6.5 and 2 hexagonal bolts M6 x 16 (F)



Spacer clip for flat conductor, with fastening hole Ø 7




Type	Fit mm	Dimension B mm	Pack Piece	Weight kg/100 pc.	Item no.
832 30	max. FL30	55	25	7.416	5032539
832 40	max. FL40	65	25	7.612	5032547

St Steel

FT Hot-dip galvanised

- Fit: FL 30 and FL 40
- With mounting hole Ø 7 mm and 2 hexagonal bolts M6 x 16

Spacer clip for flat conductor, with threaded connection M6




Type	Fit mm	Dimension B mm	Pack Piece	Weight kg/100 pc.	Item no.
831 30 M6	max. FL30	54	25	3.712	5032237
831 40 M6	max. FL40	65	25	3.880	5032245

St Steel

FT Hot-dip galvanised

- Fit: FL 30 and FL 40
- With attaching thread M6 and 2 hexagonal bolts M6 x 16 (F)

Spacer clip for flat conductor, with polyamide base




Type	Fit mm	Dimension B mm	Pack Piece	Weight kg/100 pc.	Item no.
833 35	max. FL30	60	25	4.228	5033039

St Steel

FT Hot-dip galvanised

- Fit: FL 30
- With mounting hole 6.2 x 22 mm
- With 2 cylinder bolts M6 x 16 and over-piece from hot-dip galvanised steel
- Bottom section from polyamide, black

Spacer clip for flat conductor, with wood screw and spacer




Type	Fit mm	Dimension B mm	Pack Piece	Weight kg/100 pc.	Item no.
370 H	max. FL30	55	100	10.200	5025206

St Steel

FT Hot-dip galvanised

- Fit: FL 30
- With spacer and cylinder bolts M6 x 16 (G)
- With wood bolts

Spacer clip for flat conductor, with steel spreading anchor Ø 10



Type	Fit mm	Dimension B mm	Pack Piece	Weight kg/100 pc.	Item no.
710 30	max. FL30	52	25	5.044	5028035
710 40	max. FL40	62	25	5.360	5028043

St Steel

G Electrogalvanised

- Fit: FL 30 and FL 40
- With steel straddling dowel Ø 10 mm, spacer and 2 cylinder bolts M5 x 14 (G)


Spacer clip for flat conductor, with square pin

Type	Fit mm	Dimension B mm	Pack Piece	Weight kg/100 pc.	Item no.
708 30 SP	max. FL30	52	50	3.148	5030021

St Steel

G Electrogalvanised

- Fit: FL 30 and FL 40
- With 2 cylinder bolts M5 x 12 (G) and over-piece
- With square pin




Spacer clip for flat conductor, with wood screw

Type	Fit mm	Dimension B mm	Pack Piece	Weight kg/100 pc.	Item no.
708 30 HG	max. FL30	52	50	3.148	5030234
708 40 HG	max. FL40	62	50	2.827	5030242

St Steel

G Electrogalvanised

- Fit: FL 30 and FL 40
- With 2 cylinder bolts M5 x 12 (G) and over-piece
- With wood screw




Connection clip



Type	For earth rods Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
2760 16	14.2	5	35.000	5001601

CuSn Red bronze

- For the connection of conductor materials with conductor shoes to earth rod 219 16 CU




Expansion strip for foundation earth electrode systems

Type	Dimension W x H mm	Pack Piece	Weight kg/100 pc.	Item no.
1807 DB	30x3,5	1	40.000	5016160

A2 Stainless steel, rustproof 1.4301

- Expansion strip according to VDE 0185-561-2 (IEC 62561-2)
- To pass the foundation earther through movement joints



Holders and accessories

Earthing enhancing compound




Type	Dimension	Pack Piece	Weight kg/100 pc.	Item no.
OEC 25	25kg	1	2,500.000	5009200

- To improve and maintain a constant earth electrode resistance
- Highly swellable and powdery special clay
- Tested according to IEC 62561-7 (VDE 0185-561-7)



Corrosion protection strip



Type Width Length
mm mm


356 50	50	10
356 100	100	10

Pack	Weight	Item no.
Piece	kg/100 pc.	
1	71.500	2360055
1	122.200	2360101

PETRO Petrolatum

- Approx. 1.1 mm thick
- Width: 50 mm or 100 mm, made of petrolatum-coated chemical fibre fabric
- Can be processed cold

Strip steel crimp



Type Length Fit
mm mm

366 35	35	max. FL30
366 50	50	max. FL30


Pack	Weight	Item no.
Piece	kg/100 pc.	
100	1.737	5059356
100	2.300	5059496

St Steel

FT Hot-dip galvanised

- Fit: FL 30

Number plates




Type Fit
mm

311 N-ALU 8-10	RD 8 - 10 / FL30
311 N-ALU 16	RD 16 - FL30

Pack	Weight	Item no.
Piece	kg/100 pc.	
5	2.500	3049256
5	2.800	3049345

- To identify the point of separation to DIN 48821
- Suitable for universal labelling (e.g. stamped numbers)

Number plates




Type Fit
mm

311 N-VA 8-10	RD 8 - 10 / FL30
311 N-VA 16	RD 16 - FL30

Pack	Weight	Item no.
Piece	kg/100 pc.	
5	5.600	3049221
5	6.400	3049329

- To identify the point of separation to DIN 48821
- Suitable for universal labelling (e.g. stamped numbers)

Number plates




Type Fit
mm

311 N-CU 8-10	RD 8 - 10 / FL30
Cu	Copper

Pack	Weight	Item no.
Piece	kg/100 pc.	
5	6.400	3049205

- To identify the point of separation to DIN 48821
- Suitable for universal labelling (e.g. stamped numbers)






Air-termination and down-conductor systems

	Conductor material	408
	Air-termination systems	411
	Air-termination rods	415
	Roof conductor holder	422
	Cable bracket	430
	Connectors and connection terminals	439
	Connection and separating terminals	465
	Earth entries	468
	Accessories	470



Galvanised steel flat conductor for earth




Type	Dimension W x H mm	Cross-section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
5052 DIN 20X2.5	20 x 2,5	50	122	50	122	41.000	5019340
5052 DIN 25X3	25 x 3	75	84	50	84	59.700	5019342
5052 DIN 30X3	30 x 3	90	71	50	71	70.650	5019344
5052 DIN 30X3.5	30 x 3,5	105	30	25	30	84.000	5019345
5052 DIN 30X3.5	30 x 3,5	105	60	50	60	84.000	5019347
5052 DIN 30X4	30 x 4	120	52	50	52	97.000	5019350
5052 DIN 40X4	40 x 4	160	40	51	40	128.000	5019355
5052 DIN 40X5	40 x 5	200	30	50	30	162.000	5019360

St Steel

FT Hot-dip galvanised

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Meets the requirements of VDE 0185-305 (IEC 62305)
- Zinc coating: ≥ 500 g/m² (approx. 70 µm in mean value)
- For lightning protection, earthing systems and ring equipotential bonding

Stainless steel flat conductor




Type	Dimension W x H mm	Cross-section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
5052 V2A 30X3.5	30 x 3,5	105	50	42	50	82.500	5018501
5052 V4A 30X3.5	30 x 3,5	105	50	42	50	82.425	5018706
5052 V4A 30X3.5	30 x 3,5	105	25	21	25	82.425	5018730

A2 Stainless steel, rustproof 1.4301 A4 Stainless steel, rustproof 1.4571/1.4404

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)
- According to the foundation earther standard DIN 18014, V4A is required in the earth
- For use in areas at risk of corrosion
- For lightning protection, earthing systems and ring equipotential bonding

Flat conductor, copper




Type	Dimension W x H mm	Cross-section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
FL 25-CU	25 x 3	75	50	33	50	67.000	5021830

Cu Copper

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Meets the requirements of VDE 0185-305 (IEC 62305)
- For lightning protection, earthing systems and ring equipotential bonding

Round conductor, galvanised steel



Type	Nominal size Ø mm	Cross-section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-FT	8	50	125	50	125	40.000	5021081
RD 10	10	78	80	50	80	63.000	5021103

St Steel

FT Hot-dip galvanised

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)
- RD 10 can also be used in the earth
- Zinc coating: ≥ 350 g/m² (approx. 50 µm in mean value)

Round conductor, galvanised steel with PVC jacketing



Type	Colour	Dimen- sion d mm	Dimen- sion D mm	Cross- section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 10-PVC	Black	10	13	78	75	50	75	67.000	5021162


SI Steel

FT Hot-dip galvanised

- Corresponds to the requirements according to VDE 0185-305 (IEC 62305)

- Zinc coating: ≥ 350 g/m² (approx. 50 µm in mean value)

- With PVC jacketing



Round conductor, aluminium

Type	Nominal size Ø mm	Cross- section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-ALU	8	50	150	20	150	13.500	5021286
RD 8-ALU-T	8	50	150	20	150	13.500	5021294
RD 10-ALU	10	78	95	20	95	21.000	5021308

Alu Aluminium

- According to DIN EN 62561-2 (VDE 0185-561-2)


- Corresponds to the requirements of VDE 0185-305 (IEC 62305)

- RD 8 ALU: Semi-hard (E-AlMgSi0.5 corresponds to DIN 48801)

- RD 8 ALU-T: Can be subjected to torsion (E-AlMgSi0.5 corresponds to DIN 48801)

- RD 10 ALU: Pure aluminium (E-Al corresponds to DIN 48801)

- AL and ALMgSi may not be routed directly on, in or under plaster, mortar or concrete, nor routed in the earth



Round conductor, aluminium, with PVC sheathing




Type	Nominal size Ø mm	Cross- section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-PVC	8/11	50	100	20	100	20.000	5021332

Alu Aluminium

- Meets the requirements of VDE 0185-305 (IEC 62305)

- With PVC jacketing (halogen-free)

- Suitable for routing on, in or under plasterwork, mortar or concrete



Round conductor, stainless steel A2



Type	Nominal size Ø mm	Cross- section mm ²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-V2A	8	50	125	50	125	40.000	5021235
RD 10-V2A	10	78	80	50	80	63.000	5021239
RD 10-V2A	10	78	50	32	50	63.000	5021227


A2 Stainless steel, rustproof 1.4301

- According to DIN EN 62561-2 (VDE 0185-561-2)

- Corresponds to the requirements of VDE 0185-305 (IEC 62305)


- RD 10-V4A for applications in the earth

- According to the foundation earther standard DIN 18014, V4A is required in the earth



Conductor material

Round conductor, stainless steel A4




Type	Nominal size Ø mm	Cross-section mm²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-V4A	8	50	125	50	125	40.000	5021644
RD 10-V4A 20	10	78	20	12	20	63.000	5021640
RD 10-V4A	10	78	80	50	80	63.000	5021647
RD 10-V4A	10	78	50	32	50	63.000	5021642

A4 Stainless steel, rustproof 1.4571/1.4404

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)
- RD 10-V4A for applications in the earth
- According to the foundation earther standard DIN 18014, V4A is required in the earth

Round conductor, copper sheathed




Type	Nominal size Ø mm	Cross-section mm²	Pack m	Weight kg/100 m	Item no.
RD 8-ST CU	8	50	100	40.000	5021380

St Steel

Cu Copper-plated

- According to IEC/ EN 62561-2 (VDE 0185-561-2)
- Meets the requirements of VDE 0185-305 (IEC 62305)
- Copper layer thickness: Min. 250 µm

Round conductor, copper




Type	Nominal size Ø mm	Cross-section mm²	Normal ring ca. m	Normal ring ca. kg	Pack m	Weight kg/100 m	Item no.
RD 8-CU	8	50	100	45	100	45.000	5021480
RD 8-CU 25	8	50	55	25	55	45.000	5021484
RD 10-CU	10	78	50	35	50	70.000	5021502

Cu Copper

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)

Copper cable




Type	Dimension D mm	Individual wires	Cross-section mm²	Normal ring ca. m	Normal ring ca. kg	Weight kg/100 m	Item no.
S 11-CU	10.5	19x Ø 2,1	70	50	30	58.600	5021654
S 9-CU	9	19x Ø 1,8	50	100	45	45.000	5021652

Cu Copper

- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)

Copper cable Tin-plated



Type	Dimension D mm	Individual wires	Cross-section mm²	Normal ring ca. m	Normal ring ca. kg	Weight kg/100 m	Item no.
S-11-CU SN	10.5	19x Ø 2,1	70	50	30	58.600	5021656

Cu Copper

Sn Tin-plated


- According to DIN EN 62561-2 (VDE 0185-561-2)
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)

Stand for FangFix Junior system

Type	Length mm	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
F-FIX-JUNIOR	1000	10	10	32.000	5403308

Alu | Aluminium

- Incl. aluminium air-termination rod 1,000 mm long (\varnothing 10 mm)
- Quick mounting of the air-termination rod in the base using plug technology
- With Vario quick connector 249




Air-termination rod for FangFix-Junior

Type	Length mm	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 J1000	1000	10	10	21.800	5401970

Alu | Aluminium

- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- \varnothing 10 mm, aluminium
- Without thread
- Suitable for use in FangFix-Junior




Base for FangFix Junior

Type	Pack Piece	Weight kg/100 pc.	Item no.
F-FIX-BASIS	10	3.790	5403324

PP | Polypropylene

- For mounting \varnothing 10 mm air-termination rods up to an overall length of 1,000 mm
- Quick installation of air-termination rod in base using plug-in system
- Quick and easy installation




Air-termination tip

Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
120 A	Rd 8-10	10	2.500	5405068

Zn | Die-cast zinc

G | Electrogalvanised

- To be used for Rd 8–10 (corrosion protection)
- With cylinder bolt M6 x 10
- Made of die-cast zinc, bolts made of hot-galvanised steel




Tapered pipe air-termination rod


Type	Length mm	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 VL1500	1500	10/16	10	38.000	5401980
101 VL2000	2000	10/16	10	55.000	5401983
101 VL2500	2500	10/16	10	72.000	5401986
101 VL3000	3000	10/16	10	88.000	5401989
101 VL3500	3500	10/16	10	105.000	5401993
101 VL4000	4000	10/16	10	120.000	5401995

Alu | Aluminium

- Suitable for wind loads according to Eurocode 1: DIN EN 1991-4
- From a free length of > 2.5 m, an additional fastening, e.g. insulated spacer is recommended
- Last metre is tapered from \varnothing 16 mm to \varnothing 10 mm, material: AlMgSi
- Matches stand system FangFix



Air-termination/earth entry rod, rounded-off on both ends




Type	Nominal Length mm	size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 A-1500	1500	16	10	240.000	5400155

St Steel

FT Hot-dip galvanised

- Full material Ø 16 mm
- Rounded on both ends
- Suitable for FangFix stand system

Air-termination/earth entry rod, rounded-off on both ends




Type	Nominal Length mm	size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
200 V4A-1500	1500	16	10	242.000	5420504
200 V4A-2000	2000	16	10	320.000	5420539

A4 Stainless steel, rustproof 1.4571

- Full material Ø 16 mm
- Both ends rounded

Air-termination/earth entry rod, rounded-off on both ends




Type	Nominal Length mm	size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 A-CU	1500	16	10	272.100	5400627

Cu Copper

- Full material Ø 16 mm
- Both ends rounded

Concrete base for FangFix system, min. 16 kg




Type	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
F-FIX-S16	365	1	1,700.000	5403227

BET Concrete

- Min. 16 kg block of Ø 365 mm, high level of stability
- Frost-resistant concrete
- Stackable

Concrete base for FangFix system, min. 10 kg




Type	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
F-FIX-S10	289	1	1,000.000	5403117

BET Concrete

- Min. 10 kg block of Ø 289 mm, high level of stability
- Frost-resistant concrete
- Stackable

Terminal for FangFix system



Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
F-FIX-KL	Rd 8	5	8.700	5403219

A2 Stainless steel, rustproof 1.4301


- FangFix terminal, VA for RD 8 mm
- Tested with H (100 kA) to DIN EN 50164-1
- Round conductor installed on the air-termination rod with only one screw

Air-termination rod, one end rounded, M16 thread

Type	Length mm	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 ALU-1000	1000	16	10	55.000	5401771
101 ALU-1500	1500	16	10	81.000	5401801
101 ALU-2000	2000	16	10	109.000	5401836
101 ALU-2500	2500	16	10	136.000	5401852
101 ALU-3000	3000	16	5	162.000	5401879

Alu | Aluminium

- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- From a free length of > 2.5 m, an additional fastening, e.g. insulated spacer is recommended
- Ø 16 mm, aluminium
- For stand system with M16 internal thread




Air-termination rod, one end rounded, M16 thread

Type	Length mm	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 A-L100	1000	16	10	160.000	5402808
101 A-L150	1500	16	10	240.000	5402859

St | Steel

FT | Hot-dip galvanised

- With thread M16 x 20
- With connecting strap
- Including pre-mounted connector type 5001 DIN for round conductor Rd 8-10
- For stands with female thread M16




Concrete base min. 16 kg with female thread

Type	Length mm	Nominal size Ø mm	Thread	Pack Piece	Weight kg/100 pc.	Item no.
101 B2-16 M16	364	16	M16	1	1,600.000	5402958

BET | Concrete

- Weight min. 16 kg
- Frost-resistant concrete
- Female thread M16
- Recommended air-termination rod length max. 3.0 m, depending on wind load zone




Stand 6.9 kg with female thread

Type	Thread	Pack Piece	Weight kg/100 pc.	Item no.
101 ST M16	M16	4	690.000	5402891

BET | Concrete

- Weight 6.9 kg
- Frost-resistant concrete
- Female thread M16
- Recommended air-termination rod length max. 1.0 m




Air-termination/earth entry rod with connection tabs

Type	Length mm	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 F1000	1000	16	10	160.000	5424100
101 F1500	1500	16	10	240.000	5424151
101 F2000	2000	16	10	320.000	5424208


St | Steel

FT | Hot-dip galvanised

- With 2 attaching holes Ø 12 mm
- One end rounded



Air-termination/earth entry rod with connection tabs and connector




Type	Nominal length mm	size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 G1000	1000	16	10	164.300	5402107
101 G1500	1500	16	10	240.000	5402158

St Steel

FT Hot-dip galvanised

- 1 attaching hole Ø 12 mm
- With pre-mounted conductor for Rd 8-10
- One end rounded

Air-termination rod holder for sloping roof




Type	Pack Piece	Weight kg/100 pc.	Item no.
SD-Fix	1	81.000	5403335

A2 Stainless steel, rustproof 1.4301

Stand system: rod holder for sloping roofs, for simple, quick and secure fastening of Ø 16 mm air-termination rods.

- System consists of a bracket made of V2A stainless steel
- Quick and easy mounting
- Adjustable angle
- In the case of high air-termination rods (> 1 m), additional fastening with insulated spaces is necessary

Air-termination rod holder for ridge tiles



Type	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
F-FIX-132	110	1	62.000	5403330
F-Fix-132-300	300	1	78.000	5403333


A2 Stainless steel, rustproof 1.4301

Rod holder for ridge tiles, for simple, quick and safe fastening of Ø 16 mm air-termination rods

- System consisting of holder made of V2A stainless steel and aluminium air-termination rods
- Quick and easy mounting thanks to pre-mounted air-termination rod
- Air-termination rod length: 1,000 mm
- Width adjustable between 180–260 mm
- Spacing of the ridge holders: 110 mm (5403330)
- Spacing of the ridge holders: 300 mm (5403333)

Application: To protect roof structures such as photovoltaic and TV/SAT systems.

Mushroom-shaped air-termination with connectors




Type	Fit mm	Dimen- sion D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
128 F Rd 8-10/ FL30	80	80	5	40.000	5405769

St Steel

FT Hot-dip galvanised

- Mushroom-shaped air-termination from aluminium
- With pre-mounted cross-piece and hexagonal bolt M8 x 25, hot-dip galvanised steel
- For round conductor Rd 8-10 and flat conductor FL 30

Roof penetration



Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
330 K Rd 8-16/ FL20 u. FL30	5	14.400	5201101	

PA Polyamide

- For round conductors 8-10, air-termination rods 16 mm
- Flat conductors 20 mm/30 mm
- Colour: Black, UV-resistant
- For penetration and sealing of roofs


isFang air-termination rod

Type	Dimen- sion B mm	Dimen- sion D mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
101 3B-4000	2000	1000	4000	1	400.000	5402864
101 3B-4500	2500	1000	4500	1	480.000	5402866
101 3B-5000	3000	1000	5000	1	550.000	5402868
101 3B-5500	3000	1500	5500	1	630.000	5402870
101 3B-6000	4000	1000	6000	1	700.000	5402872
101 3B-6500	4500	1000	6500	1	780.000	5402874
101 3B-7000	5000	1000	7000	1	850.000	5402876
101 3B-7500	5500	1000	7500	1	930.000	5402878
101 3B-8000	5500	1000	8000	1	1,000.000	5402880

Alu | Aluminium

- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- Tapered air-termination rod
- Suitable for 40 mm isFang tripod stand and isFang support systems

Dimensions



Insulated air-termination rod




Type	Dimen- sion A mm	Dimen- sion H mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang 4000 AL	1240	1500	1000	4000	1	580.000	5408943
isFang 6000 AL	3340	1500	1000	6000	1	600.000	5408947
isFang 4000	1240	1500	1000	4000	1	680.000	5408942
isFang 6000	3340	1500	1000	6000	1	680.000	5408946

GFK Fibre-glass-reinforced plastic


- For isolated creation of air-termination systems
- Suitable for isFang air-termination rod stands, type isFang 3B-100/150
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- For installation on the building structure with isFang support
- Fastening of the OBO isCon® conductor possible using accessories
- Suitable for externally routed isCon® conductors



Dimensions



isFang tripod



Type	Dimen- sion B mm	Dimen- sion D Ø mm	Dimen- sion L mm	Dimen- sion H mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang 3B-100 AL	1000	40	600	885	1	380.000	5408966
isFang 3B-150 AL	1500	40	900	1275	1	560.000	5408967
isFang 3B-100	1000	40	600	885	1	620.000	5408968
isFang 3B-150	1500	40	900	1275	1	950.000	5408969

A2 Stainless steel, rustproof 1.4301 Alu Aluminium

- Installation of free-standing air-termination rods as well as insulated air-termination rods with 40 mm diameter
- Roof slope to max. 5 degrees
- Incl. Rd 8-10 crossbar for quick round conductor fastening
- Concrete bases as well as threaded rods should be ordered separately



Insulated air-termination rod for inner-routed isCon conductor with side exit




Type	Dimen- sion D Ø mm	Dimen- sion A mm	Dimen- sion H mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang IN-A 4000	50	1325	1500	1000	4000	1	535.000	5408938
isFang IN-A 6000	50	3325	1500	1000	6000	1	835.000	5408940
isFang IN-A 8000	50	5335	1500	1000	8000	1	1,385.000	5408888
isFang IN-A10000	50	6000	1733	2000	10000	1	1,540.000	5408890

GFK Fibre-glass-reinforced plastic

- For installation of the OBO isCon® Pro+ conductor in the pipe
- With side conductor outlet matching isFang air-termination rod stand with side outlet, type isFang 3B-A
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- Inclusive connection element (type isCon IN connect)
- Inclusive potential connection (type IsCon In PAE)



Dimensions




Insulated air-termination rod for inner-routed isCon® conductor



Type	Dimen- sion D Ø mm	Dimen- sion A mm	Dimen- sion H mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang IN L4	50	1325	1500	1000	4000	1	535.741	5408854
isFang IN L6	50	3325	1500	1000	6000	1	835.741	5408856
isFang IN L8	50	5335	1500	1000	8000	1	1,315.741	5408858
isFang IN L10	50	6000	1733	2000	10000	1	1,540.741	5408860


GFK Fibre-glass-reinforced plastic

- For routing OBO isCon® conductors in pipes
- For installation on the building structure with isFang support
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- Tested according to VDE V 0185-561-8 (IEC TS 62561-8)



Air-termination rod systems

Insulated air-termination rod for inner-routed isCon® conductor with side exit




Type	Dimen- sion D Ø mm	Dimen- sion A mm	Dimen- sion H mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang IN-A L4	50	1325	1500	1000	4000	1	535.000	5408874
isFang IN-A L6	50	3325	1500	1000	6000	1	835.741	5408876
isFang IN-A L8	50	5335	1500	1000	8000	1	1,385.741	5408878
isFang IN-A L10	50	6000	1733	2000	10000	1	1,540.741	5408880

GFK Fibre-glass-reinforced plastic

- For routing OBO isCon® conductors in pipes
- For mounting on the building structure with isFang support
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- Tested according to VDE V 0185-561-8 (IEC TS 62561-8)

isFang tripod with side outlet




Type	Dimen- sion B mm	Dimen- sion D Ø mm	Dimen- sion L mm	Dimen- sion H mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang 3B-100-A	1026	50	600	885	1	610.000	5408930
isFang 3B-150-A	1500	50	900	1275	1	950.000	5408932
isFang 3B-250-A	2900	50	1450	2055	1	2,500.000	5408902

A2 Stainless steel, rustproof 1.4301

- Screwless installation of freestanding air-termination rods as well as insulated air-termination rods with 50 mm diameter
- E.g. for internal OBO isCon® conductor
- Roof slope to max. 5 degrees
- Incl. Rd 8–10 crossbar for quick round conductor fastening
- Concrete plinths as well as threaded rods should be ordered separately

isFang-3B threaded rod




Type	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang 3B-G1	270	3	48.000	5408971
isFang 3B-G2	340	3	60.400	5408972
isFang 3B-G3	430	3	69.500	5408973
isFang 3B-G4	500	3	75.000	5408905

A2 Stainless steel, rustproof 1.4301

- For fastening on one, two, three or four FangFix concrete bases with tripod stand

Concrete base for FangFix system, min. 16 kg




Type	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
F-FIX-S16	365	1	1,700.000	5403227

BET Concrete

- Min. 16 kg block of Ø 365 mm, high level of stability
- Frost-resistant concrete
- Stackable

Base for FangFix system 16 kg for mounting the isFang tripod



Type	Nominal size Ø mm	Dimen- sion D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
F-FIX-B16 3B	373	25	10	15.800	5403238

PP Polypropylene

- Edge protection with through hole
- For mounting isFang-3B threaded rod and FangFix concrete block F-FIX-S16

isFang, insulated air-termination rod for inner-routed isCon® conductor Professional Plus




Type	Dimension D Ø mm	Dimension A mm	Dimension H mm	Dimension B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang IN 4000	50	1325	1500	1000	4000	1	535.000	5408934
isFang IN 6000	50	3325	1500	1000	6000	1	835.000	5408936
isFang IN 8000	50	5335	1500	1000	8000	1	1,315.000	5408868
isFang IN 10000	50	6000	1733	2000	10000	1	1,540.000	5408870

GFK Fibre-glass-reinforced plastic

- For installation of the OBO isCon® Pro+ conductor in the pipe
- For mounting on the building structure with isFang support
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- Inclusive connection element (type isCon IN connect)
- Inclusive potential connection (type IsCon In PAE)



Dimensions




isFang support for wall mounting, 30 mm spacing

Type	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TW30 30		2	62.000	5408952

A2 Stainless steel, rustproof 1.4301

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.




isFang support for wall mounting, 80 mm spacing


Type	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TW80 80		2	63.000	5408950

A2 Stainless steel, rustproof 1.4301

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.



isFang support for wall mounting, 200–300 mm spacing




Type	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TW200 300		2	230.000	5408954

A2 Stainless steel, rustproof 1.4301

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.

Support for wall mounting, 200 mm spacing




Type	Dimension D Ø mm	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TW200 12 50	200		2	240.000	5408910

A2 Stainless steel, rustproof 1.4301

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.

isFang support for pipe mounting, ø 50–300 mm




Type	Dimension D Ø mm	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TR100 300 40			2	77.000	5408956

A2 Stainless steel, rustproof 1.4301

Tightening strap clip to fasten the insulated support pipes on the structure to be protected or for construction-side pipes of ø 50–300 mm.

isFang support for spaced pipe mounting, ø 50–300 mm




Type	Dimension D Ø mm	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TR100 100 300 100			2	95.500	5408955
isFang TR100 200 300 200			2	121.000	5408957
isFang TR100 300 300 300			2	146.000	5408959

A2 Stainless steel, rustproof 1.4301

Tightening strap clip to fasten the insulated support pipes on the structure to be protected or for construction-side pipes of ø 50–300 mm.

isFang support for pipe mounting, ø 40–50 mm




Type	Dimension D Ø mm	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TS40-50 50 40			2	90.000	5408958

A2 Stainless steel, rustproof 1.4301

Tightening strap clip to fasten the insulated support pipes on the structure to be protected or for construction-side pipes of ø 40–50 mm.

isFang support for pipe mounting, ø 50–60 mm



Type	Dimension D Ø mm	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TS50-60 60 30			2	76.000	5408960

A2 Stainless steel, rustproof 1.4301


Tightening strap clip to fasten the insulated support pipes on the structure to be protected or for construction-side pipes of ø 50–60 mm.

isFang support for corner pipe mounting, 50 x 50 mm

Type	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TS50x50 30		2	82.000	5408964

A2 Stainless steel, rustproof 1.4301

Fastening clip to fasten the insulated support pipes on the structure to be protected or for construction-side corner pipes of 50x50 mm.




Tele air-termination rod systems irod

10 m air-termination rod with 6-legged air-termination rod stand

Type	Dimen- sion D Ø mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
irod 10 48.3	1800	10000		1	6,500.000	5400810

A2 Stainless steel, rustproof 1.4301

- Tele lightning protection system against direct lightning strikes into plants, such as biogas plants
- Consisting of air-termination rod and air-termination rod stand
- Please order concrete foot, edge protection and threaded rods separately



12 m air-termination rod with 6-legged air-termination rod stand

Type	Dimen- sion D Ø mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
irod 12 85	3000	12000		1	10,900.000	5400812

A2 Stainless steel, rustproof 1.4301

- Tele lightning protection system against direct lightning strikes into plants, such as biogas plants
- Consisting of air-termination rod and air-termination rod stand
- Please order concrete foot, edge protection and threaded rods separately



14 m air-termination rod with 8-legged air-termination rod stand

Type	Dimen- sion D Ø mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
irod 14 85	3200	14000		1	15,400.000	5400814

A2 Stainless steel, rustproof 1.4301

- Tele lightning protection system against direct lightning strikes into plants, such as biogas plants, gas pressure regulation plants, control and greenfield photovoltaic systems
- Consisting of air-termination rod and air-termination rod stand
- Please order concrete foot, edge protection and threaded rods separately



19 m air-termination rod with 12-legged air-termination rod stand


Type	Dimen- sion D Ø mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
irod 19 198	3400	19500		1	41,500.000	5400817

A2 Stainless steel, rustproof 1.4301

- Tele lightning protection system against direct lightning strikes into plants, such as biogas plants, gas-pressure regulation plants, control and greenfield photovoltaic systems
- Consisting of air-termination rod and air-termination rod stand
- Please order concrete foot and edge protection separately
- Including 800-mm threaded rods



Concrete base for FangFix system, min. 16 kg




Nominal size Ø
mm
F-FIX-S16 | 365

BET Concrete

- Min. 16 kg block of Ø 365 mm, high level of stability
- Frost-resistant concrete
- Stackable

Pack Weight
Piece kg/100 pc. **Item no.**
| 1 | 1,700.000 | **5403227**

Base for FangFix system 16 kg for mounting the isFang tripod



Nominal size Ø
mm
F-FIX-B16 3B | 373 | 25


PP Polypropylene

- Edge protection with through hole
- For mounting isFang-3B threaded rod and FangFix concrete block F-FIX-S16

Pack Weight
Piece kg/100 pc. **Item no.**
| 10 | 15.800 | **5403238**

Roof conductor holder, ridge

Ridge conductor holder with tensioning spring




Installation height
Type Fit mm mm
132 U 35 | RD 8 | 35

A2 Stainless steel, rustproof 1.4301

- For round conductor Rd 8
- Clamping range 280-380 mm

Pack Weight
Piece kg/100 pc. **Item no.**
| 20 | 6.800 | **5203018**

Ridge conductor holder with tensioning spring




Installation height
Type Fit mm mm
132 U | RD 8 | 20

A2 Stainless steel, rustproof 1.4301

- For round conductor Rd 8
- Clamping range 280-380 mm

Pack Weight
Piece kg/100 pc. **Item no.**
| 20 | 6.000 | **5203015**

Ridge conductor holder with tensioning spring



Installation height
Type Fit mm mm
132 U-CU | RD 8 | 20


A2 Stainless steel, rustproof 1.4301

Cu Copper-plated

- For round conductor Rd 8
- Clamping range 280-380 mm

Pack Weight
Piece kg/100 pc. **Item no.**
| 10 | 0.600 | **5203023**

Roof conductor holder for ridge tiles, 185–260 mm, Rd 8



Installation height
Type Fit mm mm
132 VA 35 | Rd 8 | 35

A2 Stainless steel, rustproof 1.4301


- Adjustable width from 185-260 mm
- Fast installation using wing screw

Pack Weight
Piece kg/100 pc. **Item no.**
| 20 | 13.700 | **5202836**

Roof conductor holder for ridge tiles, 185–260 mm, Rd 8

Type	Fit mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
132 VA Rd 8 20			20	12.900	5202833


A2 Stainless steel, rustproof 1.4301
 • Adjustable width from 185–260 mm
 • Fast installation using wing screw



Roof conductor holder for ridge tiles, 185–260 mm, Rd 8

Type	Fit mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
132 CU Rd 8 20			10	13.400	5202868


Cu Copper
 • Adjustable width from 185–260 mm
 • Fast installation using wing screw



Roof conductor holder for ridge tiles, 185–260 mm, Rd 8–10

Type	Fit mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
132 K-VA Rd 8-10 20			20	10.900	5202515


A2 Stainless steel, rustproof 1.4301
 • Adjustable width from 185–260 mm
 • Bottom part made of non-rusting stainless steel (V2A)
 • Infinitely adjustable conductor holder
 • Conductor holder of polyamide
 • Fast installation using wing screw



Roof conductor holder for ridge tiles, 185–260 mm, Rd 8–10

Type	Fit mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
132 K-CU Rd 8-10 20			10	11.600	5202590


Cu Copper
 • Adjustable width from 185–260 mm
 • Bottom part made of copper
 • Infinitely adjustable conductor holder
 • Conductor holder of polyamide
 • Fast installation using wing screw



Roof cable holder for ridge tiles, 180–240 mm, Rd 8–10


Type	Fit mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
132 N-DK Rd 8-10 20			20	19.700	5202566

St Steel
 FT Hot-dip galvanised
 • Adjustable from 180–240 mm
 • With conductor 177/20, polyamide, grey
 • With 3 M8 threaded nipples for positioning the holder



Roof conductor holder, ridge

Roof conductor holder for ridge tiles with M8 threaded bolts




Type	Fit	Installation height mm	Pack Piece	Weight kg/100 pc.	Item no.
132 GB-M8 20			20	18.700	5202568

St Steel

FT Hot-dip galvanised

- Adjustable from 180–240 mm
- With conductor 177/20, polyamide, grey
- With 3 M8 threaded nipples for positioning the holder

Roof conductor holder for ridge tiles, metal roofs, Rd 8




Type	Fit	Installation height mm	Pack Piece	Weight kg/100 pc.	Item no.
132 P VA Rd 8 20			20	8.420	5202510

A2 Stainless steel, rustproof 1.4301

- For round conductors Rd 8
- Suitable for metal roofs

Roof conductor holder, tiled roof

Roof cable holder for tiled roofs, Rd 8




Type	Fit	Installation height mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
157 F-VA 230 35 Rd 8 50			230	20	8.300	5215552
157 F-VA 280 35 Rd 8 50			280	20	9.700	5215582

A2 Stainless steel, rustproof 1.4301

- Conductor holder from stainless steel (V2A)
- Including drill hole in bottom section for quick installation

Roof cable holder for tiled roofs, Rd 8




Type	Fit	Installation height mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
157 F-VA 230 Rd 8 38.5			230	20	8.350	5215552
157 F-VA 280 Rd 8 38.5			280	20	10.170	5215579
157 F-VA 410 Rd 8 38.5			410	20	14.880	5215595

A2 Stainless steel, rustproof 1.4301

- Conductor holder from stainless steel (V2A)
- Including drill hole in bottom section for quick installation

Roof cable holder for tiled roofs, Rd 8




Type	Fit	Installation height mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
157 F-CU 230 Rd 8 38.5			230	10	10.300	5216192
157 F-CU 280 Rd 8 38.5			280	10	11.100	5216206
157 F-CU 410 Rd 8 38.5			410	10	14.500	5216257

Cu Copper

- Conductor holder from copper plated stainless steel (V2A)
- Including drill hole in bottom section for quick installation

Roof conductor holder for tiled roofs, Rd 8–10

Type	Fit mm	Installation height mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
157 FK-VA 230	Rd 8-10	40	230	20	7.800	5215544
157 FK-VA 280	Rd 8-10	40	280	20	10.170	5215587
157 FK-VA 410	Rd 8-10	40	410	20	14.880	5215609




A2 Stainless steel, rustproof 1.4301

- Conductor holder of polyamide
- Including drill hole in bottom section for quick installation

Roof conductor holder for tiled roofs, Rd 8–10

Type	Fit mm	Installation height mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
157 FK-CU 230	Rd 8-10	40	230	10	8.800	5216184
157 FK-CU 280	Rd 8-10	40	280	10	9.600	5216214




Cu Copper

- Conductor holder of polyamide
- Including drill hole in bottom section for quick installation

Roof cable holder for tiled roofs, angled, Rd 8

Type	Fit mm	Installation height mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
157 I-VA	Rd 8	26.5	140	20	7.150	5215625




A2 Stainless steel, rustproof 1.4301

- Conductor holder high-grade stainless steel (V2A)
- Curved bottom strip for quick installation

Roof cable holder for tiled roofs, angled, Rd 8

Type	Fit mm	Installation height mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
157 I-CU	Rd 8	26.5	140	10	7.800	5215749




Cu Copper

- Conductor holder copper plated high-grade stainless steel (V2A)
- Curved bottom strip for quick installation

Roof cable holder for tiled roofs, angled, Rd 8

Type	Fit mm	Installation height mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
157 FX-AL	Rd 8	26.5	140	20	3.900	5215875




Alu Aluminium

- With flexible bottom section from aluminium for matching to roof tiles (easy to flex)
- Holder from stainless steel (V2A)
- Curved bottom section for quick installation

Roof cable holder for tiled roofs, angled, Rd 8

Type	Fit mm	Installation height mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
157 FX-CU	Rd 8	26.5	140	10	7.500	5215879




Cu Copper

- With flexible bottom section from copper for matching to roof tiles (easy to flex)
- Holder from copper plated stainless steel (V2A)
- Curved bottom section for quick installation

Roof conductor holder, tiled roof

Roof conductor holder for tiled roofs, angled, Rd 8–10




Type	Fit mm	height mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
157 IK-VA	Rd 8-10 40	15	140	20	7.150	5215668

- A2 Stainless steel, rustproof 1.4301
 • Conductor holder of polyamide
 • Curved bottom strip for quick installation

Roof conductor holder, slate roof


Roof conductor holder for slated roofs, crimped, Rd 8–10



Type	Fit mm	Length mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
157 EK-VA	Rd 8-10 265	95	42	20	7.800	5215838

- A2 Stainless steel, rustproof 1.4301
 • Conductor holder of polyamide
 • With Ø 5.5 mm drill hole


Roof conductor holder for slated roofs, crimped, Rd 8–10



Type	Fit mm	Length mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
157 EK-CU	Rd 8-10 265	95	42	10	8.800	5215854

- Cu Copper
 • Conductor holder of polyamide
 • With Ø 5.5 mm drill hole


Roof conductor holder for slated roofs, Rd 8



Type	Fit mm	Length mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
157 L-VA	Rd 8 212	38	32	20	8.000	5215439

- A2 Stainless steel, rustproof 1.4301
 • With Ø 5.5 mm drill hole and beading


Roof conductor holder for slated roofs, Rd 8



Type	Fit mm	Length mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
157 L-CU	Rd 8 212	38	32	10	9.900	5215471

- Cu Copper
 • With Ø 5.5 mm drill hole and beading

Roof conductor holder for slated roofs, Rd 8–10



Type	Fit mm	Length mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
157 LK-VA	Rd 8-10 212	38	38	20	8.000	5215374

- A2 Stainless steel, rustproof 1.4301
 • With Ø 5.5 mm drill hole and beading
 • Conductor holder of polyamide

Roof conductor holder for slated roofs, Rd 8–10


Type	Fit mm	Length mm	height mm	Installation
157 LK-CU	Rd 8-10	212	38	

Pack Piece Weight kg/100 pc. Item no.

| 10 | 8.400 | 5215382

Cu Copper

- With Ø 5.5 mm drill hole and beading
- Conductor holder of polyamide



Roof conductor holder for slated roofs


Type	Fit mm	Length mm	height mm	Installation
157 GB-M8	Rd 8-10	260	27	

Pack Piece Weight kg/100 pc. Item no.

| 20 | 5.000 | 5202569

A2 Stainless steel, rustproof 1.4301

- With Ø 5.5 mm drill hole
- With 3 M8 threaded nipples for positioning the holder



Roof conductor holder, flat roof

Roof conductor holder for flat roofs, black

Type	Fit mm	Pack	Weight	kg/100 pc.	Item no.
165 MBG-8-10	Rd 8-10	12	97.220	5218700	
165 MBG-8-10 FO	Rd 8-10	12	100.000	5218704	


Pack Piece Weight kg/100 pc. Item no.

| 12 | 97.220 | 5218700

| 12 | 100.000 | 5218704

PA/PE Polyamide/polyethylene

- Closed form with base
- With double conductor holder
- Filling weight 1 kg (frost-resistant concrete)
- Sleeve made of polyethylene, black, bottom polypropylene, black
- Base made of polyamide PA 6, black, UV-stabilised and weather-resistant
- Base can be used on almost all roofing felt systems (bitumen, PVC)
- Types 165 MBG...FO: Packed in foil bag



Roof conductor holder for flat roofs, with increased base section


Type	Fit mm	Pack	Weight	kg/100 pc.	Item no.
165 MBG-8-10 200	Rd 8-10	12	100.000	5218716	

Pack Piece Weight kg/100 pc. Item no.

| 12 | 100.000 | 5218716

PA/PE Polyamide/polyethylene

- DIN 48829 Form B 1
- Closed form with bottom
- With double conductor holder
- Filling weight 1 kg (frost-resistant concrete)
- Sleeve from polyethylene, black, bottom polypropylene, black
- With larger bottom section (Ø 200 mm) for improved stability



Roof conductor holder for flat roofs, without base


Type	Fit mm	Pack	Weight	kg/100 pc.	Item no.
165 OBG-8	Rd 8	12	100.000	5218683	

Pack Piece Weight kg/100 pc. Item no.

| 12 | 100.000 | 5218683


PE Polyethylene

- Without bottom
- With double conductor holder
- Filling weight 1 kg (frost-resistant concrete)
- Sleeve from polyethylene, black



Roof conductor holder, flat roof

Roof conductor holder for flat roofs, grey




Type	Fit mm	Colour	Pack Piece	Weight kg/100 pc.	Item no.
165 MBG-8-10 GR	Rd 8-10	Grey	12	100.000	5218708

PA/PE Polyamide/polyethylene

- Closed form with base
- With double conductor holder
- Filling weight 1 kg (frost resistant concrete)
- Case made from polyethylene, light grey, UV-stabilised and weatherproof
- Base made from polyamide PA 6, light grey, UV-stabilised and weatherproof
- Base suitable for nearly all roofing membrane systems (Bitumen, PVC)

Roof conductor holder for flat roofs, black



Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
165 MBL-8-10	Rd 8-10	100	7.679	5218616

PE Polyethylene

- Closed form with base
- With double conductor holder
- Filling weight 1 kg (frost-resistant concrete)
- Sleeve made of polyethylene, black, bottom polypropylene, black
- Base made of polyamide PA 6, black, UV-stabilised and weather-resistant
- Base can be used on almost all roofing felt systems (bitumen, PVC)
- Types 165 MBG...FO: Packed in foil bag

Flat conductor adapter for roof conductor holder, type 165/MBG




Type	Colour	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
165 MBG HFL	Black	Rd 8	12	0.658	5218885

PP Polypropylene

- Flat conductor holder FL 30 x 3.5 mm
- For fastening to 165/MBG in fit Rd 8

Universal flat conductor adapter for roof conductor holder, type 165/MBG




Type	Colour	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
165 MBG UH	Black	Rd 8	25	0.254	5218882

PP Polypropylene

- Universal adapter with drill hole Ø 2.5 mm
- E.g. for OBO Golden Sprint screw, type 4758 4 x L (L = depending on application)
- For fastening to 165/MBG

Roof cable holder for flat roofs, only plastic sleeve




Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
165 KR	Rd 8	50	5.449	5218861

PE Polyethylene

- For self-filling with concrete
- Potential filling weight: approx. 1.3 kg
- Sleeve from polyethylene, black

Roof conductor holder for flat roofs, with raised cable bracket



Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
165 KRB SO	Rd 8-10	9	144.000	5218977

- Filling weight 1.3 kg (frost-resistant concrete)
- With conductor holder, type 168 DIN-K
- Die-cast zinc conductor holder, electrogalvanised
- Polyethylene sleeve, black


Type	Fit mm
165 R-8-10	Rd 8-10

Pack Piece Weight
kg/100 pc. Item no.

10 | 106.000 | 5218997

PE Polyethylene

- For round cables Rd 8 to 10
- With polyethylene plastic holder, black
- Block made of frost-resistant concrete
- Weight 1 kg
- Block can be split into plastic and concrete (recyclable)



Roof conductor holder, suitable for direct bonding

Type	Fit mm	Installation height mm
165 B 60	Rd 8-10	60
165 B 100	Rd 8-10	100

Pack Piece Weight
kg/100 pc. Item no.


50 | 26.100 | 5218810

50 | 27.700 | 5218829

St Steel

FT Hot-dip galvanised

- With conductor holder and bottom section, hot-dip galvanised steel
- Bottom section Ø 100 mm



Roof conductor holder 55 mm


Type	Fit mm	Dimension H mm	Length mm
165 NBK 55	Rd 8-10	55	100

Pack Piece Weight
kg/100 pc. Item no.

75 | 13.540 | 5218314

PA Polyamide

- Suitable for bonding straight to flat roofs
- Conductor holder of polyamide
- Bottom section, hot-dip galvanised steel
- Bottom section Ø 100 mm



Roof conductor holder, tiled, slated and corrugated roofs

Roof cable holder for tiled and slated roofs


Type	Fit mm	Length mm	Installation height mm
157 NB-VA	Rd 8-10	260	27

Pack Piece Weight
kg/100 pc. Item no.

20 | 6.000 | 5215277

A2 Stainless steel, rustproof 1.4301

- With Ø 5.5 mm drill hole
- Conductor holder of polyamide



Roof cable holder for tiled and slated roofs


Type	Fit mm	Length mm	Installation height mm
157 ND-VA	Rd 8-10	260	74

Pack Piece Weight
kg/100 pc. Item no.

20 | 6.000 | 5215307


A2 Stainless steel, rustproof 1.4301

- High roof conductor holder: 74 mm
- With perforation Ø 5.5 mm
- Polyamide cable bracket



Roof conductor holder, tiled, slated and corrugated roofs

Roof conductor holder for tiled, slated and corrugated roofs, Rd 8




Type	Fit mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
159 VA-V Rd 8 21			20	3.900	5217075

A2 Stainless steel, rustproof 1.4301

- Bottom section and conductor holder stainless steel (V2A)
- Bottom section with Ø 8.5 mm slot

Roof conductor holder for tiled, slated and corrugated roofs, Rd 8-10




Type	Fit mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
159 K-VA Rd 8-10 21			20	2.540	5216818

A2 Stainless steel, rustproof 1.4301

- Bottom section stainless steel (V2A)
- Bottom section with Ø 8.5 mm slot
- Conductor holder of polyamide

Roof conductor holder for tiled, slated and corrugated roofs, with crossbar




Type	Fit mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
133 A Rd 8-10 50			20	8.217	5202248

PA Polyamide

- With weatherproof clamping collar from soft PVC
- Required drill hole Ø = 16 mm
- Spacer from polyamide, grey

Roof conductor holder for tiled, slated and corrugated roofs, with cable bracket




Type	Fit mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
133 NB Rd 8-10 67			20	4.338	5202213

PA Polyamide

- With weather-proof clamping collar from soft-PVC
- Required drill hole Ø = 16 mm
- Spacer and conductor holder from polyamide, grey

Conductor bracket

Cable bracket, raised construction type, for Rd 8 mm, through-way Ø 5 mm



Type	Fit mm	height mm	Pack Piece	Weight kg/100 pc.	Item no.
177 35 VA M6 Rd 8 35			20	2.680	5207342

A2 Stainless steel, rustproof 1.4301


- With female thread M6 or through hole Ø 5 mm
- From stainless steel (V2A)

Cable bracket for Rd 8 mm, through-way Ø 5 mm

Type	Fit mm	height mm	Installation mm	Pack 20	Weight Piece kg/100 pc.	Item no.
177 20 VA M6 Rd 8 20				20	2.500	5207339

A2 Stainless steel, rustproof 1.4301

- With female thread M6 or through hole Ø 5 mm
- From stainless steel (V2A)



**Cable bracket for Rd 8 mm, through-way Ø 5 mm, copper-plated**

Type	Fit mm	height mm	Installation mm	Pack 20	Weight Piece kg/100 pc.	Item no.
177 20 VA-VK M6 Rd 8 20				20	2.500	5207800

A2 Stainless steel, rustproof 1.4301

Cu Copper-plated


- With female thread M6 or through hole Ø 5 mm
- From stainless steel (V2A)
- VA-VK: copper-plated

**Cable bracket for Rd 8 mm, through-way Ø 7 mm**

Type	Fit mm	height mm	Installation mm	Pack 20	Weight Piece kg/100 pc.	Item no.
177 20 VA M8 Rd 8 20				20	1.838	5207347

A2 Stainless steel, rustproof 1.4301

- With female thread M8 or through hole Ø 5 mm
- From stainless steel (V2A)


**Cable bracket for Rd 8 mm, through-way Ø 7 mm, copper-plated**

Type	Fit mm	height mm	Installation mm	Pack 20	Weight Piece kg/100 pc.	Item no.
177 20 VA-VK M8 Rd 8 20				20	1.900	5207819

A2 Stainless steel, rustproof 1.4301

Cu Copper-plated


- With female thread M8 or through hole Ø 5 mm
- From stainless steel (V2A)
- VA-VK: copper-plated

**Washer for cable bracket, type 177**

Type	Colour	Pack 20	Weight Piece kg/100 pc.	Item no.
177 U Light grey		20	0.286	5207371

PP Polypropylene

- For simple wall installation
- UV-resistant

**Hard foam plate anchor**

Type	Dowel Length mm	Ø mm	Wood screws Ø mm	Break load kN	Pack 50	Weight Piece kg/100 pc.	Item no.
177 WDVS 64x25 B	63.5	9	4 - 5	0.05	50	0.658	5207375


PA Polyamide

Anchor for universal light-duty fastening in plastered composite heat insulation systems (WDVS). The self-tapping point makes pre-drilling superfluous.



Conductor bracket

Cable bracket for Rd 8 mm, fastening with screw and anchor




Type	Fit mm	Installation height mm	Pack Piece	Weight kg/100 pc.	Item no.
177 20 VA B-HD Rd 8 20			50	2.900	5207901

A2 Stainless steel, rustproof 1.4301

- With female thread M8 or through hole Ø 5 mm
- From stainless steel (V2A)
- With pre-mounted wood screws (5 x 60) and plastic dowels (8 x 40).

Cable bracket Rd 8–10 mm




Type	Fit mm	Installation height mm	Pack Piece	Weight kg/100 pc.	Item no.
177 20 M8 Rd 8-10 20			20	0.723	5207444
177 30 M8 Rd 8-10 30			20	0.790	5207460
177 55 M8 Rd 8-10 55			20	1.007	5207487

PA Polyamide

- With female thread M8 or through hole Ø 7 mm
- Weather and temperature-resistant from -35 °C to +90 °C

Cable bracket Rd 8–10 mm, copper-plated




Type	Fit mm	Installation height mm	Pack Piece	Weight kg/100 pc.	Item no.
177 20 CU Rd 8-10 20			10	0.718	5207746
177 30 CU Rd 8-10 30			10	0.784	5207754
177 55 CU Rd 8-10 55			10	1.450	5207762

PA Polyamide

- With female thread M8 for screwing and through hole for wood screws
- Colour: copper
- Weather and temperature-resistant from -35 °C to +90 °C

Cable bracket Rd 8–10 mm with pre-mounted wood screw




Type	Fit mm	Installation height mm	Pack Piece	Weight kg/100 pc.	Item no.
177 B-HD20 Rd 8-10 20			50	1.930	5207851
177 B-HD30 Rd 8-10 30			50	1.503	5207878

PA Polyamide

- With female thread M8 for screwing and through hole for wood screws
- For round conductor Rd 8-10
- Weather and temperature-resistant from -35 °C to +90 °C
- With pre-mounted wood screws (5 x 60) and plastic dowels (8 x 40).

Bonding base




Type	Colour	Thread	Pack Piece	Weight kg/100 pc.	Item no.
194 Grey M8			100	0.389	5207258

PA Polyamide

- With threaded stem M8
- For mounting cable supports with M8 female thread
- For bonding to concrete, steel or brickwork
- When installing flat conductors and round cables, expansion elements are to be used for thermal compensation

Conductor bracket



Bonding base including industrial bonding pad

Type	Colour Thread	Pack	Weight	Item no.
		Piece	kg/100 pc.	
194 K	Grey M8	20	0.600	5207266

PA Polyamide


- With threaded stem M8
- For mounting cable supports with M8 female thread
- For bonding to concrete, steel or smooth substrates
- Not suitable for rough surfaces such as plaster, wood, bitumen strips
- Processing at > +15 °C and on cleaned substrate
- When installing flat conductors and round cables, expansion elements are to be used for thermal compensation
- Use on film roofs after consultation with the responsible roof construction company

Cable bracket, Rd 8–10 mm with bonding base

Type	Dimension H mm	Pack	Weight	Item no.
		Piece	kg/100 pc.	
177 20 KL	25	50	1.239	5207451

PA Polyamide

- For bonding to concrete, steel or smooth substrates
- Not suitable for rough surfaces such as plaster, wood, bitumen strips
- Processing at > +15 °C and on cleaned substrate
- When installing flat conductors and round cables, expansion elements are to be used for thermal compensation
- Use on film roofs after consultation with the responsible roof construction company




Cable bracket with crossbar Rd 8–10 mm

Type	Fit mm	Pack	Weight	Item no.
		Piece	kg/100 pc.	
113 Z8-10	Rd 8-10	20	5.956	5229960

Zn Die-cast zinc

G Electrogalvanised

- With female thread M8 or through hole Ø 7 mm
- Over-piece installed with 2 hexagonal bolts
- Version HD with wood screws (5 x 60) and plastic dowels (8 x 40)




Cable bracket Rd 8–10 mm

Type	Fit mm	Pack	Weight	Item no.
		Piece	kg/100 pc.	
113 8-10	Rd 8-10	20	9.600	5230217

Zn Die-cast zinc

Cu Copper-plated

- With female thread M8 or through hole Ø 7 mm
- Over-piece installed with 2 hexagonal bolts




Cable bracket Rd 8–10 mm with wood screw, plastic anchor

Type	Fit mm	Pack	Weight	Item no.
		Piece	kg/100 pc.	
113 B-Z-HD	Rd 8-10	100	6.580	5230322

Zn Die-cast zinc


VZ Galvanised

- With female thread M8 or through hole Ø 7 mm
- Over-piece installed with 2 hexagonal bolts
- Version HD with wood screws (5 x 60) and plastic dowels (8 x 40)



Conductor bracket

Cable bracket Rd 8–10 mm with wood screw, plastic anchor




Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
113 B-MS-HD 8-10 Rd 8-10		100	7.280	5230365

Zn Die-cast zinc

Cu Copper-plated

- With female thread M8 or through hole Ø 7 mm
- Over-piece installed with 2 hexagonal bolts
- Version HD with wood screws (5 x 60) and plastic dowels (8 x 40)

Cable bracket with hinged crossbar Rd 8–10 mm




Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
113 Z-K 8-10 Rd 8-10		20	6.202	5229961

Zn Die-cast zinc

G Electrogalvanised

- With female thread M8 or through hole Ø 7 mm
- Hinge crossbar for quick swivel mounting
- Crossbar mounted with 2 hexagonal bolts

Cable bracket Rd 8–10 mm, 30 mm mounting height




Type	Fit mm	Thread	Pack Piece	Weight kg/100 pc.	Item no.
168 8-10 M6 Rd 8-10 M6			20	7.800	5229162
168 DIN-K-M8 Rd 8-10 M8			20	7.780	5229839

Zn Die-cast zinc

G Electrogalvanised

- With female thread (G)
- With over-piece and 2 hexagonal bolts
- Installed height 30 mm

Cable bracket with hinged crossbar




Type	Fit mm	Thread	Pack Piece	Weight kg/100 pc.	Item no.
168 ZN-M6 Rd 8-10 M6			20	8.660	5229367
168 DIN-K-M8 Rd 8-10 M8			20	8.440	5229383

Zn Die-cast zinc

Cu Copper-plated

- With female thread (G)
- With over-piece and 2 hexagonal bolts
- Installed height 30 mm

Cable bracket for flat conductors



Type	Dimen- sion B mm	Fit mm	Thread	Pack Piece	Weight kg/100 pc.	Item no.
168 FL40-M8 66 FL 40 M8				20	8.200	5229553

TG Malleable iron

FT Hot-dip galvanised


- For flat strip
- With female thread (G)
- Installed height 30 mm

Type	Dimension B mm	Fit mm	Thread	Pack Piece	Weight kg/100 pc.	Item no.
168 FL30-M6	56	FL 30	M6	20	7.640	5229464
168 DIN 30	56	FL 30	M8	20	6.570	5229480

Zn Die-cast zinc

G Electrogalvanised VZ Galvanised

- For flat strip
- With female thread (G)
- Installed height 30 mm




Cable bracket Rd 8–10 mm, with square pin

Type	Fit mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
163 70 FT	Rd 8-10	70	50	8.476	5223075
163 100 FT	Rd 8-10	100	50	10.056	5223105
163 150 FT	Rd 8-10	150	50	14.400	5223156
163 200 FT	Rd 8-10	200	20	18.880	5223202

St Steel

FT Hot-dip galvanised

- Complete with crossbar and hexagonal bolts
- With square pin for rapid mounting
- With hexagonal bolts made of VA




Cable bracket Rd 8–10 mm, with square pin, copper-plated

Type	Fit mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
163 100 CU	Rd 8-10	100	10	10.840	5223601

Cu Copper

- Complete with crossbar and hexagonal bolts
- With square pin for rapid mounting
- With hexagonal bolts made of VA




Cable bracket for flat conductors, with round pin

Type	Fit mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
166 LS 70	FL30	70	50	9.140	5226570

St Steel

FT Hot-dip galvanised

- With crossbar and 2 hexagonal bolts (VA)
- With loose round pin Ø 9 mm




Cable bracket Rd 8–10 mm, with wood screw thread

Type	Fit mm	Dimension H mm	Pack Piece	Weight kg/100 pc.	Item no.
176 A 65	Rd 8-10	65	50	9.536	5227070
176 A 80	Rd 8-10	80	50	10.025	5227089
176 A 100	Rd 8-10	100	50	11.500	5227100
176 A 150	Rd 8-10	150	20	13.100	5227151

TG Malleable iron

F Hot galvanised


- Also for flat conductor to FL 30
- With wood screw thread
- Bottom section, hot-dip galvanised cast iron
- Over-piece and screws, hot dipped galvanised steel



Conductor bracket



Base plate




Thread
Type
199 DIN | M8

Pack Weight
Piece kg/100 pc. **Item no.**
10 | 14.200 | 5208017

St Steel
FS Strip galvanised

- With threaded pin M8
- Suitable for direct bonding
- Threaded pin brass and base plate hot-dip galvanised steel

Cable bracket, upper part for FL 30 mm




Fit
Type
156 FL | FL30

Pack Weight
Piece kg/100 pc. **Item no.**
50 | 2.460 | 5228328

St Steel
FT Hot-dip galvanised

- With slot for quick installation

Cable bracket, upper part for Rd 8–10 mm, steel




Fit
Type
156 K8-10 ST | Rd 8-10

Pack Weight
Piece kg/100 pc. **Item no.**
100 | 2.000 | 5228123

St Steel
FT Hot-dip galvanised

- For Rd 8–10 mm

Cable bracket, cover for Rd 8–10 mm, stainless steel




Fit
Type
156 K8-10 VA | Rd 8-10

Pack Weight
Piece kg/100 pc. **Item no.**
100 | 2.100 | 5228134

A2 Stainless steel, rustproof 1.4301

- For Rd 8–10 mm

Cable bracket, cover for Rd 8–10 mm, copper




Fit
Type
156 K8-10 CU | Rd 8-10

Pack Weight
Piece kg/100 pc. **Item no.**
100 | 2.260 | 5228131

Cu Copper

- For Rd 8–10 mm

Cable bracket, upper part for Rd 8–10 mm



Fit
Type
156 8-10 | Rd 8-10

Pack Weight
Piece kg/100 pc. **Item no.**
100 | 2.680 | 5228026

St Steel

FT Hot-dip galvanised

- With open slot for quick installation


Conductor bracket

Type	Fit mm	Dimen- sion A mm	Pack 100	Weight Piece kg/100 pc.	Item no.
249 8-10 ST-OT	Rd 8-10 40				5311503

St Steel

FT Hot-dip galvanised

- For round conductor fastening RD 8-10
- Suitable for M10 bolts




Quick connector, cover Rd 8–10 mm

Type	Dimen- sion A mm	Fit mm	Pack 100	Weight Piece kg/100 pc.	Item no.
249 8-10 ALU-OT	44	Rd 8-10			5311585

Alu Aluminium

- For round conductor fastening RD 8-10
- Suitable for M10 bolts




Quick connector, cover Rd 8–10 mm

Type	Fit mm	Dimen- sion A mm	Pack 100	Weight Piece kg/100 pc.	Item no.
249 8-10 VA-OT	Rd 8-10 40				5311554

A2 Stainless steel, rustproof 1.4301

- For round conductor Rd 8-10
- Suitable for M10 bolts




Quick connector, cover Rd 8–10 mm

Type	Fit mm	Dimen- sion A mm	Pack 100	Weight Piece kg/100 pc.	Item no.
249 8-10 CU-OT	Rd 8-10 40				5311530

Cu Copper

- For round conductor fastening RD 8-10
- Suitable for M10 bolts




Rod holder, 16 mm

Type	Fit mm	Pack 10	Weight Piece kg/100 pc.	Item no.
113 Z-16	Rd 16			5412609

Zn Die-cast zinc

VZ Galvanised

- For lightning and ground insertion rods Rd 16
- Installed with over-piece and hex-head screws M6 x 16
- With female thread M8 or through hole Ø 7 mm




Rod holder, 16 mm

Type	Fit mm	Pack 10	Weight Piece kg/100 pc.	Item no.
113 ZN-16	Rd 16			5412633

Zn Die-cast zinc


Cu Copper-plated

- For lightning and ground insertion rods Rd 16
- Installed with over-piece and hex-head screws M6 x 16
- With female thread M8 or through hole Ø 7 mm



Conductor bracket

Rod holder, 16 mm, with screw and anchor




Type	Fit	Pack	Weight
	mm	Piece	kg/100 pc.
113 B-Z-HD	Rd 16	100	6.000

Zn Die-cast zinc

VZ Galvanised

- For lightning and ground insertion rods Rd 16
- Installed with over-piece and hexagonal bolts M6 x 16 (VA)
- Female thread M8 for screwing and through hole for wood screws
- Pre-mounted with wood screw 5 x 60 and plastic dowels 8 x 40

Rod holder, 16 mm, with screw and anchor




Type	Fit	Pack	Weight
	mm	Piece	kg/100 pc.
113 B-HD-16	Rd 16	100	10.100

Zn Die-cast zinc

Cu Copper-plated

- For lightning and ground insertion rods Rd 16
- Installed with over-piece and hexagonal bolts M6 x 16 (VA)
- Female thread M8 for screwing and through hole for wood screws
- Pre-mounted with wood screw 5 x 60 and plastic dowels 8 x 40

Rod holder, 16 mm, with square pin




Type	Fit	Dimen-	Pack	Weight
	mm	sion H	Piece	kg/100 pc.
112 DIN-100	Rd 16	100	10	12.412

St Steel

F Hot galvanised

- For lightning and ground insertion rods
- Over-piece with 2 hexagonal bolts M6 x 16 (VA)
- With square pin

Crossbar, round conductors and air-termination rods 16 mm




Type	Fit	Pack	Weight
	mm	Piece	kg/100 pc.
156 16	Rd 16	50	3.230

St Steel

FT Hot-dip galvanised

- With open slot for quick installation

Quick connector, cover Rd 16 mm




Type	Fit	Pack	Weight
	mm	Piece	kg/100 pc.
249 VA-OT	16	100	5.700

A2 Stainless steel, rustproof 1.4301

- For round conductor fastening RD 16
- Suitable for M10 bolts

Rod holder, 20 mm



Type	Fit	Pack	Weight
	mm	Piece	kg/100 pc.
113 Z-20	Rd 20	20	8.200

Zn Die-cast zinc

VZ Galvanised

- Installed with over-piece and hex-head screws M6 x 16
- With female thread M8 or through hole Ø 7 mm


Vario quick connector

Type	Fit mm	Dimension A mm	Short-circuit current (50 Hz) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 ST	Rd 8-10	40	5.6	H/100	20	9.306	5311500
249 B ST	Rd 8-10	40	5.6	H/100	100	10.800	5311705

St Steel

FT Hot-dip galvanised


- For T, cross and parallel connectors
- Quick installation using hexagonal bolt M10 x 30, high-grade stainless steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

**Vario quick connector**

Type	Fit mm	Dimension A mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 ALU	Rd 8-10	44	H/100	30	6.600	5311519
249 B ALU	Rd 8-10	44	H/100	100	7.250	5311713

Alu Aluminium


- For T, cross and parallel connectors
- Quick installation using hexagonal bolt M10 x 30, high-grade stainless steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

**Vario quick connector**

Type	Fit mm	Dimension A mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 VA	Rd 8-10	40	H/100	10	10.700	5311551

A2 Stainless steel, rustproof 1.4301


- For T, cross and parallel connectors
- Quick installation using hexagonal bolt M10 x 30, high-grade stainless steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

**Vario quick connector 200 kA**


Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 V2A 200	Rd 8-10	H/200	10	12.374	5311595

A2 Stainless steel, rustproof 1.4301

- For T, intersection and parallel connections
- Quick mounting using an M10 x 30 bolt, made from rustproof stainless steel
- Meets the requirements of VDE 0185-305 (IEC 62305)
- Tested according to VDE 0185-561-1 (IEC/EN 62561-1) with 200 kA
- For use in lightning protection class I with the isCon® Premium conductor



Vario quick connector




Type	Fit mm	Lightning current carrying capacity kA	Short-circuit current (50 Hz) kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 V4A	Rd 8-10	H/100	1.4	10	9.500	5311404

A4 Stainless steel, rustproof 1.4571/1.4404

- For T, cross and parallel connectors
- Quick installation using hexagonal bolt M10 x 30, high-grade stainless steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Vario quick connector




Type	Fit mm	Dimen- sion A mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 CU	Rd 8-10	40	H/100	10	11.900	5311527

Cu Copper

- For T, cross and parallel connectors
- Quick installation using hexagonal bolt M10 x 30, high-grade stainless steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Variable bi-metal quick connector




Type	Fit mm	Lightning current carrying capacity kA	Dimen- sion A mm	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 ZV	Rd 8-10	H/100	44	10	14.220	5311535

Cu Copper

- Intermediate plate, copper/aluminium, top section copper and aluminium
- For T, cross and parallel connectors
- Quick installation using hexagonal bolt M10 x 30, high-grade stainless steel
- With spring washer according to DIN 137
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Variable earthing connector Rd 6-8 / 8-10 mm



Type	Fit mm	Dimen- sion A mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 6-10 ST	RD 6-8 / 8-10	40	H/100	20	13.100	5311410

St Steel

FT Hot-dip galvanised

- For T, intersection and parallel connections with adapter plates
- Quick mounting using an M10 x 30 bolt, made from rustproof stainless steel
- With sprung washer to DIN 137
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)




Variable earthing connector Rd 6-8 / 8-10 mm

Type	Fit mm	Dimen- sion A mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 6-10 CU	RD 6-8 / 8-10	40	H/100	10	14.540	5311417

Cu Copper

- For T, intersection and parallel connections with adapter plates
- Quick mounting using an M10 x 30 bolt, made from rustproof stainless steel
- With sprung washer to DIN 137
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)




Vario quick connector Rd 6-8 / Rd 6-8 mm

Type	Fit mm	Dimen- sion A mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 6-8 CU	RD 6-8 / 6-8	40	H/100	10	12.710	5311407

Cu Copper

- For T, intersection and parallel connections with adapter plates
- Quick mounting using an M10 x 30 bolt, made from rustproof stainless steel
- With sprung washer to DIN 137
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)




Vario quick connector Rd 8-10x16

Type	Fit mm	Dimen- sion A mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10X16 VA	8-10X16	40	H/100	10	16.300	5311590

A2 Stainless steel, rustproof 1.4301

- For T, intersection and parallel connections with adapter plates
- Quick mounting using an M10 x 30 bolt, made from rustproof stainless steel
- With sprung washer to DIN 137
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)




Connector, Rd 8-10 mm with M10 thread

Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
5000	Rd 8-10	20	4.630	5304008


St Steel

F Hot galvanised

- With bore hole 10.2 mm
- With thread M10
- Including pre-mounted nut M10 and serrated washer
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)



Connector Rd 8–10 mm, single



Lightning current
carrying capacity
kA


Type	Fit	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5001 DIN-FT	Rd 8–10	H/100	20	7.450	5304105
5001 DIN-FT+VA	N/50		20	7.450	5304107

St Steel

FT Hot-dip galvanised

- With fix contact clamping screw, nut and serrated washer
- With bore hole 10.2 mm
- With pre-mounted pressure piece, die-cast zinc
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Connector Rd 8–10 mm, single, copper



Fit
mm
Lightning current
carrying capacity
kA


Type	Fit	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5001 ZN-CU	Rd 8–10	H/100	10	8.760	5304113

Zn Die-cast zinc

Cu Copper-plated

- With fix contact clamping screw, nut and serrated washer
- With bore hole 10.2 mm
- With pre-mounted pressure piece, die-cast zinc
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Connector Rd 8–10 mm, double



Fit
mm
Lightning current
carrying capacity
kA


Type	Fit	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5002 DIN-FT	Rd 8–10	H/100	20	14.240	5304202

St Steel

FT Hot-dip galvanised

- With 2 fix contact clamping screws, nut and serrated washer
- Including pre-mounted connecting pressure piece, die-cast zinc or copper-plated die-cast zinc
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Connector, Rd 8–10 mm with pressure trough



Fit
mm
Lightning current
carrying capacity
kA

Type	Fit	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5001 N-FT	Rd 8–10	N/50	20	5.900	5304164

St Steel

FT Hot-dip galvanised

- With 1 fix contact clamping screw, nut and serrated washer
- Including pre-mounted pressure sump, steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)




Connector, Rd 8–10 mm with pressure trough

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5001 N-VA	Rd 8-10	N/50	10	6.800	5304176

A2 Stainless steel, rustproof 1.4301


- With 1 fix contact clamping screw, nut and serrated washer
- Including pre-mounted pressure sump, steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5001 N-CU	Rd 8-10	H/100	10	6.750	5304172

Cu Copper

- With 1 fix contact clamping screw, nut and serrated washer
- Including pre-mounted pressure sump, steel
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)




Connector, Rd 8–10 mm, double, with pressure trough

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5002 N-VA	Rd 8-10	N/50	10	16.200	5304270

A2 Stainless steel, rustproof 1.4301

- With 2 Fix-Kontakt clamping bolts, nuts and serrated washers
- With pre-mounted pressure trough made of VA
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)




Connection and end piece with connector

Type	Material	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5009	St	Rd 8-10	H/100	10	14.500	5304970

St Steel

F Hot galvanised

- With 2 attaching holes Ø 11 mm
- Installed with connector (single-piece) type 5001 DIN-FT
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)




Type	Dimension D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
5011	11	10	7.064	5304997


St Steel

FT Hot-dip galvanised

- For attaching to steel structures or bolting to fixed earthing terminals
- For attachments: Round conductor Rd 8-10 and flat conductor FL 30 x 3.5
- 2 attaching holes Ø 11 mm
- 1 attaching hole Ø D mm



Connection and end piece




Type	Dimension D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
5011 VA M10	11	10	7.064	5334934
5011 VA M12	13	10	7.048	5334942

A4 Stainless steel, rustproof 1.4571

- For attaching to steel structures or bolting to fixed earthing terminals
- For attachments: Round conductor Rd 8-10 and flat conductor FL 30 x 3.5
- 2 attaching holes Ø 11 mm
- 1 attaching holes Ø D mm

Connection and end piece, DIN version




Type	Fit mm	Material	Pack Piece	Weight kg/100 pc.	Item no.
5005 DIN-FT	Rd 8-10	St Steel	10	15.518	5304601

St Steel

F Hot galvanised

- With 2 attaching holes and 1 fix contact clamping screw 5000...
- With 2 attaching holes Ø 11 mm
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Connection and end piece with connector and pressure trough




Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
5005 N-FT	Rd 8-10	10	11.600	5304660

St Steel

FT Hot-dip galvanised

- With 2 attaching holes Ø 11 mm
- Including pre-mounted connector 5001 N
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Parallel connector Rd 8–10 mm, M8 x 25




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
259 8-10	Rd 8-10	N/50	25	13.230	5315506

TG Malleable iron

FT Hot-dip galvanised

- With 2 hex-head screws M8 x 25, hot-dip galvanised steel

Parallel connector Rd 8 mm, M10 x 30



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
260 8	Rd 8	H/100	50	13.930	5315700

Zn Die-cast zinc

G Electrogalvanised

- With flat, round screw M10 x 30 and hexagonal nut, hot-dip galvanised steel

Parallel connector Rd 6–10 mm, M6 x 20




Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
260 8-10 MS	Rd 6-10	50	15.820	5315654

CuZn Brass

Cu Copper-plated

- With 2 hexagonal bolts M6 x 20 made of stainless steel (V2A)



Straight connector Rd 8 mm




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
239	Rd 8 N/50		20	12.510	5329078

Zn Die-cast zinc

G Electrogalvanised

- With truss-head bolt M10 x 30 and hexagonal nut M10
- Complies with the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)



Straight connector Rd 8–10 mm




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
237 N FT	Rd 8-10 H/100		20	8.560	5328209

St Steel

F Hot galvanised

- With 4 hexagonal bolts M6 x 10
- Complies with the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)




Straight connector Rd 6–10 mm



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
237 N CU	Rd 6-10 H/100		10	8.760	5328284

Cu Copper

- With 4 hexagonal bolts M6 x 12
- Complies with the requirements of VDE 0185-305-3 (IEC/EN 62305-3)



T connector Rd 8 mm






Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
244	Rd 8 N/50		10	11.580	5311039

Zn Die-cast zinc

G Electrogalvanised

- With truss-head bolt M10 x 30 and hexagonal nut M10
- Complies with the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)





T connector Rd 8–10 mm

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
245 8-10 FT	Rd 8-10 N/50		10	9.401	5311101

St Steel

FT Hot-dip galvanised


- With 2 hexagonal bolts M6 x 16 (VA)
- Complies with the requirements of VDE 0185-305-3 (IEC/EN 62305-3)

T connector Rd 8–10 mm

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
245 8-10 CU	Rd 8-10 N/50		10	11.560	5311152

Cu Copper

- With 2 hexagonal bolts M6 x 16 (VA)
- Complies with the requirements of VDE 0185-305-3 (IEC/EN 62305-3)


T connector Rd 8–10 mm, triple-screwed

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
247 8-10 FT	Rd 8-10 N/50		10	10.934	5311209

St Steel

FT Hot-dip galvanised



- With 3 hexagonal bolts M6 x 16 (VA)

T connector Rd 8–10 mm, triple-screwed

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
247 8-10 CU	Rd 8-10 N/50		10	10.750	5311268

Cu Copper

- With 3 hexagonal bolts M6 x 16 (VA)
- Complies with the requirements of VDE 0185-305-3 (IEC/EN 62305-3)

Cross-connector for flat conductors and round conductors

Type	Fit mm	Short-circuit current (50 Hz) (1 s; ≤ 300 °C) kA	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
250	Rd 8-10/FL30 5.6		N/50	25	10.260	5312906

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10
- Fit: Rd 8-10 x FL 30
- Fit: FL 30 x FL 30
- Mounted with 2 hexagonal bolts M8 x 20 (F)


Cross-connector for flat conductors and round conductors



Type	Fit mm	Lightning current carrying capacity kA	Short-circuit current (50 Hz) (1 s;≤300 °C) kA	Pack Piece	Weight kg/100 pc.	Item no.
250 VA	Rd 8-10/FL30	H/100	1.4	25	10.260	5312922
250 V4A	Rd 8-10/FL30	H/100	1.4	10	10.260	5312925

A2 Stainless steel, rustproof 1.4301 A4 Stainless steel, rustproof 1.4571

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10
- Fit: Rd 8-10 x FL 30
- Fit: FL 30 x FL 30
- Mounted with 2 hexagonal bolts M8 x 20




Cross-connector for round and flat conductors



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10XFL30 FT	8-10 x FL30	H/100	25	28.500	5312655

St Steel
FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8




Cross-connector for round conductors and flat conductors



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10xFL30V4A	8-10 x FL30	H/100	10	28.500	5312656

A4 Stainless steel, rustproof 1.4571

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8




Cross-connector Rd 8-10 mm





Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
251 8-10	Rd 8-10	H/100	25	11.690	5312035

St Steel
FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- For round conductors, fit: Rd 8-10 x Rd 8-10
- With 4 hexagonal bolts M6 x 16 (VA)



Cross-connector Rd 8–10 mm

Type Fit Lightning current
mm kA carrying capacity


251 CU | Rd 8-10 | H/100

Pack Weight
Piece kg/100 pc. Item no.

10 | 12.400 | **5312132**

Cu Copper

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10
- With 4 hexagonal bolts M6 x 16, made of rust-proof steel (VA)

Cross-connector Rd 8–10

Type Fit Lightning current
mm kA carrying capacity

253 8X8 | Rd 8-10 | H/100



Pack Weight
Piece kg/100 pc. Item no.

25 | 30.700 | **5312604**

St Steel

Fl Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)

Cross-connector with intermediate plate for Rd 8–10 mm

Type Fit Lightning current
mm kA carrying capacity

254 DIN 8-10 FT | Rd 8-10 | H/100




Pack Weight
Piece kg/100 pc. Item no.

25 | 16.660 | **5314038**

St Steel

Fl Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- For round conductors, fit: Rd 8-10 x Rd 8-10
- With adapter plate
- Mounted with 4 hexagonal bolts M6 x 20 and 4 hexagonal nuts M6

Cross-connector with intermediate plate for Rd 8–10 mm

Type Fit Lightning current
mm kA carrying capacity

254 DIN 8-10 CU | Rd 8-10 | H/100

Pack Weight
Piece kg/100 pc. Item no.

10 | 17.410 | **5314135**

Cu Copper

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10
- With adapter plate
- Mounted with 4 hexagonal bolts M6 x 20 and 4 hexagonal nuts M6 (F)
made of rustproof steel (VA)




Cross-connector with intermediate plate for Rd 8–10

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10 FT	Rd 8-10	H/100	25	33.530	5312310

SI Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)




Cross-connector with intermediate plate for Rd 8–10



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10 V4A	Rd 8-10	H/100	10	33.530	5312318

A4 Stainless steel, rustproof 1.4571

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8



Cross-connector with intermediate plate for Rd 8–10 x Rd 16



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10x16 V4A	Rd 8-10 x 16	H/100	10	39.000	5312346

A4 Stainless steel, rustproof 1.4571

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 16 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8



Cross-connector with intermediate plate for Rd 8–10




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 8-10 CU	Rd 8-10	H/100	10	38.940	5312418

Cu Copper

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8



Cross-connector for Rd 8–10 x Rd 16


Type	Fit	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	kA	Piece	kg/100 pc.	
253 10X16	Rd 8-10 x 16	H/100	25	29.800	5312809

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 16 / FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)

Cross-connector with intermediate plate for Rd 8–10 x Rd 16


Type	Fit	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	kA	Piece	kg/100 pc.	
252 8-10X16 FT	Rd 8-10 x 16	H/100	25	38.800	5312345

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 16 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

Cross-connector with intermediate plate for Rd 8–10 x Rd 16





Type	Fit	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	kA	Piece	kg/100 pc.	
252 8-10X16 CU	Rd 8-10 x 16	H/100	10	43.985	5312442

Cu Copper

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 16 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

Folding and construction clamp

Type	Fit	Clamping range	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	mm	kA	Piece	kg/100 pc.	
RSF 249 8-10 VA	Rd 8-10	max. 10	N/50	50	14.200	5317502

A2 Stainless steel, rustproof 1.4301


- For round standing seam systems, fixed cable routing
- Manufacturer release by Kalzip
- Tested according to VDE 0185-561-1 (IEC/EN 62561-1)



Type	Fit mm	Clamping range mm	Pack Piece	Weight kg/100 pc.	Item no.
RSF 177 20 VA M8 8 8			50	13.400	5317512

A2 Stainless steel, rustproof 1.4301

- For round standing seam systems, loose cable routing
- Manufacturer release by Kalzip
- Tested according to VDE 0185-561-1 (IEC/EN 62561-1)



Folding and construction clamp, 10–20 mm




Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5004 DIN-FT 12	Rd 8-10	max. 12	N/50	10	18.730	5304407
5004 DIN-FT 20	Rd 8-10	10 - 20	N/50	10	30.600	5304504

TG Malleable iron

FT Hot-dip galvanised

- Flange thickness to 12 or 10–20 mm
- With pre-mounted Fix-Kontakt clamping screw 5000
- 2 hexagonal bolts M8 x 20, screws made of hot galvanised steel,
- Terminal block made of malleable iron, hot galvanised
- Mounting of the round conductors either vertical or transverse to structure
- Corresponds to the requirements of DIN VDE 0185-305-3



Construction clamp to 20 mm




Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
5010 20 FT	Rd 8-10	4 - 20	N/50	10	30.600	5304520

SI Steel

FT Hot-dip galvanised

- Mounting of the round conductor possible vertically or transverse to construction
- For fastening to constructions up to a flange thickness of 20 mm
- Fastening to constructions using a hexagonal bolt M10
- Meets the requirements of DIN VDE 0185-305 (IEC 62305)



Connection terminal to 14 mm





Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
272 8	Rd 8-10	max. 8	N/50	20	22.800	5318084
272 14	Rd 8-10	max. 14	N/50	20	25.230	5318149

TG Malleable iron

FT Hot-dip galvanised

- Flange thickness to 8 and/or 14 mm
- With 4 hexagonal bolts M8
- Conforms to the requirements according to DIN VDE V 0185-3, Section 4.5




Folding clamp up to 7 mm plate thickness

Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
269 8-10	Rd 8-10	max. 7	N/50	20	14.460	5317010

Zn Die-cast zinc

G Electrogalvanised

- Plate thickness to 7 mm
- For conductor arrangement transverse and parallel to plate with 4 hexagonal bolts M6 x 16
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)


Folding clamp up to 7 mm plate thickness

Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
269 MS	Rd 8-10	max. 7	H/100	10	14.480	5317053

Zn Die-cast zinc

Cu Copper-plated

- Plate thickness to 7 mm
- For conductor arrangement transverse and parallel to plate with 4 hexagonal bolts M6 x 16
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)


Folding clamp Rd 8-10 up to 10 mm plate thickness

Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
270 8-10 FT	Rd 8-10	max. 10	N/50	20	13.810	5317207

St Steel

FT Hot-dip galvanised


- Metal thickness to 10 mm
- For conductor routing transverse and in parallel to the plate
- Corresponds to the requirements to DIN V VDE V 0185-3 section 4.5

Folding clamp Rd 8-10 up to 10 mm plate thickness

Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
270 8-10 VA	Rd 8-10	max. 10	N/50	10	13.800	5317208

A2 Stainless steel, rustproof 1.4301

- Metal thickness to 10 mm
- For conductor routing transverse and in parallel to the plate
- Corresponds to the requirements to DIN V VDE V 0185-3 section 4.5

Folding clamp Rd 8-10 up to 10 mm plate thickness

Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
270 8-10 CU	Rd 8-10	max. 10	H/100	10	14.740	5317258

Cu Copper

- Metal thickness to 10 mm
- For conductor routing transverse and in parallel to the plate
- Corresponds to the requirements to DIN V VDE V 0185-3 section 4.5




Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
271 8-10	Rd 8-10	max. 5	N/50	20	14.060	5317401

SI Steel

FT Hot-dip galvanised

- Plate thickness to 5 mm
- For conductor routing transverse and longitudinal to plate
- With 4 hexagonal bolts M6 x 12
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)
- 271 Cu: with hexagonal bolts stainless steel (VA)




Folding clamp up to 5 mm plate thickness



Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
271 8-10 VA	Rd 8-10	max. 5	N/50	10	15.000	5317481

A2 Stainless steel, rustproof 1.4301

- Plate thickness to 5 mm
- For conductor routing transverse and longitudinal to plate
- With 4 hexagonal bolts M6 x 12
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)
- 271 Cu: with hexagonal bolts stainless steel (VA)




Folding clamp up to 5 mm plate thickness



Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
271 CU	Rd 8-10	max. 5	N/50	10	15.230	5317452

Cu Copper

- Plate thickness to 5 mm
- For conductor routing transverse and longitudinal to plate
- With 4 hexagonal bolts M6 x 12
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)
- 271 Cu: with hexagonal bolts stainless steel (VA)



Folding clamp up to 10 mm plate thickness





Type	Fit mm	Clamping range mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
273 8-10	Rd 8-10	max. 10	N/50	50	17.200	5317223

SI Steel

FT Hot-dip galvanised

- Plate thickness to 10 mm
- Conductor routing transverse and longitudinal to plate with 2 hexagonal bolts M8 x 10 and 2 hexagonal bolts M8 x 16 (F)




Folding clamp up to 10 mm plate thickness

Type	Fit	Clamping range	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	mm	kA	Piece	kg/100 pc.	
273 CU	Rd 8-10	max.10	N/50	10	18.500	5317274

Cu Copper

- Plate thickness to 10 mm
- Conductor routing transverse and longitudinal to plate with 2 hexagonal bolts M8 x 10 and 2 hexagonal bolts M8 x 16 (F)
- 273 Cu: with hexagonal bolts, stainless steel (VA)


Folding clamp and connection terminal up to 10 mm plate thickness

Type	Fit	Clamping range	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	mm	kA	Piece	kg/100 pc.	
274 8-10	Rd 8-10	max. 10	N/50	20	10.400	5317428

St Steel

FT Hot-dip galvanised


- Plate thickness to 10 mm
- For conductor routing transverse and longitudinal to plate
- 4 hexagonal bolts M6 x 16
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Folding clamp and connection terminal up to 10 mm plate thickness

Type	Fit	Clamping range	Lightning current carrying capacity	Pack	Weight	Item no.
	mm	mm	kA	Piece	kg/100 pc.	
274 CU	Rd 8-10	max. 10	N/50	10	11.340	5317479

Cu Copper

- Plate thickness to 10 mm
- For conductor routing transverse and longitudinal to plate
- 4 hexagonal bolts M6 x 16
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Gutter clamp RK-FIX

Type	Fit	Material	Surface	Pack	Weight	Item no.
	mm			Piece	kg/100 pc.	
RK-FIX	2 x Rd 8	St	FT	25	19.100	5316450

St Steel

FT Hot-dip galvanised


- For up to 2 conductors Rd 8
- With double crossbar
- Suitable for all bead thicknesses (15–25 mm)
- With 1 truss-head bolt M10 x 45
- Nut and bolt made of VA stainless steel
- With spring for prefixing for rain gutter



Type	Fit mm	Material	Pack Piece	Weight kg/100 pc.	Item no.
RK-FIX VA	2 x Rd 8 A2		10	19.100	5316459

A2 Stainless steel, rustproof 1.4301

- For up to 2 conductors Rd 8
- With double crossbar
- Suitable for all bead thicknesses (15–25 mm)
- With 1 truss-head bolt M10 x 45
- Nut and bolt made of VA stainless steel
- With spring for prefixing for rain gutter
- Tested to DIN EN 50164-1



Gutter clamp RK-FIX





Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
RK-FIX CU	2 x Rd 8 / 2 x Rd 6 H/100		10	21.000	5316468

A2 Stainless steel, rustproof 1.4301

Cu Copper-plated

- For up to 2 conductors Rd 6 or Rd 8
- With double crossbar
- Suitable for all bead thicknesses (15–25 mm)
- With 1 truss-head bolt M10 x 45
- Nut and bolt made of VA stainless steel
- With spring for prefixing for rain gutter
- Tested to VDE 0185-561-1 (IEC/EN 62561-1)



Gutter clamp for all bead thicknesses

Fit
Type mm**267** | Rd 8-10


Pack Piece | Weight kg/100 pc. Item no.

| 25 | 13.950 | **5316308**

St Steel

FT Hot-dip galvanised

- Fits all bead thicknesses
- With 1 hexagonal bolt M8 x 30
- 2 hexagonal bolts M6 x 12



Gutter clamp for all bead thicknesses


Fit
Type mm**267 VA** | Rd 8-10

Pack Piece | Weight kg/100 pc. Item no.

| 10 | 11.360 | **5316324**

A2 Stainless steel, rustproof 1.4301

- Fits all bead thicknesses
- With 1 hexagonal bolt M8 x 30
- 2 hexagonal bolts M6 x 12
- VA version also for use as bimetal conductor (holder)



Gutter clamp for bead thickness 15–22 mm

Fit
Type mm**262 A-DIN FT** | Rd 8-10


Pack Piece | Weight kg/100 pc. Item no.


| 25 | 19.610 | **5316219**

St Steel

FT Hot-dip galvanised

- Suitable for bulge thickness 15–22 mm
- With 4 hexagonal bolts M6 x 16 (VA)




Gutter clamp for bead thickness 15–22 mm

Type Fit
262 A-DIN CU mm | Rd 8-10

Cu Copper

- Suitable for bulge thickness 15–22 mm
- With 4 hexagonal bolts M6 x 16 (VA)

Pack Weight
Piece kg/100 pc. **Item no.**
10 | 20.840 | 5316251

Roof gutter clamp for all bead thicknesses


Type Fit
262 mm | Rd 8-10

St Steel

FT Hot-dip galvanised

- With 4 hexagonal bolts M6 x 16
- Fits all bead thicknesses

Pack Weight
Piece kg/100 pc. **Item no.**
25 | 20.300 | 5316014


Roof gutter clamp for all bead thicknesses

Type Fit
262 CU mm | Rd 8-10

Cu Copper

- With 4 hexagonal bolts M6 x 16
- Fits all bead thicknesses

Pack Weight
Piece kg/100 pc. **Item no.**
10 | 20.940 | 5316154

Bi-metal roof gutter clamp for all bead thicknesses


Type Fit
262 ZM mm | Rd 8-10

St Steel

FT Hot-dip galvanised

- Fits all bead thicknesses
- Bi-metal for attaching round conductors aluminium or steel to roof gutters without corrosion to different metals

Pack Weight
Piece kg/100 pc. **Item no.**
10 | 23.100 | 5316170

Snow catching grate clamp


Type Fit
264 mm | Rd 8-10

St Steel

F Hot galvanised

- Plate thickness to 8 mm
- With 4 hexagonal bolts M6 x 16

Pack Weight
Piece kg/100 pc. **Item no.**
25 | 18.640 | 5316510

Snow catching grate clamp

Type Fit
264 CU mm | Rd 8-10

Cu Copper

- Plate thickness to 8 mm
- With 4 hexagonal bolts M6 x 16

Pack Weight
Piece kg/100 pc. **Item no.**
10 | 21.140 | 5316553


Clamping shoe

Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
319 8	Rd 8	25	7.800	5325307
319 10	Rd 10	25	9.650	5325315

TG Malleable iron

F Hot galvanised

- With Ø 11 mm attaching hole
- 2 hexagonal bolts M8 x 16
- Bolts hot-dip galvanised steel and clamping element hot dipped galvanised cast steel


**Quick connector, cover Rd 8–10 mm**

Type	Fit mm	Dimen-sion A mm	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 ST-OT	Rd 8-10	40	100	3.240	5311503

St Steel

FT Hot-dip galvanised


- For round conductor fastening RD 8-10
- Suitable for M10 bolts

**Quick connector, cover Rd 8–10 mm**

Type	Dimen-sion A mm	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 ALU-OT	44	Rd 8-10	100	2.100	5311585

Alu Aluminium


- For round conductor fastening RD 8-10
- Suitable for M10 bolts

**Quick connector, cover Rd 8–10 mm**

Type	Fit mm	Dimen-sion A mm	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 VA-OT	Rd 8-10	40	100	3.130	5311554

A2 Stainless steel, rustproof 1.4301


- For round conductor Rd 8-10
- Suitable for M10 bolts

**Quick connector, cover Rd 8–10 mm**

Type	Fit mm	Dimen-sion A mm	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 CU-OT	Rd 8-10	40	100	3.580	5311530

Cu Copper


- For round conductor fastening RD 8-10
- Suitable for M10 bolts


**Quick connector, cover Rd 16 mm**

Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
249 VA-OT	16	100	5.700	5311573

A2 Stainless steel, rustproof 1.4301

- For round conductor fastening RD 16
- Suitable for M10 bolts



End piece


Type mm
280 8-10 | Rd 8-10

Zn Die-cast zinc

G Electrogalvanised

- With Ø 11 mm attaching hole
- 2 hexagonal bolts M6 x 12, bolts hot-dip galvanised steel or VA
- Clamping element from die-cast zinc or copper-plated die-cast zinc

Pack
Piece kg/100 pc.
Item no.
| 20 | 6.300 | 5320011


End piece

Type mm
280 VK | Rd 8-10

Zn Die-cast zinc

- With Ø 11 mm attaching hole
- 2 hexagonal bolts M6 x 12, bolts hot-dip galvanised steel or VA
- Clamping element from die-cast zinc or copper-plated die-cast zinc

Pack
Piece kg/100 pc.
Item no.
| 20 | 9.000 | 5320054

Universal clamping block Rd 8-10 mm


Type mm
324 S-FT | Rd 8-10

St Steel

FT Hot-dip galvanised

- Including hexagonal bolt M8 x 25, washer and nuts

Pack
Piece kg/100 pc.
Item no.
| 20 | 3.400 | 5326303


Universal clamping block Rd 8-10 mm

Type mm
324 S-VA | Rd 8-10

A2 Stainless steel, rustproof 1.4301

- Including hexagonal bolt M8 x 25, washer and nuts

Pack
Piece kg/100 pc.
Item no.
| 10 | 3.400 | 5326311


Universal clamping block Rd 8-10 mm

Type mm
324 S-CU | Rd 8-10

Cu Copper

- Including hexagonal bolt M8 x 25, washer and nuts

Pack
Piece kg/100 pc.
Item no.
| 10 | 3.660 | 5326338

Expansion piece

Type
172 AR

Alu Aluminium

- For equalising temperature-related length changes
- Necessary on conductor lengths over 20 m
- From round conductor Rd 8-Al

Pack
Piece kg/100 pc.
Item no.
| 10 | 7.500 | 5218926


Type**287**

Alu Aluminium

- With 1 attaching hole Ø 11 mm
- 4 mounting holes Ø 5.2 mm
- 2 mounting holes Ø 6.9 mm

Pack
Piece
kg/100 pc.

20 | 1.600 | 5320704


**Type****287 CU**

Cu Copper

- With 1 attaching hole Ø 11 mm
- 4 mounting holes Ø 5.2 mm
- 2 mounting holes Ø 6.9 mm

Pack
Piece
kg/100 pc.

10 | 5.600 | 5320690



BETTER TESTED

Lightning current
Fit carrying capacity
Type mm kA


287 DCT | 8 | N/50

Alu Aluminium

- Quick mounting thanks to an M10x30 bolt made of rustproof stainless steel
- With spring washer
- 4 fastening holes Ø 5.2 mm
- 2 fastening holes Ø 6.9 mm
- Corresponds to the requirements of VDE 0185-305 (IEC 62305)

Pack
Piece
kg/100 pc.

10 | 6.450 | 5320707



BETTER TESTED

Alu Aluminium

- With 1 attaching hole Ø 11 mm
- With 2 x 4 mounting hole Ø 5.2 mm
- With 2 x 2 mounting hole Ø 6.9 mm

Connection and bridging component


BETTER TESTED

Alu Aluminium

- With 1 attaching hole Ø 11 mm
- With 2 x 4 mounting hole Ø 5.2 mm
- With 2 x 2 mounting hole Ø 6.9 mm

Pack
Piece
kg/100 pc.

20 | 2.900 | 5320712



BETTER TESTED

Dimension L
Type mm


853 200 | 200
853 300 | 300
853 400 | 400


Cu Copper

- With aluminium cable lugs
- From flexible copper cable 16 mm²
- Coating: Black, chlorinated EM5 India rubber mixture
- With 1 fastening hole Ø 10.5 mm per attachment side
- With 2 fastening holes Ø 6.5 mm per attachment side
- Suitable for applications outside or inside
- Temperature range -25°C - +80°C (moved) and -40°C - +80°C (not moved)
- UV-stable

Pack
Piece
kg/100 pc.

10 | 4.840 | 5331008
10 | 7.260 | 5331013
10 | 9.680 | 5331017




Bridging cable

Type
853 400 SA

Pack
Piece | 1 | Item no.
5331025

Cu Copper

- With tin-plated copper cable lugs
- Made of flexible, insulated copper cable 16 mm²
- Coating: Black PVC
- With 1 mounting hole Ø 10.5 mm
- With 2 mounting holes Ø 6.5 mm
- Suitable for applications outside or inside
- Temperature range -10 °C - +80 °C


Connection and expansion strip

Type
856

Pack Weight
Piece kg/100 pc. | 10 | 8.125 | Item no.
5331501

Cu Copper

- Copper strip 35 mm², tin-plated
- Highly flexible with rigid ends
- Each end with 1 fastening hole Ø 10 mm and 4 fastening holes Ø 4.3 mm

Universal downspout clamp 60–130 mm

Type


301 V

Pack Weight
Piece kg/100 pc. | 5 | 11.900 | Item no.
5350867

St Steel

FS Strip galvanised

- Adjustable for pipes from 60-130 mm
- With 2x attaching holes Ø 7 mm
- With 1x attaching hole Ø 9 mm
- With 1x attaching hole Ø 11 mm
- Including hexagonal bolt M6 x 20 and nuts M6

Universal downspout clamp 60–130 mm


Type

301 V-VA

Pack Weight
Piece kg/100 pc. | 5 | 11.800 | Item no.
5350905

A2 Stainless steel, rustproof 1.4301

- Adjustable for pipes from 60-130 mm
- With 2x attaching holes Ø 7 mm
- With 1x attaching hole Ø 9 mm
- With 1x attaching hole Ø 11 mm
- Including hexagonal bolt M6 x 20 and nuts M6

Universal downspout clamp 60–130 mm

Type

301 V-CU

Pack Weight
Piece kg/100 pc. | 5 | 13.500 | Item no.
5350883


Cu Copper

- Adjustable for pipes from 60-130 mm
- With 2x attaching holes Ø 7 mm
- With 1x attaching hole Ø 9 mm
- With 1x attaching hole Ø 11 mm
- Including hexagonal bolt M6 x 20 and nuts M6

Type	For pipe mm	Pack Piece	Weight kg/100 pc.	Item no.
301 DIN-80	80	10	19.580	5350085
301 DIN-90	90	10	21.880	5350093
301 DIN-100	100	10	19.880	5350107
301 DIN-110	110	10	24.920	5350115
301 DIN-120	120	10	26.240	5350123

St SteelFS Strip galvanised

- To connect conductors and downspouts
- Similar to DIN 48818 C
- Strip galvanised (rd. 275 g/m² = 40 µm average value)
- With 1x hexagonal bolt M8 x 20
- With 1x hexagonal nut M8 and 1 stainless steel serrated washer
- With connection hole Ø 11 mm




Downspout clamp

Type	For pipe mm	Pack Piece	Weight kg/100 pc.	Item no.
301 CU-80	80	10	22.500	5350689
301 CU-100	100	10	26.230	5350700
301 CU-110	110	10	30.400	5350719
301 CU-120	120	10	31.400	5350727

Cu Copper

- With 1x hexagonal bolt M8 x 20
- With 1x hexagonal nut M8 and 1 serrated disc made of rustproof steel
- With connection hole Ø 11 mm




Downspout clamp for routing Rd 8–10 mm behind pipe

Type	For pipe mm	Pack Piece	Weight kg/100 pc.	Item no.
301 S-100	100	10	5.200	5351057
301 S-120	120	10	5.950	5351073

St SteelFS Strip galvanised

- With beading
- For round conductor Rd 8-10
- Including hexagonal bolt M6 x 20 and nuts M6



Downspout clamp for routing Rd 8–10 mm behind pipe

Type	For pipe mm	Pack Piece	Weight kg/100 pc.	Item no.
301 S-AL-100	100	10	4.100	5351359
301 S-AL-120	120	10	4.600	5351375

Alu Aluminium

- With beading
- For round conductor Rd 8-10
- Including hexagonal bolt M6 x 20 and nuts M6




Downspout clamp for routing Rd 8–10 mm behind pipe

Type	For pipe mm	Pack Piece	Weight kg/100 pc.	Item no.
301 S-VA-100	100	10	5.200	5351251
301 S-VA-120	120	10	5.950	5351286

A2 Stainless steel, rustproof 1.4301

- With beading
- For round conductor Rd 8-10
- Including hexagonal bolt M6 x 20 and nuts M6



Downspout clamp for routing Rd 8–10 mm behind pipe




Type	For pipe mm	Pack Piece	Weight kg/100 pc.	Item no.
301 S-CU-100	100	10	5.850	5351456
301 S-CU-120	120	10	6.700	5351472

Cu Copper

- With beading
- For round conductor Rd 8-10
- Including hexagonal bolt M6 x 20 and nuts M6

Pipe clamp



Type	For pipe mm	For pipe inch	Pack Piece	Weight kg/100 pc.	Item no.
303 DIN-3/8	17.2	3/8	5	22.600	5102057
303 DIN-1/2	21.3	1/2	5	23.280	5102073
303 DIN-3/4	26.9	3/4	5	25.640	5102081
303 DIN-1	33.7	1	5	28.300	5102111
303 DIN-1 1/4	42.4	1 1/4	5	31.300	5102138
303 DIN-1 1/2	48.3	1 1/2	5	33.220	5102154
303 DIN-2	60.3	2	5	36.840	5102197
303 DIN-2 1/2	76.1	2 1/2	10	39.400	5102219
303 DIN-3	88.9	3	10	43.300	5102235
303 DIN-3 1/2	100	3 1/2	10	64.900	5102251
303 DIN-4	114.3	4	10	66.800	5102278

St Steel

FT Hot-dip galvanised

- DIN 48818, Form D
- With Ø 11 mm mounting hole
- 2 hexagonal bolts M8 x 20 (4 inch = M10)
- 2 hex-head nuts M8 (4 inch = M10)

Connection material

Cross-connector flat/flat without adapter plate A4



Type	Fit mm	Dimen- sion A mm	Dimen- sion B mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
256 S6 V4A	max. FL30	60	60	H/100	3600	24.100	5314574

A4 Stainless steel, rustproof 1.4401

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Max. FL 30 x FL 30
- Without adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

Cross-connector flat/flat without adapter plate FT




Type	Fit mm	Dimen- sion A mm	Dimen- sion B mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
256 S6 FT	max. FL30	—	—	H/100	3600	24.100	5314572

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Max. FL 30 x FL 30 or max. FL 40 x FL 40
- Without adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)


Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
250 VA-FR	Rd 8-10/FL30	H/100	25	8.700	5312930
A4 Stainless steel, rustproof 1.4571					



Cross-connector 250 VA

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
253 S3 V4A	Rd 8-10	H/100	3400	25.900	5312594
A4 Stainless steel, rustproof 1.4401					

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)




Cross-connector round/round without intermediate plate

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
253 S3 FT	Rd 8-10	H/100	3400	23.300	5312592

St Steel
FT Hot-dip galvanised


- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)



Cross-connector Rd 8-10

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 S4 V4A	8-10 x FL30	H/100	3600	25.000	5312308
A4 Stainless steel, rustproof 1.4401					

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8




Cross-connector for round cables and flat conductors

Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 S4 FT	8-10 x FL30	H/100	3600	25.000	5312302


St Steel
FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8



Cross-connector for round cables and flat conductors DIN

Cross-connector with intermediate plate for Rd 8–10 mm, wide version





Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 S1 V4A	Rd 8-10 H/100		2800	28.800	5312294

A4 Stainless steel, rustproof 1.4401

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

Cross-connector with intermediate plate for Rd 8–10 mm, wide version




Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
252 S1 FT	Rd 8-10 H/100		2800	28.600	5312292

St Steel

FT Hot-dip galvanised

- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 8-10 / FL 30
- With adapter plate
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)

Roof conductor holder for flat roofs, black




Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
165 MBG-8-10	Rd 8-10	12	97.220	5218700
165 MBG-8-10 FO	Rd 8-10	12	100.000	5218704

PA/PE Polyamide/polyethylene

- Closed form with base
- With double conductor holder
- Filling weight 1 kg (frost-resistant concrete)
- Sleeve made of polyethylene, black, bottom polypropylene, black
- Base made of polyamide PA 6, black, UV-stabilised and weather-resistant
- Base can be used on almost all roofing felt systems (bitumen, PVC)
- Types 165 MBG...FO: Packed in foil bag

Earth mats






Type	Length mm	Width mm	Height mm	Pack Piece	Weight kg/100 pc.	Item no.
1816 CU 6	600	600	3	1	403.000	5009250
1816 CU 9	900	900	3	1	605.000	5009256

Cu Copper

- To reduce the step and contact voltage
- In accordance with IEC 62561-2 and IEC 62305-3

Connection terminal for round conductors



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
1818 FL CU	FL 20 ÷ FL 26 —		10	10.000	5012270

Cu Copper

- For connecting round conductor Rd 8-10
- With 1 hexagonal bolt M12 x 40, 1 hexagonal nut M12 and 1 lock washer, stainless steel


Earthing rail for UF separation point

Type

5700 PIP EB**5700 CIP EB****Cu** Copper

- For UF test box 5700 CIP/PIP
- With 5 connection holes
- Diameter of drill hole 11 mm

Pack	Weight	Item no.
Piece	kg/100 pc.	
1	38.000	5106050
1	46.000	5106071



Connection and separating terminals

Separating piece, open




Type	Fit	
	mm	
223 O DIN ZN	Rd 8-10/16	

Zn Die-cast zinc**G** Electrogalvanised

- With 2 hexagonal bolts, stainless steel (VA)
- Clamping element, die-cast zinc

Pack	Weight	Item no.
Piece	kg/100 pc.	
20	12.500	5335140




Type	Fit	
	mm	
223 O DIN MS	Rd 8-10/16	

Zn Die-cast zinc**Cu** Copper-plated

- With 2 hexagonal bolts, stainless steel (VA)
- Clamping element, copper-plated die-cast zinc

Pack	Weight	Item no.
Piece	kg/100 pc.	
20	14.900	5335167




Type	Fit	
	mm	
223 DIN ZN	Rd 8-10/16	

Zn Die-cast zinc**G** Electrogalvanised

- For fitting round conductors Rd 8-10 to ground insertion rods Rd 16
- Including 2 hexagonal bolts, high-grade stainless steel (V2A)
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Pack	Weight	Item no.
Piece	kg/100 pc.	
20	12.406	5335205




Type	Fit	
	mm	
223 DIN MS	Rd 8-10/16	


Zn Die-cast zinc**Cu** Copper-plated

- For fitting round conductors Rd 8-10 to ground insertion rods Rd 16
- Including 2 hexagonal bolts, high-grade stainless steel (V2A)
- Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

Pack	Weight	Item no.
Piece	kg/100 pc.	
10	11.700	5335256



Universal separating piece



Type Fit
226 8-10 | Rd 8-10/FL30 x 16 mm


Pack Weight
Piece kg/100 pc. Item no.
20 8.600 5336007

St Steel

FT Hot-dip galvanised

- For fitting round conductors Rd 8–10 to Rd 16 or flat conductors FL30
- Including 2 hexagonal bolts M8 x 20 high-grade stainless steel (V2A)
- Conforms to the requirements according to VDE 0185-305 (IEC 62305)

Universal separating piece




Type Fit
226 VA | Rd 8-10/FL30 x 16 mm

Pack Weight
Piece kg/100 pc. Item no.
10 8.700 5336058

A2 Stainless steel, rustproof 1.4301

- For fitting round conductors Rd 8–10 to Rd 16 or flat conductors FL30
- Including 2 hexagonal bolts M8 x 20 high-grade stainless steel (V2A)
- Conforms to the requirements according to VDE 0185-305 (IEC 62305)

Universal separating piece




Type Fit
226 CU | Rd 8-10/FL30 x 16 mm

Pack Weight
Piece kg/100 pc. Item no.
10 9.700 5336023

Cu Copper

- For fitting round conductors Rd 8–10 to Rd 16 or flat conductors FL30
- Including 2 hexagonal bolts M8 x 20 high-grade stainless steel (V2A)
- Conforms to the requirements according to VDE 0185-305 (IEC 62305)

Universal bi-metal separating piece



Type Fit
226 ZV VA | Rd 8-10/FL30 x 16 mm


Material
upper part
lower part

Pack Weight
Piece kg/100 pc. Item no.
10 11.000 5336074

Cu Copper

- Fit: Rd 8-10 x 16, FL 30 x Rd 16
- With 2 hexagonal bolts M8 x 20, stainless steel (VA)
- Intermediate plate, aluminium/copper

Universal bi-metal separating piece



Type Fit
226 ZV CU | Rd 8-10/FL30 x 16 mm

Material
upper part
lower part

Pack Weight
Piece kg/100 pc. Item no.
10 11.900 5336090

A2 Stainless steel, rustproof 1.4301


- Fit: Rd 8-10 x 16, FL 30 x Rd 16
- With 2 hexagonal bolts M8 x 20, stainless steel (VA)
- Intermediate plate, aluminium/copper

Separating piece for Rd 8–10 and FL 30 mm

Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
233 8	Rd 8-10/FL30 x Rd 8-10/FL30	20	8.200	5336309

St Steel**FT** Hot-dip galvanised


- To fit round conductors Rd 8-10 or flat conductors FL 30
- With 2 hexagonal bolts M8 x 20 made of rustproof steel (VA)
- Short-circuit current Ik (50 Hz), time 0.6 s, temp. max. 300 °C: 8.5 kA

**Separating piece for Rd 8–10 and FL 30 mm**

Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
233 VA	Rd 8-10/FL30 x Rd 8-10/FL30	10	8.300	5336341

A2 Stainless steel, rustproof 1.4301


- For fitting round conductors Rd 8-10 or flat conductors FL 30
- With 2 hexagonal bolts M8 x 20, stainless steel (VA)

**Bi-metal separating piece for Rd 8–10 and FL 30 mm**

Type	Fit mm	Material upper part	Material lower part	Pack Piece	Weight kg/100 pc.	Item no.
233 ZV	Rd 8-10/FL30 x Rd 8-10/FL30	Cu	VA	10	10.100	5336376

A2 Stainless steel, rustproof 1.4301


- For fitting round conductors Rd 8-10 to flat conductors FL 30
- With 2 hexagonal bolts M8 x 20, stainless steel (VA)
- Intermediate plate aluminium/copper, top section copper, bottom section stainless steel

**Separating piece for Rd 8–10 and FL 30–40 mm**

Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
233 A VA	8-10xFL30-40	10	7.851	5336457

A2 Stainless steel, rustproof 1.4301


- Fit: Rd 8-10 x FL 30-40
- With 2 hexagonal bolts M8 x 20 (VA)

**Bi-metal separating piece for Rd 8–10 and FL 30–40 mm**

Type	Fit mm	Material upper part	Material lower part	Pack Piece	Weight kg/100 pc.	Item no.
233 A ZV	Rd 8-10 x FL30-40	Cu	VA	10	10.400	5336503

Cu Copper


- Fit: Rd 8-10 x FL 30-40, FL 30 x FL 30-40
- With 2 hexagonal bolts M8 x 20, stainless steel (VA)
- Intermediate plate, aluminium/copper
- Top section copper, bottom section stainless steel



Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
108 B DIN	Rd 8-10/16	10	13.970	5416566


St Steel**FT** Hot-dip galvanised

- Rod clamp for connecting round conductors Rd 8–10 to connector rods Rd 16
- Mounted with 2 hexagonal bolts M8 x 16 and M6 x 12
- Adapter from malleable iron
- Crossbar and bolts from hot dip galvanized steel

**Rod clamp**

Connection and separating terminals

Connection clamp for earth rod or cables




Type	For earth rods Ø mm	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
2745 20 MS	20	7-12,5/S95 mm ²	5	16.000	5001560

CuZn Brass

Cu Copper-plated

- For earth rods Ø 20 or conductors of 95 mm²
- For round conductor attachments Rd 7-12.5 with hexagonal bolts M10 x 25


Number plates



Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
311 N-ALU 8-10	RD 8 - 10 / FL30	5	2.500	3049256
311 N-ALU 16	RD 16 - FL30	5	2.800	3049345

- To identify the point of separation to DIN 48821
- Suitable for universal labelling (e.g. stamped numbers)


Number plates



Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
311 N-VA 8-10	RD 8 - 10 / FL30	5	5.600	3049221
311 N-VA 16	RD 16 - FL30	5	6.400	3049329

- To identify the point of separation to DIN 48821
- Suitable for universal labelling (e.g. stamped numbers)

Number plates



Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
311 N-CU 8-10	RD 8 - 10 / FL30	5	6.400	3049205

Cu Copper

- To identify the point of separation to DIN 48821
- Suitable for universal labelling (e.g. stamped numbers)

Earth entries

Air-termination/earth entry rod, rounded-off on both ends




Type	Nominal Length size Ø mm mm	Pack Piece	Weight kg/100 pc.	Item no.
101 A-1500	1500 16	10	240.000	5400155

St Steel

FT Hot-dip galvanised

- Full material Ø 16 mm
- Rounded on both ends
- Suitable for FangFix stand system

Air-termination/earth entry rod, rounded-off on both ends



Type	Nominal Length size Ø mm mm	Pack Piece	Weight kg/100 pc.	Item no.
200 V4A-1500	1500 16	10	242.000	5420504
200 V4A-2000	2000 16	10	320.000	5420539


A4 Stainless steel, rustproof 1.4571

- Full material Ø 16 mm
- Both ends rounded

Air-termination/earth entry rod, rounded-off on both ends

Type	Nominal Length mm	size Ø mm	Pack 10	Weight Piece kg/100 pc.	Item no.
101 A-CU	1500	16		272.100	5400627


Cu Copper
 • Full material Ø 16 mm
 • Both ends rounded



Air-termination/earth entry rod with connection tabs

Type	Nominal Length mm	size Ø mm	Pack 10	Weight Piece kg/100 pc.	Item no.
101 F1500	1500	16		240.000	5424151
101 F2000	2000	16		320.000	5424208


St Steel
FT Hot-dip galvanised
 • With 2 attaching holes Ø 12 mm
 • One end rounded



Connection lug/earth entry rod made of stainless steel

Type	Nominal size Ø mm	Cross- section mm ²	Dimen- sion L mm	Pack 5	Weight Piece kg/100 pc.	Item no.
AF RD 10 V4A	10	75	2000		123.600	5430720

A4 Stainless steel, rustproof 1.4571/1.4404
 • According to DIN EN 62561-2 (VDE 0185-561-2)
 • Corresponds to the requirements of VDE 0185-305 (IEC 62305)
 • RD 10-V4A for applications in the earth
 • According to the foundation earther standard DIN 18014, V4A is required in the earth



Earth entry rod, tapered and partially insulated

Type	Nominal Length mm	size Ø mm	Pack 1	Weight Piece kg/100 pc.	Item no.
204 KS-2000	2000	16/10		230.000	5430011
204 KS-2500	2500	16/10		310.000	5430062


St Steel
F Hot galvanised
 • 16 mm earth entry with 10 mm connection
 • With mounted heat-shrinkable sleeve (corrosion protection)




Earth entry rod with separating piece and connector

Type	Fit mm	Pack 10	Weight Piece kg/100 pc.	Item no.
204 KL-1500	Rd 8-10		260.700	5430151

St Steel
FT Hot-dip galvanised
 • With separating piece type 223 DIN and connector type 5002 DIN




Underfloor test box

Type
5700

EN-GJL Cast iron

- Without base
- Cast iron, painted black
- Without cut-off unit
- To VDE 0185-561-5 (IEC 62561-5) suitable for heavy loads (up to 40 kN/ 4.0 t)

Pack
Piece | Weight
kg/100 pc. | **Item no.**
1 | 720.000 | **5106002**


Underfloor test box

Type
5700 CIP

BET Concrete

- Made of concrete
- Without separating piece
- According to VDE 0185-561-5 (IEC 62561-5)

Pack
Piece | Weight
kg/100 pc. | **Item no.**
1 | 3.000.000 | **5106041**


Underfloor test box

Type
5700 PIP

Plastic

- Made of plastic
- Without separating piece
- According to VDE 0185-561-5 (IEC 62561-5)

Pack
Piece | Weight
kg/100 pc. | **Item no.**
1 | 180.000 | **5106045**


Inspection pit with integrated separation piece

Type
5700 SP

EN-GJL Cast iron

- Without base
- Cast iron, painted black
- With built-in cut-off unit for round conductors Rd 8-10 and flat conductors to FL 40
- To VDE 0185-561-5 (IEC 62561-5) suitable for heavy loads (up to 40 kN/ 4.0 t)

Pack
Piece | Weight
kg/100 pc. | **Item no.**
1 | 770.000 | **5106003**

Inspection door


Type
5800 VZ

St Steel

FS Strip galvanised

- Lightweight design for flush-mounted separation points
- Claw length approx. 80 mm

Pack
Piece | Weight
kg/100 pc. | **Item no.**
1 | 46.000 | **5106133**

Inspection door

Type
5800 VA

A2 Stainless steel, rustproof 1.4301

- Lightweight design for flush-mounted separation points
- Claw length approx. 80 mm

Pack
Piece | Weight
kg/100 pc. | **Item no.**
1 | 46.000 | **5106141**

Magnetic card PCS



Type
PCS

Pack PU	Weight kg/100 PUs	Item no.
1	5.000	5091438

Peak Current Sensor (PCS) card for recording pulsed/lightning currents. A continuous check of whether lightning has struck the lightning protection system and how high the most recent lightning current was in kA can thus be carried out in the simplest manner by the system operator, specialist lightning protection company or by a surveyor. Here, the printed maintenance circuit and the labelling panels support the maintenance work of the entire lightning protection system which must be performed at defined intervals according to VDE 0185-305-3 (IEC/EN 62305-3).



- Contents = 10 units
- Digital evaluation via the PCS card reading device
- Can be used in addition to the OBO lightning current meter LSC I+II
- With separate labelling panels: "Erected by", "Tested by", "Card code"
- Integrated maintenance circuit (year/month)


Magnetic card and holder MK-B



Type
MK-B

Pack PU	Weight kg/100 PUs	Item no.
1	31.000	5091322

PCS magnetic card to record pulse/lightning currents including holder




- Holder can be leaded
- For mounting on round conductor Rd 8-10
- Simple holder mounting through clamping
- 1 PU = 10 units

Magnetic card holder PCS-H

Type
PCS-H

Pack PU	Weight kg/100 PUs	Item no.
1	31.000	5091527

Magnetic card holder for mounting PCS cards.



- Sealable holder
- For installing on round conductor Rd 8-10
- Simple holder installation by means of clamp
- 1 PU = 10 pieces

Card reader PCS-CS..




Nom.
Type Country version voltage V Measuring range Measuring tolerances Pack Piece Weight kg/100 pc. Item no.

PCS-CS-D	EN	230	3 - 120 kA	< 2 kA (< 2%)	1	750.000	5091683
-----------------	----	-----	------------	---------------	---	---------	----------------


PCS-CS-GB	GB	230	3 - 120 kA	< 2 kA (< 2%)	1	750.000	5091691
------------------	----	-----	------------	---------------	---	---------	----------------

Magnetic card reader for reading and analysing PCS cards.



- Inc. rechargeable battery for 4 h continuous, no-mains operation
- Large, clear display

Lightning strike counter


CE IP 65

Type Measuring range
LSC I+II | 1 kA - 100 kA

Plastic

Pack	Weight	
Piece	kg/100 pc.	Item no.
1	32.500	5091722

The LSC I+II lightning current meter measures and permanently saves pulse currents, together with the date and time. This ensures constant monitoring in order to notice if any lightning has struck the lightning protection system. Should this be the case, then the lightning protection system must be maintained according to VDE 0185-305 (IEC 62305).

- Saving and display of time and date
- Usable both inside and outside due to its protection class of IP65
- Cable clip for round conductor or flat conductor
- Direct mounting on the conductor or the PE conductor of the surge protection device
- Long lifespan of the internal lithium batteries
- LCD display
- Internal battery
- Tested according to VDE 0185-561-6 (IEC 62561-6)

Corrosion protection strip



Width mm Length m


356 50	50	10
356 100	100	10

PETRO Petrolatum

Pack	Weight	
Piece	kg/100 pc.	Item no.
1	71.500	2360055
1	122.200	2360101

- Approx. 1.1 mm thick
- Width: 50 mm or 100 mm, made of petrolatum-coated chemical fibre fabric
- Can be processed cold

Zinc repairs

**CE**

Dimension


Type	ZSF
------	-----

| 400ml

Pack	Weight	
Piece	kg/100 pc.	Item no.
1	45.000	2362970

Zinc spray for treatment of unprotected surfaces and cutting edges. Can contents: 400 ml.

Screw-in anchor with M6 thread

**CE**

Type	Wood Shank external Ø	Shipping box Ø	
	mm	mm	Piece
985 M6 25	4.3	5	3000
985 M6 35	4.3	5	2000

Pack	Weight	
Piece	kg/100 pc.	Item no.
100	0.412	3133028
100	0.533	3133036

St Steel

G Electrogalvanised

With wood screw shank and M6 thread.

Screw-in anchor with M8 thread

CE


Wood
external Shipping
thread Ø box
mm Piece

Type 985 M8 35 | 6 | 1200 | Pack 100 | Weight 0.950 | Item no. 3133230

St Steel

G Electrogalvanised

With wood screw shank and M8 thread.



Directional irons


Length
Type mm

364 | 297 | Pack 1 | Weight 35.000 | Item no. 3051013

St Steel

FT Hot-dip galvanised

- Directional iron for bending and aligning conductors




Wire straightening machine

Type
5900

St Steel

- Factory-set for round conductor Rd 8
- Structure, steel, painted
- Straightening rolls, galvanised cast iron

Pack 1 | Weight 3,300.000 | Item no. 3059006



Insulated lightning protection



Insulated lightning protection

476




OBO isCon® system

482



Insulated lightning protection set, 3-corner fastening




Type	Dimen- sion D Ø mm	Dimen- sion L mm	Dimen- sion H mm	Pack Piece	Weight kg/100 pc.	Item no.
101 3-ES-16	16	750	1500	1	207.100	5408976

3-corner fastening for an insulated air-termination unit at the separating distance s.

- Mounting on walls and roof structures with two fastening plates
- For maintenance of the separation distance to electrically conductive parts according to VDE 0185-305-3 (IEC 62305-3)
- Acceptance of air-termination rods and round conductors with 8, 16 and 20 mm diameter
- UV-stabilised and weatherproof
- Continuous temperature range -50°C to +100°C
- Material factor km = 0.7

Insulated lightning protection set, V fastening




Type	Dimen- sion D Ø mm	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
101 VS-16	16	750	1	201.800	5408978

V fastening for an insulated air-termination unit at the separating distance s.

- Mounting on walls and roof structures with two wall connection brackets
- For maintenance of the separation distance to electrically conductive parts according to VDE 0185-305-3 (IEC 62305-3)
- Acceptance of air-termination rods and round conductors with 8, 16 and 20 mm diameter
- UV-stabilised and weatherproof
- Continuous temperature range -50°C to +100°C
- Material factor km = 0.7

Insulated lightning protection set, IR fastening




Type	Dimen- sion D Ø mm	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
101 FS-16	16	750	1	235.500	5408980

Fold fastening for an insulated air-termination unit at the separating distance s.

- Mounting on folds with a thickness of up to 20 mm
- For maintenance of the separation distance to electrically conductive parts according to VDE 0185-305-3 (IEC 62305-3)
- Acceptance of air-termination rods and round conductors with 8, 16 and 20 mm diameter
- UV-stabilised and weatherproof
- Continuous temperature range -50°C to +100°C
- Material factor km = 0.7

Insulated lightning protection set, VRS fastening



Type	Dimen- sion D Ø mm	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
101 VRS-16	16	750	1	209.400	5408982

Pipe V fastening for an insulated air-termination unit at the separating distance s.



- Mounting on pipes with two pipe clips
- Including 2 m tightening strip and tension jack
- For maintenance of the separation distance to electrically conductive parts according to VDE 0185-305-3 (IEC 62305-3)
- Acceptance of air-termination rods and round conductors with 8, 16 and 20 mm diameter
- UV-stabilised and weatherproof
- Continuous temperature range -50°C to +100°C
- Material factor km = 0.7

Insulating rod

Type	Nominal size Ø mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
101 20-3000	20	3000	5	190.000	5408105
101 20-6000	20	6000	5	380.000	5408148
101 16-750	16	750	5	30.000	5408107
101 16-1500	16	1500	5	60.000	5408108
101 16-3000	16	3000	5	120.000	5408109

GFK Fibre-glass-reinforced plastic

- For the erection of insulated air-termination systems to VDE 0185-305 (IEC 62305)
- UV-stabilised and weatherproof
- Continuous temperature range -50°C to +100°C
- Material factor km = 0.7




T connector

Type	Dimension d Ø mm	Length mm	Dimension D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 IT	20	65	40	10	16.120	5408156
101 IT-16	16	60	30	10	11.475	5408158

Alu Aluminium

- T connector for installation of insulating rods
- With M10 bolts




K connector

Type	Dimension d Ø mm	Length mm	Dimension D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 IK	20	100	40	10	20.000	5408296
101 IK-16	16	100	30	10	17.500	5408298

Alu Aluminium

- K connector for installation of insulating rods
- With M10 bolts




DK connector

Type	Dimension d Ø mm	Length mm	Dimension D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 IDK	20	125	40	10	40.000	5408245

Alu Aluminium

- DK connector link for installing insulating rods
- With M10 bolts





Wall connection

Type	Dimension d Ø mm	Length mm	Dimension D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 IW-M10	20	60	40	10	20.000	5408687
101 W-16	16	60	30	10	14.200	5408689

Alu Aluminium

- For mounting insulating rods to structures or walls
- With M8 internal thread, e.g. for mounting the cable bracket type 177 (5207347) for loose conductor routing of round conductors
- Incl. M10 bolts




End piece

Type	Dimen- sion d Ø mm	Length mm	Dimen- sion D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 IES	20	60	35	10	20.000	5408393
101 IES-16	16	60	30	10	10.000	5408395

Alu Aluminium


- End piece for attaching round conductors Rd 8-10 and air-termination tips, type 101 ISP
- With M10 internal thread, e.g. for mounting a Vario quick connector for fixed conductor routing at intersections
- With M10 bolts

Connection piece

Type	Dimen- sion d Ø mm	Length mm	Dimen- sion D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 A-M16	20	60	40	10	20.000	5408350
101 A-16	16	60	30	10	13.000	5408352

Alu Aluminium


- Fitting with M16 thread
- For mounting on stands with M16 female thread such as type 101 (5402891, 5402958)
- With M10 bolts

Concrete base min. 16 kg with female thread

Type	Nominal size Ø mm	Thread	Pack Piece	Weight kg/100 pc.	Item no.
101 B2-16 M16	364	M16	1	1,600.000	5402958

BET Concrete


- Weight min. 16 kg
- Frost-resistant concrete
- Female thread M16
- Recommended air-termination rod length max. 3.0 m, depending on wind load zone

Stand 6.9 kg with female thread

Type	Thread	Pack Piece	Weight kg/100 pc.	Item no.
101 ST	M16	4	690.000	5402891

BET Concrete


- Weight 6.9 kg
- Frost-resistant concrete
- Female thread M16
- Recommended air-termination rod length max. 1.0 m

Connection joint

Type	Dimen- sion d Ø mm	Length mm	Dimen- sion D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 IAG	20	107	40	10	40.000	5408504

Alu Aluminium

- Attaching link for installation on concrete stones
- With thread M16 on slanting roof surfaces
- With M10 bolts

Articulated connector

Type	Dimen- sion d Ø mm	Length mm	Dimen- sion D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 IGL-16	16	127	30	10	32.000	5408630


Alu Aluminium

Link for installation of insulation pipes, including M10 screws.

Type	Dimension d Ø mm	Length mm	Dimension D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 IV-16 16	16	60	30	10	16.000	5408557

Alu Aluminium


- Extension of insulating rods
- With M10 bolts

Extension

Type	Fit Colour	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
101 RH-16 Black	Black	16	25	0.187	5408101

PA Polyamide


Reduces the drill hole of the FangFix block from Ø 20 mm to Ø 16 mm. Suitable for the installation of GFK insulating rods of Ø 16 mm.

FangFix reducing sleeve**Concrete base for FangFix system, min. 16 kg**

Type	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
F-FIX-S16 365	365	1	1,700.000	5403227

BET Concrete


- Min. 16 kg block of Ø 365 mm, high level of stability
- Frost-resistant concrete
- Stackable

**Concrete base for FangFix system, min. 10 kg**

Type	Nominal size Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
F-FIX-S10 289	289	1	1,000.000	5403117

BET Concrete

- Min. 10 kg block of Ø 289 mm, high level of stability
- Frost-resistant concrete
- Stackable




Type	Length mm	Dimension B mm	Dimension H mm	Pack Piece	Weight kg/100 pc.	Item no.
101 BP-16 175	175	40	42	1	21.200	5408984

To mount insulating rods on constructions or walls

Plate made of VA stainless steel


Holder and crosspiece for 16 and 20 mm rods and Rd 8–10 mm

Fastening plate


Type	Dimension d Ø mm	Dimension L mm	Dimension D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 WG-16 16	16	110	30	1	27.960	5408986

A2 Stainless steel, rustproof 1.4301

- Wall connection for GFK rods
- Dimension D Ø: 16 mm



Fastening bolts




Type	Dimen- sion d Ø mm	Dimen- sion L mm	Dimen- sion D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 BB-16	16	40	30	1	13.920	5408988

Alu Aluminium

For GFK rods, Dimension D Ø: 16 mm

Holder, V support




Type	Dimen- sion d Ø mm	Dimen- sion L mm	Dimen- sion H mm	Dimen- sion B mm	Pack Piece	Weight kg/100 pc.	Item no.
101 HV-16	16	90	55	48	1	50.700	5408990

A2 Stainless steel, rustproof 1.4301

- Rod holder to accept two GRP rods
- Bracket and crossbar for 16 and 20 mm rods and Rd 8-10 mm

Fold fastening




Type	Dimen- sion d Ø mm	Dimen- sion L mm	Dimen- sion D Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
101 F-16	16	121	30	1	45.120	5408992

A2 Stainless steel, rustproof 1.4301

To fasten a GFK rod on constructions of 4 to 20 mm, Dimension D Ø: 16 mm

Pipe fastening




Type	Dimen- sion d Ø mm	Dimen- sion L mm	Dimen- sion D Ø mm	Dimen- sion B mm	Pack Piece	Weight kg/100 pc.	Item no.
101 R-16	16	81	30	96	1	26.830	5408994

A2 Stainless steel, rustproof 1.4301

- For pipe fastening of a GRP rod using a tightening strap
- Slot width (l x w) 17 x 6 mm

Multi adapter




Type	Dimen- sion d Ø mm	Dimen- sion L mm	Dimen- sion D Ø mm	Dimen- sion B mm	Pack Piece	Weight kg/100 pc.	Item no.
101 MA-16	16	91	30	40	1	36.280	5408996

A2 Stainless steel, rustproof 1.4301

- Connector for two GFK rods
- Dimension D Ø: 16 mm

Rod holder, 20 mm



Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
113 Z-20	Rd 20	20	8.200	5230527

Zn Die-cast zinc


VZ Galvanised

- Installed with over-piece and hex-head screws M6 x 16
- With female thread M8 or through hole Ø 7 mm

Type	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
101 ISP M10	110	10	10.000	5408458

Alu Aluminium

Air-termination tip for attaching to end piece, type 101 IES, with M10 thread




Air-termination tip

Type	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
101 IAB	18	10	2.000	5408733

Alu Aluminium

Water repellent for mounting on insulation rods with d = 20 mm



Adjustable insulating beam – pipe

Type	Pack Piece	Weight kg/100 pc.	Item no.
ISAV1000R	1	130.000	5408849

GFK Fibre-glass-reinforced plastic

Variable spacer for conductors and air-termination rods to maintain the separation distance.

- Infinitely adjustable distance range (L = 550–1,000 mm)
- Made of fibre-glass-reinforced plastic (km = 0.7)
- For pipe mounting (including 2 m tightening strap and tension jack)



Adjustable insulating beam – wall

Type	Pack Piece	Weight kg/100 pc.	Item no.
ISAV1000W	1	130.000	5408852

GFK Fibre-glass-reinforced plastic

Variable spacer for conductors and air-termination rods to maintain the separation distance.


- Infinitely adjustable distance range (L = 550–1,000 mm)
- Made of fibre-glass-reinforced plastic (km = 0.7)
- For wall mounting with 10 fastening holes (4.2 mm) and 4 fastening holes (6.9 mm)



Type	Length mm	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
ISO-A-500	500	Rd 16	15	36.000	5408806
ISO-A-800	800	Rd 16	15	55.000	5408814
ISO-A-1030	1030	Rd 16	15	68.000	5408820
ISO-A-150 8	150	Rd 8	15	13.800	5408800


Alu Aluminium PA Polyamide

- Mounting foot with 10 connection holes Ø 6.5 mm and 4 connection holes Ø 8.5 mm
- Type ...150 8 with holder suitable for round conductor RD 8
- Application for shelters, e.g. golf, barbecue or mountain huts



Insulated spacer

isCon® conductor, professional plus black




Type	Cross-section mm ²	Nominal size Ø mm	Equivalent separation distance m	Pack m	Weight kg/100 m	Item no.
isCon Pro+ 75 SW	35	23	0.75	100	69.400	5408004
isCon Pro+ 75 SW	35	23	0.75	250	69.400	5408006

Please refer to the mounting instructions for information on routing the OBO isCon® conductor.

- Highly voltage-resistant, insulated conductor
- Floating discharge-free
- Additional mechanical protection (black protective jacket)
- For maintenance of the separation distance according to IEC 62305 (VDE 0185-305-3)
- Tested according to IEC/EN 62561-1 (VDE 0185-561-1) with H1/150 kA
- Equivalent separation distance $se \leq 0.75$ m (air) and $se \leq 1.5$ (solid material)
- Tested according to IEC TS 62561-8 (VDE V 0185-561-8)
- Halogen-free
- Fire load 4.3 kWh/m
- Can be used in potentially explosive areas Ex zone 1/2 and 21/22 when taking the current mounting instructions into account

isCon® conductor, professional plus light grey





Type	Cross-section mm ²	Nominal size Ø mm	Equivalent separation distance m	Pack m	Weight kg/100 m	Item no.
isCon Pro+ 75 GR	35	26	0.75	25	86.800	5407995
isCon Pro+ 75 GR	35	26	0.75	100	86.800	5407997

Please refer to the mounting instructions for information on routing the OBO isCon® conductor.

- Highly voltage-resistant, insulated conductor
- Protection against contact voltage during rain (VDE 0432-1 (IEC/EN 60060-1))
- Floating discharge-free
- Additional mechanical protection (double protective jacket)
- For maintenance of the separation distance according to IEC 62305 (VDE 0185-305-3)
- Tested according to IEC/EN 62561-1 (VDE 0185-561-1) with H1/150 kA
- Equivalent separation distance $se \leq 0.75$ m (air) and $se \leq 1.5$ (solid material)
- Tested according to IEC TS 62561-8 (VDE V 0185-561-8)
- Halogen-free
- Fire load 5.1 kWh/m
- Can be used in potentially explosive areas EX zone 1/2 and 21/22 when taking the current mounting instructions into account

isCon® conductor, premium black



Type	Cross-section mm ²	Nominal size Ø mm	Equivalent separation distance m	Pack m	Weight kg/100 m	Item no.
isCon PR 90 SW	35	23	0.9	100	66.600	5408018


Please refer to the mounting instructions for information on routing the OBO isCon® Premium conductor.

- Highly voltage-resistant, insulated conductor
- Floating discharge-free
- Tested according to IEC/EN 62561-1 (VDE 0185-561-1) with H2/200 kA
- Equivalent separation distance $se \leq 0.90$ m (air) and $se \leq 1.8$ m (solid material)
- Tested according to IEC TS 62561-8 (VDE V 0185-561-8)
- Halogen-free
- Fire load 4.2 kWh/m

isCon® conductor, professional black



Type	Cross-section mm ²	Nominal size Ø mm	Equivalent separation distance m	Pack m	Weight kg/100 m	Item no.
isCon Pro 75 SW	35	20	0.75	100	57.000	5408008




Please refer to the mounting instructions for information on routing the OBO isCon® Pro conductor.

- Highly voltage-resistant, insulated conductor
- Floating discharge-free
- For maintenance of the separation distance according to IEC 62305 (VDE 0185-305-3)
- Tested according to IEC/EN 62561-1 (VDE 0185-561-1) with H1/150 kA
- Equivalent separation distance $se \leq 0.75$ m (air) and $se \leq 1.5$ m (solid material)
- Tested according to IEC TS 62561-8 (VDE V 0185-561-8)
- Halogen-free
- Fire load 3.3 kWh/m

isCon® conductor, basic black



Type	Cross-section mm ²	Nominal size Ø mm	Equivalent separation distance m	Pack m	Weight kg/100 m	Item no.
isCon BA 45 SW	35	20	0.45	100	57.000	5408014




Please refer to the mounting instructions for information on routing the OBO isCon® Basic conductor.

- Highly voltage-resistant, insulated conductor
- For maintenance of the separation distance according to IEC 62305 (VDE 0185-305-3)
- Tested according to IEC/EN 62561-1 (VDE 0185-561-1) with H1/150 kA
- Equivalent separation distance $se \leq 0.45$ m (air) and $se \leq 0.90$ m (solid material)
- Tested according to IEC TS 62561-8 (VDE V 0185-561-8)
- Halogen-free
- Fire load 3.3 kWh/m

IsCon® connection element



Type	Dimension Ø mm	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
isCon con 2	20	10	H1/150	2	21.500	5408021
isCon connect	23	10	H1/150	2	21.500	5408022
isCon con PRE	23	10	H2/200	2	21.500	5408023



A2 Stainless steel, rustproof 1.4301


- Screw-on termination of the connection for the isCon® conductor
- Incl. heat-shrinkable sleeve, hexagonal
- Tested up to 200 kA (lightning protection class I)

Stripping tool for IsCon® conductor


Type	Clamping range D mm	Pack Piece	Weight kg/100 pc.	Item no.
isCon stripper 2	20 - 23	1	170.000	5408013

PA/PE Polyamide/polyethylene

Stripping tool to remove the insulation of the OBO isCon® conductor.



Connection element for installation in the insulated air-termination rod isFang IN




Type	Dimension D Ø mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
isCon IN con 2	20	H1/150	1	27.800	5408019
isCon IN con PRE	23	H2/200	1	27.800	5408020

A2 Stainless steel, rustproof 1.4301

- Screw-on termination of the connection for the isCon® conductor
- Connection and installation of the conductor in the insulated air-termination rod
- Tested up to 200 kA (lightning protection Class II)

Connection element for installation in the insulated air-termination rod isFang IN




Type	Dimension D Ø mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
isCon IN connect	23	H1/150	1	26.900	5408024

A2 Stainless steel, rustproof 1.4301

- Screw-on termination of the connection for the isCon® conductor
- Connection and installation of the conductor in the insulated air-termination rod
- Tested up to 200 kA (lightning protection Class II)

Potential connection for isCon® Professional+ and Premium in the isFang IN insulated air-termination rod




Type	Dimension D Ø mm	Dimension d Ø mm	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
isCon IN PAE	23	49.9	35	1	5.900	5408031

Alu Aluminium

- To avoid surface discharges on the isCon® conductor
- Installation takes place after the first 1.5 metres in the insulated air-termination rod type isFang IN

Potential connection for isCon® Basic and Professional in the isFang IN insulated air-termination rod




Type	Dimension D Ø mm	Dimension d Ø mm	Dimension L mm	Pack Piece	Weight kg/100 pc.	Item no.
isCon IN PAE 2	20	49.9	35	1	5.900	5408032

Alu Aluminium

- To avoid surface discharges on the isCon® conductor
- Installation takes place after the first 1.5 metres in the insulated air-termination rod type isFang IN

Potential connection




Type	Fit mm	Pack Piece	Weight kg/100 pc.	Item no.
isCon PAE	ø 17-25mm	2	36.500	5408036

A2 Stainless steel, rustproof 1.4301

Potential connection

- To avoid floating discharges on the isCon® conductor
- With sprung discs to protect screws against loosening

PA cable bracket with tightening strap




Type	Colour	Dimension Ø mm	Pack Piece	Weight kg/100 pc.	Item no.
isCon HS 26 PA	Light grey	Ø 26mm 26	10	23.200	5408066

PA Polyamide

For isCon® conductor for pipe mounting including 2 m tightening strap.

Universal flat conductor adapter for roof conductor holder, type 165/MBG




Type	Fit	Colour mm	Pack Piece	Weight kg/100 pc.	Item no.
165 MBG UH	Black	Rd 8	25	0.254	5218882

PP Polypropylene

- Universal adapter with drill hole Ø 2.5 mm
- E.g. for OBO Golden Sprint screw, type 4758 4 x L (L = depending on application)
- For fastening to 165/MBG

Multi-Quick clip, metric




Type	Clamping range D mm	Pull-out value N	Colour	Shipping box Piece	Pack Piece	Weight kg/100 pc.	Item no.
M-Quick M32 LGR	25 - 32	60	Light grey	600	50	1.390	2153734

PA Polyamide

- Multi-Quick metric
- Simple fastening
- Secure locking
- Radial arrangement
- Simplified storage
- Universally applicable

VA roof conductor holder, sloping roof




Type	Installation height mm	Pack Piece	Weight kg/100 pc.	Item no.
isCon H280 VA	55	25	16.100	5408047
isCon H280 26 VA	55	25	16.900	5408074

A2 Stainless steel, rustproof 1.4301

- For routing of the isCon® conductor on pitched roofs
- Cable bracket with sprung discs to protect the screws against loosening

PA roof conductor holder, sloping roof




Type	Colour	Dimension	Pack Piece	Weight kg/100 pc.	Item no.
isCon H280 PA	Black	280mm	25	13.950	5408049
isCon H280 26 PA	Light grey	280mm	25	14.060	5408072

PA Polyamide

To route the isCon® conductor on pitched roofs.

Spacer



Type	Clamping range D mm	Pack Piece	Weight kg/100 pc.	Item no.
isCon DH	23 - 26	2	41.400	5408043

GFK Fibre-glass-reinforced plastic

For stand-off installation of the isCon® conductor in the area of the connection, incl. reducing sleeve for mounting on FangFix concrete block 10 Kg.


Vario quick connector 200 kA



Type	Fit mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
249 8-10 V2A 200	Rd 8-10	H2/200	10	12.374	5311595

A2 Stainless steel, rustproof 1.4301

- For T, intersection and parallel connections
- Quick mounting using an M10 x 30 bolt, made from rustproof stainless steel
- Meets the requirements of VDE 0185-305 (IEC 62305)
- Tested according to VDE 0185-561-1 (IEC/EN 62561-1) with 200 kA
- For use in lightning protection class I with the isCon® Premium conductor



Insulated air-termination rod for inner-routed isCon conductor with side exit




Type	Dimen- sion D Ø mm	Dimen- sion A mm	Dimen- sion H mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang IN-A 4000	50	1325	1500	1000	4000	1	535.000	5408938
isFang IN-A 6000	50	3325	1500	1000	6000	1	835.000	5408940
isFang IN-A 8000	50	5335	1500	1000	8000	1	1,385.000	5408888
isFang IN-A10000	50	6000	1733	2000	10000	1	1,540.000	5408890

GFK Fibre-glass-reinforced plastic


- For installation of the OBO isCon® Pro+ conductor in the pipe
- With side conductor outlet matching isFang air-termination rod stand with side outlet, type isFang 3B-A
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- Inclusive connection element (type isCon IN connect)
- Inclusive potential connection (type IsCon In PAE)



Dimensions



Insulated air-termination rod for inner-routed isCon® conductor with side exit




Type	Dimen- sion D Ø mm	Dimen- sion A mm	Dimen- sion H mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang IN-A L4	50	1325	1500	1000	4000	1	535.000	5408874
isFang IN-A L6	50	3325	1500	1000	6000	1	835.741	5408876
isFang IN-A L8	50	5335	1500	1000	8000	1	1,385.741	5408878
isFang IN-A L10	50	6000	1733	2000	10000	1	1,540.741	5408880

GFK Fibre-glass-reinforced plastic

- For routing OBO isCon® conductors in pipes
- For mounting on the building structure with isFang support
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- Tested according to VDE V 0185-561-8 (IEC TS 62561-8)

isFang tripod with side outlet




Type	Dimen- sion B mm	Dimen- sion D Ø mm	Dimen- sion L mm	Dimen- sion H mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang 3B-100-A	1026	50	600	885	1	610.000	5408930
isFang 3B-150-A	1500	50	900	1275	1	950.000	5408932
isFang 3B-250-A	2900	50	1450	2055	1	2,500.000	5408902

A2 Stainless steel, rustproof 1.4301

- Screwless installation of freestanding air-termination rods as well as insulated air-termination rods with 50 mm diameter
- E.g. for internal OBO isCon® conductor
- Roof slope to max. 5 degrees
- Incl. Rd 8–10 crossbar for quick round conductor fastening
- Concrete plinths as well as threaded rods should be ordered separately

Potential connection for isCon® Professional+ and Premium in the isFang IN insulated air-termination rod



Type	Dimen- sion D Ø mm	Dimen- sion d mm	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isCon IN PAE	23	49.9	35	1	5.900	5408031
isCon IN PAE 2	20	49.9	35	1	5.900	5408032

Alu Aluminium

- To avoid surface discharges on the isCon® conductor
- Installation takes place after the first 1.5 metres in the insulated air-termination rod type isFang IN

Insulated air-termination rod




Type	Dimen- sion A mm	Dimen- sion H mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang 4000 AL	1240	1500	1000	4000	1	580.000	5408943
isFang 6000 AL	3340	1500	1000	6000	1	600.000	5408947
isFang 4000	1240	1500	1000	4000	1	680.000	5408942
isFang 6000	3340	1500	1000	6000	1	680.000	5408946

GFK Fibre-glass-reinforced plastic

- For isolated creation of air-termination systems
- Suitable for isFang air-termination rod stands, type isFang 3B-100/150
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- For installation on the building structure with isFang support
- Fastening of the OBO isCon® conductor possible using accessories
- Suitable for externally routed isCon® conductors



Dimensions




isFang tripod



Type	Dimen- sion B mm	Dimen- sion D Ø mm	Dimen- sion L mm	Dimen- sion H mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang 3B-100 AL	1000	40	600	885	1	380.000	5408966
isFang 3B-150 AL	1500	40	900	1275	1	560.000	5408967
isFang 3B-100	1000	40	600	885	1	620.000	5408968
isFang 3B-150	1500	40	900	1275	1	950.000	5408969

A2 Stainless steel, rustproof 1.4301 Alu Aluminium

- Installation of free-standing air-termination rods as well as insulated air-termination rods with 40 mm diameter
- Roof slope to max. 5 degrees
- Incl. Rd 8–10 crossbar for quick round conductor fastening
- Concrete bases as well as threaded rods should be ordered separately




isFang-3B threaded rod


Type	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang 3B-G1	270	3	48.000	5408971
isFang 3B-G2	340	3	60.400	5408972
isFang 3B-G3	430	3	69.500	5408973
isFang 3B-G4	500	3	75.000	5408905

A2 Stainless steel, rustproof 1.4301

- For fastening on one, two, three or four FangFix concrete bases with tripod stand



Concrete base for FangFix system, min. 16 kg




Nominal size Ø
mm
Type F-FIX-S16 | 365

Pack Weight
Piece kg/100 pc. **Item no.**
| 1 | 1,700.000 | 5403227

BET Concrete

- Min. 16 kg block of Ø 365 mm, high level of stability
- Frost-resistant concrete
- Stackable

Base for FangFix system 16 kg for mounting the isFang tripod




Nominal size Ø Dimension D
mm mm Ø mm
Type F-FIX-B16 3B | 373 | 25

Pack Weight
Piece kg/100 pc. **Item no.**
| 10 | 15.800 | 5403238

PP Polypropylene

- Edge protection with through hole
- For mounting isFang-3B threaded rod and FangFix concrete block F-FIX-S16

Potential connection clamp for mounting on isFang




Type 927 2 6-K | –

Pack Weight
Piece kg/100 pc. **Item no.**
| 10 | 5.500 | 5057599

A2 Stainless steel, rustproof 1.4301

Potential connection for isCon® conductor for mounting on insulated air-termination rods of type isFang.

Connection plate for one isCon® conductor



Type

Dimension


Pack Weight
Piece kg/100 pc. **Item no.**
| 1 | 27.400 | 5408026

isCon AP1-16 VA | 16x8-10mm

A2 Stainless steel, rustproof 1.4301

Connection plate to connect an isCon® conductor with air-termination rod Ø 16 mm, tested up to 150 kA (lightning protection class II)

Connection plate for two isCon® conductors



Type

Dimension

Pack Weight
Piece kg/100 pc. **Item no.**
| 1 | 39.500 | 5408028

isCon AP2-16 VA | 16x8-10mm

A2 Stainless steel, rustproof 1.4301

Connection plate to connect two isCon® conductors with air-termination rod Ø 16 mm, tested up to 150 kA (lightning protection class II)

Cable tie, black, UV and weather-resistant



**UV
RESISTANT**

Type

Dimen- Dimen- Dimen- Max.
sion B sion L t Ø bundle
mm mm mm mm Colour

Pack Weight
Piece kg/100 pc. **Item no.**
| 100 | 0.533 | 2331924

PA Polyamide


Cable ties are used for quick, uncomplicated fixing or bundling of cables and pipes to cable support systems or other mounting structures.

Cleaning cloth

Type	Width mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isCon EPPA 004	140	200	50	0.420	5408060

Z-PP-P Cellulose-polypropylene paper

- Cellulose polypropylene paper with abrasive sections, folded multiple times
- Doused with 2.8 ml impregnation solution
- For cleaning the external jacket of the OBO isCon® conductor


**isCon® information panel**

Type	Pack Piece	Weight kg/100 pc.	Item no.
isCon HWS	1	2.000	5408058

PS Polystyrene

Label: "NOTE! Insulated lightning protection with the OBO isCon® system. Only a lightning protection specialist may carry out changes"

- To label the lightning protection system
- Self-adhesive and with 4 fastening holes ø 6.5 mm

**isCon® information panel EN**

Type	Pack Piece	Weight kg/100 pc.	Item no.
isCon HWS EN	1	2.000	5408059

PS Polystyrene

Label: "NOTE! Insulated lightning protection with the OBO isCon® system. Only a lightning protection specialist may carry out changes"


- To label the lightning protection system
- Self-adhesive and with 4 fastening holes ø 6.5 mm

**isFang support for corner pipe mounting, 50 x 50 mm**

Type	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TS50x50	30	2	82.000	5408964

A2 Stainless steel, rustproof 1.4301


Fastening clip to fasten the insulated support pipes on the structure to be protected or for construction-side corner pipes of 50x50 mm.

**isFang support for pipe mounting, ø 50–60 mm**

Type	Dimen- sion D Ø mm	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TS50-60	60	30	2	76.000	5408960

A2 Stainless steel, rustproof 1.4301


Tightening strap clip to fasten the insulated support pipes on the structure to be protected or for construction-side pipes of ø 50–60 mm.

**isFang support for pipe mounting, ø 40–50 mm**


Type	Dimen- sion D Ø mm	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TS40-50	50	40	2	90.000	5408958

A2 Stainless steel, rustproof 1.4301

Tightening strap clip to fasten the insulated support pipes on the structure to be protected or for construction-side pipes of ø 40–50 mm.



isFang support for spaced pipe mounting, ø 50–300 mm




Type	Dimen- sion D Ø mm	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TR100 100	300	100	2	95.500	5408955
isFang TR100 200	300	200	2	121.000	5408957
isFang TR100 300	300	300	2	146.000	5408959

A2 Stainless steel, rustproof 1.4301

Tightening strap clip to fasten the insulated support pipes on the structure to be protected or for construction-side pipes of ø 50–300 mm.

isFang support for pipe mounting, ø 50–300 mm




Type	Dimen- sion D Ø mm	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TR100 300	300	40	2	77.000	5408956

A2 Stainless steel, rustproof 1.4301

Tightening strap clip to fasten the insulated support pipes on the structure to be protected or for construction-side pipes of ø 50–300 mm.

Support for wall mounting, 200 mm spacing




Type	Dimen- sion D Ø mm	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TW200 12	50	200	2	240.000	5408910

A2 Stainless steel, rustproof 1.4301

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.

isFang support for wall mounting, 200–300 mm spacing




Type	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TW200 300	300	2	230.000	5408954

A2 Stainless steel, rustproof 1.4301

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.

isFang support for wall mounting, 80 mm spacing




Type	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TW80 80	80	2	63.000	5408950

A2 Stainless steel, rustproof 1.4301

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.

isFang support for wall mounting, 30 mm spacing



Type	Dimen- sion L mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang TW30 30	30	2	62.000	5408952


A2 Stainless steel, rustproof 1.4301

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.

isFang, insulated air-termination rod for inner-routed isCon® conductor Professional Plus



Type	Dimen- sion D Ø mm	Dimen- sion A mm	Dimen- sion H mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang IN 4000	50	1325	1500	1000	4000	1	535.000	5408934
isFang IN 6000	50	3325	1500	1000	6000	1	835.000	5408936
isFang IN 8000	50	5335	1500	1000	8000	1	1,315.000	5408868
isFang IN 10000	50	6000	1733	2000	10000	1	1,540.000	5408870




GFK Fibre-glass-reinforced plastic

- For installation of the OBO isCon® Pro+ conductor in the pipe
- For mounting on the building structure with isFang support
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- Inclusive connection element (type isCon IN connect)
- Inclusive potential connection (type IsCon In PAE)

Insulated air-termination rod for inner-routed isCon conductor with side exit



Type	Dimen- sion D Ø mm	Dimen- sion A mm	Dimen- sion H mm	Dimen- sion B mm	Length mm	Pack Piece	Weight kg/100 pc.	Item no.
isFang IN-A 4000	50	1325	1500	1000	4000	1	535.000	5408938
isFang IN-A 6000	50	3325	1500	1000	6000	1	835.000	5408940
isFang IN-A 8000	50	5335	1500	1000	8000	1	1,385.000	5408888
isFang IN-A 10000	50	6000	1733	2000	10000	1	1,540.000	5408890
isFang IN-A L4	50	1325	1500	1000	4000	1	535.000	5408874
isFang IN-A L6	50	3325	1500	1000	6000	1	835.741	5408876
isFang IN-A L8	50	5335	1500	1000	8000	1	1,385.741	5408878
isFang IN-A L10	50	6000	1733	2000	10000	1	1,540.741	5408880
isFang IN L4	50	1325	1500	1000	4000	1	535.741	5408854
isFang IN L6	50	3325	1500	1000	6000	1	835.741	5408856
isFang IN L8	50	5335	1500	1000	8000	1	1,315.741	5408858
isFang IN L10	50	6000	1733	2000	10000	1	1,540.741	5408860



GFK Fibre-glass-reinforced plastic

- For installation of the OBO isCon® Pro+ conductor in the pipe
- With side conductor outlet matching isFang air-termination rod stand with side outlet, type isFang 3B-A
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- Inclusive connection element (type isCon IN connect)
- Inclusive potential connection (type IsCon In PAE)



Directories



Numeric directory

496



Type listing

499

GTIN	Item no.	Page	GTIN	Item no.	Page	GTIN	Item no.	Page	GTIN	Item no.	Page	GTIN	Item no.	Page
5432371	1167006	375	6431168	5001511	391	6409327	5018014	380	5386292	5050081	373	5525257	5084016	248
5432432	1167014	375	6431205	5001513	391		/pc.	price/100	5386353	5050111	373	5525318	5084020	245
5432494	1167022	375	5372851	5001560	390	5800415	5018501	380	5386414	5050138	373	5525370	5084024	246
5432555	1167030	375	6431120	5001590	390	5800477	5018706	380	5386476	5050154	373	5525431	5084028	247
5432616	1167049	375	6431212	5001592	390	5022015	5018730	380	5386537	5050170	373	5525493	5084032	249
5655367	2146164	485	6431267	5001594	390	5680468	5019340	380	5386599	5050197	373	5525554	5084036	249
5595717	2146207	485	6431274	5001601	403	5694007	5019342	380	5386650	5051509	373	5110750	5084048	250
5016069	2146509	485	5635239	5001617	390	5694014	5019344	380						
5741671	2153734	486	5752653	5001625	390	5680475	5019345	380	5386834	5052076	373	6440573	5088564	233
6417353	2331924	490	5862697	5001633	390	5680482	5019347	380	5386896	5052092	373	6190263	5088566	226
6421046	2360041	398	5372912	5001641	390	5680499	5019350	380	5386957	5052114	373	6037490	5088585	227
6421053	2360043	398	5372974	5001668	390	5680505	5019355	380	5387015	5052130	373	5872658	5088629	229
6421053	/pc.		5901259	5001672	390	5680512	5019360	380	5387077	5052157	373	5780717	5088651	228
5518419	2362970	472	5754879	5001749	390	5381556	5021081	380	5387190	5052181	373	5613701	5088691	230
5230533	2360055	404	5373575	5003008	388	5381617	5021103	380	5388517	5057507	371	5613718	5088692	231
5230595	2360101	404	5373636	5003016	388	5381730	5021162	381	5388579	5057515	371	5613725	5088693	232
5242772	3041212	384	5373698	5003024	388	5801375	5021227	381	5388630	5057523	371	6441679	5089736	113
5242956	3041956	384	5373759	5003032	388	5680529	5021235	381	5388692	5057558	371	6441686	5089738	113
5243137	3042200	384	5373810	5003040	388	5680567	5021239	381	5389651	5057599	490			
5243199	3042251	384	6527069	5003081	388	5389194	5021286	381	6672813	5057630	362			
6431243	3042270	384	5374176	5003296	388	5901273	5021294	381	6672820	5057640	362	5461111	5091322	358
5243137	3042200	384	5374237	5003318	388	5381976	5021308	381	6672837	5057645	362	5461296	5091438	358
5243199	3042251	384	5374718	5003776	388	5067474	5021332	381	6672844	5057690	376	5461470	5091527	358
52431243	3042270	384	5374770	5003784	388	6564804	5021380	382	5805458	5057922	371	5461654	5091683	359
5243111	/pc.		6427925	5009200	403	6636822	5021484	382	5805519	5057930	371	5896111	5091691	359
5243311	3043207	385	5376934	5009227	389	6033768	5021652	382	5805519	5057936	404	6426713	5092420	202
5243373	3043258	385	5376996	5009235	389	5382096	5021502	382	5805519	5059496	404	6426720	5092422	201
5717492	3043312	385	6431298	5009250	389	5902058	5021642	382	5805519	5064015	375	6426751	5092424	200
5243557	3043401	385	6431304	5009256	389	5680574	5021644	382	5805519	5064015	375	6426768	5092426	199
5243618	3043452	385	6427925	5009200	403	5680581	5021647	382	5805519	5064015	375	6515400	5092431	197
5111160	3043602	386	5377719	5012015	397	6033768	5021652	382	5805519	5064015	375	6515431	5092433	198
5617419	3043606	386	6431113	5012270	464	5836209	5021654	382	5915973	5080053	278	6560844	5092440	211
5087076	3043610	386				5938668	5021656	382	5916277	5080061	280	5080886	5092451	206
5087137	3043614	386				6431199	5021830	408	5916031	5080150	279	5247098	5092460	208
5111641	3043618	386							6741908	5080301	281	5475804	5092466	207
5421627	3043628	386	5377894	5014018	400				6741915	5080303	282	6439034	5092478	195
5243793	3043703	385	5377955	5014026	400	5382690	5025206	402	6741922	5080305	283	6035441	5092480	194
5243854	3043754	385	5378013	5014212	400	5383055	5028035	402	6741939	5080307	284	6035496	5092482	196
5642312	3043908	386	5901938	5014425	397	5383116	5028043	402	6741946	5080309	285			
5453796	3043916	386	5105015	5014468	398	5383413	5030021	403	6741953	5080311	286	5390671	5093015	251
5642978	3044831	386	6656134	5014471	398	5383659	5030234	403	6741960	5080313	287	5390732	5093023	252
5643036	3044904	386	5105077	5014476	398	5383710	5030242	403	6741991	5080319	290	5391036	5093252	253
5453970	/pc.		5378136	5015057	365	5383833	5032032	401	6742004	5080321	291	5391098	5093260	255
5631699	3049205	404	5378259	5015073	362	5383895	5032040	401	6742011	5080323	292	5087250	5093270	259
5631637	3049221	404	5378310	5015081	363	5383956	5032237	402	6742028	5080325	293	5022619	5093272	262
5631576	3049256	404	6587292	5015105	364	5384014	5032245	402	6742035	5080327	294	5022732	5093275	261
5631453	3049329	404	5959427	5015111	364	5384137	5032539	402	6742042	5080329	295	5867050	5093277	263
5631392	3049345	404	6427628	5015265	368	5384199	5032547	402	6742059	5080331	296	5246268	5093378	184
5244219	/pc.		6427837	5015502	363	5384434	5033039	402	6742067	5080332	297	5076551	5093380	185
5244813	3051013	473	5378556	5015650	362	5433750	5033209	401	6742075	5080333	297			
5244813	3059006	473	5699330	5015832	366	5384557	5038014	372	6676965	5081070	276	5406778	5093415	189
5250395	/pc.		5699347	5015836	366	5384618	5038030	372	6676972	5081072	277	5382799	5093418	192
5250456	3133028	472	5699354	5015844	366	5384670	5038057	372	6742087	5081690	239	6398638	5093440	115
5250579	3133036	472	5699361	5015847	366	5384731	5038081	372	6742094	5081694	240	6398645	5093446	116
5250579	3133230	473	5699408	5015849	366	5384854	5038111	372	6742444	5081698	238	6398669	5093448	118
6431229	5000481	384	5002277	5015854	365	5384915	5038138	372	6514364	5081800	265	6398676	5093452	119
6336340	5000500	384	6681921	5015870	366	5384977	5038154	372	6532766	5081802	267	6398683	5093454	121
5018049	5000742	383	6681945	5015874	366	5385219	5040035	372	6415656	5081975	241	6398690	5093460	120
5111047	5000769	383	6681938	5015876	365	5385271	5040051	372	6415663	5081977	242	6412952	5093500	123
5740650	5000858	383	5033615	5015880	366	5385332	5040078	372	6415670	5081982	243	6412969	5093502	124
5371830	5000866	383	5033677	5015884	366	5385394	5040094	372	6415687	5081984	244	6153718	5093505	134
5371892	5000947	383	5379157	5016037	367	5385516	5040116	372	6415694	5081990	268	6159598	5093508	134
5371953	5000955	383	5379096	5016029	367	5385578	5040159	372	5685333	5082382	272	6159628	5093513	127
6431236	5001190	385	5379218	5016045	367	5385936	5040507	372	6415717	5082430	269	6159642	5093516	126
5372370	/pc.		5922216	5016096	367	5385998	5043018	374	6415724	5082432	270	6159659	5093518	128
5372431	5001218	389	5800354	5016118	367	5386056	5043107	374	5022978	5083400				

GTIN	Item no.	Page	GTIN	Item no.	Page										
	/pc.			/pc.			/pc.			/100 pc.			/100 pc.		
5709022	5093625	219	6487325	5096981	101	5900375	5106133	470	5408970	5218829	429	5417316	5311039	445	
5708841	5093726	234	6608768	5096982	106	5900436	5106141	470	5409038	5218861	428	5417378	5311101	446	
5962243	5093988	257	6608775	5096983	106					/pc.		5417439	5311152	446	
5805991	5093996	256	6608744	5096985	107	5401599	/100 pc.	414	5674580	5218882	428	5417491	5311209	446	
6463831	5093998	258		/pc.							5417552	5311268	446		
			6487332	5096987	100				5623052	5218885	428	6466283	5311404	440	
6603695	5094210	220	6608751	5096988	107	5904335	5202213	430	5409090	5218926	458	6416912	5311407	441	
6603701	5094212	221		/pc.		5402138	5202248	430	5952213	5218977	428	5816584	5311410	440	
6603718	5094230	216	5995029	5096990	140	6379965	5202510	424	5625889	5218997	429	5816591	5311417	441	
6603725	5094232	217	5995036	5096992	139	5403036	5202515	423				5417675	5311500	439	
6603732	5094240	214	5995043	5096994	140	5902294	5202566	423	5409458	5223075	435	5737063	5311503	373	
6603749	5094242	215				5894124	5202568	424	5409519	5223105	435	5417736	5311519	439	
5648482	5094574	223	5578116	5097453	297	5894223	5202569	427	5409632	5223156	435	5417798	5311527	440	
5709084	5094576	225	5736561	5097454	303	5902232	5202590	423	5409755	5223202	435	5835394	5311530	367	
5708872	5094605	224	5578123	5097607	298	5403814	5202833	423	5409939	5223601	435	5417859	5311535	440	
5478621	5094608	222	5578130	5097615	299	5784920	5202836	422				5417910	5311551	367	
5363903	5094920	190	5578147	5097623	300	5902171	5202868	423	5410416	5226570	435	5835349	5311554	367	
5363941	5094931	191	5578154	5097631	301							5693789	5311573	374	
			5578161	5097650	302	5038269	5203015	422	5410539	5227070	435	5466192	5311585	374	
6159727	5095141	144	5578185	5097820	304	5784968	5203018	422	5410591	5227089	435	5925446	5311590	370	
6159741	5095142	146	5812258	5097822	305	5289746	5203023	422	5410652	5227100	435	6656141	5311595	439	
6159758	5095151	147	5578215	5097858	306				5410713	5227151	435	/100 pc.			
6159772	5095152	148	5578260	5097939	307	5404651	5207258	432	5410836	5228026	436	5451990	5311705	439	
6159789	5095153	151	5578277	5097976	310	5110392	5207266	433				5452058	5311713	439	
6159802	5095161	155				5404774	5207339	431	5410959	5228123	436				
6159819	5095162	157	5683339	5098380	345	5735762	5207342	430	5411017	5228131	436	5417972	5312035	447	
6159826	5095163	161	5683346	5098382	346	5404835	5207347	431	5851011	5228134	436	5418030	5312132	448	
6159833	5095164	163	5683384	5098390	347	5069546	5207371	431	5411079	5228220	438	6428038	5312292	464	
6159949	5095201	169	5683391	5098392	348	6657940	5207375	431	5411192	5228328	436	6428045	5312294	464	
6159956	5095211	170	5406839	5098404	325							6428106	5312302	395	
6159963	5095212	171	5406846	5098407	326	5404897	5207444	432	5411499	5229162	434	6428113	5312308	463	
6160006	5095213	173	5406853	5098411	327	5009726	5207451	433	5411550	5229367	434	5418092	5312310	393	
6160013	5095214	175	5848516	5098412	342	5404958	5207460	432	5411611	5229383	434	5700869	5312318	393	
6160020	5095221	145	5625124	5098413	334	5405016	5207487	432	5411673	5229464	435	5418153	5312345	394	
6160051	5095231	152	5787372	5098415	335	5904991	5207746	432	5411734	5229480	435	5893103	5312346	394	
6160075	5095232	149	5773610	5098419	336	5905059	5207754	432	5411970	5229553	434	5418214	5312418	393	
6163847	5095233	153	5406860	5098422	328	5905110	5207762	432	5412151	5229839	434	5418276	5312442	394	
6161140	5095251	165	5787389	5098425	337	5904878	5207800	431	5412212	5229960	433	6466306	5312582	393	
6161324	5095252	159	5406877	5098427	329	5904939	5207819	431	5840886	5229961	434	6428083	5312592	463	
6161331	5095253	167	5406884	5098431	330	5336433	5207851	432							
6162000	5095281	156	5848523	5098432	343	5334811	5207878	432	5446231	5230217	433	5418337	5312604	392	
6162185	5095282	158	5406891	5098442	331	5915836	5207901	432	5629535	5230322	433	5418399	5312655	395	
6162338	5095283	162	5406907	5098446	332				5629474	5230365	434	5893141	5312656	395	
6162819	5095284	164	5406914	5098450	333	5405252	5208017	436	5739999	5230446	401	6454563	5312657	396	
6162901	5095312	172	5848530	5098452	344				5740056	5230462	401	5418573	5312809	393	
6162949	5095313	174	5410461	5098470	338	5903673	5215277	429	5959601	5230527	438	5418696	5312906	395	
6162956	5095314	176	5813521	5098475	338	5903796	5215307	429				5418757	5312922	395	
6163007	5095321	154	5578284	5098492	311	5811879	5215374	426				5700876	5312925	395	
6162963	5095322	150	5578291	5098506	312	5811930	5215382	427	6517381	5240030	352	5103158	5312930	463	
6163014	5095331	166	5578307	5098514	313	5407171	5215439	426	6521180	5240031	352				
6163243	5095332	160	5578314	5098522	314	5812111	5215471	426	6522941	5240032	353	6428151	5313012	396	
6163427	5095333	168	5578338	5098557	315	5902591	5215544	425	6522965	5240033	353	6466290	5313013	396	
6163533	5095360	177	5578345	5098571	308	5407294	5215552	424	6521159	5240102	354	5740537	5313015	396	
6163540	5095362	177	5578352	5098575	309	5784982	5215555	424	6521166	5240104	354	5740476	5313023	396	
6163557	5095364	178	5578369	5098600	317	5812234	5215579	424	6521173	5240106	354	5543015	5313031	396	
6163618	5095370	178	5578376	5098603	318	5785019	5215582	424	6524181	5240360	354	5237372	5313058	396	
6163625	5095372	179	5578383	5098611	319	5812296	5215587	425	6524242	5240362	354	5806530	5313066	397	
6163656	5095378	179	5578390	5098630	320	5812357	5215595	424	6524259	5240366	354				
6329694	5095600	180	5578413	5098646	321	5812418	5215609	425	6524273	5240370	354	5418993	5314038	448	
6337620	5095609	134	5578420	5098727	316	5407355	5215625	425	6524297	5240374	354	5419112	5314135	448	
			5578444	5098808	322	5812531	5215668	426	65						

GTIN	Item no.	Page	GTIN	Item no.	Page	GTIN	Item no.	Page	GTIN	Item no.	Page
	/100 pc.			/100 pc.			/pc.			/pc.	
5420132	5316308	455	5426974	5351057	461	5674696	5408026	490	5670131	5408964	421
5420194	5316324	455	5427032	5351073	461	5674702	5408028	490	5802433	5408966	416
5433682	5316450	454	5427094	5351251	461	5871569	5408031	484	5802440	5408967	416
5433729	5316459	455	5427155	5351286	461	6591633	5408032	484	5670148	5408968	416
5433736	5316468	455	5890652	5351359	461	5674719	5408036	484	5674931	5408969	416
5420316	5316510	456	5890713	5351375	461	5674863	5408043	486	5674948	5408971	418
5420378	5316553	456	5427216	5351456	462	5674870	5408047	486	5674979	5408972	418
			5427278	5351472	462	5674887	5408049	486	5674986	5408973	418
5420439	5317010	452				5674726	5408052	485	5613329	5408976	476
5420491	5317053	452	5427575	5400155	386	5699668	5408056	485	5613336	5408978	476
5420552	5317207	452	5629054	5400627	387	5813774	5408058	491	5613343	5408980	476
5893158	5317208	452				6586981	5408059	491	5613350	5408982	476
5420613	5317223	453	6219339	5400810	421	5813781	5408060	491	5613367	5408984	479
5420675	5317258	452	6219346	5400812	421				5613374	5408986	479
5420736	5317274	454	6219353	5400814	421	5872696	5408064	485	5613381	5408988	480
5420798	5317401	453	6219360	5400817	421	5872702	5408066	486	5613428	5408992	480
5420859	5317428	454				5872740	5408068	485	5613435	5408994	480
5420910	5317452	453				5872757	5408072	486	5613442	5408996	480
5420972	5317479	454	5901334	5401771	413						
5850861	5317481	453	5427810	5401801	413	5872764	5408074	486			
6622368	5317502	450	5427872	5401836	413						
6622375	5317512	451	5898399	5401852	413	5674924	5408101	479	5428893	5410096	438
			5902119	5401879	413						
5421030	5318084	451	5034810	5401970	411	5690733	5408105	477	5429616	5412609	437
5421092	5318149	451	5105619	5401980	411	5613206	5408107	477	5446415	5412633	437
			5107774	5401983	411	5613213	5408108	477	5459071	5412706	401
5421276	5320011	458	5108672	5401986	411	5613220	5408109	477	5752356	5412803	438
5421337	5320054	458	5108733	5401989	411	5636731	5408148	477	5752295	5412811	438
5421511	5320690	459	5045359	5401993	411	5681496	5408156	477			
5421573	5320704	459	5050803	5401995	411	5613237	5408158	477	5429678	5416566	467
6127504	5320707	459				5895817	5408245	477			
5421634	5320712	459	5428053	5402107	414	5613251	5408298	477	6505869	5420020	398
			5428176	5402158	414	5674474	5408350	478	6505890	5420022	399
5421870	5325307	457	5428411	5402808	413	5613268	5408352	478	6505906	5420024	399
5421931	5325315	457	5428473	5402859	413	5674412	5408393	478			
						5613275	5408395	478	5751571	5420504	387
5422419	5326303	458	5674733	5402864	415	5674451	5408458	481	5331575	5420539	387
5422471	5326311	458	5674740	5402866	415	5674497	5408504	478			
5422532	5326338	458	5674757	5402868	415	5613299	5408557	479	5430094	5424100	413
			5674764	5402870	415	5613312	5408630	478	5430216	5424151	387
5453611	5328209	445	5674795	5402872	415	5673811	5408687	477	5430339	5424208	387
5453673	5328284	445	5674801	5402874	415	5613305	5408689	477			
			5674818	5402876	415	5673750	5408733	481			
5423195	5329078	445	5674825	5402878	415	6036226	5408800	481	5901457	5430011	387
			5674856	5402880	415	5542773	5408806	481	5901570	5430062	387
5885573	5331008	459				5542834	5408814	481			
5423379	5331013	459	5428534	5402891	413	5770497	5408820	481	5430575	5430151	387
5885580	5331017	459	6389766	5402958	413	5004608	5408849	481			
6775743	5331025	460				6456161	5430720	387			
			5070078	5403117	412	5009733	5408852	481			
5423430	5331501	460	5548775	5403219	412	6647842	5408854	417			
			5548898	5403227	412	6647859	5408856	417	6117611	6117465	210
5629115	5334934	399	5926320	5403238	418	6647866	5408858	417	6117673	6117473	209
5959663	5334942	399				6647873	5408860	417			
			5034872	5403308	411	6219391	5408868	419			
5890058	5335140	465	5034933	5403324	411	6219407	5408870	419	6049080	6404006	375
5890119	5335167	465	5613572	5403330	414	6647804	5408874	418	6049202	6404014	375
5423614	5335205	465	5813903	5403333	414	6647811	5408876	418			
5423676	5335256	465	5670735	5403335	414	6647828	5408878	418			
						6647835	5408880	418			
5424215	5336007	466				6219414	5408888	417			
5424277	5336023	466	5428657	540568	411	6219421	5408890	417			
5424338	5336058	466				6219452	5408902	418			
5424390	5336074	466	5428718	5405769	414	6219469	5408905	418			
5424451	5336090	466				6219476	5408910	420			
5424635	5336309	467		price/100		5859550	5408930	418			
5424758	5336341	467	5888123	5407995	482	5859567	5408932	418			
5424819	5336376	467	5888154	5407997	482	5871613	5408934	419			
5424871	5336457	467				5871620	5408936	419			
5424932	5336503	467	5674627	5408004	482	5871668	5408938	417			
			5854265	5408006	482	5871675	5408940	417			
5425595	5350085	461	6591640	5408008	483	5670056	5408942	416			
5425656	5350093	461				5785330	5408943	416			
5425717	5350107	461	6095346	5408013	483	5670063	5408946	416			
5425779	5350115	461		price/100		5785347	5408947	416			
5425830	5350123	461	6591664	5408014	483	5670070	5408950	419			
5426257	5350689	461	6591657	5408018	482	5670087	5408952	419			
5426370	5350700	461				5670094	5408954	420			
5426431	5350719	461	6591695	5408019	484	5849360	5408955	420			
5426493	5350727	461	6591701	5408020	484	5670100	5408956	420			
5426790	5350867	460	6591671	5408021	483	5849391	5408957	420			
5426851	5350883	460	5674689	5408022	483	5670117	5408958	420			
5426912	5350905	460	6591688	5408023	483	5849407	5408959	420			
			5864172	5408024 </							

Type	GTIN	Item no.	Page	Type	GTIN	Item no.	Page
		/pc.				/100 pc.	
101 16-1500	5613213	5408108	477	101 VL3500	5045359	5401993	411
101 16-3000	5613220	5408109	477	101 VL4000	5050803	5401995	411
101 16-750	5613206	5408107	477			/pc.	
101 20-3000	5690733	5408105	477	101 VRS-16	5613350	5408982	476
101 20-6000	5636731	5408148	477	101 VS-16	5613336	5408978	476
101 3B-4000	5674733	5402864	415	101 W-16	5613305	5408689	477
101 3B-4500	5674740	5402866	415	101 WG-16	5613374	5408986	479
101 3B-5000	5674757	5402868	415			/100 pc.	
101 3B-5500	5674764	5402870	415	108 B DIN	5429678	5416566	467
101 3B-6000	5674795	5402872	415				
101 3B-6500	5674801	5402874	415	112 DIN-100	5428893	5410096	438
101 3B-7000	5674818	5402876	415				
101 3B-7500	5674825	5402878	415	113 8-10	5446231	5230217	433
101 3B-8000	5674856	5402880	415	113 B-HD-16	5752295	5412811	438
101 3-ES-16	5613329	5408976	476	113 B-MS-HD 8-10	5629474	5230365	434
		/100 pc.		113 B-Z16	5459071	5412706	401
101 A-1500	5427575	5400155	386	113 BZ-FL	5739999	5230446	401
101 A-1500	5427575	5400155	412	113 BZ-HD	5629535	5230322	433
101 A-1500	5427575	5400155	468	113 BZ-HD	5752356	5412803	438
		/pc.		113 BZ-HD-FL	5740056	5230462	401
101 A-16	5613268	5408352	478	113 Z-16	5429616	5412609	437
		/100 pc.		113 Z-20	5959601	5230527	438
101 A-CU	5629054	5400627	387	113 Z-20	5959601	5230527	480
101 A-CU	5629054	5400627	412	113 Z8-10	5412212	5229960	433
101 A-CU	5629054	5400627	469	113 Z-K 8-10	5840886	5229961	434
101 A-L100	5428411	5402808	413	113 ZN-16	5446415	5412633	437
101 A-L150	5428473	5402859	413				
101 ALU-1000	5901334	5401771	413	120 A	5428657	5405068	411
101 ALU-1500	5427810	5401801	413				
101 ALU-2000	5427872	5401836	413	128 F	5428718	5405769	414
101 ALU-2500	5898399	5401852	413				
101 ALU-3000	5902119	5401879	413				
		/pc.					
101 A-M16	5674474	5408350	478			/100 pc.	
		/100 pc.		132 CU	5902171	5202868	423
101 B2-16 M16	6389766	5402958	413	132 GB-M8	5894124	5202568	424
101 B2-16 M16	6389766	5402958	478	132 K-CU	5902232	5202590	423
		/pc.		132 K-VA	5403036	5202515	423
101 BB-16	5613381	5408988	480	132 N-DK	5902294	5202566	423
101 BP-16	5613367	5408984	479	132 P VA	6379965	5202510	424
		/100 pc.		132 U	5038269	5203015	422
101 F1000	5430094	5424100	413	132 U 35	5784968	5203018	422
101 F1500	5430216	5424151	387	132 U-CU	5289746	5203023	422
101 F1500	5430216	5424151	469	132 VA	5403814	5202833	423
101 F1500	5430216	5424151	413	132 VA 35	5784920	5202836	422
		/pc.					
101 F-16	5613428	5408992	480	133 A	5402138	5202248	430
		/100 pc.		133 NB	5904335	5202213	430
101 F2000	5430339	5424208	387				
101 F2000	5430339	5424208	469	156 16	5411079	5228220	438
101 F2000	5430339	5424208	413	156 8-10	5410836	5228026	436
		/pc.		156 FL	5411192	5228328	436
101 FS-16	5613343	5408980	476	156 K8-10 CU	5411017	5228131	436
		/100 pc.		156 K8-10 ST	5410959	5228123	436
101 G1000	5428053	5402107	414	156 K8-10 VA	5851011	5228134	436
101 G1500	5428176	5402158	414				
		/pc.		157 EK-CU	5902478	5215854	426
101 HV-16	5613411	5408990	480	157 EK-VA	5902416	5215838	426
101 IAB	5673750	5408733	481	157 F-CU 230	5902539	5216192	424
101 IAG	5674290	5408504	478	157 F-CU 280	5813019	5216206	424
101 IDK	5895817	5408245	477	157 F-CU 410	5813132	5216257	424
101 IES	5674412	5408393	478	157 FK-CU 230	5902652	5216184	425
101 IES-16	5613275	5408395	478	157 FK-CU 280	5813071	5216214	425
101 IGL-16	5613312	5408630	478	157 FK-VA 230	5902591	5215544	425
101 IK	5895879	5408296	477	157 FK-VA 280	5812296	5215587	425
101 IK-16	5613251	5408298	477	157 FK-VA 410	5812418	5215609	425
101 ISP M10	5674351	5408458	481	157 F-VA 230	5407294	5215552	424
101 IT	5681496	5408156	477	157 F-VA 230 35	5784982	5215555	424
101 IT-16	5613237	5408158	477	157 F-VA 280	5812234	5215579	424
101 IV-16	5613299	5408557	479	157 F-VA 280 35	5785019	5215582	424
101 IW-M10	5673811	5408687	477	157 F-VA 410	5812357	5215595	424
		/100 pc.		157 FX-AL	5531791	5215875	425
101 J1000	5034810	5401970	411	157 FX-CU	5531852	5215879	425
		/pc.		157 GB-M8	5894223	5202569	427
101 MA-16	5613442	5408996	480	157 I-CU	5812593	5215749	425
101 R-16	5613435	5408994	480	157 IK-VA	5812531	5215668	426
		/100 pc.		157 I-VA	5407355	5215625	425
101 RH-16	5674924	5408101	479	157 L-CU	5812111	5215471	426
101 ST	5428534	5402891	413	157 LK-CU	5811930	5215382	427
101 ST	5428534	5402891	478	157 LK-VA	5811879	5215374	426
101 VL1500	5105619	5401980	411	157 L-VA	5407171	5215439	426
101 VL2000	5107774	5401983	411	157 NB-VA	5903673	5215277	429
101 VL2500	5108672	5401986	411	157 ND-VA	5903796	5215307	429
101 VL3000	5108733	5401989	411				

Type	GTIN	Item no.	Page	Type	GTIN	Item no.	Page
159 K-VA	5813255	5216818	/100 pc. 430	1802 8 CU	5699347	5015836	369
159 VA-V	5407959	5217075	430	1802 AH 10	5033677	5015884	366
163 100 CU	5409939	5223601	435	1802 AH 10	5033677	5015884	369
163 100 FT	5409519	5223105	435	1802 AH 5	5033615	5015880	366
163 150 FT	5409632	5223156	435	1802 AH 5	5033615	5015880	369
163 200 FT	5409755	5223202	435	1802 DC 5+1 CU	6681921	5015870	366
163 70 FT	5409458	5223075	435	1802 DC 5+5 CU	6681945	5015874	366
163 70 FT	5409458	5223075	435	1802 DC 5+5 VA	6681938	5015876	365
165 B 100	5408970	5218829	429			/pc.	
165 B 60	5408918	5218810	429	1805 2 FT	5379096	5016029	367
165 KR	5409038	5218861	428	1805 2 FT	5379096	5016029	400
165 KRB SO	5952213	5218977	428	1805 2 VA	5922216	5016096	367
165 MBG HFL	5623052	5218885	428	1805 2 VA	5922216	5016096	401
165 MBG HFL			/pc.	1805 4 FT	5379157	5016037	367
165 MBG UH	5674580	5218882	428	1805 4 FT	5379157	5016037	400
165 MBG UH	5674580	5218882	/100 pc. 486	1805 4 VA	5800354	5016118	367
165 MBG UH				1805 4 VA	5800354	5016118	401
165 MBG-8-10	6648290	5218700	427	1805 6 FT	5379218	5016045	367
165 MBG-8-10	6648290	5218700	464	1805 6 FT	5379218	5016045	400
165 MBG-8-10 200	6648320	5218716	427	1805 6 VA	5922278	5016126	367
165 MBG-8-10 FO	6648306	5218704	427	1805 6 VA	5922278	5016126	401
165 MBG-8-10 FO	6648306	5218704	464				
165 MBG-8-10 GR	6648313	5218708	428	1807	5379270	5016142	400
165 MBL-8-10	5548478	5218616	428	1807 DB	6561063	5016160	403
165 NBK 55	5904274	5218314	429				
165 OBG-8	5408796	5218683	427	1809	5378259	5015073	362
165 R-8-10	5625889	5218997	429	1809 A	5959427	5015111	364
166 LS 70	5410416	5226570	435	1809 AM	6587292	5015105	364
168 8-10 M6	5411499	5229162	434	1809 BG	5378372	5015502	363
168 DIN 30	5411734	5229480	435	1809 M	5378310	5015081	363
168 DIN-K-M8	5412151	5229839	434	1809 NR	5931669	5015075	363
168 DIN-K-M8	5411611	5229383	434	1810	5378136	5015057	365
168 FL30-M6	5411673	5229464	435				
168 FL40-M8	5411970	5229553	434	1811	5377894	5014018	400
168 ZN-M6	5411550	5229367	434	1811 L	5377955	5014026	400
172 AR	5409090	5218926	458	1813 DIN	5378013	5014212	400
176 A 100	5410652	5227100	435	1813 KL	5901938	5014425	397
176 A 150	5410713	5227151	435	1814 FT	5105015	5014468	398
176 A 65	5410539	5227070	435	1814 FT D14	6656134	5014471	398
176 A 80	5410591	5227089	435	1814 ST	5105077	5014476	398
177 20 CU	5904991	5207746	432	1816 CU 6	6431298	5009250	389
177 20 KL	5009726	5207451	433	1816 CU 6	6431298	5009250	464
177 20 M8	5404897	5207444	432	1816 CU 9	6431304	5009256	389
177 20 VA B-HD	5915836	5207901	432	1816 CU 9	6431304	5009256	464
177 20 VA M6	5404774	5207339	431	1816 F-1000X1000	5376996	5009235	389
177 20 VA M8	5404835	5207347	431	1816 F-500X1000	5376934	5009227	389
177 20 VA-VK M6	5904878	5207800	431				
177 20 VA-VK M8	5904939	5207819	431	1818	5377719	5012015	397
177 30 CU	5905059	5207754	432	1818 FL CU	6431113	5012270	464
177 30 M8	5404958	5207460	432				
177 35 VA M6	5735762	5207342	430	1819 20BP	5242772	3041212	384
177 55 CU	5905110	5207762	432	1819 25BP	5242956	3041956	384
177 55 M8	5405016	5207487	432	1820 16	6431243	3042270	384
177 B-HD20	5336433	5207851	432	1820 20	5243137	3042200	384
177 B-HD30	5334811	5207878	432	1820 25	5243199	3042251	384
177 U	5069546	5207371	431				
177 WDVS 64x25 B	6657940	5207375	431	1820 25	5243199	3042251	384
1801 VDE	5378556	5015650	/pc. 362				
1802 10 CU	5002260	5015842	366	194	5404651	/100 pc. 5207258	432
1802 10 CU	5002260	5015842	369				
1802 10 VA	5002284	5015866	366	194 K	5110392	5207266	433
1802 10 VA	5002284	5015866	368				
1802 12 CU	5699354	5015844	366	199 DIN	5405252	5208017	436
1802 12 CU	5699354	5015844	369				
1802 14 CU	5699361	5015847	366	200 V4A-1500	5751571	5420504	387
1802 14 CU	5699361	5015847	369	200 V4A-1500	5751571	5420504	412
1802 20 CU	5699408	5015849	366	200 V4A-1500	5751571	5420504	468
1802 20 CU	5699408	5015849	369	200 V4A-2000	5331575	5420539	387
1802 5 CU	5002253	5015830	366	200 V4A-2000	5331575	5420539	412
1802 5 CU	5002253	5015830	369	200 V4A-2000	5331575	5420539	468
1802 5 VA	5002277	5015854	365				
1802 5 VA	5002277	5015854	368	2019 16	6431236	5001190	385
1802 6 CU	5699330	5015832	366				
1802 6 CU	5699330	5015832	369	204 KL-1500	5430575	/100 pc. 5430151	387
1802 8 CU	5699347	5015836	366				

Type	GTIN	Item no.	Page	Type	GTIN	Item no.	Page
204 KL-1500	5430575	5430151 /pc.	469	249 8-10 CU-OT	5835394	5311530	437
204 KS-2000	5901457	5430011	387	249 8-10 CU-OT	5835394	5311530	457
204 KS-2000	5901457	5430011	469	249 8-10 ST	5417675	5311500	439
204 KS-2500	5901570	5430062	387	249 8-10 ST-OT	5737063	5311503	373
204 KS-2500	5901570	5430062	469	249 8-10 ST-OT	5737063	5311503	437
205 DG L180 FT	6505906	5420024	399	249 8-10 V2A 200	6656141	5311595	439
205 DG L180 V4A	6505890	5420022	399	249 8-10 V2A 200	6656141	5311595	487
205 DG V4A	6505869	5420020	398	249 8-10 V4A	6466283	5311404	440
		/100 pc.		249 8-10 VA	5417910	5311551	367
2056N SAS 12 A2	5432432	1167014	375	249 8-10 VA	5417910	5311551	439
2056N SAS 16 A2	5432494	1167022	375	249 8-10 VA-OT	5835349	5311554	367
2056N SAS 22 A2	5432555	1167030	375	249 8-10 VA-OT	5835349	5311554	369
2056N SAS 28 A2	5432616	1167049	375	249 8-10 VA-OT	5835349	5311554	374
2056N SAS 8 A2	5432371	1167006	375	249 8-10 VA-OT	5835349	5311554	437
		/pc.		249 8-10 VA-OT	5835349	5311554	457
213 1000 DIN	5373575	5003008	388	249 8-10 ZV	5417859	5311535	440
213 1000 DIN HS	6527069	5003081	388	249 8-10X16 VA	5925446	5311590	370
213 1500 DIN	5373636	5003016	388	249 8-10X16 VA	5925446	5311590	441
213 1500 F	5374718	5003776	388	249 B ALU	5452058	5311713	439
213 1500 M	5374053	5003261	388	249 B ST	5451990	5311705	439
213 2000 DIN	5373698	5003024	388	249 VA-OT	5693789	5311573	374
213 2000 F	5374770	5003784	388	249 VA-OT	5693789	5311573	438
213 2000 M	5374114	5003288	388	249 VA-OT	5693789	5311573	457
213 2500 DIN	5373759	5003032	388	250	5418696	5312906	395
213 2500 M	5374176	5003296	388	250	5418696	5312906	446
213 3000 DIN	5373810	5003040	388	250 A	5237372	5313058	396
213 3000 M	5374237	5003318	388	250 A-BO	5806530	5313066	397
219 16 CU	6431229	5000481 /pc.	384	250 A-FT	5740537	5313015	396
219 20 BP CU	6336340	5000500	384	250 AS-FT	5543015	5313031	396
219 20 BP FT	5371892	5000947	383	250 A-VA	5740476	5313023	396
219 20 BP V4A	5740650	5000858	383	250 VAA	5700876	5312925	395
219 20 BP V4A	5371830	5000866	383	250 VAA	5700876	5312925	447
219 20 ST FT	5018049	5000742	383	250 VA	5418757	5312922	395
219 25 BP FT	5371953	5000955	383	250 VA-FR	5418757	5312922	447
219 25 ST FT	5111047	5000769	383		5103158	5312930	463
		/pc.					
223 DIN MS	5423676	5335256	465	2500 20	5243311	3043207	385
223 DIN ZN	5423614	5335205	465	2500 25	5243373	3043258	385
223 O DIN MS	5890119	5335167	465	251 8-10	5417972	5312035	447
223 O DIN ZN	5890058	5335140	465	251 CU	5418030	5312132	448
226 8-10	5424215	5336007	466				
226 CU	5424277	5336023	466	2510 20	5717492	3043312	385
226 VA	5424338	5336058	466				
226 ZV CU	5424451	5336090	466	252 8-10 CU	5418214	5312418	393
226 ZV VA	5424390	5336074	466	252 8-10 CU	5418214	5312418	449
		/100 pc.		252 8-10 FT	5418092	5312310	393
233 8	5424635	5336309	467	252 8-10 FT	5418092	5312310	449
233 A VA	5424871	5336457	467	252 8-10 FT	5418092	5312310	449
233 A ZV	5424932	5336503	467	252 8-10 VAA	5700869	5312318	393
233 VA	5424758	5336341	467	252 8-10 VAA	5700869	5312318	449
233 ZV	5424819	5336376	467	252 8-10 VAA	5700869	5312318	449
		/100 pc.		252 8-10X16 CU	5418276	5312442	394
237 N CU	5453673	5328284	445	252 8-10X16 CU	5418276	5312442	450
237 N FT	5453611	5328209	445	252 8-10X16 FT	5418153	5312345	394
		/pc.		252 8-10X16 FT	5418153	5312345	450
239	5423195	5329078	445	252 8-10X16 V4A	5893103	5312346	394
		/100 pc.		252 8-10X16 V4A	5893103	5312346	449
244	5417316	5311039	445	252 8-10XFL30 FT	5418399	5312655	395
		/pc.		252 8-10XFL30 FT	5418399	5312655	447
245 8-10 CU	5417439	5311152	446	252 8-10XFL30V4A	5893141	5312656	395
245 8-10 FT	5417378	5311101	446	252 8-10XFL30V4A	5893141	5312656	447
		/pc.		252 GB 10x45	6454563	5312657	396
247 8-10 CU	5417552	5311268	446	252 GB 10x45	6454563	5312657	396
247 8-10 FT	5417491	5311209	446	252 S1 FT	6428038	5312292	464
		/pc.		252 S1 V4A	6428045	5312294	464
249 6-10 CU	5816591	5311417	441	252 S4 FT	6428106	5312302	463
249 6-10 ST	5816584	5311410	440	252 S4 FT	6428106	5312302	395
249 6-8 CU	6416912	5311407	441	252 S4 V4A	6428113	5312308	463
249 8-10 ALU	5417736	5311519	439				
249 8-10 ALU-OT	5466192	5311585	374	2520 20	5243793	3043703	385
249 8-10 ALU-OT	5466192	5311585	437	2520 25	5243854	3043754	385
249 8-10 ALU-OT	5466192	5311585	457				
249 8-10 CU	5417798	5311527	440				
249 8-10 CU-OT	5835394	5311530	367	253 10X16	5418573	5312809	394
249 8-10 CU-OT	5835394	5311530	369	253 10X16	5418573	5312809	450
249 8-10 CU-OT	5835394	5311530	374	253 8-10 V4A	6466306	5312582	393

Type	GTIN	Item no.	Page	Type	GTIN	Item no.	Page
253 8X8	5418337	5312604	/100 pc. 392	274 8-10	5420859	5317428	454
253 8X8	5418337	5312604	448	274 CU	5420972	5317479	454
253 S3 FT	6428083	5312592	463	2740 16	6431168	5001511	391
253 S3 V4A	6428090	5312594	463	2740 16 KL	6431205	5001513	391
253 S3 V4A	6428090	5312594	393	2745 16 25	6431120	5001590	390
2530 20	5243557	3043401	/pc. 385	2745 16 30	6431212	5001592	390
2530 25	5243618	3043452	385	2745 16 70	6431267	5001594	390
2531 20	5642312	3043908	386	2745 20 MS	5372851	5001560	390
2535 20	5453796	3043916	386	2745 20 MS	5372851	5001560	468
2535 25	5453970	3044912	386	2760 16	6431274	5001601	403
2536 20	5643036	3044904	386	2760 20 FT	5372912	5001641	390
2536 25	5642978	3044831	386	2760 20 V4A	5862697	5001633	390
			/100 pc.	2760 20 VA	5635239	5001617	390
254 DIN 8-10 CU	5419112	5314135	448	2760 25 FT	5372974	5001668	390
254 DIN 8-10 FT	5418993	5314038	448	2760 25 V4A	5901259	5001672	390
			/100 pc.	2760 8-10 V4A	6466290	5313013	396
255 30	5419174	5314518	391	2760 B-20 FT	5754879	5001749	390
255 A-FL30 FT	5419235	5314534	391	2760 B-20 VA	5752653	5001625	390
256 A-DIN 30 FT	5419471	5314658	391	2760 S8 V4A	6428151	5313012	396
256 A-DIN 30 V4A	5893080	5314659	392			/100 pc.	
256 A-DIN 30 VA	5925873	5314720	392			5313012	396
256 A-DIN 40 FT	5419532	5314666	391	280 8-10	5421276	5320011	458
256 DIN 30 FT	5419297	5314615	392	280 VK	5421337	5320054	458
256 DIN 30 V4A	5893097	5314616	392				
256 DIN 40 FT	5419358	5314623	392	287	5421573	5320704	459
256 S6 FT	6428120	5314572	462				
256 S6 V4A	6428137	5314574	462	287 CU	5421511	5320690	459
				287 DCT	6127504	5320707	459
259 8-10	5419716	5315506	444				
259 A FT	5740414	5315514	397	288 DIN	5421634	5320712	459
259 A ST	5237198	5315557	397				
259 A VA	5740353	5315522	397	301 CU-100	5426370	5350700	461
				301 CU-110	5426431	5350719	461
260 8	5419839	5315700	444	301 CU-120	5426493	5350727	461
260 8-10 MS	5419778	5315654	445	301 CU-80	5426257	5350689	461
				301 DIN-100	5425717	5350107	461
262	5419891	5316014	456	301 DIN-110	5425779	5350115	461
				301 DIN-120	5425830	5350123	461
262 A-DIN CU	5420071	5316251	456	301 DIN-80	5425595	5350085	461
262 A-DIN FT	5420019	5316219	455	301 DIN-90	5425656	5350093	461
262 CU	5419952	5316154	456	301 S-100	5426974	5351057	461
262 ZM	5818359	5316170	456	301 S-120	5427032	5351073	461
				301 S-AL-100	5890652	5351359	461
264	5420316	5316510	456	301 S-AL-120	5890713	5351375	461
				301 S-CU-100	5427216	5351456	462
264 CU	5420378	5316553	456	301 S-CU-120	5427278	5351472	462
				301 S-VA-100	5427094	5351251	461
267	5420132	5316308	455	301 S-VA-120	5427155	5351286	461
				301 V	5426790	5350867	460
267 VA	5420194	5316324	455	301 V-CU	5426851	5350883	460
				301 V-VA	5426912	5350905	460
269 8-10	5420439	5317010	452				
269 MS	5420491	5317053	452	303 DIN-1	5399971	5102111	462
				303 DIN-1 1/2	5400097	5102154	462
270 8-10 CU	5420675	5317258	452	303 DIN-1 1/4	5400035	5102138	462
270 8-10 FT	5420552	5317207	452	303 DIN-1/2	5399858	5102073	462
270 8-10 VA	5893158	5317208	452	303 DIN-2	5400158	5102197	462
				303 DIN-2 1/2	5400219	5102219	462
271 8-10	5420798	5317401	453	303 DIN-3	5400271	5102235	462
271 8-10 VA	5850861	5317481	453	303 DIN-3 1/2	5400332	5102251	462
271 CU	5420910	5317452	453	303 DIN-3/4	5399919	5102081	462
				303 DIN-3/8	5399797	5102057	462
2710 20 FT	5372370	5001218	/pc. 389	303 DIN-4	5400394	5102278	462
2710 25 FT	5372431	5001226	389				
				311 N-ALU 16	5631392	3049345	404
				311 N-ALU 16	5631392	3049345	468
				311 N-ALU 8-10	5631576	3049256	404
272 14	5421092	5318149	451	311 N-ALU 8-10	5631576	3049256	468
272 8	5421030	5318084	451	311 N-CU 8-10	5631699	3049205	404
				311 N-CU 8-10	5631699	3049205	468
273 8-10	5420613	5317223	453	311 N-VA 16	5631453	3049329	404
273 CU	5420736	5317274	454	311 N-VA 16	5631453	3049329	468
				311 N-VA 8-10	5631637	3049221	404
2730 20 FT	5372554	5001404	/pc. 389	311 N-VA 8-10	5631637	3049221	468
2730 20 VA	5635475	5001366	389				
2730 25 FT	5372615	5001412	389	319 10	5421931	5325315	457
				319 8	5421870	5325307	457

Type	GTIN	Item no.	Page	Type	GTIN	Item no.	Page
324 S-CU	5422532	5326338	458	5700 PIP	6431311	5106045	470
324 S-FT	5422419	5326303	458	5700 PIP EB	6439614	5106050	465
324 S-VA	5422471	5326311	458	5700 SP	6089512	5106003	470
330 K	5401599	5201101	414	5800 VA	5900436	5106141	470
		/pc.		5800 VZ	5900375	5106133	470
356 100	5230595	2360101	404	5900	5244813	3059006	473
356 100	5230595	2360101	472	708 30 HG	5383659	5030234	403
356 50	5230533	2360055	404	708 30 SP	5383413	5030021	403
356 50	5230533	2360055	472	708 40 HG	5383710	5030242	403
364	5244219	3051013	473	710 30	5383055	5028035	402
		/100 pc.		710 40	5383116	5028043	402
366 35	5388876	5059356	404	831 30	5383833	5032032	401
366 50	5389057	5059496	404	831 30 M6	5383956	5032237	402
370 H	5382690	5025206	402	831 40	5383895	5032040	401
470 4-16	5389231	5064015	375	831 40 M6	5384014	5032245	402
5000	5415695	5304008	441	832 30	5384137	5032539	402
5001 DIN-FT	5415879	5304105	442	832 40	5384199	5032547	402
5001 DIN-FT+VA	5858034	5304107	442	833 35	5384434	5033039	402
5001 N-CU	5817574	5304172	443	835	5433750	5033209	401
5001 N-FT	5817512	5304164	442	853 200	5885573	5331008	459
5001 N-VA	5892809	5304176	370	853 300	5423379	5331013	459
5001 N-VA	5892809	5304176	443	853 400	5885580	5331017	459
5001 ZN-CU	5415930	5304113	442	853 400 SA	6775743	5331025	460
5002 DIN-FT	5416050	5304202	442	856	5423430	5331501	460
5002 N-VA	5892847	5304270	370	925 1	5385455	5040116	372
5002 N-VA	5892847	5304270	443	925 1 1/2	5385578	5040159	372
5004 DIN-FT 12	5416357	5304407	451	925 1 1/4	5385516	5040132	372
5004 DIN-FT 20	5416418	5304504	451	925 1/2	5385332	5040078	372
5005 DIN-FT	5416470	5304601	444	925 1/4	5385219	5040035	372
5005 N-FT	5817758	5304660	444	925 3/4	5385394	5040094	372
5009	5416951	5304970	443	925 3/8	5385271	5040051	372
5010 20 FT	5503057	5304520	451	927 0	5388517	5057507	371
5011	5417071	5304997	399	927 1	5388579	5057515	371
5011	5417071	5304997	443	927 2	5388630	5057523	371
5011 VA M10	5629115	5334934	399	927 2 6-K	5699651	5057599	490
5011 VA M10	5629115	5334934	444	927 4	5388692	5057558	371
5011 VA M12	5959663	5334942	399	927 BAND-VA	5805458	5057922	371
5011 VA M12	5959663	5334942	444	927 BES VSW 25	6672844	5057690	376
		price/100		927 SCH-K-VA	5805519	5057930	371
5052 DIN 20X2.5	5680468	5019340	380	928	5385936	5040507	372
5052 DIN 20X2.5	5680468	5019340	408	937 50	5385998	5043018	374
5052 DIN 25X3	5694007	5019342	380	939	5386056	5043107	374
5052 DIN 25X3	5694007	5019342	408	942 11	5384557	5038014	372
5052 DIN 30X3	5694014	5019344	380	942 15	5384618	5038030	372
5052 DIN 30X3	5694014	5019344	408	942 18	5384670	5038057	372
5052 DIN 30X3.5	5680475	5019345	380	942 22	5384731	5038073	372
5052 DIN 30X3.5	5680475	5019345	408	942 28	5384793	5038081	372
5052 DIN 30X3.5	5680482	5019347	380	942 35	5384854	5038111	372
5052 DIN 30X3.5	5680482	5019347	408	942 43	5384915	5038138	372
5052 DIN 30X4	5680499	5019350	380	942 49	5384977	5038154	372
5052 DIN 30X4	5680499	5019350	408	950 Z 1	5386353	5050111	373
5052 DIN 40X4	5680505	5019355	380	950 Z 1 1/2	5386476	5050154	373
5052 DIN 40X4	5680505	5019355	408	950 Z 1 1/4	5386414	5050138	373
5052 DIN 40X5	5680512	5019360	380	950 Z 1 3/4	5386537	5050170	373
5052 DIN 40X5	5680512	5019360	408	950 Z 1/2	5386230	5050073	373
5052 V2A 30X3.5	5800415	5018501	380	950 Z 1/4	5386117	5050030	373
5052 V2A 30X3.5	5800415	5018501	408	950 Z 2	5386599	5050197	373
5052 V4A 30X3.5	5800477	5018706	380	950 Z 3/4	5386292	5050081	373
5052 V4A 30X3.5	5800477	5018706	408	950 Z 3/8	5386179	5050057	373
		/100 pc.		951	5386650	5051509	373
565 7.6x380 SWUV	6417353	2331924	490				
		/pc.					
5700	6089505	5106002	470				
5700 CIP	6431137	5106041	470				
5700 CIP EB	6431281	5106071	465				

Type	GTIN	Item no.	Page	Type	GTIN	Item no.	Page
952 Z 1	5386957	5052114	/100 pc. 373	F-FIX-B16 3B	5926320	5403238	418
952 Z 1 1/2	5387077	5052157	373	F-FIX-B16 3B	5926320	5403238	422
952 Z 1 1/4	5387015	5052130	373	F-FIX-B16 3B	5926320	5403238	490
952 Z 1/2	5386834	5052076	373	F-FIX-BASIS	5034933	5403324	/pc. 411
952 Z 2	5387190	5052181	373	F-FIX-JUNIOR	5034872	5403308	411
952 Z 3/4	5386896	5052092	373			/100 pc.	
985 M6 25	5250395	3133028	472	F-FIX-KL	5548775	5403219	412
985 M6 35	5250456	3133036	472	F-FIX-S10	5070078	5403117	412
985 M8 35	5250579	3133230	473	F-FIX-S10	5070078	5403117	479
			/pc. 354	F-FIX-S16	5548898	5403227	412
AB EX ISG S M10	6524181	5240360	354	F-FIX-S16	5548898	5403227	422
AB EX ISG S M12	6524242	5240362	354	F-FIX-S16	5548898	5403227	479
AB EX ISG S M16	6524259	5240366	354	F-FIX-S16	5548898	5403227	490
AB EX ISG S M20	6524273	5240370	354	FL 25-CU	6431199	5021830	408
AB EX ISG S M24	6524297	5240374	354			/pc.	
AB EX ISG SW M10	6524433	5240380	354	FLD 110	5578413	5098646	321
AB EX ISG SW M12	6524457	5240382	354	FLD 12	5578376	5098603	318
AB EX ISG SW M16	6524464	5240386	354	FLD 2-110	5578512	5098859	324
AB EX ISG SW M20	6524471	5240390	354	FLD 2-12	5578444	5098808	322
AB EX ISG SW M24	6524488	5240394	354	FLD 2-24	5578451	5098816	323
AF RD 10 V4A	6456161	5430720	387	FLD 24	5578383	5098611	319
AF RD 10 V4A	6456161	5430720	469	FLD 48	5578390	5098630	320
AL EX ISG 100	6521159	5240102	354	FLD 5	5578369	5098600	317
AL EX ISG 200	6521166	5240104	354	FRD 110	5578338	5098557	315
AL EX ISG 300	6521173	5240106	354	FRD 12	5578291	5098506	312
C20-0-255	6329694	5095600	180	FRD 2-24	5578420	5098727	316
C50-0-255	6337620	5095609	134	FRD 24	5578307	5098514	313
DLS-BS	5685333	5082382	272	FRD 24 HF	5578352	5098575	309
DS-7 16 M/W	5030881	5093171	260	FRD 48	5578314	5098522	314
DS-BNC M/M	5391098	5093260	255	FRD 5	5578284	5098492	311
DS-BNC M/W	5391036	5093252	253	FRD 5 HF	5578345	5098571	308
DS-BNC W/W	5390978	5093236	254	irod 10	6219339	5400810	421
DS-F M/W	5022732	5093275	261	irod 12	6219346	5400812	421
DS-F W/W	5022619	5093272	262	irod 14	6219353	5400814	421
			irod 19	6219360	5400817	421	
DS-N M/W	5805991	5093996	256	ISAV1000R	5004608	5408849	481
DS-N W/W	5962243	5093988	257	ISAV1000W	5009733	5408852	481
DS-N 6 M/W	6463831	5093998	258	isCon AP1-16 VA	5674696	5408026	490
DS-SMA W/W	5867050	5093277	263	isCon AP2-16 VA	5674702	5408028	490
DS-TNC M/W	5087250	5093270	259	isCon BA 45 SW	6591664	5408014	483
			/pc.			/pc.	
DW FL30x3,5	6421053	2360043	398	isCon con 2	6591671	5408021	483
DW RD10	6421046	2360041	398	isCon con PRE	6591688	5408023	483
EKL 25 M6	6049080	6404006	375	isCon connect	5674689	5408022	483
EKL 35 M6	6049202	6404014	375	isCon DH	5674863	5408043	486
EX BES 28	6672813	5057630	362	isCon EPPA 004	5813781	5408060	491
EX BES 300	6672820	5057640	362			/pc.	
EX BES 500	6672837	5057645	362	isCon H 26 VA	5872696	5408064	485
			/pc.	isCon H VA	5699668	5408056	485
EX ISG H	6517381	5240030	352	isCon H280 26 PA	5872757	5408072	486
EX ISG H 350	6521180	5240031	352	isCon H280 26 VA	5872764	5408074	486
EX ISG H 350 2L	6522965	5240033	353	isCon H280 PA	5674887	5408049	486
EX ISG H KU	6522941	5240032	353	isCon H280 VA	5674870	5408047	486
EX PAS 10	6427680	5015270	368	isCon HS 26 PA	5872702	5408066	486
EX PAS 5	6427628	5015265	368	isCon HS 26 VA	5872740	5408068	485
			/pc.	isCon HS VA	5674726	5408052	485
FDB-2 24-M	5683339	5098380	345	isCon HWS	5813774	5408058	491
FDB-2 24-N	5683384	5098390	347	isCon HWS EN	6586981	5408059	491
FDB-3 24-M	5683346	5098382	346	isCon IN con 2	6591695	5408019	484
FDB-3 24-N	5683391	5098392	348	isCon IN con PRE	6591701	5408020	484
F-FIX-132	5613572	5403330	414	isCon IN connect	5864172	5408024	484
F-Fix-132-300	5813903	5403333	414	isCon IN PAE	5864172	5408024	485
			/pc.	isCon IN PAE	5871569	5408031	488
				isCon IN PAE 2	6591633	5408032	484
				isCon IN PAE 2	6591633	5408032	488
				isCon PAE	5674719	5408036	484
					6591657	5408018	482
				isCon PR 90 SW	6591640	5408008	483
				isCon Pro 75 SW	5888123	5407995	482
				isCon Pro+ 75 GR	5888154	5407997	482
				isCon Pro+ 75 SW	5674627	5408004	482
				isCon Pro+ 75 SW	5854265	5408006	482

Type	GTIN	Item no.	Page		Type	GTIN	Item no.	Page
		/pc.					/pc.	
isCon stripper 2	6095346	5408013	483		isFang TS50x50	5670131	5408964	421
isFang 3B-100	5670148	5408968	416		isFang TS50x50	5670131	5408964	491
isFang 3B-100	5670148	5408968	489		isFang TW200	5670094	5408954	420
isFang 3B-100 AL	5802433	5408966	416		isFang TW200	5670094	5408954	492
isFang 3B-100 AL	5802433	5408966	489		isFang TW200 12	6219476	5408910	420
isFang 3B-100-A	5859550	5408930	418		isFang TW200 12	6219476	5408910	492
isFang 3B-100-A	5859550	5408930	488		isFang TW30	5670087	5408952	419
isFang 3B-150	5674931	5408969	416		isFang TW30	5670087	5408952	492
isFang 3B-150	5674931	5408969	489		isFang TW80	5670070	5408950	419
isFang 3B-150 AL	5802440	5408967	416		isFang TW80	5670070	5408950	492
isFang 3B-150 AL	5802440	5408967	489		ISO-A-1030	5770497	5408820	481
isFang 3B-150-A	5859567	5408932	418		ISO-A-150 8	6036226	5408800	481
isFang 3B-150-A	5859567	5408932	488		ISO-A-500	5542773	5408806	481
isFang 3B-250-A	6219452	5408902	418		ISO-A-800	5542834	5408814	481
isFang 3B-250-A	6219452	5408902	488		KOAX B-E2 FF-F	6415731	5082434	271
isFang 3B-G1	5674948	5408971	418		KOAX B-E2 MF-C	6415717	5082430	269
isFang 3B-G1	5674948	5408971	489		KOAX B-E2 MF-F	6415724	5082432	270
isFang 3B-G2	5674979	5408972	418		LE HAMMER-AC	5111641	3043618	386
isFang 3B-G3	5674986	5408973	418		LE HAMMER-B	5087137	3043614	386
isFang 3B-G3	5674986	5408973	489		LE HAMMER-B-II	5421627	3043628	386
isFang 3B-G4	6219469	5408905	418		LE HAMMER-H	5087076	3043610	386
isFang 3B-G4	6219469	5408905	489		LE HAMMER-SDS-M	5111160	3043602	386
isFang 4000	5670056	5408942	416		LE HAMMER-W	5617419	3043606	386
isFang 4000	5670056	5408942	489		LFC	5425182	5096786	358
isFang 4000 AL	5785330	5408943	416		LSA-A-LEI	5525134	5084008	247
isFang 4000 AL	5785330	5408943	489		LSA-BF-180	5525370	5084024	246
isFang 6000	5670063	5408946	416		LSA-BF-24	5525431	5084028	247
isFang 6000 AL	5785347	5408947	416		LSA-B-MAG	5525318	5084020	245
isFang 6000 AL	5785347	5408947	489		LSA-E	5525493	5084032	249
isFang IN 10000	6219407	5408870	419		LSA-E-LEI	5525257	5084016	248
isFang IN 10000	6219407	5408870	493		LSA-G	5110750	5084048	250
isFang IN 4000	5871613	5408934	419		LSA-M	5525554	5084036	249
isFang IN 4000	5871613	5408934	493		LSA-T-LEI	5525196	5084012	248
isFang IN 6000	5871620	5408936	419		LSA-TOOL	5525615	5084040	250
isFang IN 6000	5871620	5408936	493		LSC I+II	6465644	5091722	359
isFang IN 8000	6219391	5408868	419		LSC I+II	6465644	5091722	472
isFang IN 8000	6219391	5408868	493		MCD 125-B NPE	5541394	5096865	112
isFang IN L10	6647873	5408860	417		MCD 50-B	5541158	5096849	110
isFang IN L10	6647873	5408860	493		MCD 50-B 0	5544517	5096822	114
isFang IN L4	6647842	5408854	417		MCD 50-B 0-OS	5051473	5096827	114
isFang IN L4	6647842	5408854	493		MCD 50-B 3+1	5077091	5096879	108
isFang IN L6	6647859	5408856	417		MCD 50-B 3+1-OS	5288299	5096836	109
isFang IN L6	6647859	5408856	493		MCD 50-B-OS	5051466	5096852	111
isFang IN L8	6647866	5408858	417		MCF 35-1+FS-440	5990116	5096974	138
isFang IN L8	6647866	5408858	493		MCF 35-P3+FS-440	5995012	5096976	139
isFang IN-A 4000	5871668	5408938	417		MCF100-3+NPE+FS	6487332	5096987	100
isFang IN-A 4000	5871668	5408938	493		MCF100-NAR-TT	6608744	5096985	107
isFang IN-A 6000	5871675	5408940	417		MCF100-NAR-TT+FS	6608751	5096988	107
isFang IN-A 6000	5871675	5408940	487		MCF25-NAR-TNC	6585588	5096950	102
isFang IN-A 6000	5871675	5408940	493		MCF25-NAR-TNC+FS	6585595	5096953	102
isFang IN-A 8000	6219414	5408888	417		MCF30-NAR-TT	6585564	5096961	103
isFang IN-A 8000	6219414	5408888	487		MCF30-NAR-TT+FS	6585571	5096963	103
isFang IN-A 8000	6219414	5408888	493		MCF38-NAR-TNC	6608805	5096971	104
isFang IN-A L10	6647835	5408880	418		MCF38-NAR-TNC+FS	6608812	5096973	104
isFang IN-A L10	6647835	5408880	488		MCF50-NAR-TT	6608782	5096975	105
isFang IN-A L10	6647835	5408880	493		MCF50-NAR-TT+FS	6608799	5096977	105
isFang IN-A L4	6647804	5408874	418		MCF75-3+FS	6487325	5096981	101
isFang IN-A L4	6647804	5408874	488		MCF75-NAR-TNC	6608768	5096982	106
isFang IN-A L4	6647804	5408874	493		MCF75-NAR-TNC+FS	6608775	5096983	106
isFang IN-A L6	6647811	5408876	418				/pc.	
isFang IN-A L6	6647811	5408876	488				/pc.	
isFang IN-A L6	6647811	5408876	493				/pc.	
isFang IN-A L8	6647828	5408878	418				/pc.	
isFang IN-A L8	6647828	5408878	488				/pc.	
isFang IN-A L8	6647828	5408878	493				/pc.	
isFang IN-A 10000	6219421	5408890	417					
isFang IN-A10000	6219421	5408890	487					
isFang IN-A10000	6219421	5408890	493					
isFang TR100	5670100	5408956	420					
isFang TR100	5670100	5408956	492					
isFang TR100 100	5849360	5408955	420					
isFang TR100 100	5849360	5408955	492					
isFang TR100 200	5849391	5408957	420					
isFang TR100 200	5849391	5408957	492					
isFang TR100 300	5849407	5408959	420					
isFang TR100 300	5849407	5408959	492					
isFang TS40-50	5670117	5408958	420					
isFang TS40-50	5670117	5408958	491					
isFang TS50-60	5670124	5408960	420					
isFang TS50-60	5670124	5408960	491					

Type	GTIN	Item no.	Page	Type	GTIN	Item no.	Page
		/pc.				price/100	
MDP-2 D-48-T	5406891	5098442	331	RD 10-V4A	5902058	5021642	410
MDP-2 D-5-T	5406839	5098404	325	RD 10-V4A 20	6282425	5021640	382
MDP-3 D-24-T	5406877	5098427	329	RD 10-V4A 20	6282425	5021640	410
MDP-3 D-48-T	5406907	5098446	332				
MDP-3 D-5-T	5406846	5098407	326	RD 8-ALU	5381914	5021286	381
MDP-4 D-12-T-10	5773610	5098419	336	RD 8-ALU	5381914	5021286	409
MDP-4 D-24-EX	5848523	5098432	343	RD 8-ALU-T	5901273	5021294	381
MDP-4 D-24-T	5406884	5098431	330	RD 8-ALU-T	5901273	5021294	409
MDP-4 D-48-EX	5848530	5098452	344	RD 8-CU	5382034	5021480	382
MDP-4 D-48-T	5406914	5098450	333	RD 8-CU	5382034	5021480	410
MDP-4 D-5-EX	5848516	5098412	342	RD 8-CU 25	6636822	5021484	382
MDP-4 D-5-T	5406853	5098411	327	RD 8-CU 25	6636822	5021484	410
MDP-4 D-5-T-10	5625124	5098413	334			price/100	
		price/pac				5381556	5021081
MK-B	5461111	5091322	358	RD 8-FT	5381556	5021081	380
MK-B	5461111	5091322	471	RD 8-FT	5067474	5021332	381
		/100 pc.		RD 8-PVC	5067474	5021332	409
M-Quick M32 LGR	5741671	2153734	486	RD 8-PVC	6564804	5021380	382
		/pc.		RD 8-ST CU	6564804	5021380	410
ND-CAT6/E-B	6532773	5081804	266	RD 8-ST CU		price/100	
ND-CAT6/E-F	6532766	5081802	267	RD 8-V2A	5680529	5021235	381
ND-CAT6A/EA	5614364	5081800	265	RD 8-V2A	5680529	5021235	409
OEC 25	6427925	5009200	403	RD 8-V4A	5680574	5021644	382
		price/pac		RD 8-V4A	5680574	5021644	410
PCS	5461296	5091438	358	RJ11-TELE 4-C	6415656	5081975	241
PCS	5461296	5091438	471	RJ11-TELE 4-F	6415663	5081977	242
		/pc.				/pc.	
PCS-CS-D	5461654	5091683	359	RJ45 S-ATM 8-F	6415694	5081990	268
PCS-CS-D	5461654	5091683	471	RJ45 S-E100 4-B	6415748	5081001	273
PCS-CS-GB	5896111	5091691	359	RJ45 S-E100 4-C	6415755	5081003	274
PCS-CS-GB	5896111	5091691	471	RJ45 S-E100 4-F	6415762	5081005	275
		price/pac		RJ45-TELE 4-C	6415670	5081982	243
PCS-H	5461470	5091527	358	RJ45-TELE 4-F	6415687	5081984	244
PCS-H	5461470	5091527	471			/100 pc.	
PDP-2-12-D	6741915	5080303	282	RK-FIX	5433682	5316450	454
PDP-2-12-I	6741953	5080311	286	RK-FIX CU	5433736	5316468	455
PDP-2-24-D	6741922	5080305	283	RK-FIX VA	5433729	5316459	455
PDP-2-24-I	6741960	5080313	287				
PDP-2-48-D	6741939	5080307	284	RSF 177 20 VA M8	6622375	5317512	451
PDP-2-48-I	6741977	5080315	288	RSF 249 8-10 VA	6622368	5317502	450
PDP-2-5-D	6741908	5080301	281			price/100	
PDP-2-5-I	6741946	5080309	285	S 11-CU	5836209	5021654	382
PDP-2x2-12-D	6741991	5080319	290	S 11-CU	5836209	5021654	410
PDP-2x2-12-I	6742035	5080327	294				
PDP-2x2-24-D	6742004	5080321	291	S 9-CU	6033768	5021652	382
PDP-2x2-24-I	6742042	5080329	295	S 9-CU	6033768	5021652	410
PDP-2x2-48-D	6742011	5080323	292	S-11-CU SN	5938668	5021656	382
PDP-2x2-48-I	6742059	5080331	296	S-11-CU SN	5938668	5021656	410
PDP-2x2-5-D	6741984	5080317	289	SD09-V11 9	5916277	5080061	280
PDP-2x2-5-I	6742028	5080325	293	SD09-V24 9	5915973	5080053	278
		price/100				/pc.	
PND-2in1-C-OS	6676965	5081070	276	SD15-V24 15	5916031	5080150	279
PND-3in1-C-OS	6676972	5081072	277	SD-Fix	5670735	5403335	414
		/100 pc.					
ProtectionBall	6409327	5018014	380	SQ M6	5016069	/100 pc.	
		/pc.				2146509	485
PS 2-B+C TNC	6441679	5089736	113	SQ-20 SW	5655367	2146164	485
PS 2-B+C TNC+FS	6441686	5089738	113	SQ-25 LGR	5595717	2146207	485
		price/100				/pc.	
RD 10	5381617	5021103	380	S-UHF M/W	5390732	5093023	252
RD 10	5381617	5021103	408	S-UHF W/W	5390671	5093015	251
RD 10-ALU	5381976	5021308	381				
RD 10-ALU	5381976	5021308	409	TD-2/D-HS	6087723	5081694	240
RD 10-CU	5382096	5021502	382	TD-2D-V	6427444	5081698	238
RD 10-CU	5382096	5021502	410				
RD 10-PVC	5381730	5021162	381	TD-4/I	6034352	5081690	239
RD 10-PVC	5381730	5021162	409				
RD 10-V2A	5680567	5021239	381	TKS-B	5578277	5097976	310
RD 10-V2A	5680567	5021239	409				
RD 10-V2A	5801375	5021227	381	TV 4+1	5022978	5083400	264
RD 10-V2A	5801375	5021227	409				
RD 10-V4A	5680581	5021647	382	ÜSM-10-230I1P+PE	6426720	5092422	201
RD 10-V4A	5680581	5021647	410	ÜSM-10-230I1P-0	6426713	5092420	202
RD 10-V4A	5902058	5021642	382	ÜSM-10-230I1PE25	6560844	5092440	211

Type	GTIN	Item no.	Page	Type	GTIN	Item no.	Page
		/pc.				/pc.	
ÜSM-10-230I2P+PE	6426768	5092426	199	V50-3+FS-280	6159642	5093516	126
ÜSM-10-230I2P-0	6426751	5092424	200	V50-3+NPE+FS-150	6398706	5093462	122
ÜSM-20-230I1P+PE	6515400	5092431	197	V50-3+NPE+FS-280	6159710	5093533	133
ÜSM-20-230I1PE65	6515431	5092433	198	V50-3+NPE-150	6398683	5093454	121
ÜSM-A	5080886	5092451	206	V50-3+NPE-280	6159697	5093526	132
ÜSM-A-150	5475804	5092466	207	V50-3-150	6398652	5093442	117
ÜSM-A-2	5247098	5092460	208	V50-3-280	6159604	5093511	125
ÜSM-LED 230	6035441	5092480	194	V50-4+FS-280	6159659	5093518	128
ÜSM-LED 230-65	6439034	5092478	195	V50-4-280	6159628	5093513	127
ÜSM-LED 440	6035496	5092482	196	V50-B+C 0-300PV	5708841	5093726	234
ÜSS 45-A-RW	6117611	6117465	210	V50-B+C 3-PH600	5478546	5093623	218
ÜSS 45-O-RW	6117673	6117473	209	V50-B+C 3PHFS600	5709022	5093625	219
V10 COMPACT 150	5246268	5093378	184	VB-MDP 10-MD	5410461	5098470	338
V10 COMPACT 255	5076551	5093380	185	VF110-AC DC	5578154	5097631	301
V10 COMPACT 385	5126041	5093384	186	VF12-AC DC	5578116	5097453	297
V10 COMPACT-AS	5299448	5093391	187	VF12-AC/DC-FS	5736561	5097454	303
V10 COMPACT-FS	6098583	5093382	188	VF2-230-AC/DC-FS	5578260	5097939	307
V10-C 0-150	5158103	5093400	193	VF230-AC/DC	5578161	5097650	302
V10-C 1+NPE-280	5382799	5093418	192	VF230-AC-FS	5578215	5097858	306
V10-C 1-280	5406778	5093415	189	VF24-AC/DC	5578123	5097607	298
V10-C 3+NPE	5363903	5094920	190	VF24-AC/DC-FS	5578185	5097820	304
V10-C 3+NPE+FS	5363941	5094931	191	VF48-AC/DC	5578130	5097615	299
V20-0-1000	6163656	5095378	179	VF48-AC/DC-FS	5812258	5097822	305
V20-0-150	6163540	5095362	177	VF60-AC/DC	5578147	5097623	300
V20-0-280	6163557	5095364	178	VF-FS	5813521	5098475	338
V20-0-440	6163618	5095370	178	VG-BC DCPH900-31	5872658	5088629	229
V20-0-550	6163625	5095372	179	VG-BC DCPH-MS600	5613725	5088693	232
V20-0-75	6163533	5095360	177	VG-BC DCPH-MS900	5613718	5088692	231
V20-1+FS-280	6162000	5095281	156	VG-BC900S1	6440573	5088564	233
V20-1+NPE+FS-280	6163014	5095331	166	VG-BCPV900K 22	6190263	5088566	226
V20-1+NPE-150	6160051	5095231	152	VG-C DCPH1000-4S	5780717	5088651	228
V20-1+NPE-280	6161140	5095251	165	VG-C DCPH-MS1000	5613701	5088691	230
V20-1+NPE-75	6160020	5095221	145	VG-C PV 1000K 333	6037490	5088585	227
V20-1-150	6159758	5095151	147	ZSF	5518419	2362970	472
V20-1-280	6159802	5095161	155				
V20-1-440	6159949	5095201	169				
V20-1-550	6159956	5095211	170				
V20-1-75	6159727	5095141	144				
V20-2+FS-280	6162185	5095282	158				
V20-2+FS-550	6162901	5095312	172				
V20-2+NPE+FS-150	6162963	5095322	150				
V20-2+NPE+FS-280	6163243	5095332	160				
V20-2+NPE-150	6160075	5095232	149				
V20-2+NPE-280	6161324	5095252	159				
V20-2-150	6159772	5095152	148				
V20-2-280	6159819	5095162	157				
V20-2-550	6159963	5095212	171				
V20-2-75	6159741	5095142	146				
V20-3+FS-280	6162338	5095283	162				
V20-3+FS-550	6162949	5095313	174				
V20-3+NPE+FS-150	6163007	5095321	154				
V20-3+NPE+FS-280	6163427	5095333	168				
V20-3+NPE-150	6163847	5095233	153				
V20-3+NPE-280	6161331	5095253	167				
V20-3-150	6159789	5095153	151				
V20-3-280	6159826	5095163	161				
V20-3-550	6160006	5095213	173				
V20-4+FS-280	6162819	5095284	164				
V20-4+FS-550	6162956	5095314	176				
V20-4-280	6159833	5095164	163				
V20-4-550	6160013	5095214	175				
V20-C 3-PH-1000	5478621	5094608	222				
V20-C 3PH-600	5708872	5094605	224				
V20-C 3PHFS-1000	5648482	5094574	223				
V20-C 3PHFS-600	5709084	5094576	225				
V20-C U-3PH-Y	5299455	5096647	234				
V20-C U-3PH-Y-FS	5648499	5096646	235				
V50-0-150	6153718	5093505	134				
V50-0-280	6159598	5093508	134				
V50-1+FS-150	6398645	5093446	116				
V50-1+FS-280	6412969	5093502	124				
V50-1+NPE+FS-150	6398690	5093460	120				
V50-1+NPE+FS-280	6159703	5093531	130				
V50-1+NPE-150	6398676	5093452	119				
V50-1+NPE-280	6159666	5093522	129				
V50-1-150	6398638	5093440	115				
V50-1-280	6412952	5093500	123				
V50-2+NPE-280	6159680	5093524	131				
V50-3+FS-150	6398669	5093448	118				

SOUTH AFRICA

O-line (Pty) Ltd - Head Office

Reg. No. 1982/000082/07

14/16 Prop Street

Selby Ex t. 11

Johannesburg 2001

P.O Box 6457

Johannesburg 2000

South Africa

Tel: (+27) 011-378-3700

Fax: (+27) 011-493-0048

email: o-line@o-line.com

O-line Kwazulu-Natal

13 Young Road,

Westmead

3610

P.O. Box 2534

New Germany

3620

South Africa

Tel: (+27) 031-705-6355

Fax: (+27) 031-705-6358

email: o-linekzn@o-line.com

O-line Port Elizabeth

26 Paterson Road

North End

Port Elizabeth 6001

P.O. Box 1352

Port Elizabeth 6000

South Africa

Tel: (+27) 041-486-3674

Fax: (+27) 041-484-5463

email: o-linepe@o-line.com

O-line Pretoria

219 Battery Street

Silverton

Pretoria

P.O. Box 2039 Silverton

0127

South Africa

Tel: (+27) 012-803-1803

Fax: (+27) 012-803-1733

email: o-linepta@o-line.com

O-line Cape Town

Unit 2, 6 Thor Circle

Viking Place

Thornton 7460

P.O. Box 506

Eppindust 7475

South Africa

Tel: (+27) 021-531-9071

Fax: (+27) 021-531-8092

E-mail o-linecpt@o-line.com

O-line Bloemfontein

21 Sand Du Plessis Lane

Estoire, Bloemfontein 9301

P.O.Box 29809

Danhof 9310

Tel:(+27) 051-432-0707

Fax: (+27) 051-432-0708

email: o-linebfm@o-line.com

INTERNATIONAL

O-line Mocambique Limitada

Reg. No. 2009/1001240/68

Rua Beleluane

Parcela 510

Djuba, Matola-Rio

Maputo

Tel: (00) 258-217 30243

Fax: (00) 258-217 30244

e-mail: o-linemz@o-line.com

OBO Ghana

Reg. No CS036372016

Plot No.53, Flower Pot,

Spintex Road Accra Ghana

Tel: (00) 233-5015 22488

Fax: (00) 233-2441 94426

e-mail: obo.ghana@obo-bettermann.com

www.o-line.com



o-line